

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Revision date 26-Jan-2023 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name E/S PLASTERBOARD ADHESIVE GUN FOAM

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Insulation foams

Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Effects on or via lactation	Yes - (H362)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Category 3 Respiratory irritation	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 4 - (H413)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Diphenylmethane-diisocyanate, isomers and homologues, Alkanes, C14-17, chloro

United Kingdom - BE Page 1 / 16

Revision date 26-Jan-2023

Revision Number 3.01

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021



Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H362 - May cause harm to breast-fed children.

H373 - May cause damage to organs through prolonged or repeated exposure.

H413 - May cause long lasting harmful effects to aquatic life.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH066 - Repeated exposure may cause skin dryness or cracking

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P260 - Do not breathe spray

P263 - Avoid contact during pregnancy and while nursing

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P405 - Store locked up

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Reserved for industrial and professional use. As from 24 August 2023 adequate training is required before industrial or professional use. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During

United Kingdom - BE Page 2/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Revision date 26-Jan-2023

Revision Number 3.01

transportation by car the cans should stand upright in the cargo space. When foaming the propellants are highly flammable. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	, ,	REACH registration number
Diphenylmethane-diisoc yanate, isomers and homologues	618-498-9	9016-87-9	>25 - <40	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]
Alkanes, C14-17, chloro	(602-095-00- X) 287-477-0	85535-85-9	20 - 25	Lact. (H362) (EUH066) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) [H]	-	01-2119519269- 33-XXXX
Dimethyl ether	(603-019-00- 8) 204-065-8	115-10-6	5 - <10	Flam. Gas 1 (H220) Press. Gas (H280)	-	01-2119472128- 37-XXXX
Isobutane	(601-004-00- 0) (601-004-01- 8) 200-857-2	75-28-5	5 - <10	Flam. Gas 1 (H220) Press. Gas (H280)	-	01-2119485395- 27-XXXX
Octamethylcyclotetrasilo xane [D4]	(014-018-00- 1) 209-136-7	556-67-2	0.01 - < 0.05	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238- 36-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

United Kingdom - BE Page 3 / 16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Full text of H- and EUH-phrases: see section 16

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	EC No (EU Index No)	CAS No	SVHC candidates
Alkanes, C14-17, chloro	(602-095-00-X)	85535-85-9	X
	287-477-0		

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, Inhalation

give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.

Revision date 26-Jan-2023

Revision Number 3.01

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact

Remove contact lenses, if present and easy to do. Continue rinsing, Keep eve wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do

not use solvents or thinners to dissolve the material.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give

anything by mouth to an unconscious person. Get immediate medical attention.

Remove all sources of ignition. Ensure that medical personnel are aware of the Self-protection of the first aider

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as

required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ **Symptoms**

or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

May cause sensitisation in susceptible persons. Treat symptomatically. Note to doctors

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE Unsuitable extinguishing media

STOPPED.

United Kingdom - BE Page 4/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021 Revision Number 3.01

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin

Revision date 26-Jan-2023

contact.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Hydrogen chloride. Nitrogen

oxides (NOx). Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

> section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or **Environmental precautions**

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without

risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open Advice on safe handling

> flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in

United Kingdom - BE Page 5/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse.

Revision date 26-Jan-2023

Revision Number 3.01

General hygiene considerations

Supercedes Date: 20-Dec-2021

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition

(i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children. Keep from freezing. Keep/store only in original container. Store in a dry place. Store in a closed

container.

Recommended storage temperature

Do not freeze.

7.3. Specific end use(s)

Specific use(s) Insulation foams.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Diphenylmethane-diisocyanate, isomers and	-	TWA: 0.02 mg/m ³
homologues		STEL: 0.07 mg/m ³ SEN; as -NCO
9016-87-9		
Dimethyl ether	TWA: 1000 ppm	TWA: 400 ppm
115-10-6	TWA: 1920 mg/m ³	TWA: 766 mg/m ³
	•	STEL: 500 ppm
		STEL: 958 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (85535-85-9)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term	Inhalation	6.7 mg/m ³	

United Kingdom - BE Page 6 / 16

Revision date 26-Jan-2023

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021 Revision Number 3.01

			
Systemic health effects			
worker	Dermal	47.9 mg/kg bw/d	
Systemic health effects			
Long term			

Dimethyl ether (115-10-6)			
Туре		Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	1894 mg/m³	
Long term		-	
Systemic health effects			

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре	1	Derived No Effect Level (DNEL)	Safety factor
worker		73 mg/m ³	
Long term Systemic health effects			

Derived No Effect Level (DN	Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (855	535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	2 mg/m³		
Consumer Long term Systemic health effects	Dermal	28.75 mg/kg bw/d		
Consumer Long term Systemic health effects	Oral	0.58 mg/kg bw/d		

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	
Consumer	Inhalation	471 mg/m³	
Long term			
Systemic health effects			

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Alkanes, C14-17, chloro (85535-85-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 μg/l
Marine water	0.2 μg/l

United Kingdom - BE Page 7 / 16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Revision date 26-Jan-2023 Revision Number 3.01

Microorganisms in sewage treatment	80 mg/l
Freshwater sediment	13 mg/kg dry weight
Marine sediment	2.6 mg/kg dry weight
Soil	11.9 mg/kg dry weight

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The

breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform

to standard EN 374

Skin and body protection Respiratory protection

Wear appropriate personal protective clothing to prevent skin contact.

Ensure adequate respiratory protection during spray applications. In case of insufficient

ventilation, wear suitable respiratory equipment.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming

to EN 140 with Type A filter or better.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearanceAerosol Foam

Colour Yellow

Odour Characteristic. Slight.
Odour threshold No information available

PropertyValuesRemarks • MethodMelting point / freezing pointNo data availableNo data availableInitial boiling point and boilingNot applicable, AerosolNot applicable, Aerosol

range

Flammability Not applicable for liquids . None known Flammability Limit in Air None known

Upper flammability or explosive 18.6 Vol%

limits

Lower flammability or explosive 1.7 Vol%

limits

United Kingdom - BE Page 8 / 16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Not applicable, Aerosol

Revision date 26-Jan-2023

Revision Number 3.01

Flash point Not applicable, Aerosol .

Autoignition temperature°CNo data availableDecomposition temperatureNo data available

ecomposition temperature No data available No data available Not applicable. Insoluble in water.

pH (as aqueous solution)

Kinematic viscosity

No data available

Dynamic viscosity

No data available

Water solubility

Solubility(ies)

No data available

No data available

No data available

None known

Partition coefficient
Vapour pressure
6 - 7
Relative density
No data available
No data available
bar @ 23 °C
None known

Relative density

Bulk Density

Liquid Density

No data available

None know

No data available

No data available

0.98 g/cm³

Relative vapour density No data available None known **Particle characteristics**

Particle Size No information available
Particle Size Distribution No information available

9.2. Other information

Solid content (%)

VOC content

No information available

No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

Minimum Ignition Temperature 235 Not applicable .

(°C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Heat, flames and sparks. Excessive heat. Do not freeze.

Protect from moisture. Keep away from open flames, hot surfaces and sources of

ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines.

Incompatible with oxidising agents.

United Kingdom - BE Page 9 / 16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of

Revision date 26-Jan-2023

Revision Number 3.01

respiratory tract. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional

affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause

redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 3.08 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane-diisocyanate,	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg	=1.5 mg/L (Rattus) 4 h
isomers and homologues		(Oryctolagus cuniculus)	-
Alkanes, C14-17, chloro	>4000 mg/kg (Rattus)	> 2000 mg/kg (Rattus)	-
Dimethyl ether	1	-	=164000 ppm (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m³ (Rattus) 4 h
[D4]	OECD 401	OECD 402	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

United Kingdom - BE Page 10 / 16

Revision date 26-Jan-2023

Revision Number 3.01

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		sensitising
Sensitisation: Local Lymph Node			_
Assay			

Octamethylcyclotetrasiloxane [D4] (556-67-2)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

Component Information

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic
Toxicity/Carcinogenicity Studies		

Reproductive toxicity Classification based on data available for ingredients. May cause harm to breast-fed

children.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Alkanes, C14-17, chloro	Lact.
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

United Kingdom - BE Page 11 / 16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021 Revision Number 3.01

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

May cause long lasting harmful effects to aquatic life. Cured foam has no C14-C17 chloroalkanes leaching in water for a maximum 20% C14-C17 chloroalkanes in mixture. Study: "Pulverized PU Foam HM23. Leaching study, Limit test" by Dr. Christine Jahns and sponsored by FEICA AISBL, 09.12.2014.

Revision date 26-Jan-2023

Product Information					
Method	Species	Endpoint type	Effective dose	Exposure time	Results
OECD Test No. 202: Daphnia sp., Acute Immobilisation Test	Daphnia magna	EC50	1000 mg/L	48 hours	Harmless to aquatic organisms up to the tested concentration

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Diphenylmethane-diiso	ErC50 (72h)	CL50 (96h)	-	EC50 (24H)		
cyanate, isomers and	>1640 mg/L	>1000 mg/L		>1000 mg/L		
homologues	Algae	(Danio rerio)		Daphnia magna		
9016-87-9	(scenedesmus					
	subspicatus) (OECD 201)					
Alkanes, C14-17, chloro		LC50: >500mg/L	_	EC50 (48h) =	100	10
85535-85-9		(48h, Leuciscus		0.007 mg/l	100	
		idus)		(Daphnia		
		,		magna) OECD		
				202		
Dimethyl ether	-	LC50: >4.1g/L	-	> 4400 mg/L		
115-10-6		(96h, Poecilia		(Daphnia) (NEN		
		reticulata)		6501)		
Octamethylcyclotetrasil	=	LC50:	-	EC50:		10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		
556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				
		rerio)				

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent	28 days	0% biodegradation	Not readily biodegradable
Biodegradability: Modified MITI Test	-	_	
(II)			

Octamethylcyclotetrasiloxane [D4] (556-67-2)

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Alkanes, C14-17, chloro	7
Dimethyl ether	-0.18

United Kingdom - BE Page 12/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Revision date 26-Jan-2023

Revision Number 3.01

Isobutane	2.8	
Octamethylcyclotetrasiloxane [D4]	6.49	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Alkanes, C14-17, chloro	PBT & vPvB	
Dimethyl ether	The substance is not PBT / vPvB	
Isobutane	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	

12.6. Endocrine disrupting properties

No information available. **Endocrine disrupting properties**

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal.

according to EWC

Waste codes / waste designations Waste codes should be assigned by the user based on the application for which the

product was used.

European Waste Catalogue 08 05 01* waste isocyanates

16 05 04* gases in pressure containers (including halons) containing dangerous

substances

17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Keep from freezing. Note:

United Kingdom - BE Page 13/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Revision date 26-Jan-2023

Revision Number 3.01

Land transport (ADR/RID)

Supercedes Date: 20-Dec-2021

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
Labels
UN1950
Aerosols
2
2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2, (D), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special Provisions 190, 327, 344, 625

Classification code 5F
Tunnel restriction code (D)
Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID numberUN195014.2 Proper Shipping NameAerosols14.3 Transport hazard class(es)2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols (Alkanes, C14-17, chloro), 2.1, (0°C c.c.), Marine Pollutant

14.5 Marine pollutant

14.6 Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ)

EmS-No

14.7 Maritime transport in bulk

See SP277

F-D, S-U

Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, flammable, 2.1

14.5 Environmental hazards Yes

14.6 Special Provisions A145, A167, A802

Limited quantity (LQ) 30 kg G ERG Code 10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No
Alkanes, C14-17, chloro	85535-85-9

United Kingdom - BE Page 14/16

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Revision date 26-Jan-2023

Revision Number 3.01

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH
		Annex XVII
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56
		74.
Diisocyantes		74

56 . If product supplied to the general public with substance ≥0.1%, then gloves must be provided with the product. **74** If product supplied to the industrial or professional users with total monomeric diisocyanates ≥ 0.1%, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H226 - Flammable liquid and vapour

H280 - Contains gas under pressure; may explode if heated

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H361f - Suspected of damaging fertility

H362 - May cause harm to breast-fed children

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

United Kingdom - BE Page 15/16

Revision date 26-Jan-2023

Revision Number 3.01

E/S PLASTERBOARD ADHESIVE GUN FOAM

Supercedes Date: 20-Dec-2021

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 26-Jan-2023

Indication of changes

Revision note SDS sections updated, 3.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE

INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 16 / 16