

**EVO-STIK EPOXY RAPID METAL - RESIN**  
Supersedes Date: 19-Oct-2020**Revision Date: 19-Oct-2020**  
**Revision Number 1.02****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** EVO-STIK EPOXY RAPID METAL - RESIN  
**Pure substance/mixture** Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Resin.  
**Uses advised against** None known**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik SA  
420 rue d'Estienne d'Orves  
92700 Colombes  
FRANCE  
Tel: +33 (0)1 49 00 90 00**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Chronic aquatic toxicity</b>	Category 2 - (H411)

**2.2. Label Elements**

Contains: Bisphenol-A-Epichlorhydrin Epoxy resin &lt;= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW&lt;700, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs., N,N'-Ethylenebis(12-hydroxyoctadecanamide)

**Signal word**  
WARNING**Hazard statements**H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

## Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves and eye/face protection.  
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P391 - Collect spillage.  
P337 + P313 - If eye irritation persists: Get medical advice/attention.  
P501 - Dispose of contents/ container to an approved waste disposal plant.

## 2.3. Other Hazards

No information available

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	40 - <80	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx
Reaction product of Bisphenol F and Epichlorohydrine MW<700	608-164-0	28064-14-4	10 - <20	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)		--
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	271-846-8	68609-97-2	10 - <20	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)		01-2119485289-22-XXXX
N,N'-Ethylenebis(12-hydroxyoctadecanamide)	204-613-6	123-26-2	0.1 - <1	Skin Sens. 1B (H317) Aquatic Chronic 3 (H412)		01-2119978265-26-XXXX

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Get medical attention immediately if symptoms occur. Remove to fresh air.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

### 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

**Personal precautions** Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash it before reuse. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Store locked up. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Resin.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### **Exposure Limits**

**Derived No Effect Level (DNEL)** No information available

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
 Supercedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
 Revision Number 1.02

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

Predicted No Effect Concentration (PNEC)	
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Please refer also to Safety Data Sheet of Part B.

### Personal Protective Equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).  
**Hand protection** Wear protective gloves: Nitrile rubber, Butyl rubber. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.  
**Skin and body protection** Wear suitable protective clothing.  
**Respiratory protection** Ensure adequate ventilation, especially in confined areas.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

## 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	dark brown
Odour	No information available
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	> 250 °C	
Flash point	250 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	> 21 mm <sup>2</sup> /s	@ 40 °C
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

## 9.2. Other information

Solid content (%)	82.13
VOC Content (%)	No information available
Density	1.1 g/cm <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

#### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

## 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Skin contact</b>	Irritating to skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

#### Numerical measures of toxicity

##### Acute toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	=17100 mg/kg (Rattus)	LD50 >4000 mg/Kg Rabbit	

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		24 hours	Product score 5.75 irritant

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Component Information					
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Product score 2 irritant

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

Component Information			
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-09	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.



# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW 25068-38-6	3.26	31
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	3.77	-

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** . The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW 25068-38-6	The substance is not PBT / vPvB
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	The substance is not PBT / vPvB
N,N'-Ethylenebis(12-hydroxyoctadecanamide) 123-26-2	The substance is not PBT / vPvB

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## Endocrine Disruptor Information

Chemical name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin ≤ 700 MW	Group III Chemical	-

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/ container to an approved landfill.

**Contaminated packaging** Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

**Waste codes / waste designations according to EWC / AVV** 15 01 10\*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03\* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

# SAFETY DATA SHEET

EVO-STIK EPOXY RAPID METAL - RESIN  
Supersedes Date: 19-Oct-2020

Revision Date: 19-Oct-2020  
Revision Number 1.02

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

## Land transport (ADR/RID)

**14.1 UN number** UN3082  
**14.2 Proper Shipping Name** Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700)  
**14.3 Transport hazard class(es)** 9  
**Labels** 9  
**14.4 Packing group** III  
**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700), 9, III, (-)  
**14.5 Environmental hazards** Yes  
**14.6 Special Provisions** 274, 335, 601, 375  
**Classification code** M6  
**Tunnel restriction code** (-)  
**Limited Quantity (LQ)** 5 L  
**ADR Hazard Id (Kemmler Number)** 90

## IMDG

**14.1 UN number** UN3082  
**14.2 Proper Shipping Name** Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700), Marine Pollutant  
**14.3 Transport hazard class(es)** 9  
**14.4 Packing group** III  
**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700), 9, III, Marine Pollutant  
**14.5 Marine pollutant** P.  
**14.6 Special Provisions** 274, 335, 969  
**Limited Quantity (LQ)** 5 L  
**EmS-No** F-A, S-F  
**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable

## Air transport (ICAO-TI / IATA-DGR)

**14.1 UN number** UN3082  
**14.2 Proper Shipping Name** Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700)  
**14.3 Transport hazard class(es)** 9  
**14.4 Packing group** III  
**Description** UN3082, Environmentally hazardous substances, liquid, n.o.s (Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Reaction product of Bisphenol F and Epichlorohydrine MW<700), 9, III  
**14.5 Environmental hazards** Yes  
**14.6 Special Provisions** A97, A158, A197  
**Limited Quantity (LQ)** 30 kg G  
**ERG Code** 9L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

# SAFETY DATA SHEET

**EVO-STIK EPOXY RAPID METAL - RESIN**  
**Supersedes Date:** 19-Oct-2020

**Revision Date:** 19-Oct-2020  
**Revision Number** 1.02

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## **Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Dangerous substance category per Seveso Directive (2012/18/EU)**

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

#### **Legend**

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

\*

Skin designation

SVHC

Substance(s) of Very High Concern

PBT

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB

Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE

Specific target organ toxicity - Repeated exposure

STOT SE

Specific target organ toxicity - Single exposure

# SAFETY DATA SHEET

**EVO-STIK EPOXY RAPID METAL - RESIN**  
**Supersedes Date:** 19-Oct-2020

**Revision Date:** 19-Oct-2020  
**Revision Number** 1.02

---

EWC European Waste Catalogue

## **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision Date:** 19-Oct-2020

## **Indication of changes**

**Revision note** Not applicable.

**Training Advice** When working with hazardous materials, regular training of operators is required by law

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**