

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Hazardous to the aquatic environment - chronic Category 3 - (H412)

2.2. Label elements

Signal word

None

Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

United Kingdom - BE Page 1 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No. (Index No.)		Specific concentration limit (SCL)		M-Factor (long-ter m)	Notes
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4		01-2119827000 -58-XXXX	934-956-3	Asp. Tox. 1 (H304)	-	-	-	-
Triacetoxy(propyl)sil ane 17865-07-5	1 - <2.5	01-2119966899 -07-XXXX	241-816-9	Skin Corr. 1B (H314) (EUH071)	-	-	-	-
Octamethylcyclotetra siloxane [D4] 556-67-2	0.036 - < 0.05		209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
4,5-dichloro-2-octyl- 2H-isothiazol-3-one [DCOIT] 64359-81-5	0.01 < 0.036	No data available		Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Corr. 1 (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	0.025%<=C< 5%	100	100	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

<u>Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes</u> [G] - PBT / vPvB substance

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

United Kingdom - BE Page 2 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	1	-	1	-	-
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one IDCOITI	264-843-8 (613-335-00-8)	64359-81-5	567+	-	0.16+	0.16+	0.16+

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

United Kingdom - BE Page 3 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 **Revision Number** 2.03

chemical

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products

Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of

irritating and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions**

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Take up mechanically, placing in appropriate containers for disposal. Methods for cleaning up

Equipment cleaned with organic solvent, washings are collected and disposed of as Prevention of secondary hazards

solvent waste. Collect water from cleaning tools and reuse it or dispose it in local sewage

systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Advice on safe handling

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, **Storage Conditions**

drink and animal feedingstuffs. Protect from moisture.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

United Kingdom - BE Page 4 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	TWA/8h	-
< 0.03% aromatics	5mg/m ³	
RR-100252-4	STEL/15 mins 10mg/m ³	
Silica, amorphous, fumed, crystalline-free	-	TWA: 6 mg/m ³ ; inhalable dust
112945-52-5		TWA: 2.4 mg/m ³ ; respirable dust
		STEL: 18 mg/m³; inhalable dust
		STEL: 7.2 mg/m ³ ; respirable dust
Acetic acid	TWA: 25 mg/m ³ ;	TWA: 10 ppm;
64-19-7	TWA: 10 ppm;	TWA: 25 mg/m ³ ;
	STEL: 50 mg/m ³ ;	STEL: 20 ppm;
	STEL: 20 ppm;	STEL: 50 mg/m ³ ;
Silica, amorphous	-	TWA: 6 mg/m ³ ; inhalable dust
7631-86-9		TWA: 2.4 mg/m ³ ; respirable dust
		STEL: 18 mg/m³; inhalable dust
		STEL: 7.2 mg/m³; respirable dust

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Process of the second	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	73 mg/m³		

Derived No Effect Level (DNEL)					
Octamethylcyclotetrasiloxau	ne [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	13 mg/m³			
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.0015 mg/l			
Marine water	0.00015 mg/l			
Freshwater sediment	3 mg/kg			
Marine sediment	0.3 mg/kg			

United Kingdom - BE Page 5 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearancePasteColourBrown

Odour No information available.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point No data available None known

Initial boiling point and boiling 301 °C

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 100 °C Autoignition temperature > 200 °C

Decomposition temperature None known

pH No data available Not applicable. Insoluble in water.
pH (as aqueous solution) No data available None known

pH (as aqueous solution)

Kinematic viscosity

Dynamic viscosity

Water solubility

No data available

> 50 mm²/s

No data available

Insoluble in water.

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVanour pressure<100</th>hPa

Vapour pressure <100 Relative density 0.94

Bulk density

No data available

Density

No data available

Relative vapour density

No data available

None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

United Kingdom - BE Page 6 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contactBased on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

United Kingdom - BE Page 7 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/L
ATEmix (inhalation-vapour) >20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20,	LD50 > 5000 mg/kg (Rattus)	LD50 > 3160 mg/kg	LC50 Inhalation(4h) >5266
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	mg/m³ (Rattus)
< 0.03% aromatics		OECD 402	
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m³ (Rattus) 4 h
[D4]	OECD 401	OECD 402	-
4,5-dichloro-2-octyl-2H-isothiaz	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus	=0.26 mg/L (Rattus) 4 h
ol-3-one [DCOIT]		cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationThe assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
	Rabbit	Dermal		6	Product score <=1	
					Non-irritant	
	Rabbit	Dermal		6 days	Product score <=1	
					Non-irritant	

Serious eye damage/eye irritation

By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye		6 days	Product score <=1 Non-irritant

Respiratory or skin sensitisationNo classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information						
Method	Species	Exposure route	Results			
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses			
Sensitisation			were observed			

Octamethylcyclotetrasiloxane [D4] (556-67-2)					
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)					
Method Species Exposure route Results					
OECD 406	Guinea pig	Dermal	Sensitising		

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons,	EL50 (72h)	LL50 (96h) >	-	LL50 (48h)>		
C15-C20, n-alkanes,	>10,000 mg/L	1028 mg/L		3193 mg/l		
isoalkanes, cyclics, <	(Skeletonema	(Scophthalmus		(Acartia tonsa)		
0.03% aromatics	costatum)	maximus)				
RR-100252-4	ISO 10253	OECD 203				
Triacetoxy(propyl)silane	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
17865-07-5	approx. 24	108.89 mg/L		89.59 mg/L		
	mg/l(Pseudokirc					
henriella						
	subpicata)					
Octamethylcyclotetrasil	-	LC50:	-	EC50:		10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		
556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				

United Kingdom - BE Page 9 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

		rerio)				
4,5-dichloro-2-octyl-2H-	EC50 (72h)	LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus	mykiss)(OECD		(OECD 202)		
	subspicatus)(OE	203)				
	CD 201)					

12.2. Persistence and degradability

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days
Anaerobic Transformation in Aquatic			-
Sediment Systems			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

	Chemical name	Partition coefficient		
Triacetoxy(propyl)silane Octamethylcyclotetrasiloxane [D4]		1.23		
		6.49		
	4.5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

	70(0) 0.00000 00 . 2 . 02.	
Chemical name	PBT and vPvB assessment	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	Not PBT/vPvB	
aromatics		
Triacetoxy(propyl)silane	Not PBT/vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	Not PBT/vPvB	

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment

Based on available data, the classification criteria are not met.

Component Information			
Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Method	Results	Species	
Endocrine disrupting properties in accordance	Negative.		
with the criteria set out in Commission			
Delegated Regulation (EU) 2017/2100(3) or			
Commission Regulation (EU) 2018/605(4).			

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.

United Kingdom - BE Page 10 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

PMT or vPvM propertiesBased on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 Not regulated
 Not regulated
 Not regulated
 Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

United Kingdom - BE Page 11 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

United Kingdom - BE Page 12 / 13

EVO-STIK MULTI-PURPOSE SILICONE SEALANT BROWN

Supercedes date 09-Feb-2023

Revision date 10-Nov-2025 Revision Number 2.03

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways H314 - Causes severe skin burns and eye damage H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 10-Nov-2025

Indication of changes

Revision Note Not applicable.

Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13