



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK GLAZING SILICONE SEALANT CLEAR**  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** EVO-STIK GLAZING SILICONE SEALANT CLEAR  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant.  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

### 2.2. Label elements

**Signal word**  
None

**Hazard statements**  
H412 - Harmful to aquatic life with long lasting effects.

**EU Specific Hazard Statements**  
EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

**Precautionary Statements - EU (§28, 1272/2008)**  
P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P273 - Avoid release to the environment  
P501 - Dispose of contents/ container to an approved waste disposal plant

### 2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

**PBT & vPvB**  
This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	40 - <80	Asp. Tox. 1 (H304)		01-2119827000-58-XXXX
Triacetoxypoly(propyl)silane	241-816-9	17865-07-5	1- <2.5	Skin Corr. 1B (H314) (EUH071)		01-2119966899-07-XXXX
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	264-843-8	64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (H410) M=100 (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	-

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

**Skin contact** Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

**Ingestion** Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

#### **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Treat symptomatically.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon dioxide (CO<sub>2</sub>). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

#### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

#### **6.2. Environmental precautions**

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

#### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### **6.4. Reference to other sections**

**Reference to other sections** See section 8 for more information. See section 13 for more information.

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

Chemical name	European Union	United Kingdom
Acetic acid 64-19-7	TWA: 25 mg/m <sup>3</sup> TWA: 10 ppm STEL: 50 mg/m <sup>3</sup> STEL: 20 ppm	TWA: 10 ppm TWA: 25 mg/m <sup>3</sup> STEL: 20 ppm STEL: 50 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)** No information available.

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

#### Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.

**Skin and body protection** None under normal use conditions.

**Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Recommended filter type: especially in confined areas.  
Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Clear, colourless
Odour	Acetic acid
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	0.94	
Water solubility	Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	> 21 mm <sup>2</sup> /s	@ 40°C
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

### 9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Density	0.94 g/cm <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Numerical measures of toxicity

##### Acute toxicity

##### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 Inhalation(4h) >5266 MG/M3 (Rattus)
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal		6 days	Product score <=1 Non-irritant

**Serious eye damage/eye irritation** By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye		6 days	Product score <=1 Non-irritant

**Respiratory or skin sensitisation** May produce an allergic reaction. No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Triacetoxyl(propyl)silane 17865-07-5	EC50 (72h): approx. 24 mg/l(Pseudokirchneriella subpicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OECD 201)	LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss)(OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems		Half-life	1.1-1.3 days

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Triacetoxyl(propyl)silane 17865-07-5	1.23	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	4.4	13

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	The substance is not PBT / vPvB



# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supercedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

Triacetoxyp(propyl)silane 17865-07-5	The substance is not PBT / vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	The substance is not PBT / vPvB

## 12.6. Other adverse effects

Other adverse effects No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

EVO-STIK GLAZING SILICONE SEALANT CLEAR  
Supersedes Date: 19-Oct-2020

Revision date 20-Oct-2021  
Revision Number 2

## European Union

### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Full text of H-Statements referred to under section 3**

EUH071 - Corrosive to the respiratory tract  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure

# SAFETY DATA SHEET

**EVO-STIK GLAZING SILICONE SEALANT CLEAR**  
**Supersedes Date:** 19-Oct-2020

**Revision date** 20-Oct-2021  
**Revision Number** 2

---

EWC European Waste Catalogue

**Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 20-Oct-2021

**Indication of changes**

**Revision note** SDS sections updated, 2, 3, 11, 12, 13, 15, 16.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**