



SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT

Product Code(s)

30800828
30800828

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Sealant

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Carcinogenicity

Category 2 - (H351)

Label elements

Health hazard



SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Signal word
Warning

Hazard statements
H351 - Suspected of causing cancer

Precautionary Statements - Prevention

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P281 - Use personal protective equipment as required

Precautionary Statements - Response

P308 + P313 - IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing
Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing
Causes mild skin irritation

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
2-Butanone, O,O',O''-(methylsilylydyne)trioxime	22984-54-9	< 5%
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	< 2 %
2-Butanone, oxime	96-29-7	< 2%
Toluene	108-88-3	< 0.5%
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact If skin irritation persists, call a physician.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapors.

Hazardous combustion products Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feeding stuffs.

Recommended storage temperature Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Incompatible materials Strong oxidizing agents.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	Australia
Toluene 108-88-3	50 ppm TWA 191 mg/m ³ TWA 150 ppm STEL 574 mg/m ³ STEL

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing.

Hand protection Wear suitable gloves. Butyl rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Nitrile rubber. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Organic gases and vapors filter conforming to EN 14387. Recommended filter type: White. Brown.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid
Appearance Viscous
Color Clear
Odor Organic
Odor threshold No information available

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Property	Values	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.01	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	150000 250000 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Solid content (%)	No information available	
Density	No information available	
VOC Content (%)		No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Hazardous decomposition products Carbon oxides. 2-Butanone, oxime. Methyl alcohol. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms Prolonged contact may cause redness and irritation.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, O,O',O''-(methylsilylidyne)trioxime	LD50 = 2463 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol) 1.5 - 2.44 mg/L air
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	SafeWork Australia	European Union	IARC
2-Butanone, oxime	Carc. 2	Carc. 1B	

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

96-29-7			
Toluene 108-88-3			Group 3

IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Component Information		
2-Butanone, oxime (96-29-7)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity No information available.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
2-Butanone, O,O',O''-(methylsilylidyn e)trioxime 22984-54-9	EC50 (72h) = 94 mg/L (Pseudokirchneriella subcapitata) OECD 201	EC50 (96h) >120 mg/L (Oncorhynchus mykiss) Freshwater static (OECD guideline 203)	-	EC50 (48h) > 120 mg/L (Daphnia magna) OECD 202
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio) Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability Not readily biodegradable. Product cures with moisture.

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
2-Butanone, O,O',O''-(methylsilyldiyl)trioxime 22984-54-9	1.69
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3
2-Butanone, oxime 96-29-7	0.65
Toluene 108-88-3	2.7

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

National pollutant inventory
Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene 108-88-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS	Listed
NZIoC	Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Listed
PICCS	Listed

Legend:

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 01-Sep-2021

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

SAFETY DATA SHEET

ROOF & GUTTER PREMIUM SILICONE TRANSLUCENT
Revision Number 3

Revision date 01-Sep-2021
Supersedes Date: 11-Nov-2019

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet