



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**EVO-STIK ADHESIVE CLEANER**  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name EVO-STIK ADHESIVE CLEANER

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cleaning agent

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Flammable liquids	Category 2 - (H225)
Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Category 3 Target organ effects: Narcotic effects.	
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Aspiration hazard	Category 1 - (H304)
Hazardous to the aquatic environment - chronic	Category 2 - (H411)

### 2.2. Label elements

Contains Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane; Ethyl acetate; Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Acetone

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04



**Signal word**  
Danger

## Hazard statements

H225 - Highly flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H336 - May cause drowsiness or dizziness.  
H373 - May cause damage to organs through prolonged or repeated exposure.  
H411 - Toxic to aquatic life with long lasting effects.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P271 - Use only outdoors or in a well-ventilated area  
P273 - Avoid release to the environment  
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P331 - Do NOT induce vomiting  
P391 - Collect spillage  
P405 - Store locked up  
P501 - Dispose of contents/ container to an approved waste disposal plant

## Additional information

This product requires child resistant fastenings when supplied to the general public unless the product is placed on the market in the form of aerosols or in a container with a sealed spray attachment. This product requires tactile warnings if supplied to the general public.

## 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Hydrocarbons,	>25 - <40	01-2119486291	926-605-8	STOT SE 3 (H336)	-	-	-	-

# SAFETY DATA SHEET

**EVO-STIK ADHESIVE CLEANER**  
**Supersedes date** 03-Dec-2024

**Revision date** 23-Mar-2026  
**Revision Number** 3.04

C6-C7, isoalkanes, cyclics, <5% n-hexane RR-100223-9		-36-xxxx		Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225) (EUH066) [E]				
Ethyl acetate 141-78-6	>25 - <40	01-2119475103 -46-XXXX	205-500-4 (607-022-00-5)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	10 - <20	01-2119475515 -33-xxxx	927-510-4	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	-	-	-
Acetone 67-64-1	10 - <20	01-2119471330 -49-XXXX	200-662-2 (606-001-00-8)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	10 - <20	01-2119484651 -34-XXXX	931-254-9	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066) [E]	-	-	-	P
n-Hexane contained in UVCB 110-54-3	1 - <2.5	-	203-777-6 (601-037-00-0)	Skin Irrit. 2 (H315) Repr. 2 (H361 f) STOT SE 3 (H336) STOT RE 1 (H372) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	-	-	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

**Full text of H- and EUH-phrases: see section 16**

**Substance of unknown or variable composition, complex reaction products or biological material (UVCB)**

### **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5%	926-605-8	RR-100223-9	-	3400	-	-	-

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
n-hexane							
Ethyl acetate	205-500-4 (607-022-00-5)	141-78-6	-	-	-	14.4131	-
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	-	-	-	-	-
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	16750	3350	-	-	-
n-Hexane contained in UVCB	203-777-6 (601-037-00-0)	110-54-3	-	-	-	-	-

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.	SVHC candidates
n-Hexane contained in UVCB	110-54-3	X

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Inhalation</b>	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Erythema (skin redness). May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapour
-----------------	---

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Effects of Exposure** May cause damage to organs through prolonged or repeated exposure.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Dry chemical. Carbon dioxide (CO<sub>2</sub>). Water spray. Alcohol resistant foam.

**Unsuitable extinguishing media** No information available.

#### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Risk of ignition. Vapours may form explosive mixture with air. Most vapours are heavier than air. Vapours may spread along ground and collect in low or confined areas (sewers, basements, tanks).

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

#### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

#### **6.2. Environmental precautions**

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

#### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Methods for cleaning up** Take precautionary measures against static discharges. Dam up. Soak up with inert

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Eliminate all ignition sources if safe to do so. Residues which cannot be recycled are disposed of as chemical waste. Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protective equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

**Recommended storage temperature** Keep at temperatures between 5 and 25 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Cleaning agent.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane RR-100223-9	-	VME= 400 mg/m <sup>3</sup> (supplier)
Ethyl acetate	TWA: 734 mg/m <sup>3</sup> ;	TWA: 734 mg/m <sup>3</sup> ;

# SAFETY DATA SHEET

**EVO-STIK ADHESIVE CLEANER**  
**Supersedes date** 03-Dec-2024

**Revision date** 23-Mar-2026  
**Revision Number** 3.04

141-78-6	TWA: 200 ppm; STEL: 1468 mg/m <sup>3</sup> ; STEL: 400 ppm;	TWA: 200 ppm; STEL: 1468 mg/m <sup>3</sup> ; STEL: 400 ppm;
Acetone 67-64-1	TWA: 500 ppm; TWA: 1210 mg/m <sup>3</sup> ;	TWA: 500 ppm; TWA: 1210 mg/m <sup>3</sup> ; STEL: 1500 ppm; STEL: 3620 mg/m <sup>3</sup> ;
n-Hexane contained in UVCB 110-54-3	TWA: 20 ppm; TWA: 72 mg/m <sup>3</sup> ;	TWA: 20 ppm; TWA: 72 mg/m <sup>3</sup> ; STEL: 60 ppm; STEL: 216 mg/m <sup>3</sup> ;

Chemical name	European Union	Ireland	United Kingdom
Acetone 67-64-1	-	50 mg/L (urine - Acetone end of shift)	-
n-Hexane contained in UVCB 110-54-3	-	0.4 mg/L (urine - 2,5-Hexanedione end of shift at end of workweek)	-

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Hydrocarbons, C6-C7, isoalkanes, cyclics, &lt;5% n-hexane (RR-100223-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	13 964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	5 306 mg/m <sup>3</sup>	

<b>Ethyl acetate (141-78-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	

<b>Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d	

<b>Acetone (67-64-1)</b>			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

**EVO-STIK ADHESIVE CLEANER**  
**Supersedes date** 03-Dec-2024

**Revision date** 23-Mar-2026  
**Revision Number** 3.04

		(DNEL)	
Long term Systemic health effects worker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Inhalation	1210 mg/m <sup>3</sup>	

### Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m <sup>3</sup>	

### Derived No Effect Level (DNEL)

#### Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (RR-100223-9)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	1 377 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	1 131 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	1 301 mg/kg bw/d	

#### Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	367 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	367 mg/m <sup>3</sup>	

#### Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Type	Exposure route	Derived No Effect Level	Safety factor
------	----------------	-------------------------	---------------

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
 Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
 Revision Number 3.04

		(DNEL)	
Consumer Long term Systemic health effects	Inhalation	447 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d	

Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

Predicted No Effect Concentration (PNEC)	
Ethyl acetate (141-78-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.24 mg/l
Marine water	0.024 mg/l
Freshwater sediment	1.15 mg/kg
Marine sediment	0.115 mg/kg
Soil	0.148 mg/kg
Microorganisms in sewage treatment	650 mg/l

Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

### Personal protective equipment

#### Eye/face protection

Tight sealing safety goggles. Face protection shield.

#### Hand protection

Wear protective gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

#### Skin and body protection

Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Liquid  
**Appearance** Liquid  
**Colour** Colourless  
**Odour** Solvent.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	
<b>Initial boiling point and boiling range</b>	>= 48 °C	
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	>= -20 °C	
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	>= 0.4 mPa s	
<b>Water solubility</b>	Insoluble in water.	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	<110 kPa	None known
<b>Relative density</b>	No data available	None known
<b>Bulk density</b>	No data available	
<b>Liquid Density</b>	0.78	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

**Solid content (%)** No information available  
**VOC content** No data available

#### 9.2.1. Information with regards to physical hazard classes

Not applicable

#### 9.2.2. Other safety characteristics

No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

## Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge Yes.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

## 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

#### Acute toxicity

##### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/L  
ATEmix (inhalation-vapour) >20 mg/L

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	LD50 >16.5 g/Kg (Rattus) (OECD Guideline 201)	LD50 >3.35 g/Kg (Oryctolagus cuniculus) (OECD 402)	LC50 (4h) =73680 ppm (Vapour - Rat)
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m <sup>3</sup> (vapour) (rat OECD 403)
n-Hexane contained in UVCB	= 25 g/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 48000 ppm ( Rat ) 4 h

Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

Ethyl acetate (141-78-6)			
Acetone (67-64-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Not a skin sensitiser

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information		
Ethyl acetate (141-78-6)		
Method	Species	Results
OECD Test No. 474: Mammalian Erythrocyte Micronucleus Test	in vivo Hamster	Negative
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro Salmonella typhimurium	Negative
OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test	in vitro Hamster Ovary	Negative

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
n-Hexane contained in UVCB	Repr. 2

**STOT - single exposure** May cause drowsiness or dizziness.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Experiences made in practice					Narcotic effects

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

H373 - May cause damage to the following organs through prolonged or repeated exposure: nervous system.

Acetone (67-64-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Oral	200-3400 mg/kg bw/d	91 days	No Observed Adverse Effect Level LOAEL 1700 mg/kg bw/d
Not specified	Rat	Inhalation	19000 ppm	14, 28, 56 days	NOAEC 19000 ppm No Observed Adverse Effect Level

**Aspiration hazard** May be fatal if swallowed and enters airways.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C6-C7,	EL50 (72h) = 55	LL50	-	EL50 (48h) = 3		

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

isoalkanes, cyclics, <5% n-hexane RR-100223-9	mg/l (Pseudokirchneriella subcapitata)	(96h)=12mg/L (Oncorhynchus mykiss)Semi-static OECD 203		mg/l (Daphnia magna)		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RR-100219-3	ErL50 (72h) = 10-30 mg/L (Pseudokirchneriella subcapitata)	LL50 (96h) >13.4 mg/L (Oncorhynchus mykiss) OECD 203	-	EL50 (48h) = 3.0 mg/L (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
n-Hexane contained in UVCB 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	-		

Substance of unknown or variable composition, complex reaction products or biological material (UVCB)

## 12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (RR-100223-9)			
Method	Exposure time	Value	Results
	28 days	biodegradation	98 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	98%	Readily biodegradable

Acetone (67-64-1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	91 % Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
---------------	-----------------------

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

Ethyl acetate	0.73
Acetone	-0.24
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
n-Hexane contained in UVCB	4

## 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Ethyl acetate	Not PBT/vPvB
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	Not PBT/vPvB
Acetone	Not PBT/vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Not PBT/vPvB
n-Hexane contained in UVCB	Not PBT/vPvB

## 12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

## 12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.  
PMT or vPvM properties Based on available data, the classification criteria are not met.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances  
15 01 10\*: Packaging containing residues of or contaminated by dangerous substances

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

14.1 UN number or ID number UN1263  
14.2 UN proper shipping name Paint  
14.3 Transport hazard class(es) 3

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

Labels 3  
14.4 Packing group II  
Description UN1263, Paint, 3, II, (D/E), Environmentally Hazardous  
14.5 Environmental hazards Yes  
14.6 Special precautions for user  
Special Provisions 163, 640D, 650, 367  
Classification code F1  
Tunnel restriction code (D/E)  
Limited quantity (LQ) 5 L  
ADR Hazard Id (Kemmler Number) 33

## IMDG

14.1 UN number or ID number UN1263  
14.2 UN proper shipping name Paint  
14.3 Transport hazard class(es) 3  
14.4 Packing group I  
Description UN1263, Paint, 3, I, (-20°C c.c.), Marine pollutant  
14.5 Marine pollutant P  
14.6 Special precautions for user  
Special Provisions 163, 367  
Limited Quantity (LQ) 500 mL  
EmS-No. F-E, S-E  
14.7 Maritime transport in bulk according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1263  
14.2 UN proper shipping name Paint  
14.3 Transport hazard class(es) 3  
14.4 Packing group I  
Description UN1263, Paint, 3, I  
14.5 Environmental hazards Yes  
14.6 Special precautions for user  
Special Provisions A3, A72, A192  
Limited quantity (LQ) Forbidden  
ERG Code 3L

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)  $\geq 0.1\%$

Chemical name	CAS No.
n-Hexane contained in UVCB	110-54-3

# SAFETY DATA SHEET

**EVO-STIK ADHESIVE CLEANER**  
Supercedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

## Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

## Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0		25000

## Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted	Registration
Acetone - 67-64-1	Regulated		

## Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

## Regulation (EC) No. 648/2004 (Detergents regulation)

No ingredients to be mentioned according to the rules

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

# SAFETY DATA SHEET

EVO-STIK ADHESIVE CLEANER  
Supersedes date 03-Dec-2024

Revision date 23-Mar-2026  
Revision Number 3.04

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking  
H225 - Highly flammable liquid and vapour  
H304 - May be fatal if swallowed and enters airways  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H372 - Causes damage to organs through prolonged or repeated exposure  
H411 - Toxic to aquatic life with long lasting effects

#### Notes relating to the identification, classification and labelling of substances

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs  
Revision date 23-Mar-2026

#### Indication of changes

Revision Note SDS sections updated, 2, 3, 5, 6, 7, 8, 15.  
Training Advice No information available  
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**