

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

#### IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023

### Revision date 15-Nov-2024

Revision Number 2.02

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier							
Product Name	IDENDEN ET-150 SPRAYABLE VAPOL	JR BARRIER COATING GREY					
Pure substance/mixture	Mixture	Mixture					
1.2. Relevant identified uses of	f the substance or mixture and uses advise	ed against					
Recommended use	Primers, Sealers, and Undercoaters						
Uses advised against	None known						
1.3. Details of the supplier of t	he safety data sheet						
<u>Company Name</u> Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36							
E-mail address	SDS.box-EU@bostik.com						
1.4. Emergency telephone nui	nber						
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm NHS: 111	Mon-Fri)					
SECTION 2: Hazards ide	ntification						
2.1. Classification of the subs	tance or mixture						
GB CLP (SI 2020/1567 as ame	nded)						
Skin sensitisation		Category 1 - (H317)					

### 2.2. Label elements

Contains Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imidazole-2,5(1H,3H)-dione; 1,2-benzisothiazol-3(2H)-one [BIT]; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word Warning

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

#### Hazard statements

H317 - May cause an allergic skin reaction.

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing vapours

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

### 2.3. Other hazards

No information available.

### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

### **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	Notes
Titanium dioxide 13463-67-7	1 - <5	01-2119489379 -17-XXXX	236-675-5 (022-006-00-2)	[C]	-	-	-	V,W,10
Diethylene glycol monobutyl ether acetate 124-17-4	1 - <2.5	01-2119475110 -51-XXXX	204-685-9	Eye Irrit. 2 (H319)	-	-	-	-
Tetrahydro-1,3,4,6-t etrakis(hydroxymeth yl)imidazo[4,5-d]imid azole-2,5(1H,3H)-dio ne 5395-50-6		No data available	226-408-0	Skin Sens. 1B (H317)	-	-	-	-
1,2-benzisothiazol-3( 2H)-one [BIT] 2634-33-5	0.01 < 0.036	01-2120761540 -60-XXXX		Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		1	1	-
reaction mass of 5-chloro-2-methyl-2 H-isothiazol-3-one and 2-methyl-2H-isothiaz	0.0015 - < 0.0025	No data available		Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330)	C>=0.6%	100	100	В

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

					-
ol-3-one (3:1)		Eye Dam. 1 (H318)	Skin Corr. 1C		
[C(M)IT/MIT]		Skin Sens. 1A	:: C>=0.6%		
55965-84-9		(H317)	Skin Irrit. 2 ::		
		Aquatic Acute 1	0.06%<=C<0		
		(H400)	.6%		
		Aquatic Chronic 1	Skin Sens.		
		(H410)	1A ::		
		(EUH071)	C>=0.0015%		

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[*C*] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Note V - If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation. Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10 µm.

### Full text of H- and EUH-phrases: see section 16

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Diethylene glycol monobutyl ether acetate	204-685-9	124-17-4	-	-	-	-	-
Tetrahydro-1,3,4,6-tetra kis(hydroxymethyl)imid azo[4,5-d]imidazole-2,5 (1H,3H)-dione		5395-50-6	-	-	-	-	-
1,2-benzisothiazol-3(2 H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21 +	0.21 +
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT]		55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

SECTION 4: First aid measu	res			
4.1. Description of first aid measured	res_			
General advice	Show this safety data sheet to the doctor in attendance.			
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.			
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.			
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.			
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.			
4.2. Most important symptoms and	d effects, both acute and delayed			
Symptoms	Itching. Rashes. Hives.			
Effects of Exposure	No information available.			
4.3. Indication of any immediate m	edical attention and special treatment needed			
Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.			
SECTION 5: Firefighting me	asures			
5.1. Extinguishing media				
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Unsuitable extinguishing media	No information available.			
5.2. Special hazards arising from t	he substance or mixture			
Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.			
Hazardous combustion products	Carbon oxides. Hydrogen chloride. Silicon dioxide.			
5.3. Advice for firefighters				
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.			
SECTION 6: Accidental release measures				
6.1. Personal precautions, protect	ive equipment and emergency procedures			
Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2. Environmental precautions				

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

Environmental precautions	See Section 12 for additional Ecological Information.				
6.3. Methods and material for cont	ainment and cleaning up				
Methods for containment	Prevent further leakage or spillage if safe to do so.				
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.				
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.				
6.4. Reference to other sections					
Reference to other sections	See section 8 for more information. See section 13 for more information.				
SECTION 7: Handling and st	orage				
7.1. Precautions for safe handling	_				
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.				
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.				
7.2. Conditions for safe storage, in	cluding any incompatibilities				
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing. Protect from moisture.				
Recommended storage temperature	Keep at temperatures between 5 and 35 °C.				
7.3. Specific end use(s)					
<b>Specific use(s)</b> Primers, Sealers, and Undercoaters.					
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.				
Other information	Observe technical data sheet.				
SECTION 8: Exposure contr	SECTION 8: Exposure controls/personal protection				

### 8.1. Control parameters

**Exposure Limits** 

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Kaolin	-	TWA: 2 mg/m <sup>3</sup>
1332-58-7		STEL: 6 mg/m <sup>3</sup>
Limestone	-	TWA: 10 mg/m <sup>3</sup>
1317-65-3		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Aluminum hydroxide (Al(OH)3)	-	TWA: 10 mg/m <sup>3</sup>
21645-51-2		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 4 mg/m <sup>3</sup>

**IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY** Supercedes date 24-Jul-2023

### Revision date 15-Nov-2024

Revision Number 2.02

		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Carbon black	-	TWA: 3.5 mg/m <sup>3</sup>
1333-86-4		STEL: 7 mg/m <sup>3</sup>
Silica, amorphous	-	TWA: 6 mg/m <sup>3</sup>
7631-86-9		TWA: 2.4 mg/m <sup>3</sup>
		STEL: 18 mg/m <sup>3</sup>
		STEL: 7.2 mg/m <sup>3</sup>

### Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)							
Titanium dioxide (13463-67-7)	Titanium dioxide (13463-67-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
worker Long term Local health effects	Inhalation	10 mg/m³					

Diethylene glycol monobutyl ether acetate (124-17-4)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker	Dermal	100 mg/kg bw/d				
Systemic health effects						
Long term						

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
worker	Inhalation	6.81 mg/m <sup>3</sup>			
Long term					
Systemic health effects					
worker	Dermal	0.966 mg/kg bw/d			
Long term					
Systemic health effects					

Derived No Effect Level (DNEL)							
Titanium dioxide (13463-67-7	Titanium dioxide (13463-67-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer	Oral	700 mg/kg bw/d					
Long term							
Systemic health effects							

Diethylene glycol monobutyl ether acetate (124-17-4)			
Туре		Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Dermal	60 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	7.9 mg/kg bw/d	

1,2-benzisothiazol-3(2H)-one [BIT]	(2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	1.2 mg/m <sup>3</sup>	

### IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023

### Revision date 15-Nov-2024

Revision Number 2.02

Long term Systemic health effects			
Consumer	Dermal	0.345 mg/kg bw/d	
Long term			
Systemic health effects			

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Diethylene glycol monobutyl ether acetate (124-17-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.108 mg/l
Marine water	0.0108 mg/l
Freshwater - intermittent	0.6 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	0.8 mg/kg dry weight
Marine sediment	0.08 mg/kg dry weight
Soil	0.29 mg/kg dry weight

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	4.03 μg/l	
Marine water	0.403 µg/l	
Sewage treatment plant	1.03 mg/l	
Freshwater sediment	49.9 µg/l	
Marine sediment	4.99 μg/l	
Soil	3 mg/kg dry weight	

### 8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye/face protection	Wear safety glasses with side shields (or goggles). Avoid contact with eyes. Eye protection must conform to standard EN 166.
Hand protection	Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.
Skin and body protection	Wear suitable protective clothing.
Respiratory protection	During spraying wear suitable respiratory equipment.
Environmental exposure controls	Do not allow into any sewer, on the ground or into any body of water.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Liquid

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023

### Revision date 15-Nov-2024

Revision Number 2.02

Colour Odour	Grey Acrylic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	100 °C	None known
range		
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	> 80 °C	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН	7 - 9	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	Miscible in water.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.26	None known
Bulk density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information Solid content (%) VOC content	60	No data available
9.2.1. Information with regards to p Not applicable	physical hazard classes	

9.2.2. Other safety characteristics No information available

**SECTION 10: Stability and reactivity** 

10.1. Reactivity	
Reactivity	No information available.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
10.3. Possibility of hazardous reactions	

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid	
Conditions to avoid	Do not freeze. Protect from moisture.
10.5. Incompatible materials	
Incompatible materials	None known based on information supplied.
10.6. Hazardous decomposition pro	oducts
Hazardous decomposition products	Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Information on likely routes of exposure

### **Product Information**

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical	, chemical and toxicological characteristics
O	Itabing Bashaa Llives

Symptoms

Itching. Rashes. Hives.

Acute toxicity

### Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

>2000 mg/kg
>2000 mg/kg
>20000 ppm
>5 mg/l
>20 mg/l

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h
Diethylene glycol monobutyl ether acetate	=6500 mg/kg (Rattus)	5400 - 5700 mg/kg (Oryctolagus cuniculus)	=72500 mg/m <sup>3</sup> (Rattus) 4 h
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazo	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

### IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023

Revision date 15-Nov-2024

Revision Number 2.02

I-3-one and		
2-methyl-2H-isothiazol-3-one		
(3:1) [C(M)IT/MIT]		

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical na	ime	European Union
Titanium dio	xide	Carc. 2
Reproductive toxicity	Based on available data,	the classification criteria are not met.
STOT - single exposure	Based on available data,	the classification criteria are not met.
STOT - repeated exposure	Based on available data,	the classification criteria are not met.
Aspiration hazard	Based on available data,	the classification criteria are not met.
11.2. Information on other hazard	<u>ls</u>	
11.2.1. Endocrine disrupting pro	perties	
Endocrine disrupting properties	No information available.	
11.2.2. Other information		
Other adverse effects	No information available.	

Revision Number 2.02

### **SECTION 12: Ecological information**

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Diethylene glycol monobutyl ether acetate 124-17-4		LC50: 50 - 70mg/L (96h, Brachydanio rerio) LC50: =77mg/L (96h, Pimephales promelas)	-	LC50: =665mg/L (48h, Daphnia magna)		
Tetrahydro-1,3,4,6-tetr akis(hydroxymethyl)imi dazo[4,5-d]imidazole-2, 5(1H,3H)-dione 5395-50-6	Desmodesmus subspicatus (OECD 201)	EC50 (96h) =17.6 mg/L (Brachydanio rerio) (OECD 203)	-	EC50 (48h) >38.9 mg/L (Daphnia magna) (OECD 202)		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5		LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner	· · · ·	<u> </u>	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

### 12.2. Persistence and degradability

Persistence and degradability

No information available.

Diethylene glycol monobutyl ether acetate (124-17-4)				
Method	Exposure time	Value	Results	
OECD Test No. 301C: Ready	28 days	100%	Readily biodegradable	
Biodegradability: Modified MITI Test	-			
(I) (TG 301 C)				

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)				
Method	Exposure time	Value	Results	
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	, , , , , , , , , , , , , , , , , , ,	biodegradation	Not readily biodegradable	

### 12.3. Bioaccumulative potential

### **Bioaccumulation**

### **Component Information**

### IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023

Revision date 15-Nov-2024

Revision Number 2.02

Chemical name	Partition coefficient
Diethylene glycol monobutyl ether acetate	1.7
Tetrahydro-1,3,4,6-tetrakis(hydroxymethyl)imidazo[4,5-d]imida	2
zole-2,5(1H,3H)-dione	
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

### 12.4. Mobility in soil

Mobility in soil	No information available.
12.5. Results of PBT and vPvB	assessment

#### PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB
Diethylene glycol monobutyl ether acetate	The substance is not PBT / vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

### **SECTION 14: Transport information**

Note:

Keep from freezing.

I and	trans	nort	(RID)
Lanu	uans	ρυιι	/1/10/

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

### IMDG

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

- 14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group 14.5 Marine pollutant NP 14.6 Special precautions for user **Special Provisions** None 14.7 Maritime transport in bulk according to IMO instruments Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable Air transport (ICAO-TI / IATA-DGR) 14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated
- 14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable
- 14.6 Special precautions for user

   Special Provisions
   None

### Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

Ozone-depleting substances (ODS) Regulation (EU) 2024/590 Not applicable

Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

### SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### Notes relating to the identification, classification and labelling of substances

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Note V - If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio  $\ge 3:1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation **Notes relating to the classification and labelling of mixtures** 

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu$ m

Legend	
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure

IDENDEN ET-150 SPRAYABLE VAPOUR BARRIER COATING GREY Supercedes date 24-Jul-2023 Revision date 15-Nov-2024

Revision Number 2.02

EWC ADR	European Waste Catalogue European Agreement concerning the International Carriage of Dangerous Goods by
IMDG IATA	Road International Maritime Dangerous Goods (IMDG) International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sour No information available Prepared By Revision date Indication of changes	ces for data Product Safety & Regulatory Affairs 15-Nov-2024
Revision Note	SDS sections updated, 3.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet