

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**EVO-STIK GRIPFILL ADHESIVE Supercedes date** 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK GRIPFILL ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

## 1.3. Details of the supplier of the safety data sheet

### **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

# **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

| Flammable liquids                              | Category 2 - (H225) |
|--|---------------------|
| Skin irritation                                | Category 2 - (H315) |
| Eye irritation                                 | Category 2 - (H319) |
| Hazardous to the aquatic environment - chronic | Category 3 - (H412) |

### 2.2. Label elements



Signal word Danger

United Kingdom - BE Page 1 / 16

### EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023

Revision date 11-Jun-2025 Revision Number 8

#### **Hazard statements**

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

H225 - Highly flammable liquid and vapour.

### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Additional information**

This product requires tactile warnings if supplied to the general public.

### 2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

#### 3.2 Mixtures

| Chemical name   | Weight-<br>% | REACH<br>registration<br>number | EC No (EU<br>Index No) | Classification<br>according to<br>Regulation (EC) No.<br>1272/2008 [CLP]  | concentration |   | M-Factor<br>(long-ter<br>m) | Notes |
|---|--------------|---------------------------------|------------------------|---|---------------|---|-----------------------------|-------|
| Xylenes (o-, m-, p-<br>isomers)<br>1330-20-7                          | 5 - <10      | 01-2119488216<br>-32-XXXX       |                        | Acute Tox. 4 (H312)<br>Acute Tox. 4 (H332)<br>Skin Irrit. 2 (H315)<br>Eye Irrit. 2 (H319)<br>STOT SE 3 (H335)<br>STOT RE 2 (H373)<br>Asp. Tox. 1 (H304)<br>Aquatic Chronic 3<br>(H412)<br>Flam. Liq. 3 (H226) |               | - | -                           | С     |
| Acetone<br>67-64-1  | 5 - <10      | 01-2119471330<br>-49-XXXX       |                        | Eye Irrit. 2 (H319)<br>STOT SE 3 (H336)<br>Flam. Liq. 2 (H225)<br>(EUH066)  |               | - | -                           | -     |
| Hydrocarbons, C7,<br>n-alkanes,<br>isoalkanes, cyclics<br>RR-100219-3 | 5 - <10      | 01-2119475515<br>-33-xxxx       | 927-510-4              | STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)   |               | - | -                           | -     |

United Kingdom - BE Page 2 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

| Hydrocarbons, C6,<br>isoalkanes, <5%<br>n-hexane<br>64742-49-0 | 1 - <5   | 01-2119484651<br>-34-XXXX | 931-254-9 | STOT SE 3 (H336)<br>Asp. Tox. 1 (H304)<br>Skin Irrit. 2 (H315)<br>Aquatic Chronic 2<br>(H411)<br>Flam Liq. 2 (H225)<br>(EUH066) | - | - | Р |
|--|----------|---------------------------|-----------|---|---|---|---|
| Ethylbenzene<br>100-41-4                                       | 1 - <2.5 | 01-2119489370<br>-35-XXXX |           | Acute Tox. 4 (H332)<br>STOT RE 2 (H373)<br>Asp. Tox. 1 (H304)<br>Aquatic Chronic 3<br>(H412)<br>Flam. Liq. 2 (H225)             | - | - | - |

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

### Full text of H- and EUH-phrases: see section 16

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

| Chemical name  | EC No (EU<br>Index No)      | CAS No.     | Oral LD50<br>mg/kg | Dermal LD50<br>mg/kg | Inhalation<br>LC50 - 4 hour -<br>dust/mist -<br>mg/L | Inhalation<br>LC50 - 4 hour -<br>vapour - mg/L | Inhalation<br>LC50 - 4 hour -<br>gas - ppm |
|--|-----------------------------|-------------|--------------------|----------------------|--|--|--|
| Xylenes (o-, m-, p-<br>isomers)                        | 215-535-7<br>(601-022-00-9) | 1330-20-7   | 2500               | 1990                 | 4.8  | -  | -  |
| Acetone  | 200-662-2<br>(606-001-00-8) | 67-64-1     | 5800               | -                    | -  | -  | -  |
| Hydrocarbons, C7,<br>n-alkanes, isoalkanes,<br>cyclics | 927-510-4                   | RR-100219-3 | -                  | -                    | -  | -  | -  |
| Hydrocarbons, C6,<br>isoalkanes, <5%<br>n-hexane       | 931-254-9                   | 64742-49-0  | 16750              | 3350                 | -  | -  | -  |
| Ethylbenzene   | 202-849-4<br>(601-023-00-4) | 100-41-4    | 3500               | 15400                | 4.99   | 17.6   | -  |

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

United Kingdom - BE Page 3 / 16

**EVO-STIK GRIPFILL ADHESIVE** Supercedes date 09-Jun-2023

Revision date 11-Jun-2025 **Revision Number** 8

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact

Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Wash off immediately with soap and plenty of water while removing all contaminated Skin contact

clothes and shoes. Get medical attention if irritation develops and persists.

Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce Ingestion

vomiting. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

May cause redness and tearing of the eyes. Burning sensation. **Symptoms** 

**Effects of Exposure** No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

## **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

No information available. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

fire extinguishing water must be disposed of in accordance with local regulations.

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide. **Hazardous combustion products** 

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

United Kingdom - BE 4 / 16 Page

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

**Environmental precautions** Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

**Methods for containment**Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to

vapour suppressing foam may be used to reduce vapours. Dyke far anead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

### SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using

this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or

clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

particular national regulations. Store in accordance with local regulations.

Recommended storage

temperature

Keep at temperatures between 5 and 25  $^{\circ}\text{C}.$ 

7.3. Specific end use(s)

Specific use(s) Adhesives.

United Kingdom - BE Page 5 / 16

**EVO-STIK GRIPFILL ADHESIVE Supercedes date** 09-Jun-2023

Revision date 11-Jun-2025 Revision Number 8

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### **Exposure Limits**

| Chemical name                | European Union                | United Kingdom                              |
|------------------------------|-------------------------------|---|
| Kaolin                       | -                             | TWA: 2 mg/m³; respirable dust               |
| 1332-58-7                    |                               | STEL: 6 mg/m <sup>3</sup> ; respirable dust |
| Xylenes (o-, m-, p- isomers) | TWA: 50 ppm;                  | TWA: 50 ppm;                                |
| 1330-20-7                    | TWA: 221 mg/m <sup>3</sup> ;  | TWA: 220 mg/m <sup>3</sup> ;                |
|                              | STEL: 100 ppm;                | STEL: 100 ppm;                              |
|                              | STEL: 442 mg/m <sup>3</sup> ; | STEL: 441 mg/m <sup>3</sup> ;               |
|                              | pSk                           | pSk   |
| Acetone                      | TWA: 500 ppm;                 | TWA: 500 ppm;                               |
| 67-64-1                      | TWA: 1210 mg/m <sup>3</sup> ; | TWA: 1210 mg/m <sup>3</sup> ;               |
|                              |                               | STEL: 1500 ppm;                             |
|                              |                               | STEL: 3620 mg/m <sup>3</sup> ;              |
| Ethylbenzene                 | TWA: 100 ppm;                 | TWA: 100 ppm;                               |
| 100-41-4                     | TWA: 442 mg/m <sup>3</sup> ;  | TWA: 441 mg/m <sup>3</sup> ;                |
|                              | STEL: 200 ppm;                | STEL: 125 ppm;                              |
|                              | STEL: 884 mg/m <sup>3</sup> ; | STEL: 552 mg/m <sup>3</sup> ;               |
|                              | pSk                           | pSk   |

| Chemical name                | European Union | Ireland                            | United Kingdom                      |
|------------------------------|----------------|------------------------------------|-------------------------------------|
| Xylenes (o-, m-, p- isomers) | •              | 1.5 g/g Creatinine (urine -        | 650 mmol/mol creatinine - urine     |
| 1330-20-7                    |                | Methylhippuric acids end of shift) | (Methyl hippuric acid) - post shift |
| Acetone                      | -              | 50 mg/L (urine - Acetone end of    | -                                   |
| 67-64-1                      |                | shift)                             |                                     |
| Ethylbenzene                 | -              | 0.7 g/g Creatinine (urine - sum of | -                                   |
| 100-41-4                     |                | Mandelic acid and Phenylglyoxylic  |                                     |
|                              |                | acid end of shift at end of        |                                     |
|                              |                | workweek)                          |                                     |
|                              |                | 0.7 g (end-exhaled air - not       |                                     |
|                              |                | critical)                          |                                     |

Derived No Effect Level (DNEL) No information available

| Derived No Effect Level (DN   | Derived No Effect Level (DNEL) |                                |               |  |  |  |
|---|--------------------------------|--------------------------------|---------------|--|--|--|
| Xylenes (o-, m-, p- isomers)  | (1330-20-7)                    |                                |               |  |  |  |
| Туре  | Exposure route                 | Derived No Effect Level (DNEL) | Safety factor |  |  |  |
| Long term<br>Systemic health effects<br>worker                          | Dermal                         | 180 mg/kg bw/d                 |               |  |  |  |
| Long term<br>Systemic health effects<br>worker                          | Inhalation                     | 77 mg/m³                       |               |  |  |  |
| Short term<br>Local health effects<br>Systemic health effects<br>worker | Inhalation                     | 289 mg/m³                      |               |  |  |  |

| Acetone (67-64-1)       |                |                         |               |
|-------------------------|----------------|-------------------------|---------------|
| Туре                    | Exposure route | Derived No Effect Level | Safety factor |
|                         |                | (DNEL)                  |               |
| Long term               | Dermal         | 186 mg/kg bw/d          |               |
| Systemic health effects |                |                         |               |

United Kingdom - BE Page 6 / 16

## **EVO-STIK GRIPFILL ADHESIVE Supercedes date** 09-Jun-2023

Revision date 11-Jun-2025 Revision Number 8

| worker                  |            |                        |  |
|-------------------------|------------|------------------------|--|
| Short term              | Inhalation | 2420 mg/m³             |  |
| Local health effects    |            |                        |  |
| worker                  |            |                        |  |
| Long term               | Inhalation | 1210 mg/m <sup>3</sup> |  |
| Systemic health effects |            |                        |  |
| worker                  |            |                        |  |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3) |                |                                |               |  |  |
|--|----------------|--------------------------------|---------------|--|--|
| Туре   | Exposure route | Derived No Effect Level (DNEL) | Safety factor |  |  |
| worker<br>Long term<br>Systemic health effects                 | Inhalation     | 2085 mg/m³                     |               |  |  |
| worker<br>Long term<br>Systemic health effects                 | Dermal         | 300 mg/kg bw/d                 |               |  |  |

| Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0) |                |                                |               |  |  |
|---|----------------|--------------------------------|---------------|--|--|
| Type  | Exposure route | Derived No Effect Level (DNEL) | Safety factor |  |  |
| worker<br>Systemic health effects<br>Long term          | Dermal         | 13964 mg/kg bw/d               |               |  |  |
| worker<br>Long term<br>Systemic health effects          | Inhalation     | 2085 mg/m³                     |               |  |  |

| <b>Derived No Effect Level (DN</b>               | Derived No Effect Level (DNEL) |                                |               |  |  |  |
|--|--------------------------------|--------------------------------|---------------|--|--|--|
| Acetone (67-64-1)                                |                                |                                |               |  |  |  |
| Туре   | Exposure route                 | Derived No Effect Level (DNEL) | Safety factor |  |  |  |
| Consumer<br>Long term<br>Systemic health effects | Inhalation                     | 200 mg/m³                      |               |  |  |  |
| Consumer<br>Long term<br>Systemic health effects | Dermal                         | 62 mg/kg bw/d                  |               |  |  |  |
| Consumer<br>Long term<br>Systemic health effects | Oral                           | 62 mg/kg bw/d                  |               |  |  |  |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3) |                |                                |               |  |  |  |
|--|----------------|--------------------------------|---------------|--|--|--|
| Туре   | Exposure route | Derived No Effect Level (DNEL) | Safety factor |  |  |  |
| Consumer   | Inhalation     | 447 mg/m³                      |               |  |  |  |
| Long term  |                |                                |               |  |  |  |
| Systemic health effects  |                |                                |               |  |  |  |
| Consumer   | Dermal         | 149 mg/kg bw/d                 |               |  |  |  |
| Long term  |                |                                |               |  |  |  |
| Systemic health effects  |                |                                |               |  |  |  |
| Consumer   | Oral           | 149 mg/kg bw/d                 |               |  |  |  |
| Long term  |                |                                |               |  |  |  |
| Systemic health effects  |                |                                |               |  |  |  |

# Predicted No Effect Concentration (PNEC)

United Kingdom - BE Page 7 / 16

**EVO-STIK GRIPFILL ADHESIVE** Supercedes date 09-Jun-2023

Revision date 11-Jun-2025 **Revision Number** 8

| Predicted No Effect Concentration (PNEC) |  |  |  |  |
|--|--|--|--|--|
| Acetone (67-64-1)                        |  |  |  |  |
| Environmental compartment                | Predicted No Effect Concentration (PNEC) |  |  |  |
| Freshwater                               | 10.6 mg/l                                |  |  |  |
| Freshwater - intermittent                | 21 mg/l                                  |  |  |  |
| Marine water                             | 1.06 mg/l                                |  |  |  |
| Microorganisms in sewage treatment       | 100 mg/l                                 |  |  |  |
| Freshwater sediment                      | 30.4 mg/kg dry weight                    |  |  |  |
| Marine water                             | 3.04 mg/kg dry weight                    |  |  |  |
| Soil                                     | 29.5 mg/kg dry weight                    |  |  |  |

8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Tight sealing safety goggles. Face protection shield. Eye/face protection

Hand protection Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature.

Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective Skin and body protection

clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

Organic gases and vapours filter conforming to EN 14387. Recommended filter type:

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

**Physical state** Liquid **Appearance** Paste Colour Beige Odour Solvent.

Values\_ Remarks • Method Property

Melting point / freezing point No data available None known

= 60 °C Initial boiling point and boiling

range

**Flammability** No data available Flammable liquid None known

Flammability Limit in Air

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

Flash point -10 °C

**Autoignition temperature** No data available None known **Decomposition temperature** None known

No data available Not applicable. Insoluble in water.

No data available None known pH (as aqueous solution) Kinematic viscosity 500 mm<sup>2</sup>/s @ 40°C

**Dynamic viscosity** No data available

Water solubility Insoluble in water. None known No data available Solubility(ies) None known **Partition coefficient** No data available None known Vapour pressure <110 kPa None known Relative density No data available None known

**Bulk density** No data available

Density 1.18

Relative vapour density No data available None known

Particle characteristics

**Particle Size** No information available

United Kingdom - BE Page 8 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

Particle Size Distribution No information available

9.2. Other information

Solid content (%) < 80

VOC content approx 350 g/L

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

### SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** No information available.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

None under normal use conditions. Stable under recommended storage conditions.

products

# SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Information on likely routes of exposure

### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

**Skin contact** Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

United Kingdom - BE Page 9 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. May cause redness and tearing of the eyes.

Acute toxicity

**Numerical measures of toxicity** 

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) 23,253.60 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) 47.90 mg/l
ATEmix (inhalation-vapour) 128.50 mg/l

### **Component Information**

| Chemical name                 | Oral LD50             | Dermal LD50                | Inhalation LC50            |
|-------------------------------|-----------------------|----------------------------|----------------------------|
| Xylenes (o-, m-, p- isomers)  | =3500 mg/kg (Rattus)  | > 1700 mg/kg (Oryctolagus  | = 11 mg/L (ATE)            |
|                               |                       | cuniculus) > 4350 mg/kg    |                            |
|                               |                       | (Oryctolagus cuniculus)    |                            |
| Acetone                       | =5800 mg/kg (Rattus)  | >15800 mg/Kg (Rattus)      | =79 mg/l(Rattus) 4 h       |
|                               | 3000 mg/Kg (mouse)    |                            |                            |
| Hydrocarbons, C7, n-alkanes,  | LD50 >5840 mg/kg Rat  | LD50 >2920 mg/kg (Rattus)  | LC50 >23.3 mg/L (4h)(Rat,  |
| isoalkanes, cyclics           |                       |                            | vapour)                    |
|                               |                       |                            | (OECD 403)                 |
| Hydrocarbons, C6, isoalkanes, | >16750 mg/Kg (Rattus) | >3350 mg/Kg (Oryctolagus   | 259354 mg/m³ (vapour) (rat |
| <5% n-hexane                  |                       | cuniculus) OECD 402        | OECD 403)                  |
| Ethylbenzene                  | =3500 mg/kg (Rattus)  | = 15400 mg/kg (Oryctolagus | =17.6 mg/L (Rattus) 4 h    |
|                               | -                     | cuniculus)                 |                            |

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

| Acetone (67-64-1)    |         |                |                |               |          |
|----------------------|---------|----------------|----------------|---------------|----------|
| Method               | Species | Exposure route | Effective dose | Exposure time | Results  |
| OECD Test No. 405:   | Rabbit  | eye            |                |               | irritant |
| Acute Eye            |         |                |                |               |          |
| Irritation/Corrosion |         |                |                |               |          |

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

| Xylenes (o-, m-, p- isomers) (1330-20-7) |            |                |                       |  |  |
|--|------------|----------------|-----------------------|--|--|
| Acetone (67-64-1)                        |            |                |                       |  |  |
| Method                                   | Species    | Exposure route | Results               |  |  |
| GPMT - Guinea pig maximisation test      | Guinea pig | Dermal         | Not a skin sensitiser |  |  |

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

United Kingdom - BE Page 10 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

| Acetone (67-64-1)   |         |                |                |               |                  |
|---------------------|---------|----------------|----------------|---------------|------------------|
| Method              | Species | Exposure route | Effective dose | Exposure time | Results          |
| Experiences made in |         |                |                |               | Narcotic effects |
| practice            |         |                |                |               |                  |

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

| Acetone (67-64-1)   |         |                |                        |                 |   |
|---|---------|----------------|------------------------|-----------------|---|
| Method  | Species | Exposure route | Effective dose         | Exposure time   | Results   |
| OECD Test No. 408:<br>Repeated Dose 90-Day<br>Oral Toxicity Study in<br>Rodents | Rat     | Oral           | 200-3400 mg/kg<br>bw/d | 91 days         | No Observed<br>Adverse Effect<br>Level LOAEL 1700<br>mg/kg bw/d |
| Not specified   | Rat     | Inhalation     | 19000 ppm              | 14, 28, 56 days | NOAEC 19000 ppm<br>No Observed<br>Adverse Effect<br>Level       |

**Aspiration hazard** 

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

| Chemical name       | Algae/aquatic plants | Fish          | Toxicity to microorganisms | Crustacea       | M-Factor | M-Factor<br>(long-term) |
|---------------------|----------------------|---------------|----------------------------|-----------------|----------|-------------------------|
| Xylenes (o-, m-, p- | -                    | LC50 96 h 2.6 | EC50 = 0.0084              | EC50 48 h = 3.4 |          |                         |
| isomers)            |                      | mg/L          | mg/L 24 h                  | mg/L (Dappnia   |          |                         |
| 1330-20-7           |                      | (Oncorhynchus | -                          | magna)          |          |                         |

United Kingdom - BE Page 11 / 16

# **EVO-STIK GRIPFILL ADHESIVE Supercedes date** 09-Jun-2023

Revision date 11-Jun-2025 Revision Number 8

|                        |                    | mykiss ) (OECD<br>203) |                 |                |  |
|------------------------|--------------------|------------------------|-----------------|----------------|--|
| Acetone                | -                  | LC50 96 h 4.74         | EC50 = 14500    | EC50 48 h      |  |
| 67-64-1                |                    | - 6.33 mL/L            | mg/L 15 min     | 10294 - 17704  |  |
|                        |                    | (Oncorhynchus          |                 | mg/L (Daphnia  |  |
|                        |                    | mykiss)                |                 | magna Static)  |  |
| Hydrocarbons, C7,      | ErL50 (72h) =      | LL50 (96h)             | -               | EL50 (48h) =   |  |
| n-alkanes, isoalkanes, | 10-30 mg/L         | >13.4 mg/L             |                 | 3.0 mg/L       |  |
| cyclics                | (Pseudokirchner    | (Oncorhynchus          |                 | (Daphnia       |  |
| RR-100219-3            | iella subcapitata) | mykiss)                |                 | magna)         |  |
|                        |                    | OECD 203               |                 |                |  |
| Hydrocarbons, C6,      | EL50 (72h) =       | LL50 (96h) =           | -               | EL50 (48h)=    |  |
| isoalkanes, <5%        | 13.6 mg/l          | 18.27 mg/l             |                 | 31.9 mg/l      |  |
| n-hexane               | (Pseudokirchner    | (Oncorhynchus          |                 | (Daphnia       |  |
| 64742-49-0             | iella subcapitata) | mykiss)                |                 | magna)         |  |
| Ethylbenzene           | EC50 72 h 2.6 -    | LC50 96 h = 4.2        | EC50 = 9.68     | EC50: 1.8 -    |  |
| 100-41-4               | 11.3 mg/L          | mg/L                   | mg/L 30 min     | 2.4mg/L (48h,  |  |
|                        | (Pseudokirchner    | (Oncorhynchus          | EC50 = 96  mg/L | Daphnia magna) |  |
|                        | iella subcapitata) | mykiss                 | 24 h            |                |  |
|                        |                    | semi-static)           |                 |                |  |

## 12.2. Persistence and degradability

Persistence and degradability No information available.

| Xylenes (o-, m-, p- isomers) (1330-20-7)  |               |                |                              |  |  |
|---|---------------|----------------|------------------------------|--|--|
| Method  | Exposure time | Value          | Results                      |  |  |
| OECD Test No. 301F: Ready<br>Biodegradability: Manometric<br>Respirometry Test (TG 301 F) | 28 days       | biodegradation | 87.8 % Readily biodegradable |  |  |

| Acetone (67-64-1)   |               |                |                            |  |  |
|---|---------------|----------------|----------------------------|--|--|
| Method  | Exposure time | Value          | Results                    |  |  |
| OECD Test No. 301B: Ready<br>Biodegradability: CO2 Evolution Test | ,             | biodegradation | 91 % Readily biodegradable |  |  |
| (TG 301 B)  |               |                |                            |  |  |

| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3) |               |       |                       |  |  |
|--|---------------|-------|-----------------------|--|--|
| Method   | Exposure time | Value | Results               |  |  |
| OECD Test No. 301F: Ready                                      | 28 days       | 98%   | Readily biodegradable |  |  |
| Biodegradability: Manometric                                   | -             |       |                       |  |  |
| Respirometry Test (TG 301 F)                                   |               |       |                       |  |  |

# 12.3. Bioaccumulative potential

# Bioaccumulation

**Component Information** 

| Component information                      |                       |  |
|--|-----------------------|--|
| Chemical name                              | Partition coefficient |  |
| Xylenes (o-, m-, p- isomers)               | 3.15                  |  |
| Acetone                                    | -0.24                 |  |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane | 3.6                   |  |
| Ethylbenzene                               | 3.6                   |  |

### 12.4. Mobility in soil

**Mobility in soil** No information available.

# 12.5. Results of PBT and vPvB assessment

United Kingdom - BE Page 12 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

PBT and vPvB assessment Based on available data, the classification criteria are not met.

| Chemical name                                    | PBT and vPvB assessment |  |
|--|-------------------------|--|
| Xylenes (o-, m-, p- isomers)                     | Not PBT/vPvB            |  |
| Acetone  | Not PBT/vPvB            |  |
| Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics | Not PBT/vPvB            |  |
| Hydrocarbons, C6, isoalkanes, <5% n-hexane       | Not PBT/vPvB            |  |
| Ethylbenzene                                     | Not PBT/vPvB            |  |

#### 12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.

**PMT or vPvM properties**Based on available data, the classification criteria are not met.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

15 01 10\*: Packaging containing residues of or contaminated by dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

## **SECTION 14: Transport information**

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to

shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

**14.1 UN number or ID number** UN1133 **14.2 UN proper shipping name** Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group

**Description**UN1133, Adhesives, 3, II, (D/E)
No

14.5 Environmental hazards

14.6 Special precautions for user

Special Provisions 640D
Classification code F1
Tunnel restriction code (D/E)
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler 33

Number)

### **IMDG**

United Kingdom - BE Page 13 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

**14.1 UN number or ID number** UN1133 **14.2 UN proper shipping name** Adhesives

14.3 Transport hazard class(es) 3 14.4 Packing group ||

**Description** UN1133, Adhesives, 3, II, (-10°C c.c.)

14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None
Limited Quantity (LQ) 5 L
EmS-No. F-E, S-D

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

#### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
3 UN 133
Adhesives
3 3

14.3 Transport nazard class(es) 3 14.4 Packing group

**Description** UN1133, Adhesives, 3, II

14.5 Environmental hazards No
14.6 Special precautions for user
Special Provisions A3
Limited quantity (LQ) 1 L
ERG Code 3L

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

United Kingdom - BE Page 14 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

### Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS

P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Named dangerous substances per Seveso Directive (2012/18/EU)

| Chemical name                                | Lower-tier requirements (tons) | Upper-tier requirements (tons) |
|--|--------------------------------|--------------------------------|
| Hydrocarbons, C6, isoalkanes, <5% n-hexane - |                                | 25000                          |
| 64742-49-0                                   |                                |                                |

### Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. This product contains:

| Chemical name     | Reporting of suspicious transactions, | Restricted | Registration |
|-------------------|---------------------------------------|------------|--------------|
|                   | disappearances and thefts             |            |              |
| Acetone - 67-64-1 | Regulated                             |            |              |

#### National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

## Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

### Notes relating to the identification, classification and labelling of substances

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Note P - The harmonized classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0.1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

United Kingdom - BE Page 15 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes date 09-Jun-2023 Revision date 11-Jun-2025 Revision Number 8

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 11-Jun-2025

Indication of changes

**Revision Note** SDS sections updated: 2.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 16 / 16