

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK GRIPFILL ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

2.2. Label elements

Contains Xylenes (o-, m-, p- isomers), Acetone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6,isoalkanes, <5% n-hexa



United Kingdom - BE Page 1 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H412 - Harmful to aquatic life with long lasting effects.

H225 - Highly flammable liquid and vapour.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403 + P235 - Store in a well-ventilated place. Keep cool

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Xylenes (o-, m-, p- isomers)	(601-022-00- 9) 215-535-7	1330-20-7	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226)	-	01-2119488216- 32-XXXX

United Kingdom - BE Page 2 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

				Aquatic Chronic 3 (H412)		
Acetone	(606-001-00- 8) 200-662-2	67-64-1	5 - <10	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119471330- 49-XXXX
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	-	01-2119475515- 33-xxxx
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	RR-100242-2	1 - <5	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)	-	01-2119484651- 34-XXXX
Ethylbenzene	(601-023-00- 4) 202-849-4	100-41-4	1 - <2.5	STOT RE 2 (H373) Asp. Tox. 1 (H304) Acute Tox. 4 (H332) Flam Liq. 2 (H225) Aquatic Chronic 3 (H412)	-	01-2119489370- 35-XXXX

Full text of H- and EUH-phrases: see section 16
Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Xylenes (o-, m-, p- isomers) - 1330-20-7	С

SECTION 4: First aid measures

United Kingdom - BE Page 3/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022

Revision date 09-Jun-2023 Revision Number 7.01

4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. General advice

Remove to fresh air. Get medical attention immediately if symptoms occur. Inhalation

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and

persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Get medical attention if irritation develops and persists.

Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce Ingestion

vomiting. Call a doctor.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

> material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more

information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

No information available. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide. **Hazardous combustion products**

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment as required. See Personal precautions

> section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

United Kingdom - BE Page 4 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using

this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should

not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or

clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from

heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the

particular national regulations. Store in accordance with local regulations.

Recommended storage

temperature

Keep at temperatures between 5 and 25 $^{\circ}\text{C}.$

7.3. Specific end use(s)

Specific use(s) Adhesives.

United Kingdom - BE Page 5 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022

Revision date 09-Jun-2023 Revision Number 7.01

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Kaolin	-	TWA: 2 mg/m ³
1332-58-7		STEL: 6 mg/m ³
Xylenes (o-, m-, p- isomers)	TWA: 50 ppm	TWA: 50 ppm
1330-20-7	TWA: 221 mg/m ³	TWA: 220 mg/m ³
	STEL: 100 ppm	STEL: 100 ppm
	STEL: 442 mg/m ³	STEL: 441 mg/m ³
	*	Sk*
Acetone	TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1210 mg/m ³	TWA: 1210 mg/m ³
		STEL: 1500 ppm
		STEL: 3620 mg/m ³
Ethylbenzene	TWA: 100 ppm	TWA: 100 ppm
100-41-4	TWA: 442 mg/m ³	TWA: 441 mg/m ³
	STEL: 200 ppm	STEL: 125 ppm
	STEL: 884 mg/m ³	STEL: 552 mg/m ³
	*	Sk*

Chemical name	European Union	Ireland	United Kingdom
Xylenes (o-, m-, p- isomers)	-	1.5 g/g Creatinine (urine -	650 mmol/mol creatinine urine
1330-20-7		Methylhippuric acids end of shift)	
Acetone	-	50 mg/L (urine - Acetone end of	-
67-64-1		shift)	
Ethylbenzene	-	0.7 g/g Creatinine (urine - sum of	-
100-41-4		Mandelic acid and Phenylglyoxylic	
		acid end of shift at end of	
		workweek)	
		0.7 g (end-exhaled air - not	
		critical)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Xylenes (o-, m-, p- isomers) (13	330-20-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Long term Systemic health effects worker	Dermal	180 mg/kg bw/d		
Long term Systemic health effects worker	Inhalation	77 mg/m³		
Short term Local health effects Systemic health effects worker	Inhalation	289 mg/m³		

Acetone (67-64-1)			
Туре	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	
Long term	Dermal	186 mg/kg bw/d	
Systemic health effects			

United Kingdom - BE Page 6 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022

Revision date 09-Jun-2023 Revision Number 7.01

worker			
Short term Local health effects worker	Inhalation	2420 mg/m³	
Long term Systemic health effects worker	Inhalation	1210 mg/m³	

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	2085 mg/m³		
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d		

Derived No Effect Level (DN	EL)		
Acetone (67-64-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	200 mg/m³	
Consumer Long term Systemic health effects	Dermal	62 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	62 mg/kg bw/d	

Hydrocarbons, C7, n-alkane	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	447 mg/m³			
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)			
Acetone (67-64-1)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	10.6 mg/l		
Freshwater - intermittent	21 mg/l		
Marine water	1.06 mg/l		
Microorganisms in sewage treatment	100 mg/l		
Freshwater sediment	30.4 mg/kg dry weight		
Marine water	3.04 mg/kg dry weight		
Soil	29.5 mg/kg dry weight		

United Kingdom - BE Page 7 / 16

EVO-STIK GRIPFILL ADHESIVE Revision date 09-Jun-2023 Supercedes Date: 19-Apr-2022 Revision Number 7.01

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. **Engineering controls**

Personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be

replaced regularly and if there is any sign of damage to the glove material.

Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Suitable protective

Respiratory protection In case of inadequate ventilation wear respiratory protection. In case of mist, spray or

aerosol exposure wear suitable personal respiratory protection and protective suit.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Liquid

No information available Colour

Solvent. Odour

Odour threshold No information available

Remarks • Method Property Values

Melting point / freezing point No data available None known = 60 °C

Initial boiling point and boiling

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

-10 °C Flash point

Autoignition temperature No data available None known None known

Decomposition temperature

pН No data available Not applicable. Insoluble in water.

No data available None known pH (as aqueous solution) Kinematic viscosity 500 mm²/s @ 40°C

Dynamic viscosity No data available

Water solubility No data available. None known Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available None known Vapour pressure Relative density No data available None known

Bulk Density No data available

Density 1.18

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available No information available Particle Size Distribution

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

United Kingdom - BE Page 8/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation.

(based on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes.

United Kingdom - BE Page 9 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) 23,253.60 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) 47.90 mg/l
ATEmix (inhalation-vapour) 128.50 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers)	=3500 mg/kg (Rattus)	> 1700 mg/kg (Oryctolagus cuniculus) > 4350 mg/kg (Oryctolagus cuniculus)	= 11 mg/L (ATE)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m³ (vapour) (rat OECD 403)
Ethylbenzene	=3500 mg/kg (Rattus)	= 15400 mg/kg (Oryctolagus cuniculus)	=17.6 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse	Dermal	No sensitisation responses
Sensitisation: Local Lymph Node			were observed
Assay			

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			

Germ cell mutagenicity Based on available data, the classification criteria are not met.

United Kingdom - BE Page 10 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Xylenes (o-, m-, p-	-	LC50 96 h 2.6	EC50 = 0.0084	EC50 48 h = 3.4		
isomers)		mg/L	mg/L 24 h	mg/L (Dappnia		
1330-20-7		(Oncorhynchus		magna)		
		mykiss) (OECD				
		203)				
Acetone	-	LC50 96 h 4.74	EC50 = 14500	EC50 48 h		
67-64-1		- 6.33 mL/L	mg/L 15 min	10294 - 17704		
		(Oncorhynchus		mg/L (Daphnia		
		mykiss)		magna Static)		
Hydrocarbons, C7,	ErL50 (72h) =	LL50 (96h)	-	EL50 (48h) =		
n-alkanes, isoalkanes,	10-30 mg/L	>13.4 mg/L		3.0 mg/L		
cyclics	(Pseudokirchner	(Oncorhynchus		(Daphnia		
RR-100219-3	iella subcapitata)	mykiss)		magna)		
		OECD 203				
Hydrocarbons, C6,	EL50 (72h) =	LL50 (96h) =	-	EL50 (48h)=		
isoalkanes, <5%	13.6 mg/l	18.27 mg/l		31.9 mg/l		
n-hexane	(Pseudokirchner	(Oncorhynchus		(Daphnia		
RR-100242-2	iella subcapitata)	mykiss)		magna)		
Ethylbenzene	EC50 72 h 2.6 -	LC50 96 h = 4.2		EC50: 1.8 -		
100-41-4	11.3 mg/L	mg/L	mg/L 30 min	2.4mg/L (48h,		
	(Pseudokirchner	(Oncorhynchus	EC50 = 96 mg/L	Daphnia magna)		
	iella subcapitata)	mykiss	24 h			
		semi-static)				

12.2. Persistence and degradability

United Kingdom - BE Page 11 / 16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Persistence and degradability

No information available.

Xylenes (o-, m-, p- isomers) (1330-20-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	biodegradation	87.8 % Readily biodegradable
Biodegradability: Manometric	-	-	
Respirometry Test (TG 301 F)			

Acetone (67-64-1)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	98%	Readily biodegradable
Biodegradability: Manometric			
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name		Partition coefficient
	Xylenes (o-, m-, p- isomers)	3.15
Acetone		-0.24
	Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
	Ethylbenzene	3.6

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Xylenes (o-, m-, p- isomers)	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB PBT assessment does
	not apply
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB
Ethylbenzene	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

United Kingdom - BE Page 12/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

15 01 10*: Packaging containing residues of or contaminated by dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note:

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number UN1133 **14.2 UN proper shipping name** Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing group II

Description UN1133, Adhesives, 3, II, (D/E)

14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions 640C
Classification code F1
Tunnel restriction code (D/E)
Limited quantity (LQ) 5 L
ADR Hazard Id (Kemmler 33

Number)

<u>IMDG</u>

14.1 UN number or ID number UN1133
14.2 UN proper shipping name Adhesives

14.3 Transport hazard class(es) 314.4 Packing group | |

Description UN1133, Adhesives, 3, II, (-10°C c.c.)

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions None Limited Quantity (LQ) 5 L EmS-No. F-E, S-D

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1133
14.2 UN proper shipping name Adhesives
14.3 Transport hazard class(es)

14.3 Transport hazard class(es) 314.4 Packing group | |

Description UN1133, Adhesives, 3, II

14.5 Environmental hazards Not applicable

14.6 Special precautions for user Special Provisions A3

United Kingdom - BE Page 13/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 Revision date 09-Jun-2023 Revision Number 7.01

Limited quantity (LQ) 1 L ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS

P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

National regulations

United Kingdom - BE Page 14/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022 **Revision Number** 7.01

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 09-Jun-2023

Indication of changes

Revision note SDS sections updated: 2.

Training Advice Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

United Kingdom - BE Page 15/16

EVO-STIK GRIPFILL ADHESIVE Supercedes Date: 19-Apr-2022

Revision date 09-Jun-2023 Revision Number 7.01

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 16 / 16