



SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name CONFLEX TILE ADHESIVE

Product Code(s)

30840342
30615423; 30840342; 30840344

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

Label elements

Exclamation mark
Corrosion

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016



Signal word
Danger

Hazard statements

H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling
Wear protective gloves/protective clothing/eye protection/face protection
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor/physician
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
Call a POISON CENTER or doctor/physician if you feel unwell

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Quartz	14808-60-7	30 - 60
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	10 - <30
Limestone	1317-65-3	0 - <10
Ethylene-vinyl acetate copolymer	24937-78-8	0 - <10
polymer	--	0 - <10
carbon	--	0 - <10
Calcium diformate	544-17-2	0 - <10

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

organic material	--	0 - <10
Slags, ferrous metal, blast furnace	65996-69-2	0 - <10
Ashes, residues	68131-74-8	0 - <10
Cellulose, 2-hydroxyethyl methyl ether	9032-42-2	0 - <10
Magnesium oxide (MgO)	1309-48-4	0 - <10
Gypsum (Ca(SO ₄).2H ₂ O)	13397-24-5	0 - <10
Calcium oxide	1305-78-8	0 - <10
Magnesite	13717-00-5	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash before reuse.

Ingestion Clean mouth with water. Drink 1 or 2 glasses of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Do NOT induce vomiting.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Specific hazards arising from the No information available.

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

chemical

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂). Silicon dioxide.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
---------------	-----------

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Quartz 14808-60-7	TWA: 0.05 mg/m ³
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	TWA: 10 mg/m ³
Magnesium oxide (MgO) 1309-48-4	TWA: 10 mg/m ³
Calcium oxide 1305-78-8	TWA: 2 mg/m ³

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Color Gray
Odor Slight
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	Not applicable .	
Initial boiling point and boiling range	Not applicable .	
Flash point	Not applicable .	
Evaporation rate	Not applicable .	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.36	
Water solubility	Insoluble in water Cement based products react and solidify in contact with water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Kinematic viscosity Not applicable . mm²/s
Dynamic viscosity Not applicable .
Explosive properties No information available
Oxidizing properties No information available

Other information

Softening Point Not relevant
Solid content (%) No information available
Density No information available
VOC Content (%) No information available

Section 10: Stability and reactivity

Reactivity

Reactivity Product cures with moisture.

Chemical stability

Stability Stable under recommended storage conditions. Keep away from Incompatible materials.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Product cures with moisture.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Causes serious eye damage.

Skin contact Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Burning. May cause blindness. Redness. May cause redness and tearing of the eyes.

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Numerical measures of toxicity - Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m ³ (Rattus)
Limestone	>5000 mg/kg (Rattus)	-	-
Calcium diformate	=2650 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Slags, ferrous metal, blast furnace	LD50 >2000 mg/Kg	>4000 mg/Kg (Rattus) (OECD 402)	>5235 mg/m ³ Dust (OECD 403)
Ashes, residues	>2000 mg/kg (Rattus)	-	-
Cellulose, 2-hydroxyethyl methyl ether	LD50 >10000 mg/Kg (Rattus)	-	-
Magnesium oxide (MgO)	3800 mg/kg (Rattus)	-	-
Calcium oxide	>2000 mg/kg (Rattus)	LD50 > 2500 mg/kg (Oryctolagus cuniculus)	> 6.04 mg/L (Rat) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Irritating to skin.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.

Chemical name	Australia	European Union	IARC
Quartz 14808-60-7	Carc. 1A		Group 1
Ashes, residues 68131-74-8			Group 1

Reproductive toxicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondosmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Calcium diformate 544-17-2	RC50 (72h) > 1000 mg/l (Pseudokirchnerella subcapitata)	LC50: >=1000mg/L (96h, Brachydanio rerio)	-	EC50 (48h) > 1000 mg/l (Daphnia magna) EPA-660/3-75-009
Ashes, residues 68131-74-8	-	-	-	EC50: 140 - 2000mg/L (24h, Daphnia magna)
Cellulose, 2-hydroxyethyl methyl ether 9032-42-2	-	CL50 (96h) >500 mg/L (Danio rerio)	-	-
Magnesium oxide (MgO) 1309-48-4	-	-	-	48H 190mg/L Daphnia Magna
Calcium oxide 1305-78-8	EC50 (Pseudokirchneriella subcapitata (green algae)): 106,02 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes	LC50 96 h = 50.6 mg/L (Oncorhynchus mykiss)	EC50 (Bacteria): 229,2 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes	EC50 (48h) = 49.1 mg/l(Daphnia magna) OECD 202

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Cellulose, 2-hydroxyethyl methyl ether 9032-42-2	-0.1

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Ashes, residues 68131-74-8	10 tonne/yr Threshold category 1 2000 tonne/yr Threshold category 2b 60000 MWH Threshold category 2b 20 MW Threshold category 2b
Magnesium oxide (MgO) 1309-48-4	10 tonne/yr Threshold category 1 fume 2000 tonne/yr Threshold category 2b fume 60000 MWH Threshold category 2b fume 20 MW Threshold category 2b fume

International Inventories

AIIC Listed
NZIoC Not Listed
ENCS Not Listed
IECSC Not Listed
KECL Not Listed
PICCS Not Listed

Legend:

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

SAFETY DATA SHEET

CONFLEX TILE ADHESIVE
Revision Number 1.01

Revision date 05-Apr-2022
Supersedes Date: 08-Oct-2016

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Revision date 05-Apr-2022

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet