

DESIGNER GROUT 210 ANTIQUE WHITE Revision Number 2.01

Revision date15-Jun-2022Supersedes Date:27-Oct-2020

Section 1: Identification: Product i	dentifier and chemical identity
Product identifier	
Product Name	DESIGNER GROUT 210 ANTIQUE WHITE
Product Code(s) 30604366 30604366; 30604367; 30616253; 308	840385
Other means of identification	
Pure substance/mixture	Mixture
Recommended use of the chemica	I and restrictions on use
Recommended use	Grout
Uses advised against	No information available
Details of manufacturer or importe	<u>r</u>
Supplier Bostik Australia Pty Ltd 51-71 High Street, Thomastown Victoria Australia Tel: 613 9279-9333 Fax: 613 9279-9342	
ABN: 79 003 893 838	
E-mail address	au-bostik-sds@bostik.com
Emergency telephone number	
Emergency telephone number	24-hr Emergency: 1800 033 111
Section 2: Hazard(s) identification	

GHS Classification

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

Label elements

Exclamation mark Corrosion

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

Revision date 15-Jun-2022 Supersedes Date: 27-Oct-2020



Signal word DANGER

Hazard statements

H315 - Causes skin irritation
H318 - Causes serious eye damage
H335 - May cause respiratory irritation
Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Wear protective gloves/clothing and eye/face protection IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a doctor IF ON SKIN: Wash with plenty of water and soap If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a doctor if you feel unwell **Precautionary Statements - Storage** Store in well-ventilated place

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Poison Schedule Number Not applicable

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	30 - 60
Calcium diformate	544-17-2	0 - <10
Sulfuric acid, aluminum salt (3:2)	10043-01-3	0 - <10
Calcium hydroxide	1305-62-0	0 - <10

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

Non-hazardous ingredients		Proprietary	Balance	
rton nazarada ingradionia		riophotaly	Dalanoo	
Section 4: First aid measures				
Emergency telephone number	Poisons Information Center Poisons Information Center	er, Australia: 13 11 26 er, New Zealand: 0800 764 766		
Description of first aid measures				
General advice	If medical advice is neede	d, have product container or lab	el at hand.	
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.			
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.			
Skin contact	Brush off loose particles fr contaminated clothing and	om skin. Remove material from I wash before reuse.	skin immediately. Take off	
Ingestion	Rinse mouth. Never give a vomiting. Call a physician.	anything by mouth to an uncons	cious person. Do NOT induce	
Self-protection of the first aider	Avoid contact with skin, ey 8).	ves or clothing. Wear personal p	rotective clothing (see section	
Most important symptoms and eff	ects, both acute and delay	ved		
Symptoms	high concentration may ca water a strong alkaline sol concrete may cause serio	s serious eye damage. Irritating suse irritation of respiratory systerution is produced. Prolonged of us burns because they develop ent even when wearing trousers	em. When cement reacts with contact with wet cement or wet without pain being felt e.g.	
Indication of any immediate medic	al attention and special tr	eatment needed		
Note to physicians	Treat symptomatically.			
Section 5: Firefighting measures				
Suitable Extinguishing Media				
Suitable Extinguishing Media	Use extinguishing measur surrounding environment.	es that are appropriate to local	circumstances and the	
Unsuitable extinguishing media	No information available.			
Specific hazards arising from the	<u>chemical</u>			
Specific hazards arising from the chemical	No information available.			
Hazardous combustion products	Carbon oxides. Silicon dic	xide.		
Special protective actions for fire-	fighters			
Special protective equipment and precautions for fire-fighters	Firefighters should wear s gear. Use personal protect	elf-contained breathing apparatition equipment.	us and full firefighting turnout	

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

Section 6: Accidental release mea	isures
Personal precautions, protective	equipment and emergency procedures
Personal precautions	Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil.
Methods and material for contain	nent and cleaning up
Methods for containment	Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.
Methods for cleaning up	Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.
Precautions to prevent secondary	hazards
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
Section 7: Handling and storage,	including how the chemical may be safely used
Precautions for safe handling	
Advice on safe handling	Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash before reuse.
General hygiene considerations	Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.
Conditions for safe storage, inclu-	ding any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Protect from moisture.
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.
Section 8: Exposure controls and	personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1	TWA: 10 mg/m ³
Sulfuric acid, aluminum salt (3:2) 10043-01-3	TWA: 2 mg/m ³
Calcium hydroxide 1305-62-0	TWA: 5 mg/m ³

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

OEL as published by Safe Work Australia

Appropriate engineering controls	
Engineering controls	Showers, eyewash stations, and ventilation systems.
Individual protection measures, su	uch as personal protective equipment
Eye/face protection	Tight sealing safety goggles.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing.
Hand protection	Wear suitable gloves. Impervious gloves.
Respiratory protection	with filter for particulates. Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Appearance Color Odor Odor threshold	Solid Powder Off-white None No information available	
Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	No data available	
Melting point / freezing point	Not applicable . °C	
Initial boiling point and boiling	Not applicable . °C	
range		
Flash point	Not applicable . °C	
Evaporation rate	Not applicable	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data avallable	
Lower flammability or explosive	No data available	
limits		
Vapor pressure	No data available	
Relative vapor density	No data available	
Relative density	1.7 - 1.9	
Water solubility	Cement based products react and	
-	solidify in contact with water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	Not applicable	
Dynamic viscosity	Not applicable	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information Softening Point Solid content (%)	Not relevant 100	

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

Liquid Density Bulk density VOC Content (%)	No information available 1.15 No information available
Section 10: Stability and reactivity	
Reactivity	
Reactivity	Product cures with moisture.
Chemical stability	
Stability	Keep away from Incompatible materials. Stable under recommended storage conditions.
Explosion data Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.
Possibility of hazardous reactions	
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	
Conditions to avoid	Product cures with moisture. Protect from moisture.
Incompatible materials	
Incompatible materials	Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.
Hazardous decomposition product	<u>'S</u>
Hazardous decomposition products	Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of irritating and toxic gases and vapors.
Section 11: Toxicological informat	ion
Acute toxicity	
Information on likely routes of exp	osure
Product Information	
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity - Product Information

DESIGNER GROUT 210 ANTIQUE WHITE Revision Number 2.01

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, portland, chemicals (Chromium VI reduced)	-	>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)
Calcium diformate	=2650 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Sulfuric acid, aluminum salt (3:2)	>2000 mg/kg (Rattus)	> 5000 mg/kg (Rabbit)	-
Calcium hydroxide	=7340 mg/kg (Rattus)	LD50 > 2500 mg/kg bw (OECD 402, Oryctolagus cuniculus)	>6.04 mg/L (Rat)4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

May cause skin irritation. Classification based on data available for ingredients. Causes skin irritation.

Component Information					
Calcium hydroxide (1305	-62-0)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Component Informati	ion				
Calcium hydroxide (1	305-62-0)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
Method	opecies		Ellective dose	Exposure time	Results

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity	No information available.
STOT - single exposure	May cause respiratory irritation.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

DESIGNER GROUT 210 ANTIQUE WHITE Revision Number 2.01

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Calcium diformate 544-17-2	RC50 (72h) > 1000 mg/l (Pseudokirchnerella subcapitata)	LC50: >=1000mg/L (96h, Brachydanio rerio)	-	EC50 (48h) > 1000 mg/l (Daphnia magna) EPA-660/3-75-009
Sulfuric acid, aluminum salt (3:2) 10043-01-3	-	LC50 96 h = 100 mg/L (Carassius auratus)	-	EC50: =136mg/L (15min, Daphnia magna)
Calcium hydroxide 1305-62-0	EC50 = 184.57 g/ml (72Hr)	LC50: =160mg/L (96h, Gambusia affinis)	-	EC50 = 49.1 g/ml (48 hr)
Persistence and degrad	lability			
Persistence and degrad	lability No information	on available.		
Bioaccumulative potential				
Bioaccumulation	There is no c	data for this product.		
<u>Mobility</u>				
Mobility in soil	No information	on available.		
Mobility	No information	on available.		
Other adverse effects				
Other adverse effects	No information	No information available.		
Section 13: Disposal co	onsiderations			
Disposal methods				
Waste from residues/ur products		Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.		
Contaminated packagin	Do not reuse	Do not reuse empty containers.		
Section 14: Transport in	nformation			
ADG	Not regulated	Not regulated		
IATA	Not regulated	Not regulated		
IMDG	Not regulated	Not regulated		

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

|--|

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

<u>Australia</u> See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)No poisons schedule number allocatedPoison Schedule NumberNot applicable

International Inventories	
AIIC	Listed
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

AIIC - Australian Inventory of Industrial Chemicals

NZIOC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information				
Prepared By	Product Safety & Regulatory Affairs			
Revision date	15-Jun-2022			

Revision Note

***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

STEL

DESIGNER GROUT 210 ANTIQUE WHITE

Revision Number 2.01

Revision date 15-Jun-2022 Supersedes Date: 27-Oct-2020

STEL (Short Term Exposure Limit)

Skin designation

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

 TWA
 TWA (time-weighted average)

 Ceiling
 Maximum limit value

 C
 Carcinogen

 Section 11: TOXICOLOGICAL INFORMATION

 LD50 (lethal dose)

 Section 12: Ecological information

 EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet