

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021 Revision date 31-Oct-2022

Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE
Other means of identification	
Pure substance/mixture	Mixture
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Recommended use	Sealant
Uses advised against	None known
1.3. Details of the supplier of the s	afety data sheet
Company Name Bostik Benelux B.V. Denariusstraat 11 4903 RC Oosterhout The Netherlands Tel: + 31 162 491 000	
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone number	_
Ireland United Kingdom Europe	NPIC - National Poison Information Centre Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week) Healthcare Professionals: +353 (01) 8092566 (24 hour service) Bostik: +44 (1785) 272650 112
SECTION 2: Hazards identifi	cation
2.1. Classification of the substance	e or mixture
Regulation (EC) No 1272/2008	
This mixture is classified as not haza	rdous according to regulation (EC) 1272/2008 [CLP]
2.2. Label elements	

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

2.3. Other hazards

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No.	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]	× /		,	
Silica, amorphous	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499-
0.1- <1 %							16-XXXX
Sodium hydroxide	(011-002-00-	1310-73-2	Skin Corr. 1A (H314)	Eye Irrit. 2 ::	-	-	01-2119457892-
0.1- <1 %	6)		Eye Dam. 1 (H318)	0.5%<=C<2%			27-XXXX
	215-185-5		Met. Corr. 1 (H290)	Eye Dam. 1 :: C>=2%			
				Skin Corr. 1A ::			
				C>=5%			
				Skin Corr. 1B ::			
				2%<=C<5%			
				Skin Irrit. 2 ::			
				0.5%<=C<2%			
1,2-benzisothiazol-3(2H)	`	2634-33-5	Acute Tox. 4 (H302)	Skin Sens. 1 ::	1	-	01-2120761540-
-one [BIT]	6)		Skin Irrit. 2 (H315)	C>=0.05%			60-XXXX
0.01 - < 0.05 %	220-120-9		Eye Dam. 1 (H318)				
			Skin Sens. 1 (H317)				
			Aquatic Acute 1 (H400)				
			Aquatic Chronic 2 (H411)				
reaction mass of	611-341-5	55965-84-9	Acute Tox. 3 (H301)	Eye Dam. 1 ::	100	100	01-2120764691-
5-chloro-2-methyl-2H-iso				C>=0.6% Eye Irrit. 2 ::			48-XXXX
thiazol-3-one and			Acute Tox. 2 (H330)	0.06%<=C<0.6%			
2-methyl-2H-isothiazol-3-			Skin Corr. 1C (H314)	Skin Corr. 1C ::			
one (3:1) [C(M)IT/MIT]			Eye Dam. 1 (H318)	C>=0.6%			
<0.0015 %			Skin Sens. 1A (H317)	Skin Irrit. 2 ::			
			Aquatic Acute 1 (H400)	0.06%<=C<0.6%			
			Aquatic Chronic 1 (H410)				
Full text of H- and Ell				C>=0.0015%			

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes [B] - Substance with a Community workplace exposure limit

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Sodium hydroxide	(011-002-00-6) 215-185-5	1310-73-2	-	-	-	-	-
1,2-benzisothiazol-3(2 H)-one [BIT]	(613-088-00-6) 220-120-9	2634-33-5	670	-	-	-	-
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT]		55965-84-9	100	87.12	0.33	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	IF exposed or concerned: Get medical advice/attention. Remove to fresh air.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and water.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms	No information available.
4.3. Indication of any immediate me	edical attention and special treatment needed
Note to doctors	Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE

Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

Unsuitable extinguishing media	No information available.					
5.2. Special hazards arising from the	ne substance or mixture					
Specific hazards arising from the chemical	No information available.					
Hazardous combustion products	Silicon dioxide.					
5.3. Advice for firefighters						
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.					
SECTION 6: Accidental relea	ise measures					
6.1. Personal precautions, protections	ve equipment and emergency procedures					
Personal precautions	Ensure adequate ventilation.					
For emergency responders	Use personal protection recommended in Section 8.					
6.2. Environmental precautions						
Environmental precautions	See Section 12 for additional Ecological Information.					
6.3. Methods and material for conta	ainment and cleaning up					
Methods for containment	Do not scatter spilled material with high pressure water streams.					
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.					
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.					
6.4. Reference to other sections						
Reference to other sections	See section 8 for more information. See section 13 for more information.					
SECTION 7: Handling and st	orage					
7.1. Precautions for safe handling	_					
Advice on safe handling	Ensure adequate ventilation.					
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.					
7.2. Conditions for safe storage, in	cluding any incompatibilities					
Storage Conditions	Keep from freezing.					
Recommended storage temperature	Do not freeze. Keep at temperatures between 5 and 35 °C.					
7.3. Specific end use(s)						
Specific use(s) Sealant.						
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.					
Other information	Observe technical data sheet.					

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m³	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ TWA: 0.1 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³ STEL: 0.3 mg/m ³
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m ³	STEL: 2 mg/m ³

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)					
1,2-benzisothiazol-3(2H)-one [BIT]	(2634-33-5)				
Туре		Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	6.81 mg/m³			
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d			

Derived No Effect Level (DNEL)						
1,2-benzisothiazol-3(2H)-one [E	BIT] (2634-33-5)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m ³				
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d				

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)	
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment Eye/face protection

Tight sealing safety goggles.

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Skin and body protection

Suitable protective clothing.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical	and chemical properties	
Physical state	Paste	
Appearance Colour	See section 1 for more information	
Odour	Characteristic.	
Odour threshold	No information available	
Odour threshold	No information available	
Property_	Values	Remarks • Method
Melting point / freezing point	$= 0 ^{\circ}C$	
Initial boiling point and boiling	= 100 °C	
range		
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	approx No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН	7 - 9	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	
Dynamic viscosity	No data available	
Water solubility	Soluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	0.71	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data av	ailable

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity

No information available.

10.2. Chemical stability

Revision Number 2

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021 Revision date 31-Oct-2022

Revision Number 2

Stability	Stable under normal conditions.			
Explosion data				
Sensitivity to mechanical	None.			
impact Sensitivity to static discharge	None.			
10.3. Possibility of hazardous reac	tions			
Possibility of hazardous reactions	None under normal processing.			
10.4. Conditions to avoid				
Conditions to avoid	Do not freeze.			
10.5. Incompatible materials				
Incompatible materials	None known based on information supplied.			
10.6. Hazardous decomposition pr	oducts			
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.			
SECTION 11: Toxicological	information			
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008			
Information on likely routes of exp	osure			
Product Information				
Inhalation	Based on available data, the classification criteria are not met.			
Eye contact	Based on available data, the classification criteria are not met.			
Skin contact	Based on available data, the classification criteria are not met.			
Ingestion	Based on available data, the classification criteria are not met.			
	above in a low determination of the second states			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus	>2.2 mg/L (Rattus) 1 h
		cuniculus)	
Sodium hydroxide	=325 mg/kg (Rattus)	= 1350 mg/kg (Oryctolagus	-
		cuniculus)	
1,2-benzisothiazol-3(2H)-one	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
[BIT]			

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

reaction mass of 5-chloro-2-methyl-2H-isothiazo	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h	
I-3-one and 2-methyl-2H-isothiazol-3-one				
(3:1) [C(M)IT/MIT]				
Delayed and immediate effects	as well as chronic effects fr	om short and long-term expos	sure	
Skin corrosion/irritation	Based on available data,	the classification criteria are not	met.	
Serious eye damage/eye irritatio	on Based on available data,	the classification criteria are not	met.	
Respiratory or skin sensitisation	n Based on available data,	the classification criteria are not	met.	
Germ cell mutagenicity	Based on available data,	the classification criteria are not	met.	
Carcinogenicity	Based on available data,	the classification criteria are not	met.	
Reproductive toxicity	Based on available data,	the classification criteria are not	met.	
STOT - single exposure	Based on available data,	the classification criteria are not	met.	
STOT - repeated exposure	Based on available data,	the classification criteria are not	met.	
Aspiration hazard	Based on available data,	the classification criteria are not	met.	
11.2. Information on other haza	<u>rds</u>			
11.2.1. Endocrine disrupting properties				
Endocrine disrupting properties	No information available.			
11.2.2. Other information				
Other adverse effects	se effects No information available.			
SECTION 12: Ecological in	nformation			

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous	EC50: =440mg/L	LC50:	-	EC50:		
7631-86-9	(72h,	=5000mg/L (96h,		=7600mg/L (48h,		
	Pseudokirchneri	Brachydanio		Ceriodaphnia		
	ella subcapitata)	rerio)		dubia)		
Sodium hydroxide	-	LC50:	-	-		
1310-73-2		=45.4mg/L (96h,				

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

		Oncorhynchus mykiss)				
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	13mg/l (activated	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner		-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining
			biodegradability are not
			applicable to inorganic
			substances

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does
	not apply
Sodium hydroxide	The substance is not PBT / vPvB PBT assessment does
	not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision Number 2

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1.	Waste	treatment	methods

Waste from residues/unused products	Dispose of waste in accordance with environmental legislation. Dispose of in accordance with local regulations.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note:

Keep from freezing.

14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Environmental hazards	Not applicable	
14.6 Special Provisions	None	
IMDG		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special Provisions	None	
14.7 Maritime transport in bulk	Not applicable	
according to IMO instruments		
Air transport (ICAO-TI / IATA-DGR)		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Not applicable

European Union

14.5 Environmental hazards

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

- H302 Harmful if swallowed
- H310 Fatal in contact with skin
- H314 Causes severe skin burns and eve damage
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eve damage
- H330 Fatal if inhaled
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects
- H411 Toxic to aquatic life with long lasting effects

Notes assigned to an entry

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations.

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE

Supercedes Date: 27-Nov-2021

Revision date 31-Oct-2022

Revision Number 2

In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis SVHC: Substances of Very High Concern for Authorisation: PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals STOT RE: Specific target organ toxicity - Repeated exposure STOT SE: Specific target organ toxicity - Single exposure EWC: European Waste Catalogue LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm) ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road IATA: International Air Transport Association ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG: International Maritime Dangerous Goods RID: Regulations concerning the International Carriage of Dangerous Goods by Rail Legend SECTION 8: Exposure controls/personal protection TWA (time-weighted average) STEL (Short Term Exposure Limit) TWA STEL AGW Occupational exposure limit value Biological limit value BGW Maximum limit value Skin designation Ceiling Classification procedure Classification according to Regulation (EC) No. 1272/2008 [CLP] Method Used Acute oral toxicity Calculation method Calculation method Acute dermal toxicity Calculation method Acute inhalation toxicity - gas Calculation method Acute inhalation toxicity - Vapour Acute inhalation toxicity - dust/mist Calculation method Skin corrosion/irritation Calculation method Calculation method Serious eye damage/eye irritation Respiratory sensitisation Calculation method Skin sensitisation Calculation method mutagenicity Calculation method Carcinogenicity Calculation method Reproductive toxicity Calculation method STOT - single exposure Calculation method STOT - repeated exposure Calculation method Acute aquatic toxicity Calculation method Chronic aquatic toxicity Calculation method Aspiration hazard Calculation method Calculation method Ozone Key literature references and sources for data used to compile the SDS European Food Safety Authority (EFSA) European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC) European Chemicals Agency (ECHA) (ECHA_API) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) International Uniform Chemical Information Database (IUCLID) National Institute of Technology and Evaluation (NITE) NIOSH (National Institute for Occupational Safety and Health) Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set **Prepared By** Product Safety & Regulatory Affairs

Revision date	31-Oct-2022
no n	0.00.2022

No information available

Training Advice

BOSTIK INSTANT PAINTABLE CAULK DECORATION WHITE Supercedes Date: 27-Nov-2021 Revision date 31-Oct-2022

Revision Number 2

Further information

No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet