SAFETY DATA SHEET

BOSTIK 83211C
Revision Number 2

Revision date 03-Feb-2022
Supersedes Date: 09-Oct-2016

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK 83211C

Product Code(s)
30608507
30608507; 30608511; 30840747

Other means of identification

Proper Shipping Name Adhesives

UN number or ID number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against No information available

Details of manufacturer or importer

Supplier
Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Flammable liquids	Category 2 - (H225)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)

Label elements

Flame

Exclamation mark
Health hazard

Signal word
Danger

Hazard statements
H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Wash face, hands and any exposed skin thoroughly after handling
Use only outdoors or in a well-ventilated area
Do not breathe dust/fume/gas/mist/vapors/spray
Ground and bond container and receiving equipment
Use non-sparking tools
Take action to prevent static discharges
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Keep cool
Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN: Wash with plenty of water and soap
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
IF INHALED: Remove person to fresh air and keep comfortable for breathing
Call a POISON CENTER or doctor if you feel unwell
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish
Precautionary Statements - Storage
Store in a well-ventilated place
Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other hazards which do not result in classification
Harmful to aquatic life with long lasting effects.
In use, may form flammable/explosive vapor-air mixture.

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)
Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Toluene	108-88-3	10 - <30
Methyl ethyl ketone	78-93-3	10 - <30
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	64742-49-0	10 - <30
Pentane	109-66-0	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable Extinguishing Media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	No information available.

Specific hazards arising from the chemical

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO2). Hydrogen chloride.

Special protective actions for fire-fighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Precautions to prevent secondary hazards

Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static

discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

Recommended storage temperature Keep at temperatures between 41 and 77 °F / 5 and 25 °C.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Toluene 108-88-3	50 ppm TWA 191 mg/m³ TWA 150 ppm STEL 574 mg/m³ STEL
Methyl ethyl ketone 78-93-3	150 ppm TWA 445 mg/m³ TWA 300 ppm STEL 890 mg/m³ STEL
Pentane 109-66-0	600 ppm TWA 1770 mg/m³ TWA 750 ppm STEL 2210 mg/m³ STEL

Biological occupational exposure limits

Appropriate engineering controls

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Hand protection	Wear suitable gloves. Impervious gloves.
Respiratory protection	Organic gases and vapors filter conforming to EN 14387.
Environmental exposure controls	No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Dispersion
Color	clear
Odor	Aliphatic hydrocarbons
Odor threshold	No information available

Property	**Values**	**Remarks • Method**
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	> 55 °C	
Flash point	< 0 °C	
Evaporation rate	No data available	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	8.0	
Lower flammability or explosive limits	1.2	
Vapor pressure	3 - 3.5	
Relative vapor density	No data available	
Relative density	0.83	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	200 °C	
Decomposition temperature	No data available	
Kinematic viscosity	> 400 mm²/s	@ 25 °C
Dynamic viscosity	3500 4500 mPa s	@ 25 °C
Explosive properties	No information available	
Oxidizing properties	No information available	

Other information

Solid content (%)	approx 26	
Liquid Density	No information available	
VOC Content (%)	638 g/L	SCAQMD Method 304-91

Section 10: Stability and reactivity

Reactivity

Reactivity	No information available.

Chemical stability

Stability	Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	>5000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=73680 ppm (Rattus) 4 h
Pentane	>2000 mg/kg (Rattus)	= 3000 mg/kg (Oryctolagus	=364 g/m³ (Rattus) 4 h

		cuniculus)	

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information					
Methyl ethyl ketone (78-93-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			irritant

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	No sensitization responses were observed

Germ cell mutagenicity No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Toluene 108-88-3			Group 3
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	Carc. 1A		

Legend
IARC (International Agency for Research on Cancer)
Group 3 - Not Classifiable as to Carcinogenicity in Humans

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. Suspected of damaging fertility or the unborn child.

Component Information		
Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness. May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Pentane 109-66-0	-	LC50: =11.59mg/L (96h, Pimephales promelas) LC50: =9.87mg/L (96h, Oncorhynchus mykiss) LC50: =9.99mg/L (96h, Lepomis macrochirus)	-	EC50: =9.74mg/L (48h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	**Exposure time**	**Value**	**Results**
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Toluene 108-88-3	2.7
Methyl ethyl ketone 78-93-3	0.3
Pentane 109-66-0	3.39

Mobility

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
Special Provisions	*
Limited quantity (LQ)	5 L
Description	UN1133, Adhesives, 3, II

IATA

UN number or ID number	UN1133
Transport hazard class(es)	3
Packing group	II
ERG Code	3L
Special Provisions	A3
Limited quantity (LQ)	1 L
Description	UN1133, Adhesives, 3, II

IMDG

UN number or ID number	UN1133
Transport hazard class(es)	3
Packing group	II
EmS-No	F-E, S-D
Limited Quantity (LQ)	5 L
Marine pollutant	NP
Description	UN1133, Adhesives, 3, II, (0°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia
See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)
Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number 5

Major hazard (accident/incident planning) regulation
Verify that license requirements are met

Hazardous chemical	Threshold quantity (T)
Liquids that meet the criteria for Class 3 Packing Group II or III	50 000
Liquids with flash points <61°C kept above their boiling points at ambient conditions	200

National pollutant inventory
Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene 108-88-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Pentane 109-66-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AIIC	Listed
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed
PICCS	Not Listed

Legend:
AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:
This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS
This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Feb-2022

Revision Note
***Indicates updated data since last publication.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION
LD50 (lethal dose)
Section 12: Ecological information
EC50 (effective concentration)

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet