



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK S115 SILICONE SEALANT GREY WHITE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

### 2.2. Label elements

**Signal word**  
None

**Hazard statements**  
H412 - Harmful to aquatic life with long lasting effects.

**EU Specific Hazard Statements**  
EUH208 - Contains Trimethoxyvinylsilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

**Precautionary Statements - EU (§28, 1272/2008)**  
P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P273 - Avoid release to the environment

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

## PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Silica, amorphous	231-545-4	7631-86-9	5 - <10	[B]	-	01-2119379499-16-XXXX
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	1 - <3	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	0.1 - <1	[C]	-	01-2119489379-17-XXXX
Methyl alcohol	(603-001-00-X) 200-659-6	67-56-1	0.1 - <0.3	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	01-2119433307-44-XXXX
Diocetyl tin oxide	212-791-1	870-08-6	0.1 - <0.3	STOT SE 2 (H371)	-	01-2119971268-27-xxxx
Octamethylcyclotetrasiloxane [D4]	(014-018-00-1) 209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238-36-XXXX
2-octyl-2H-isothiazol-3-one [OIT]	(613-112-00-5) 247-761-7	26530-20-1	0.0025 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B	Skin Sens. 1A :: C>=0.0015%	-

# SAFETY DATA SHEET

BOSTIK S115 SILICONE SEALANT GREY WHITE  
Supersedes Date: 02-Feb-2023

Revision date 26-May-2023  
Revision Number 2.02

				(H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		
--	--	--	--	--	--	--

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - This substance meets the PBT criteria of REACH, annex XIII

This substance meets the vPvB criteria of REACH, annex XIII

**Full text of H- and EUH-phrases: see section 16**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** No information available.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the

# SAFETY DATA SHEET

BOSTIK S115 SILICONE SEALANT GREY WHITE  
Supercedes Date: 02-Feb-2023

Revision date 26-May-2023  
Revision Number 2.02

surrounding environment.

**Unsuitable extinguishing media** No information available.

## **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** No information available.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

## **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### **6.2. Environmental precautions**

**Environmental precautions** See Section 12 for additional Ecological Information.

### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### **6.4. Reference to other sections**

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

### **7.2. Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place.

### **7.3. Specific end use(s)**

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

Chemical name	European Union	United Kingdom
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup> STEL: 0.3 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*
Diocetyl tin oxide 870-08-6	-	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Short term Local health effects worker	Inhalation	260 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Long term Systemic health effects worker	Inhalation	260 mg/m <sup>3</sup>	
Long term Local health effects worker	Inhalation	260 mg/m <sup>3</sup>	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m <sup>3</sup>	

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Trimethoxyvinylsilane (2768-02-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>Methyl alcohol (67-56-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term	Oral	8 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Systemic health effects			
Consumer	Inhalation	50 mg/m <sup>3</sup>	
Long term			
Local health effects			
Consumer	Oral	8 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	50 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Dermal	50 mg/kg bw/d	
Long term			
Systemic health effects			

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Oral	0.0005 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Dermal	0.025 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	0.0009 mg/m <sup>3</sup>	
Long term			
Systemic health effects			

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	13 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Oral	3.7 mg/kg bw/d	
Long term			
Systemic health effects			

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Trimethoxyvinylsilane (2768-02-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>Diocetyl tin oxide (870-08-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

## Personal protective equipment

**Eye/face protection** Tight sealing safety goggles.  
**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.  
**Skin and body protection** Suitable protective clothing.

**Environmental exposure controls** No information available.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Paste / Gel Liquid  
**Appearance** Paste  
**Colour** Grey White  
**Odour** Characteristic.  
**Odour threshold** No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	= 301 °C	
<b>Flammability</b>	Not applicable for liquids .	
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	None known.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	Immiscible in water.	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Liquid Density</b>	1.03 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	



# SAFETY DATA SHEET

BOSTIK S115 SILICONE SEALANT GREY WHITE  
Supersedes Date: 02-Feb-2023

Revision date 26-May-2023  
Revision Number 2.02

Particle Size Distribution No information available

## 9.2. Other information

Solid content (%) No information available  
VOC content No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

### 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

Inhalation Based on available data, the classification criteria are not met.  
Eye contact Based on available data, the classification criteria are not met.  
Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.  
Ingestion Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

BOSTIK S115 SILICONE SEALANT GREY WHITE  
Supersedes Date: 02-Feb-2023

Revision date 26-May-2023  
Revision Number 2.02

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

## Acute toxicity

## Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 38,876.30 mg/kg

ATEmix (inhalation-dust/mist) 86.40 mg/l

ATEmix (inhalation-vapour) 177.90 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Diocetyl tin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m <sup>3</sup> (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Acute Eye Irritation/Corrosion					
--------------------------------	--	--	--	--	--

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

**Respiratory or skin sensitisation** OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

Octamethylcyclotetrasiloxane [D4] (556-67-2)

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

**Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
--------	---------	---------

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable
--	-----	------------------

## STOT - single exposure

Based on available data, the classification criteria are not met.

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

## STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

## Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, <i>Pseudokirchneriella subcapitata</i> )	LC50: =5000mg/L (96h, <i>Brachydanio rerio</i> )	-	EC50: =7600mg/L (48h, <i>Ceriodaphnia dubia</i> )		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l ( <i>Desmodesmus subspicatus</i> ) EU Method C.3	LC50 (96h) = 191 mg/l ( <i>Oncorhynchus mykiss</i> )	-	EC50(48hr) 168.7mg/l ( <i>Daphnia magna</i> )		

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Octamethylcyclotetrasil oxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

Octamethylcyclotetrasiloxane [D4] (556-67-2)  
 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

Mineralization in Surface Water - Simulation Biodegradation Test			
---	--	--	--

## **12.3. Bioaccumulative potential**

### **Bioaccumulation**

#### **Component Information**

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Methyl alcohol	-0.77
Dioctyltin oxide	6
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## **12.4. Mobility in soil**

**Mobility in soil** No information available.

## **12.5. Results of PBT and vPvB assessment**

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does not apply
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Methyl alcohol	The substance is not PBT / vPvB PBT assessment does not apply Further information relevant for the PBT assessment is necessary
Dioctyltin oxide	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## **12.6. Endocrine disrupting properties**

**Endocrine disrupting properties** No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

## **12.7. Other adverse effects**

No information available.

## **SECTION 13: Disposal considerations**

### **13.1. Waste treatment methods**

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

# SAFETY DATA SHEET

BOSTIK S115 SILICONE SEALANT GREY WHITE  
Supersedes Date: 02-Feb-2023

Revision date 26-May-2023  
Revision Number 2.02

**Contaminated packaging** Do not reuse empty containers.

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None  
14.7 Maritime transport in bulk according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	69. 75.
Diocetyl tin oxide	870-08-6	20.

# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 2-octyl-2H-isothiazol-3-one [OIT]

## Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 649/2012 - Annex Number
Diocetyl tin oxide	I.1

## Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour  
H226 - Flammable liquid and vapour  
H301 - Toxic if swallowed  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H330 - Fatal if inhaled  
H331 - Toxic if inhaled  
H332 - Harmful if inhaled  
H361f - Suspected of damaging fertility  
H370 - Causes damage to organs  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### Notes relating to the identification, classification and labelling of substances

**Note V:** If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in



# SAFETY DATA SHEET

**BOSTIK S115 SILICONE SEALANT GREY WHITE**  
**Supersedes Date:** 02-Feb-2023

**Revision date** 26-May-2023  
**Revision Number** 2.02

quantities leading to significant impairment of particle clearance mechanisms in the lung

## Notes relating to the classification and labelling of mixtures

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 26-May-2023

## Indication of changes

**Revision note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

**This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**