



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK EPOXY CONTROL - RESIN

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA
420 rue d'Estienne d'Orves
92700 Colombes
FRANCE
Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains bis-[4-(2,3-epoxypropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01



Signal word
Warning

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H411 - Toxic to aquatic life with long lasting effects

EU Specific Hazard Statements

EUH205 - Contains epoxy constituents. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P337 + P313 - If eye irritation persists: Get medical advice/attention
P391 - Collect spillage
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
bis-[4-(2,3-epoxipropoxy)phenyl]propane 40 - <80 %	(603-073-00-2) 216-823-5	1675-54-3	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411) (EUH205)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	-	-	01-2119456619-26-xxxx
Bisphenol-A-Epichlorhyd	500-033-5	25068-38-6	Skin Irrit. 2 (H315)	Eye Irrit. 2 :: C>=5%	-	-	01-2119456619-

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

rin Epoxy resin <= 700 MW 10 - <20 %			Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Skin Irrit. 2 :: C>=5%			26-xxxx
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol 10 - <20 %	500-006-8	9003-36-5	Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	-	-	-	01-2119454392-40-XXXX
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) 5 - <10 %	618-939-5	933999-84-9	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 3 (H412)	-	-	-	01-2119463471-41-XXXX
Benzyl alcohol 1 - <5 %	(603-057-00-5) 202-859-9	100-51-6	Acute Tox. 4 (H302) Acute Tox. 4 (H332) Eye Irrit. 2 (H319)	-	-	-	01-2119492630-38-XXXX
Glycidoxypropyltrimethoxysilane 1 - <2.5 %	219-784-2	2530-83-8	Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)	-	-	-	01-2119513212-58-XXXX

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(603-073-00-2) 216-823-5	1675-54-3	-	-	-	-	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	-	-	-	-	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	500-006-8	9003-36-5	-	-	-	-	-
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	618-939-5	933999-84-9	-	-	-	-	-
Benzyl alcohol	(603-057-00-5) 202-859-9	100-51-6	1620	-	4.2	-	-
Glycidoxypropyltrimethoxysilane	219-784-2	2530-83-8	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Hydrogen chloride. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. See section 8 for more information.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12.25 mg/m ³	
worker Short term Systemic health effects	Inhalation	12.25 mg/m ³	

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	12.25 mg/kg bw/d	

Benzyl alcohol (100-51-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	22 mg/m ³	
worker Short term Systemic health effects	Inhalation	110 mg/m ³	
worker Long term Systemic health effects	Dermal	8 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	40 mg/kg bw/d	

Glycidoxypropyltrimethoxysilane (2530-83-8)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	70.5 mg/m ³	
worker Long term Systemic health effects	Dermal	10 mg/kg bw/d	

Derived No Effect Level (DNEL)

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d	
---	--------	-----------------	--

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)			
---	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	

Benzyl alcohol (100-51-6)			
----------------------------------	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	5.4 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	27 mg/m ³	
Consumer Long term Systemic health effects	Dermal	4 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	20 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	4 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	20 mg/kg bw/d	

Glycidoxypropyltrimethoxysilane (2530-83-8)			
--	--	--	--

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	5 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supercedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.001 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	0.996 mg/kg dry weight
Marine sediment	0.1 mg/kg dry weight
Soil	0.196 mg/kg dry weight

Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW (25068-38-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.0006 mg/l
Freshwater sediment	0.996 mg/l
Marine sediment	0.0996 mg/l
Soil	0.196 mg/l

Benzyl alcohol (100-51-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Microorganisms in sewage treatment	39 mg/l
Freshwater sediment	5.27 mg/kg dry weight
Marine sediment	0.527 mg/kg dry weight
Soil	0.456 mg/kg dry weight
Freshwater - intermittent	2,3 mg/l

Glycidoxypropyltrimethoxysilane (2530-83-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.45 mg/l
Marine water	0.045 mg/l
Freshwater sediment	1.6 mg/kg dry weight
Sewage treatment plant	8.2 mg/l
Soil	0.063 mg/kg dry weight
Marine sediment	0.16 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Please refer also to Safety Data Sheet of Part B.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear protective gloves. Nitrile rubber. Butyl rubber. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374. Gloves must conform to standard EN 374.

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Off-white
Odour	Slight.
Odour threshold	No information available

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Initial boiling point and boiling range	> 200 °C	
Flammability	Not applicable for liquids	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	150 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	4 - 6	solution (1 %). Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	10 - 20 Pa.s	@ 25 °C
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.16 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
 Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	33,061.20 mg/kg
ATEmix (dermal)	36,231.90 mg/kg
ATEmix (inhalation-dust/mist)	85.70 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
bis-[4-(2,3-epoxypropoxy)phenyl]propane	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	>2 g/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) (OECD 402)	-
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	LD50 = 2190 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Benzyl alcohol	LD50 = 1620 mg/kg (Rattus)	> 2 g/kg (Oryctolagus cuniculus)	>4.17 mg/L (Rattus) 4 h

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Glycidoxypropyltrimethoxysilane	=8025 mg/kg (Rattus)	= 4250 mg/kg (Oryctolagus cuniculus)	>5.3 mg/L (Rattus) 4 h
---------------------------------	----------------------	--------------------------------------	------------------------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Eye Damage

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects. Harmful to aquatic life.

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) = 2.7 mg/L (Daphnia magna) (OECD 202)		
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna		
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2) 933999-84-9	-	LC50 (96h) = 30 mg/L (Oncorhynchus mykiss) OECD 203	-	EC50 (48h) = 39 - 57 mg/L (Daphnia magna) OECD 202		
Benzyl alcohol 100-51-6	EC 50 (72h) = 700 mg/L (Pseudokirchnerella subcapitata) OECD 201	LC50 96 h = 460 mg/L (Pimephales promelas static)	EC50 = 50 mg/L 5 min EC50 = 63.7 mg/L 15 min EC50 = 63.7 mg/L 5 min EC50 = 71.4 mg/L 30 min	EC50 48 h = 230 mg/L (Daphnia magna)		
Glycidoxypropyltrimethoxysilane 2530-83-8	EC50 (96hr): 350 mg/l Pseudokirchnerella subcapitata	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203	-	EC50 (48h) = 473 mg/L Daphnia magna		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
bis-[4-(2,3-epoxipropoxy)phenyl]propane	3.78
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	3.26
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3.6
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	0.822
Benzyl alcohol	1.05

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

bis-[4-(2,3-epoxipropoxy)phenyl]propane	The substance is not PBT / vPvB
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	The substance is not PBT / vPvB
Reaction products of hexane-1,6-diol with 2-(chloromethyl)oxirane (1:2)	The substance is not PBT / vPvB
Benzyl alcohol	The substance is not PBT / vPvB
Glycidoxypropyltrimethoxysilane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/ container to an approved landfill.
Contaminated packaging	Do not reuse empty containers.
Waste codes / waste designations according to EWC	15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW)
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW), 9, III, (-)
14.5 Environmental hazards	Yes
14.6 Special Provisions	274, 335, 601, 375
Classification code	M6
Tunnel restriction code	(-)

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	90
IMDG	
14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW), 9, III, Marine Pollutant
14.5 Marine pollutant	P
14.6 Special Provisions	274, 335, 969
Limited Quantity (LQ)	5 L
EmS-No	F-A, S-F
14.7 Maritime transport in bulk according to IMO instruments	Not applicable
Air transport (ICAO-TI / IATA-DGR)	
14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxy)phenyl]propane, Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW), 9, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A97, A158, A197
Limited quantity (LQ)	30 kg G
ERG Code	9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH205 - Contains epoxy constituents. May produce an allergic reaction
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H332 - Harmful if inhaled
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure

Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method

SAFETY DATA SHEET

EVO-STIK EPOXY CONTROL - RESIN
Supersedes Date: 24-Jun-2021

Revision date 02-Feb-2023
Revision Number 1.01

Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By	Product Safety & Regulatory Affairs
Revision date	02-Feb-2023
Revision note	SDS sections updated: 2 3 11 12
Training Advice	When working with hazardous materials, regular training of operators is required by law
Further information	No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet