



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**SIROFLEX CONTRACTORS CAULK ACRYLIC**  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** SIROFLEX CONTRACTORS CAULK ACRYLIC

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant

**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

## 2.3. Other hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Ethylene glycol 0.1 - <1 %	203-473-3 (603-027-00-1)	107-21-1	Acute Tox. 4 (H302) STOT RE 2 (H373)	-	-	-	01-2119456816-28-XXXX
Sodium hydroxide 0.1 - <0.3 %	215-185-5 (011-002-00-6)	1310-73-2	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 0.5%≤C<2% Eye Dam. 1 :: C>=2% Skin Corr. 1A :: C>=5% Skin Corr. 1B :: 2%≤C<5% Skin Irrit. 2 :: 0.5%≤C<2%	-	-	01-2119457892-27-XXXX
1,2-benzisothiazol-3(2H)-one [BIT] 0.0025 - <0.01 %	220-120-9 (613-088-00-6)	2634-33-5	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.036%	1	1	01-2120761540-60-XXXX
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] <0.0015 %	611-341-5	55965-84-9	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%≤C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%≤C<0.6% Skin Sens. 1 :: C>=0.0015%	100	100	-

**Full text of H- and EUH-phrases: see section 16**

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE<sub>mix</sub>) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Ethylene glycol	203-473-3	107-21-1	500	-	-	-	-

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
	(603-027-00-1)						
Sodium hydroxide	215-185-5 (011-002-00-6)	1310-73-2	-	-	-	-	-
1,2-benzisothiazol-3(2H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21+	0.21+
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	100	87.12	0.33	-	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	B

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	If swallowed, rinse mouth with water (only if the person is conscious).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	No information available.
<b>Effects of Exposure</b>	No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	No information available.
------------------------	---------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

**Unsuitable extinguishing media** Full water jet.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** No information available.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protective equipment as required.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from frost. Keep away from food, drink and animal feedingstuffs. Keep from freezing.

**Recommended storage temperature** Keep at temperatures between 5 and 35 °C. Do not freeze.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
 Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
 Revision Number 1

Other information Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Ethylene glycol 107-21-1	TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> *	TWA: 10 mg/m <sup>3</sup> TWA: 20 ppm TWA: 52 mg/m <sup>3</sup> STEL: 40 ppm STEL: 104 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> Sk*
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	35 mg/m <sup>3</sup>	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Ethylene glycol (107-21-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	7 mg/m <sup>3</sup>	

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	
--	--------	------------------	--

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
- Hand protection** Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 480 min. Gloves must conform to standard EN 374
- Skin and body protection** Suitable protective clothing.
- Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White
Odour	Characteristic.

Property	Values	Remarks • Method
Melting point / freezing point	0 °C	
Initial boiling point and boiling range	100 °C	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive	No data available	

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

limits		
Flash point	Not applicable	
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	7 - 9	
pH (as aqueous solution)	No data available	
Kinematic viscosity	> 21 mm <sup>2</sup> /s	@ 40 °C
Dynamic viscosity	No data available	
Water solubility	Miscible in water. Partially soluble.	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	No data available	
Relative density	No data available	
Bulk density	No data available	
Density	ca. 1.55 - 1.57 g/cm <sup>3</sup>	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

## 9.2. Other information

Solid content (%)	No information available	
VOC content		approx 14.6 g/L

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Protect from frost. Do not freeze.

### 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

### 10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions.

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

products

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	> 2.5 mg/L ( Rat ) 6 h
Sodium hydroxide	=325 mg/kg (Rattus)	= 1350 mg/kg (Oryctolagus cuniculus)	-
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
reaction mass of 5-chloro-2-methyl-2H-isothiazolo- [3,4-b]pyridin-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	= 53 mg/kg ( Rat )	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May produce an allergic reaction.



# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneriella subcapitata)	LC50 96 h = 16000 mg/L (Poecilia reticulata static)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
Sodium hydroxide 1310-73-2	-	LC50: =45.4mg/L (96h, Oncorhynchus mykiss)	-	-		
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006	-	EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	EC50 (72h) =0.048 mg/L (Pseudokirchneriella subcapitata) (OECD 201)	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	biodegradation	Not readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation**

### Component Information

Chemical name	Partition coefficient
Ethylene glycol	-1.36
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Ethylene glycol	The substance is not PBT / vPvB
Sodium hydroxide	The substance is not PBT / vPvB
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name -  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None  
14.7 Maritime transport in bulk  
according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

##### **Export Notification requirements**

# SAFETY DATA SHEET

SIROFLEX CONTRACTORS CAULK ACRYLIC  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

**Note B:** Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations.

In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

#### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)

# SAFETY DATA SHEET

**SIROFLEX CONTRACTORS CAULK ACRYLIC**  
Supersedes date 26-Jun-2024

Revision date 26-Jun-2024  
Revision Number 1

---

IATA International Air Transport Association (IATA)  
RID Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 26-Jun-2024

## Indication of changes

**Revision note** SDS sections updated: 11.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**