

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes date 01-Aug-2022 Revision date 01-Aug-2024 Revision Number 3.02

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1	.1.	Prod	uct id	lentifier	

Product Name EVO-STIK BUILD SILICONE SEALANT WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Sealant

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Chronic aquatic toxicity Category 3 - (H412)

### 2.2. Label elements

Signal word None

### Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

### **EU Specific Hazard Statements**

EUH208 - Contains Trimethoxyvinylsilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children

P273 - Avoid release to the environment

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

P501 - Dispose of contents/ container to an approved waste disposal plant

### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

### PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

### SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]	(002)		,	nambol
Hydrocarbons, C13-C23,	932-078-5	RR-100254-6		_	_	-	01-2119552497-
n-alkanes, isoalkanes,	352-070-5	1111-100234-0	Asp. 10x. 1 (11504)	-	-	-	29-xxxx
cyclics, < 0.03%							20 ////
aromatics							
10 - <20 %							
Trimethoxyvinylsilane	220-449-8	2768-02-7	Acute Tox. 4 (H332)	-	-	-	01-2119513215-
1 - <3 %	(014-049-00-		Skin Sens. 1B (H317)				52-XXXX
	0)		Flam. Liq. 3 (H226)				
			,				
Titanium dioxide	236-675-5	13463-67-7	[C]	-	-	-	01-2119489379-
0.1- <1 %	(022-006-00-						17-XXXX
	2)						
Methyl alcohol	200-659-6	67-56-1	( )	STOT SE 1 :: C>=10%	-	-	01-2119433307-
0.1 - <0.3 %	(603-001-00-		Acute Tox. 3 (H311)	STOT SE 2 ::			44-XXXX
	X)		Acute Tox. 3 (H331)	3%<=C<10%			
			STOT SE 1 (H370)				
			Flam. Liq. 2 (H225)				
Dioctyltin oxide	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268-
0.1 - <0.3 %							27-xxxx
Octamethylcyclotetrasilo	209-136-7	556-67-2	Repr. 2 (H361f)	-	-	10	01-2119529238-
xane [D4]	(014-018-00-		Aquatic Chronic 1 (H410)				36-XXXX
0.05 - <0.1 %	1)		Flam. Liq. 3 (H226)				
	047 704 7	26530-20-1	[G]	Skin Sens. 1A ::	400	100	
2-octyl-2H-isothiazol-3-o	247-761-7	26530-20-1	Acute Tox. 3 (H301)		100	100	-
ne [OIT] 0.0025 - <0.01 %	(613-112-00-		Acute Tox. 3 (H311) Acute Tox. 2 (H330)	C>=0.0015%			
0.0025 - <0.01 %	5)		Skin Corr. 1B (H314)				
			Eye Dam 1 (H318)				
			Skin Sens. 1A (H317)				
			Aquatic Acute 1 (H400)				
			Aquatic Acute 1 (1400) Aquatic Chronic 1				
			(H410)				
			(EUH071)				
Substances identified b							

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

### Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to	Specific concentration	M-Factor	M-Factor (long-term)	REACH registration
		Regulation (EC) No. 1272/2008	limit (SCL)			number

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

		[CLP]				
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring [G] - PBT / vPvB substance

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	RR-100254-6	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	-	3	-
Dioctyltin oxide	212-791-1	870-08-6	-	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3- one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125+	311+	0.27+	0.27 +	0.27+

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

### SECTION 4: First aid measures

### 4.1. Description of first aid measures

### EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes date 01-Aug-2022

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed,			
	have product container or label at hand.			
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.			
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.			
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.			
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.			
4.2. Most important symptoms and	d effects, both acute and delayed			
Symptoms	None known.			
Effects of Exposure	No information available.			
4.3. Indication of any immediate medical attention and special treatment needed				
Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.			
SECTION 5: Firefighting me	asures			
5.1. Extinguishing media				
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.			
Unsuitable extinguishing media	Full water jet.			
5.2. Special hazards arising from t	he substance or mixture			
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.			
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.			
5.3. Advice for firefighters				
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.			
SECTION 6: Accidental relea	ase measures			
6.1. Personal precautions, protect	ive equipment and emergency procedures			
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2 Environmental pressutions				

6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

EVO-STIK BUILD SILICONE SEALANT WHITE

6.3. Methods and material for cont	6.3. Methods and material for containment and cleaning up						
Methods for containment	Do not scatter spilled material with high pressure water streams.						
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.						
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.						
6.4. Reference to other sections							
Reference to other sections	See section 8 for more information. See section 13 for more information.						
SECTION 7: Handling and s	torage						
7.1. Precautions for safe handling	_						
Advice on safe handling	Ensure adequate ventilation.						
General hygiene considerations	General hygiene considerations Take off all contaminated clothing and wash it before reuse.						
7.2. Conditions for safe storage, ir	ncluding any incompatibilities						
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.						
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.						
7.3. Specific end use(s)							
<b>Specific use(s)</b> Sealant.							
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.						
Other information Observe technical data sheet.							
SECTION 8: Exposure contr	rols/personal protection						
8.1. Control parameters	8.1. Control parameters						

### 8.1. Control parameters

**Exposure Limits** 

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Silica, amorphous	-	TWA: 6 mg/m <sup>3</sup>
7631-86-9		TWA: 2.4 mg/m <sup>3</sup>
		STEL: 18 mg/m <sup>3</sup>
		STEL: 7.2 mg/m <sup>3</sup>
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 250 ppm
		STEL: 333 mg/m <sup>3</sup>
		Sk*
Dioctyltin oxide	-	TWA: 0.1 mg/m <sup>3</sup>
870-08-6		STEL: 0.2 mg/m <sup>3</sup>
		Sk*

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

1	Chemical name	European Union	Ireland	United Kingdom
	Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
	67-56-1		shift)	

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)							
Trimethoxyvinylsilane (2768-	Frimethoxyvinylsilane (2768-02-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
worker Systemic health effects Long term	Inhalation	27,6 mg/m³					
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d					

Titanium dioxide (13463-6)	7-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	10 mg/m <sup>3</sup>	
Long term Local health effects			

Methyl alcohol (67-56-1)	Methyl alcohol (67-56-1)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d			
Short term Systemic health effects worker	Inhalation	260 mg/m³			
Short term Local health effects worker	Inhalation	260 mg/m³			
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d			
worker Long term Systemic health effects	Inhalation	260 mg/m³			
Long term Local health effects worker	Inhalation	260 mg/m³			

Dioctyltin oxide (870-08-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m³	

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

worker	Inhalation	73 mg/m³	
Long term		-	
Systemic health effects			

Derived No Effect Level (DNE	EL)		
Trimethoxyvinylsilane (2768-	02-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Туре		Derived No Effect Level (DNEL)	Safety factor
Consumer	Oral	700 mg/kg bw/d	
Long term Systemic health effects			

Methyl alcohol (67-56-1)	Methyl alcohol (67-56-1)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	50 mg/m³	
Consumer Long term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	50 mg/m³	
Consumer Long term Systemic health effects	Dermal	50 mg/kg bw/d	

Dioctyltin oxide (870-08-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m³	

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Dioctyltin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.0015 mg/l		
Marine water	0.00015 mg/l		
Freshwater sediment	3 mg/kg		
Marine sediment	0.3 mg/kg		
Soil	0.54 mg/kg		
Sewage treatment plant	10 mg/l		

### 8.2. Exposure controls

**Engineering controls** 

Ensure adequate ventilation, especially in confined areas.

# Personal protective equipment<br/>Eye/face protectionWear safety glasses with side shields (or goggles). Eye protection must conform to<br/>standard EN 166.Hand protectionWear suitable gloves. Gloves must conform to standard EN 374. Ensure that the<br/>breakthrough time of the glove material is not exceeded. Refer to glove supplier for<br/>information on breakthrough time for specific gloves. The breakthrough time of the gloves<br/>depends on the material and the thickness as well as the temperature. Gloves should be<br/>replaced regularly and if there is any sign of damage to the glove material.<br/>None under normal use conditions.<br/>In case of inadequate ventilation wear respiratory protection. Wear a respirator<br/>conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

Revision date 01-Aug-2024 Revision Number 3.02

Recommended filter type:	especially in confined areas. Organic gases and vapours filter conforming to EN 14387. White. Brown.	
Recommended filter type:		n.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

### SECTION 9: Physical and chemical properties

9.1. Information on basic physical	and chemical properties		
Physical state	Solid	<u> </u>	
Appearance	Paste		
Colour	White		
Odour	Characteristic.		
Property	Values		Remarks • Method
Melting point / freezing point	No data available		None known
Initial boiling point and boiling	No data available		
range			
Flammability	No data available		
Flammability Limit in Air			None known
Upper flammability or explosive	No data available		
limits			
Lower flammability or explosive	No data available		
limits			
Flash point	> 60 °C		
Autoignition temperature	No data available		
Decomposition temperature			None known
рН	No data available		Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available		None known
Kinematic viscosity	> 21 mm²/s		
Dynamic viscosity	No data available		
Water solubility	Insoluble in water.		
Solubility(ies)	No data available		None known
Partition coefficient	No data available		None known
Vapour pressure	No data available		None known
Relative density	1.00		
Bulk density	No data available		
Density Relative veneur density	No data available		None known
Relative vapour density Particle characteristics	No data available		None known
Particle Size	No information available		
Particle Size Distribution	No information available		
Particle Size Distribution			
9.2. Other information			
Solid content (%)	No information available		
VOC content		No data ava	ailable
9.2.1. Information with regards to p	physical hazard classes		

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

### SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity

Product cures with moisture.

10.2. Chemical stability

EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

Stability	Stable under normal conditions.	
Explosion data		
Sensitivity to mechanical impact	None.	
Sensitivity to static discharge	None.	
10.3. Possibility of hazardous reac	tions	
Possibility of hazardous reactions	None under normal processing.	
10.4. Conditions to avoid		
Conditions to avoid	Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.	
10.5. Incompatible materials		
Incompatible materials	Strong oxidising agents.	
10.6. Hazardous decomposition pro	oducts	
Hazardous decomposition products	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.	
SECTION 11: Toxicological i	nformation	
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008_	
Information on likely routes of exp	osure	
Product Information		
Inhalation	Based on available data, the classification criteria are not met.	
Eye contact	Based on available data, the classification criteria are not met.	
Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.	
Ingestion	Based on available data, the classification criteria are not met.	
Symptoms related to the physical,	chemical and toxicological characteristics	
Symptoms	No information available.	
Acute toxicity		
Numerical measures of toxicity		
The following values are calculated ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist) ATEmix (inhalation-vapour)	d based on chapter 3.1 of the GHS document 37,769.20 mg/kg 113,307.60 mg/kg >20000 ppm 92.50 mg/l 194.00 mg/l	

### **Component Information**

### EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes date 01-Aug-2022

Revision date 01-Aug-2024 Revision Number 3.02

	0, 11, 550		
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C13-C23,	LD50 > 5000 mg/kg (Rattus)	LD50 > 2000 mg/kg	-
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	
< 0.03% aromatics		OECD 402	
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus	=22500 ppm (Rattus) 8 h =
		cuniculus)	64000 ppm (Rattus) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-
-		OECD 402	
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m <sup>3</sup> (Rattus) 4 h
[D4]	OECD 401	OECD 402	,
2-octyl-2H-isothiazol-3-one	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus	-
[OIT]		cuniculus)	

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant
Acute Eye					
Irritation/Corrosion					

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

**Respiratory or skin sensitisation** OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

**Component Information** 

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

# Method Species Results OECD Test No. 471: Bacterial Reverse in vitro Not mutagenic Mutation Test In vitro Not mutagenic

Carcinogenicity

Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

**Reproductive toxicity** 

Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure

Based on available data, the classification criteria are not met.

Dioctvltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developme	Rat			28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs:
ntal Toxicity Screening Test					Immune system

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Dioctyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects

No information available.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100254-6	EL50 (72h) > 10 000 mg/L (Skeletonema costatum)	LL50 (96h) > 1028 mg/L (Scophthalmus maximus)	-	LL50 (48h) > > 3193 mg/l (Acartia tonsa)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
Dioctyltin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	_	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Octamethylcyclotetrasil oxane [D4] 556-67-2		LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

### Revision date 01-Aug-2024 Revision Number 3.02

### Persistence and degradability

No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			

### Dioctyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	755 hours	biodegradation	Not readily biodegradable 2
Biodegradability: Manometric			%
Respirometry Test (TG 301 F)			

### Octamethylcyclotetrasiloxane [D4] (556-67-2)

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Exposure time	Value	Results		
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable		
Mineralization in Surface Water -					
Simulation Biodegradation Test					

### 12.3. Bioaccumulative potential

### Bioaccumulation

### **Component Information**

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Methyl alcohol	-0.77
Dioctyltin oxide	6
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

### 12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Trimethoxyvinylsilane	The substance is not PBT / vPvB	
Titanium dioxide	The substance is not PBT / vPvB	
Methyl alcohol	The substance is not PBT / vPvB	
Dioctyltin oxide	The substance is not PBT / vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB	

### 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission	Negative.	
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes date 01-Aug-2022

12.7. Other adverse effects

No information available.

### **SECTION 13: Disposal considerations**

|--|

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)

Lanu		
14.1	UN number or ID number	Not regulated
	UN proper shipping name	-
	Transport hazard class(es)	Not regulated
	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	
S	pecial Provisions	None
IMDG		
	UN number or ID number	Not regulated
	UN proper shipping name	Not regulated
	Transport hazard class(es)	Not regulated
	Packing group	Not regulated
	Marine pollutant	NP
	Special precautions for user	
	pecial Provisions	None
	Maritime transport in bulk	
	rding to IMO instruments	
TI	ransport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable
•••		
	ansport (ICAO-TI / IATA-DGR)	-
	UN number or ID number	Not regulated
	UN proper shipping name	Not regulated
	Transport hazard class(es)	Not regulated
	Packing group	Not regulated
-	Environmental hazards	Not applicable

### Section 15: REGULATORY INFORMATION

None

14.6 Special precautions for user

**Special Provisions** 

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	Use restricted. See entry 69.
	07 00 1	Use restricted. See entry 75.
Dioctyltin oxide	870-08-6	Use restricted. See entry 20.

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

### Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

### **Persistent Organic Pollutants**

Not applicable

### <u>REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the</u> marketing and use of explosives precursors

Not applicable

### National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

### SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

### EVO-STIK BUILD SILICONE SEALANT WHITE

Supercedes date 01-Aug-2022

Revision date 01-Aug-2024 Revision Number 3.02

### Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour

### H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

### H304 - May be fatal if swallowed and enters airways

### H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H331 - Toxic if inhaled

H332 - Harmful if inhaled

H370 - Causes damage to organs

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### Notes relating to the identification, classification and labelling of substances

**Note V:** If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

### Notes relating to the classification and labelling of mixtures

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10 µm

Legend	
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sour No information available Prepared By Revision date Indication of changes	ces for data Product Safety & Regulatory Affairs 01-Aug-2024
Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process,

### EVO-STIK BUILD SILICONE SEALANT WHITE Supercedes date 01-Aug-2022

Revision date 01-Aug-2024 Revision Number 3.02

unless specified in the text.

End of Safety Data Sheet