



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK FRAME SILICONE SEALANT WHITE

Form This substance/ mixture contains nanoforms

Other means of identification

Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Benelux B.V.
Denariusstraat 11
4903 RC Oosterhout
The Netherlands
Tel: + 31 162 491 000

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazardous to the aquatic environment - chronic	Category 3 - (H412)
---	---------------------

2.2. Label elements

Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
 Supercedes date 01-Aug-2024

Revision date 10-Jun-2026
 Revision Number 1.02

P102 - Keep out of reach of children
 P273 - Avoid release to the environment
 P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100254-6	10 - <20	01-2119552497-29-xxxx	932-078-5	Asp. Tox. 1 (H304)	-	-	-	-
Trimethoxyvinylsilane 2768-02-7	1 - <3	01-2119513215-52-XXXX	220-449-8 (014-049-00-0)	Acute Tox. 4 (H332) Skin Sens. 1B (H317) Flam. Liq. 3 (H226)	-	-	-	-
Titanium dioxide 13463-67-7	0.1 - <1	01-2119489379-17-XXXX	236-675-5	[C]	-	-	-	-
Methyl alcohol 67-56-1	0.1 - <0.3	01-2119433307-44-XXXX	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	-
Diocetyl tin oxide 870-08-6	0.1 - <0.3	01-2119971268-27-xxxx	212-791-1	STOT SE 2 (H371)	-	-	-	-
Octamethylcyclotetra siloxane [D4] 556-67-2	0.05 - <0.1	01-2119529238-36-XXXX	209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	0.0025 - <0.01	[10]	247-761-7 (613-112-00-5)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318)	Skin Sens. 1A :: C>=0.0015%	100	100	-

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

				Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)				
--	--	--	--	---	--	--	--	--

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

NOTE [10] - Biocides are regarded as registered substances according to Regulation (EC) No. 1907/2006 [REACH], Article 15 (1 and 2)

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - PBT / vPvB substance

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	932-078-5	RR-100254-6	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Titanium dioxide	236-675-5	13463-67-7	-	-	-	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	-	3	-
Diocetyl tin oxide	212-791-1	870-08-6	-	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125 ⁺	311 ⁺	0.27 ⁺	0.27 ⁺	0.27 ⁺

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supercedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Equipment cleaned with organic solvent, washings are collected and disposed of as

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

solvent waste. Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	Ireland	United Kingdom
Silica, amorphous, fumed, crystalline-free 112945-52-5	-	TWA: 6 mg/m ³ ; total inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ (calculated); respirable dust STEL: 7.2 mg/m ³ (calculated); respirable dust	TWA: 6 mg/m ³ ; inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ ; inhalable dust STEL: 7.2 mg/m ³ ; respirable dust
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ ; total inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ (calculated); respirable dust STEL: 7.2 mg/m ³ (calculated); respirable dust	TWA: 6 mg/m ³ ; inhalable dust TWA: 2.4 mg/m ³ ; respirable dust STEL: 18 mg/m ³ ; inhalable dust STEL: 7.2 mg/m ³ ; respirable dust
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m ³ ; total inhalable dust	TWA: 10 mg/m ³ ; total inhalable

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

		TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ (calculated); respirable dust STEL: 12 mg/m ³ (calculated);	TWA: 4 mg/m ³ ; respirable STEL: 30 mg/m ³ ; total inhalable STEL: 12 mg/m ³ ; respirable
Methyl alcohol 67-56-1	TWA: 200 ppm; TWA: 260 mg/m ³ ; pSk	TWA: 200 ppm; TWA: 260 mg/m ³ ; STEL: 600 ppm (calculated); STEL: 780 mg/m ³ (calculated); pSk	TWA: 200 ppm; TWA: 266 mg/m ³ ; STEL: 250 ppm; STEL: 333 mg/m ³ ; pSk
Diocetyl tin oxide 870-08-6	-	TWA: 0.1 mg/m ³ ; STEL: 0.2 mg/m ³ ;	TWA: 0.1 mg/m ³ ; STEL: 0.2 mg/m ³ ; pSk

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m ³	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m ³	
Short term Local health effects worker	Inhalation	260 mg/m ³	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m ³	
Long term Local health effects worker	Inhalation	260 mg/m ³	

Diocetyl tin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m ³	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m ³	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Dermal	50 mg/kg bw/d	

Diocetyl tin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level	Safety factor

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
 Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
 Revision Number 1.02

		(DNEL)	
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m ³	

Octamethylcyclotetrasiloxane [D4] (556-67-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m ³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

Trimethoxyvinylsilane (2768-02-7)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Diocetyl tin oxide (870-08-6)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™, Nitrile rubber, Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	White
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 60 °C	
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.00	
Bulk density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
 Supercedes date 01-Aug-2024

Revision date 10-Jun-2026
 Revision Number 1.02

ATEmix (oral) 37,734.60 mg/kg
 ATEmix (dermal) 113,203.80 mg/kg
 ATEmix (inhalation-gas) >20000 ppm
 ATEmix (inhalation-dust/mist) >5 mg/L
 ATEmix (inhalation-vapour) 189.00 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Oryctolagus cuniculus) OECD 402	-
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	> 5000 mg/kg (Rattus) OECD 425	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Diocetyl tin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye	Rabbit	Eye			Non-irritant

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supercedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

Irritation/Corrosion					
----------------------	--	--	--	--	--

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Eye Damage

Respiratory or skin sensitisation OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
 Supercedes date 01-Aug-2024

Revision date 10-Jun-2026
 Revision Number 1.02

Diocetyl tin oxide (870-08-6)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100254-6	EL50 (72h) > 1000 mg/L (Skeletonema costatum)	LL50 (96h) > 1028 mg/L (Scophthalmus maximus)	-	LL50 (48h) > > 3193 mg/l (Acartia tonsa)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

Octamethylcyclotetrasiloxane [D4] (556-67-2) 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Methyl alcohol	-0.77
Diocetyl tin oxide	6

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	Not PBT/vPvB
Titanium dioxide	Not PBT/vPvB
Methyl alcohol	Not PBT/vPvB
Diocetyl tin oxide	Not PBT/vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	Not PBT/vPvB

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Methyl alcohol	67-56-1	69 75

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

This product contains a biocidal product for the preservation of the dry film. Contains OIT.

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H301 - Toxic if swallowed
H304 - May be fatal if swallowed and enters airways
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H330 - Fatal if inhaled
H331 - Toxic if inhaled
H332 - Harmful if inhaled
H361f - Suspected of damaging fertility
H370 - Causes damage to organs
H371 - May cause damage to organs
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	SK*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
U.S. Environmental Protection Agency
U.S. EPA Acute Exposure Guideline Level(s) (AEGl(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
U.S. National Institute for Occupational Safety and Health (NIOSH)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 10-Jun-2026

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

SAFETY DATA SHEET

EVO-STIK FRAME SILICONE SEALANT WHITE
Supersedes date 01-Aug-2024

Revision date 10-Jun-2026
Revision Number 1.02

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet