

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022 Revision date 03-Jan-2025 Revision Number 3.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Product Name	EVO-STIK MULTI PURPOSE SILICONE WHITE	
Pure substance/mixture	Mixture	
1.2. Relevant identified uses of the	e substance or mixture and uses advised against	
Recommended use	Sealant	
Uses advised against	None known	
1.3. Details of the supplier of the s	afety data sheet	
Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36		
E-mail address	SDS.box-EU@bostik.com	
1.4. Emergency telephone number	<u>.</u>	
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111	
SECTION 2: Hazards identifi	ication	
2.1. Classification of the substance	e or mixture	
GB CLP (SI 2020/1567 as amended)	
Hazardous to the aquatic environn	nent - chronic Category 3 - (H412)	
2.2. Label elements		
Signal word None		

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] & Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand P102 - Keep out of reach of children

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Regulation (ĔC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)		M-Factor (long-ter m)	Notes
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	>25 - <40	01-2119827000 -58-XXXX	934-956-3	Asp. Tox. 1 (H304)	-	-	-	-
Triacetoxy(propyl)sil ane 17865-07-5	1 - <2.5	01-2119966899 -07-XXXX	241-816-9	Skin Corr. 1B (H314) (EUH071)	-	-	-	-
Silanetriol, methyl-, triacetate 4253-34-3	1 - <2.5	01-2119962266 -32-XXXX	224-221-9	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	-
Octamethylcyclotetra siloxane [D4] 556-67-2	0.036 - < 0.05		(014-018-00-1)	(H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
4,5-dichloro-2-octyl- 2H-isothiazol-3-one [DCOIT] 64359-81-5	0.01 < 0.036	No data available		Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Corr. 1 (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	0.025%<=C< 5%	100	100	-
Dimethylbis[(1-oxon eodecyl)oxy]stannan e 68928-76-7	0.01 < 0.036	01-2120770324 -57-xxxx	273-028-6	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Aquatic Chronic 3	-	-	-	-

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

		(H412)		
		, , , , , , , , , , , , , , , , , , ,		

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes [G] - PBT / vPvB substance

Full text of H- and EUH-phrases: see section 16

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Acetic acid 64-19-7	200-580-7 (607-002-00-6)	Skin Corr. 1A (H314) Flam. Liq. 3 (H226)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 25%<=C<90% Skin Irrit. 2 :: 10%<=C<25%	_	-	01-2119475328- 30-XXXX

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation	Inhalation LC50 - 4 hour -	Inhalation
	Index NO)		mg/kg	mg/kg	dust/mist -	vapour - mg/L	gas - ppm
					mg/L	rapour mg/E	guo ppin
Hydrocarbons,	934-956-3	RR-100252-4	-	-	-	-	-
C15-C20, n-alkanes,							
isoalkanes, cyclics, < 0.03% aromatics							
	044.040.0	47005 07 5					
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-,	224-221-9	4253-34-3	1600	-	-	-	-
triacetate							
Octamethylcyclotetrasil	209-136-7	556-67-2	-	-	-	-	-
oxane [D4]	(014-018-00-1)						
4,5-dichloro-2-octyl-2H-	264-843-8	64359-81-5	567 +	-	0.16+	0.16+	0.16+
isothiazol-3-one	(613-335-00-8)						
[DCOIT]	` '						
Dimethylbis[(1-oxoneod	273-028-6	68928-76-7	892	-	-	-	-
ecyl)oxy]stannane							

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.	
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.	
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.	
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.	
4.2. Most important symptoms and	effects, both acute and delayed	
Symptoms	None known.	
Effects of Exposure	No information available.	
4.3. Indication of any immediate m	edical attention and special treatment needed	
Note to doctors	Treat symptomatically.	
SECTION 5: Firefighting me	asures	
5.1. Extinguishing media		
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.	
Unsuitable extinguishing media	Full water jet.	
5.2. Special hazards arising from t	he substance or mixture	
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.	
Hazardous combustion products	Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.	
5.3. Advice for firefighters		
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.	
SECTION 6: Accidental relea	ase measures	
6.1. Personal precautions, protecti	ive equipment and emergency procedures	
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.	
For emergency responders	Use personal protection recommended in Section 8.	
6.2. Environmental precautions		
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.	

6.3. Methods and material for containment and cleaning up

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022

Methods for containment	Do not scatter spilled material with high pressure water streams.			
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
6.4. Reference to other sections				
Reference to other sections	See section 8 for more information. See section 13 for more information.			
SECTION 7: Handling and st	orage			
7.1. Precautions for safe handling	_			
Advice on safe handling	Ensure adequate ventilation.			
General hygiene considerations	Take off all contaminated clothing and wash it before reuse.			
7.2. Conditions for safe storage, in	cluding any incompatibilities			
Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.			
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.			
7.3. Specific end use(s)				
Specific use(s) Sealant.				
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.			
Other information	Observe technical data sheet.			
SECTION 8: Exposure contr	ols/personal protection			
8.1 Control parameters				

8.1. Control parameters

Exposure Limits

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product to this product from exposure to this product the product from exposure to this product by the product from exposure to this product.

Chemical name	European Union	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	TWA/8h	-
< 0.03% aromatics	5mg/m ³	
RR-100252-4	STEL/15 mins 10mg/m ³	
Silica, amorphous	-	TWA: 6 mg/m ³
7631-86-9		TWA: 2.4 mg/m ³
		STEL: 18 mg/m ³
		STEL: 7.2 mg/m ³
Acetic acid	TWA: 25 mg/m ³	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m ³
	STEL: 50 mg/m ³	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Dimethylbis[(1-oxoneodecyl)oxy]stannane	-	TWA: 0.1 mg/m ³

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

68928-76-7	STEL: 0.2 mg/m ³
	Sk*

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре		Derived No Effect Level (DNEL)	Safety factor	
worker Long term	Inhalation	73 mg/m³		
Systemic health effects				

Derived No Effect Level (DNEL)	Derived No Effect Level (DNEL)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	13 mg/m³			
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

8.2. Exposure controls

En	aine	erina	controls	
	3		001101010	

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene [™] . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
	De not elle sur en trelle d'als de nors of mende et inter the one income ent

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022

9.1. Information on basic physical and chemical properties				
Physical state	Solid			
Appearance	Paste			
Colour	White			
Odour	Acetic acid.			
Property	Values	Remarks • Method		
Melting point / freezing point	No data available	None known		
Initial boiling point and boiling	No data available	None known		
range				
Flammability	No data available			
Flammability Limit in Air		None known		
Upper flammability or explosive	No data available			
limits				
Lower flammability or explosive	No data available			
limits				
Flash point	> 100 °C			
Autoignition temperature	No data available	None known		
Decomposition temperature		None known		
рН		Not applicable. Insoluble in water.		
pH (as aqueous solution)	No data available	None known		
Kinematic viscosity	> 21 mm²/s			
Dynamic viscosity	No data available			
Water solubility	Insoluble in water. Product cures			
	with moisture			
Solubility(ies)	No data available	None known		
Partition coefficient	No data available	None known		
Vapour pressure	No data available	None known		
Relative density	No data available	None known		
Bulk density	No data available			
Density	0.97			
Relative vapour density	No data available	None known		
Particle characteristics				
Particle Size	No information available			
Particle Size Distribution	No information available			
0.2 Other information				
9.2. Other information Solid content (%)	No information available			
VOC content	No data av	ailabla		
	NO Gala av			
9.2.1. Information with regards to p	hysical hazard classes			
Not applicable				

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and	SECTION 10: Stability and reactivity			
10.1. Reactivity				
Reactivity	Product cures with moisture.			
10.2. Chemical stability				
Stability	Stable under normal conditions.			
Explosion data				
Sensitivity to mechanical impact	None.			
United Kingdom - BE		Page	7 / 14	

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022 Revision date 03-Jan-2025 Revision Number 3.01

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions. products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical,	chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS documentATEmix (oral)152,813.80 mg/kgATEmix (dermal)>2000 mg/kgATEmix (inhalation-gas)>20000 ppmATEmix (inhalation-dust/mist)>5 mg/lATEmix (inhalation-vapour)>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 3160 mg/kg (Oryctolagus cuniculus)	LC50 Inhalation(4h) >5266 mg/m ³ (Rattus)
< 0.03% aromatics		OECD 402	3 ()
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus)	-	-

EVO-STIK MULTI PURPOSE SILICONE WHITE

	OECD 401		
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m ³ (Rattus) 4 h
[D4]	OECD 401	OECD 402	
4,5-dichloro-2-octyl-2H-isothiaz	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus	=0.26 mg/L (Rattus) 4 h
ol-3-one [DCOIT]		cuniculus)	
Dimethylbis[(1-oxoneodecyl)ox	LD50 =892 mg/Kg (Rattus)	LD50 >2000 mg/Kg (rattus)	-
vlstannane	(OECD 401)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal			Non-irritant
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye			Non-irritant
	Rabbit	eye		6 days	Product score
					<=1
					Non-irritant

Respiratory or skin sensitisation No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information						
Method Species Exposure route Results						
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses			
Sensitisation			were observed			

Octamethylcyclotetrasiloxane [D4] (556-67-2)						
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)						
Method	Species	Exposure route	Results			
OECD 406	Guinea pig	Dermal	Sensitising			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

EVO-STIK MULTI PURPOSE SILICONE WHITE Supercedes date 19-Oct-2022

STOT - single exposure	Based on available data, the classification criteria are not met.	
STOT - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Based on available data, the classification criteria are not met.	
11.2. Information on other hazards		
11.2.1. Endocrine disrupting properties		
Endocrine disrupting properties	No information available.	
11.2.2. Other information		
Other adverse effects	No information available.	

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	EL50 (72h) >10,000 mg/L (Skeletonema costatum) ISO 10253	LL50 (96h) > 1028 mg/L (Scophthalmus maximus) OECD 203	-	LL50 (48h)> 3193 mg/l (Acartia tonsa)		
Triacetoxy(propyl)silane 17865-07-5	EC50 (72h): approx. 24 mg/l(Pseudokirc henriella subpicata)	LC50 (96h) = 108.89 mg/L	-	EC50 (48h) = 89.59 mg/L		
Silanetriol, methyl-, triacetate 4253-34-3	EC50 (72h): >500 mg/l (Pseudokirchner ella subcapitata)	LC50 (96h) >500 mg/l (Brachydanio rerio)	-	EC50 (48h) >500 mg/l (Daphnia magna)		
Octamethylcyclotetrasil oxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT] 64359-81-5	=0.025 mg/L Algae (Scenedesmus subspicatus)(OE CD 201)	LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss)(OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100
Dimethylbis[(1-oxoneod ecyl)oxy]stannane 68928-76-7	-	-	-	EC50 =39 mg/L (Daphnia magna) (OECD 201)		

12.2. Persistence and degradability

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

Persistence and degradability

No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days
Anaerobic Transformation in Aquati	c		
Sediment Systems			

Dimethylbis[(1-oxoneodecyl)oxy]stannane (68928-76-7)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)		0%	Not readily biodegradable
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	3%	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Triacetoxy(propyl)silane	1.23
Silanetriol, methyl-, triacetate	-2.4
Octamethylcyclotetrasiloxane [D4]	6.49
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB
aromatics	
Triacetoxy(propyl)silane	The substance is not PBT / vPvB
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

12.7. Other adverse effects

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

No information available.

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.	
Contaminated packaging	Handle contaminated packages in the same way as the product itself.	
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances	
Other information	Waste codes should be assigned by the user based on the application for which the product was used.	

SECTION 14: Transport information

Note:	Keep from freezing.
Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions	Not regulated Not regulated Not regulated Not regulated Not applicable
•	
IMDG14.1UN number or ID number14.2UN proper shipping name14.3Transport hazard class(es)14.4Packing group14.5Marine pollutant14.6Special precautions for user Special Provisions	Not regulated Not regulated Not regulated Not regulated NP None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR)	
14.1 UN number or ID number14.2 UN proper shipping name14.3 Transport hazard class(es)14.4 Packing group	Not regulated Not regulated Not regulated Not regulated

14.5Packing groupNot regulated14.4Packing groupNot regulated14.5Environmental hazardsNot applicable14.6Special precautions for userSpecial ProvisionsNone

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

O1 - Substances or mixtures with hazard statement EUH014

Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H302 - Harmful if swallowed

- H304 May be fatal if swallowed and enters airways
- H314 Causes severe skin burns and eye damage
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage

EVO-STIK MULTI PURPOSE SILICONE WHITE

Supercedes date 19-Oct-2022

H330 - Fatal if inhaled H400 - Very toxic to aquatic life H410 - Very toxic to aquatic life wit H412 - Harmful to aquatic life with	5 5
Legend TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by
	Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and No information available	sources for data
Prepared By Revision date Indication of changes	Product Safety & Regulatory Affairs 03-Jan-2025
Revision Note	Not applicable.

Revision Note	Not applicable.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet