

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK SANITARY SILICONE SEALANT WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

**Company Name** 

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Hazardous to the aquatic environment - chronic Category 3 - (H412)

### 2.2. Label elements

### Signal word

None

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects.

### **EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] & Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction

### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

United Kingdom - BE Page 1 / 14

# EVO-STIK SANITARY SILICONE SEALANT WHITE Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

# SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	Notes
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics RR-100252-4	>25 - <40	01-2119827000 -58-XXXX	934-956-3	Asp. Tox. 1 (H304)	-	1	-	-
Triacetoxy(propyl)sil ane 17865-07-5	1 - <2.5	01-2119966899 -07-XXXX	241-816-9	Skin Corr. 1B (H314) (EUH071)	-	ı	-	-
Silanetriol, methyl-, triacetate 4253-34-3	1 - <2.5	01-2119962266 -32-XXXX	224-221-9	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	-
Octamethylcyclotetra siloxane [D4] 556-67-2	0.05	-36-XXXX	209-136-7 (014-018-00-1)	· (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
4,5-dichloro-2-octyl- 2H-isothiazol-3-one [DCOIT] 64359-81-5	0.01 < 0.036	No data available	264-843-8 (613-335-00-8)	(H317) Aquatic Acute 1 (H400)	0.025%<=C< 5%	100	100	-
Dimethylbis[(1-oxon eodecyl)oxy]stannan e 68928-76-7	0.01 < 0.036	01-2120770324 -57-xxxx	273-028-6	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Aquatic Chronic 3	-	-	-	-

United Kingdom - BE Page 2 / 14

# EVO-STIK SANITARY SILICONE SEALANT WHITE Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

(H412)					
			(H412)		

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[G] - PBT / vPvB substance

### Full text of H- and EUH-phrases: see section 16

### Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Acetic acid 64-19-7	200-580-7 (607-002-00-6)	Skin Corr. 1A (H314) Flam. Liq. 3 (H226)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 25%<=C<90% Skin Irrit. 2 :: 10%<=C<25%	-	-	01-2119475328- 30-XXXX

#### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	-	-	-	-	-
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1600	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT]	264-843-8 (613-335-00-8)	64359-81-5	567+	-	0.16+	0.16+	0.16+
Dimethylbis[(1-oxoneod ecyl)oxy]stannane	273-028-6	68928-76-7	892	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

United Kingdom - BE Page 3 / 14

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with Ingestion

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

No information available. **Effects of Exposure** 

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

# SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of **Hazardous combustion products** 

irritating and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

# SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Do not get in eyes, on skin, or on clothing. Use personal protective equipment as Personal precautions

required. Ensure adequate ventilation.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions** 

12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Page 4 / 14 United Kingdom - BE

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

**General hygiene considerations** Take off all contaminated clothing and wash it before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food,

drink and animal feedingstuffs. Protect from moisture.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

### Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon

curing This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from

exposure to this product

Chemical name	European Union	United Kingdom
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics,	TWA/8h	-
< 0.03% aromatics	5mg/m <sup>3</sup>	
RR-100252-4	STEL/15 mins 10mg/m <sup>3</sup>	
Silica, amorphous	-	TWA: 6 mg/m <sup>3</sup>
7631-86-9		TWA: 2.4 mg/m <sup>3</sup>
		STEL: 18 mg/m <sup>3</sup>
		STEL: 7.2 mg/m <sup>3</sup>
Acetic acid	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>
	STEL: 50 mg/m <sup>3</sup>	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m <sup>3</sup>
Titanium dioxide	-	TWA: 10 mg/m <sup>3</sup>
13463-67-7		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Dimethylbis[(1-oxoneodecyl)oxy]stannane	-	TWA: 0.1 mg/m <sup>3</sup>

United Kingdom - BE Page 5 / 14

# **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

68928-76-7	STEL: 0.2 mg/m <sup>3</sup>
	Sk*

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term	Inhalation	73 mg/m³			
Systemic health effects					

Derived No Effect Level (DNEL)						
Octamethylcyclotetrasiloxar	Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Inhalation	13 mg/m³				
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d				

# Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC) Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.0015 mg/l				
Marine water	0.00015 mg/l				
Freshwater sediment	3 mg/kg				
Marine sediment	0.3 mg/kg				
Soil	0.54 mg/kg				
Sewage treatment plant	10 mg/l				

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

**Hand protection** Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

### SECTION 9: Physical and chemical properties

United Kingdom - BE Page 6 / 14

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White
Odour Acetic acid.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing pointNo data availableNone knownInitial boiling point and boilingNo data availableNone known

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point > 100 °C

Autoignition temperatureNo data availableNone knownDecomposition temperatureNo data availableNone known

pH Not applicable. Insoluble in water.
pH (as aqueous solution) No data available None known

pH (as aqueous solution)
No data available
Kinematic viscosity
> 21 mm²/s

Dvnamic viscosity No data available

Water solubility Insoluble in water. Product cures

with moisture

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk density No data available

Density 0.97

Relative vapour density No data available None known

Particle characteristics

Particle SizeNo information availableParticle Size DistributionNo information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical

impact

None.

United Kingdom - BE Page 7 / 14

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

### **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

**Product Information** 

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Acute toxicity

**Numerical measures of toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 152,813.80 mg/kg

 ATEmix (dermal)
 >2000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20,	LD50 > 5000 mg/kg (Rattus)	LD50 > 3160 mg/kg	LC50 Inhalation(4h) >5266
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	mg/m³ (Rattus)
< 0.03% aromatics		OECD 402	
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus)	-	-

United Kingdom - BE Page 8 / 14

# **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 **Revision Number** 3.01

	OECD 401		
Octamethylcyclotetrasiloxane	LD50 > 4800 mg/kg (Rattus)	LD50 > 2400 mg/kg (Rattus)	=36 g/m <sup>3</sup> (Rattus) 4 h
[D4]	OECD 401	OECD 402	
4,5-dichloro-2-octyl-2H-isothiaz	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus	=0.26 mg/L (Rattus) 4 h
ol-3-one [DCOIT]		cuniculus)	
Dimethylbis[(1-oxoneodecyl)ox	LD50 =892 mg/Kg (Rattus)	LD50 >2000 mg/Kg (rattus)	-
y]stannane	(OECD 401)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal			Non-irritant
	Rabbit	Dermal		6 days	Product score
					<=1
					Non-irritant

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye			Non-irritant
	Rabbit	eye		6 days	Product score
					<=1
					Non-irritant

Respiratory or skin sensitisation

No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed		

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)				
Method Species Exposure route Results				
OECD 406	Guinea pig	Dermal	Sensitising	

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

United Kingdom - BE Page 9 / 14

# **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons,	EL50 (72h)	LL50 (96h) >	-	LL50 (48h)>		
C15-C20, n-alkanes,	>10,000 mg/L	1028 mg/L		3193 mg/l		
isoalkanes, cyclics, <	(Skeletonema	(Scophthalmus		(Acartia tonsa)		
0.03% aromatics	costatum)	maximus)				
RR-100252-4	ISO 10253	OECD 203				
Triacetoxy(propyl)silane	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
17865-07-5	approx. 24	108.89 mg/L		89.59 mg/L		
	mg/I(Pseudokirc					
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h) >500	-	EC50 (48h) >500		
triacetate	>500 mg/l	mg/l		mg/l (Daphnia		
4253-34-3	(Pseudokirchner	(Brachydanio		magna)		
	ella subcapitata)	rerio)				
Octamethylcyclotetrasil		LC50:	-	EC50:		10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		
556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				
		rerio)				
4,5-dichloro-2-octyl-2H-		LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus	mykiss)(OECD		(OECD 202)		
	subspicatus)(OE	203)				
	CD 201)					
Dimethylbis[(1-oxoneod	-	-	-	EC50 =39 mg/L		
ecyl)oxy]stannane				(Daphnia		
68928-76-7				magna)		
				(OECD 201)		

### 12.2. Persistence and degradability

United Kingdom - BE Page 10 / 14

# **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2) 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)				
	/	Value	Results	
OECD Test No. 308: Aerobic and	_	Half-life	1.1-1.3 days	
Anaerobic Transformation in Aquatic			-	
Sediment Systems				

Dimethylbis[(1-oxoneodecyl)oxy]stannane (68928-76-7)				
Method	Exposure time	Value	Results	
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	0%	Not readily biodegradable	
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	3%	Not readily biodegradable	

### 12.3. Bioaccumulative potential

#### **Bioaccumulation**

**Component Information** 

Chemical name	Partition coefficient	
Triacetoxy(propyl)silane	1.23	
Silanetriol, methyl-, triacetate	-2.4	
Octamethylcyclotetrasiloxane [D4]	6.49	
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4	

### 12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB	
aromatics		
Triacetoxy(propyl)silane	The substance is not PBT / vPvB	
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB	

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

Component Information				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Method	Results	Species		
Endocrine disrupting properties in accordance	Negative.			
with the criteria set out in Commission				
Delegated Regulation (EU) 2017/2100(3) or				
Commission Regulation (EU) 2018/605(4).				

### 12.7. Other adverse effects

United Kingdom - BE Page 11 / 14

### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

No information available.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

### **SECTION 14: Transport information**

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated
 Not regulated
 Not regulated
 Not regulated
 Not regulated
 Not applicable

14.6 Special precautions for user

Special Provisions None

<u>IMDG</u>

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 Not regulated
 Not regulated
 Not regulated
 Not regulated

14.5 Marine pollutant NP
 14.6 Special precautions for user Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

# Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

### **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

United Kingdom - BE Page 12 / 14

# **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Revision date 03-Jan-2025 Supercedes date 19-Oct-2022 Revision Number 3.01

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

### Dangerous substance category per Seveso Directive (2012/18/EU)

O1 - Substances or mixtures with hazard statement EUH014

#### Ozone-depleting substances (ODS) Regulation (EU) 2024/590

Not applicable

### **Persistent Organic Pollutants**

Not applicable

### REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

# National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

### **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

United Kingdom - BE Page 13 / 14

#### **EVO-STIK SANITARY SILICONE SEALANT WHITE**

Supercedes date 19-Oct-2022

Revision date 03-Jan-2025 Revision Number 3.01

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Jan-2025

Indication of changes

**Revision Note** Not applicable.

Training Advice No information available Further information No information available

### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 14 / 14