

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022

Revision date 26-Sep-2023 Revision Number 1.04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK EPOXY RAPID - RESIN

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

 $\label{lem:contains} Contains Formaldehyde, oligomeric reaction products with 1-chloro-2, 3-epoxypropane and phenol; bis-[4-(2,3-epoxipropoxi)phenyl] propane$



United Kingdom - BE Page 1 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 Revision date 26-Sep-2023 Revision Number 1.04

Signal word

Warning

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H411 - Toxic to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH205 - Contains epoxy constituents. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P261 - Avoid breathing vapours/spray

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
bis-[4-(2,3-epoxipropoxi) phenyl]propane	(603-073-00- 2) 216-823-5	1675-54-3	80 - 100	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411) (EUH205)		01-2119456619- 26-xxxx
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropa ne and phenol	500-006-8	9003-36-5	5 - <10	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Aquatic Chronic 2 (H411)	<u>-</u>	01-2119454392- 40-XXXX

United Kingdom - BE Page 2 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 **Revision Number** 1.04

Glycidoxypropyltrimetho xysilane	219-784-2	2530-83-8	1 - <2.5	Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)		01-2119513212- 58-XXXX
----------------------------------	-----------	-----------	----------	---	--	---------------------------

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Silicon dioxide.

United Kingdom - BE Page 3 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022

Revision date 26-Sep-2023 **Revision Number** 1.04

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. See section 8 for more information.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. **Environmental precautions**

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. This product is

part of a kit. Please also refer to the SDS for the other component(s) of the kit.

General hygiene considerations Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from food, drink and animal feedingstuffs. Keep containers tightly closed in a

dry, cool and well-ventilated place.

Recommended storage

temperature

Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Observe technical data sheet. Other information

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

United Kingdom - BE Page 4 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 Revision date 26-Sep-2023 Revision Number 1.04

Exposure Limits

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
bis-[4-(2,3-epoxipropoxi)phe	enyl]propane (1675-54-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	12.25 mg/m³			
worker Short term Systemic health effects	Inhalation	12.25 mg/m³			
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d			
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d			

Glycidoxypropyltrimethoxysilane (2530-83-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term	Inhalation	70.5 mg/m³			
Systemic health effects					
worker	Dermal	10 mg/kg bw/d			
Long term Systemic health effects					

Derived No Effect Level (DNEL)						
bis-[4-(2,3-epoxipropoxi)phenyl]propane (1675-54-3)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d				
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d				
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d				
Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d				

Glycidoxypropyltrimethoxysilane (2530-83-8)					
Туре		Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	17 mg/m³			
Consumer	Dermal	5 mg/kg bw/d			

United Kingdom - BE Page 5 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 **Revision Number** 1.04

Long term Systemic health effects			
Consumer	Oral	5 mg/kg bw/d	
Long term			
Systemic health effects			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
bis-[4-(2,3-epoxipropoxi)phenyl]propane (1675-54-3)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.006 mg/l			
Marine water	0.001 mg/l			
Sewage treatment plant	10 mg/l			
Freshwater sediment	0.996 mg/kg dry weight			
Marine sediment	0.1 mg/kg dry weight			
Soil	0.196 mg/kg dry weight			

Glycidoxypropyltrimethoxysilane (2530-83-8)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.45 mg/l			
Marine water	0.045 mg/l			
Freshwater sediment	1.6 mg/kg dry weight			
Sewage treatment plant	8.2 mg/l			
Soil	0.063 mg/kg dry weight			
Marine sediment	0.16 mg/kg dry weight			

8.2. Exposure controls

Engineering controls Please refer also to Safety Data Sheet of Part B.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear protective gloves: Nitrile rubber, Butyl rubber. Ensure that the breakthrough time of

the glove material is not exceeded. Refer to glove supplier for information on

breakthrough time for specific gloves. Gloves must conform to standard EN 374. Gloves

must conform to standard EN 374

Skin and body protection Wear suitable protective clothing.

Respiratory protection Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateLiquidColourLight yellowOdourSlight.

Property Values Remarks • Method

Melting point / freezing point No data available Initial boiling point and boiling > 200 °C

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

United Kingdom - BE Page 6 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022

Revision date 26-Sep-2023 Revision Number 1.04

Flash point 150 °C

Autoignition temperature No data available

Decomposition temperature
pHNo data availableNone known
Not applicable.

pH (as aqueous solution) 4 - 6 solution (1 %)

Kinematic viscosity No data available

Dynamic viscosity 8000 - 12000 mPa s @ 25 °C

Partially soluble. Water solubility Solubility(ies) No data available Partition coefficient No data available Vapour pressure No data available Relative density No data available **Bulk Density** No data available Density 1.15 g/cm³ Relative vapour density No data available

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under recommended storage conditions.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoidNone known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decompositionNone under normal use conditions.

products

United Kingdom - BE Page 7 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 Revision date 26-Sep-2023 Revision Number 1.04

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met. Specific test data for the

substance or mixture is not available. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Based on available data, the classification criteria are not met. Specific test data for the

substance or mixture is not available. Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) 28,626.60 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
bis-[4-(2,3-epoxipropoxi)phenyl	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
]propane			
Formaldehyde, oligomeric	LD50 > 5 g/kg (Rattus) (OECD	LD50 > 2000 mg/kg	-
reaction products with	401)	(Rattus)(OECD 402)	
1-chloro-2,3-epoxypropane and			
phenol			
Glycidoxypropyltrimethoxysilan	=8025 mg/kg (Rattus)	= 4250 mg/kg (Oryctolagus	>5.3 mg/L (Rattus) 4 h
е	_	cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Glycidoxypropyltrimethoxysilane (2530-83-8)

United Kingdom - BE Page 8 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 Revision date 26-Sep-2023 Revision Number 1.04

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Eye Damage
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation May cause an allergic skin reaction.

Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation	-		were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

Note: PC-ADH-8 Multi-component adhesives and sealants This product is part of a kit Please

also refer to the SDS for the other component(s) of the kit

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

ſ	Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
		plants		microorganisms			(long-term)
Į	ois-[4-(2,3-epoxipropoxi	EC50 (72h) = 9.4	1.5 mg/l 96Hr	-	LD50 (48h) =2.7		
)phenyl]propane	mg/L	(Oncorhynchus		mg/L (Daphnia		
	1675-54-3	(Scenedesmus	mykiss)		magna)		
		capricornutum)	(OECD 203)		(OECD 202)		
		EPA-660/3-75-0					
		09					

United Kingdom - BE Page 9 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 **Revision Number** 1.04

Glycidoxypropyltrimeth	EC50 (96hr):	LC50 (96h) =	-	EC50 (48h) =473	
oxysilane	350 mg/l	55 mg/L		mg/L Daphnia	
2530-83-8	Pseudokirchneri	(Cyprinus carpio)		magna	
	ella subcapitata	OECD 203		_	

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Component information					
Chemical name	Partition coefficient				
bis-[4-(2,3-epoxipropoxi)phenyl]propane	3.78				

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment		
bis-[4-(2,3-epoxipropoxi)phenyl]propane	The substance is not PBT / vPvB		
Formaldehyde, oligomeric reaction products with	The substance is not PBT / vPvB		
1-chloro-2,3-epoxypropane and phenol			
Glycidoxypropyltrimethoxysilane	The substance is not PBT / vPvB		

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/ container to an approved landfill. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging

Handle contaminated packages in the same way as the product itself.

European Waste Catalogue

 $08\ 04\ 09^{\star}$ waste adhesives and sealants containing organic solvents or other dangerous substances

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number UN3082

United Kingdom - BE Page 10 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 **Revision Number** 1.04

14.2 UN proper shipping name Environmentally hazardous substances, liquid, n.o.s

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol)

14.3 Transport hazard class(es)

Labels 9
14.4 Packing group III

Description UN3082, Environmentally hazardous substances, liquid, n.o.s

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)

14.5 Environmental hazards Ye

14.6 Special precautions for user

Special Provisions 274, 335, 601, 375

Classification code
Tunnel restriction code
Limited quantity (LQ)

ADR Hazard Id (Kemmler

M6
(-)
5 L
90

Number)

IMDG

14.1 UN number or ID number UN3082

14.2 UN proper shipping name Environmentally hazardous substances, liquid, n.o.s

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol)

14.3 Transport hazard class(es)

14.4 Packing group

Description UN3082, Environmentally hazardous substances, liquid, n.o.s

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol), 9, III, Marine Pollutant

14.5 Marine pollutant

14.6 Special precautions for user

Special Provisions 274, 335, 969 Limited Quantity (LQ) 5 L EmS-No. F-A, S-F

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN308

14.2 UN proper shipping name Environmentally hazardous substances, liquid, n.o.s

Yes

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol)

14.3 Transport hazard class(es) 9

14.4 Packing group

Description UN3082, Environmentally hazardous substances, liquid, n.o.s

(bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products

with 1-chloro-2,3-epoxypropane and phenol), 9, III

14.5 Environmental hazards

14.6 Special precautions for user

Special Provisions A97, A158, A197

Limited quantity (LQ) 30 kg G **ERG Code** 9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

United Kingdom - BE Page 11 / 13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022

Revision date 26-Sep-2023 Revision Number 1.04

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH205 - Contains epoxy constituents. May produce an allergic reaction

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value

* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

United Kingdom - BE Page 12/13

EVO-STIK EPOXY RAPID - RESIN Supercedes Date: 02-Mar-2022 **Revision Number** 1.04

vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 26-Sep-2023

Indication of changes

Revision note SDS sections updated: 3.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13