

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020 Revision date 20-Mar-2023 Revision Number 2

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1	.1	Ρ	ro	du	ct	identifi	er

Product Name EVO-STIK EPOXY EXPRESS - RESIN

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

None known

Recommended use	Resin

Uses advised against

## 1.3. Details of the supplier of the safety data sheet

Company Name Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address

SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

### 2.2. Label elements

Contains Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol, bis-[4-(2,3-epoxipropoxi)phenyl]propane



EVO-STIK EPOXY EXPRESS - RESIN

Supercedes Date: 30-Dec-2020

## Signal word

Warning

## Hazard statements

H315 - Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H411 Toxic to aquatic life with long lasting effects.

### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

- P102 Keep out of reach of children
- P273 Avoid release to the environment
- P280 Wear protective gloves and eye/face protection
- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention
- P337 + P313 If eye irritation persists: Get medical advice/attention

P391 - Collect spillage

P501 - Dispose of contents/ container to an approved waste disposal plant

### Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## **SECTION 3: Composition/information on ingredients**

## 3.1 Substances

Not applicable

## 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
bis-[4-(2,3-epoxipropoxi) phenyl]propane	(603-073-00- 2) 216-823-5	1675-54-3	80 - 100	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411) (EUH205)		01-2119456619- 26-xxxx
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropa ne and phenol	500-006-8	9003-36-5	5 - <10	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Aquatic Chronic 2 (H411)	-	01-2119454392- 40-XXXX
Glycidoxypropyltrimetho xysilane	219-784-2	2530-83-8	1 - <2.5	Eye Dam. 1 (H318)	-	01-2119513212- 58-XXXX

### **EVO-STIK EPOXY EXPRESS - RESIN**

	Aquatic Chronic 3 (H412)	
	3 (П412)	

## Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measu	res				
4.1. Description of first aid measured	res_				
General advice	Show this safety data sheet to the doctor in attendance.				
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.				
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.				
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.				
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.				
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).				
4.2. Most important symptoms and	d effects, both acute and delayed				
Symptoms May cause redness and tearing of the eyes. May cause allergic skin reaction.					
4.3. Indication of any immediate m	edical attention and special treatment needed				
Note to doctors	Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.				
SECTION 5: Firefighting me	asures				
5.1. Extinguishing media					
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.				
Unsuitable extinguishing media	No information available.				
5.2. Special hazards arising from t	he substance or mixture				
Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.				
Hazardous combustion products	Carbon oxides. Silicon dioxide.				
5.3. Advice for firefighters					
Special protective equipment and	Firefighters should wear self-contained breathing apparatus and full firefighting turnout				
United Kingdom DE	Dama 0 (44				

## **EVO-STIK EPOXY EXPRESS - RESIN**

Supercedes Date: 30-Dec-2020

precautions for fire-fighters	gear. Use personal protection equipment.			
SECTION 6: Accidental relea	ase measures			
6.1. Personal precautions, protecti	ve equipment and emergency procedures			
Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. See section 8 for more information.			
Other information	Refer to protective measures listed in Sections 7 and 8.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2. Environmental precautions				
Environmental precautions	Prevent further leakage or spillage if safe to do so.			
6.3. Methods and material for conta	ainment and cleaning up			
Methods for containment	Prevent further leakage or spillage if safe to do so.			
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
6.4. Reference to other sections				
Reference to other sections	See section 8 for more information. See section 13 for more information.			
SECTION 7: Handling and st	orage			
7.1. Precautions for safe handling	_			
Advice on safe handling	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Please also refer to the SDS for the other component(s) of the kit. This product is part of a kit.			
General hygiene considerations	Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.			
7.2. Conditions for safe storage, in	cluding any incompatibilities			
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.			
Recommended storage temperature	Keep at temperatures between 5 and 35 °C.			
7.3. Specific end use(s)				
<b>Specific use(s)</b> Resin.				
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.			
Other information	Observe technical data sheet.			
SECTION 8: Exposure control				

## 8.1. Control parameters

**Exposure Limits** 

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

EVO-STIK EPOXY EXPRESS - RESIN

Supercedes Date: 30-Dec-2020

## Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)					
bis-[4-(2,3-epoxipropoxi)pher	nyl]propane (1675-54-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	12.25 mg/m³			
worker Short term Systemic health effects	Inhalation	12.25 mg/m <sup>3</sup>			
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d			
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d			

Glycidoxypropyltrimethoxysilane (2530-83-8)					
Туре		Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	70.5 mg/m <sup>3</sup>			
worker Long term Systemic health effects	Dermal	10 mg/kg bw/d			

Derived No Effect Level (DNEL)					
bis-[4-(2,3-epoxipropoxi)phen	yl]propane (1675-54-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d			
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d			
Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d			

Glycidoxypropyltrimethoxysilane (2530-83-8)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	17 mg/m³			
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d			
Consumer	Oral	5 mg/kg bw/d			

### **EVO-STIK EPOXY EXPRESS - RESIN**

Supercedes Date: 30-Dec-2020

Long term		
Systemic health effects		

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
bis-[4-(2,3-epoxipropoxi)phenyl]propane (1675-54-3)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.006 mg/l			
Marine water	0.001 mg/l			
Sewage treatment plant	10 mg/l			
Freshwater sediment	0.996 mg/kg dry weight			
Marine sediment	0.1 mg/kg dry weight			
Soil	0.196 mg/kg dry weight			

Glycidoxypropyltrimethoxysilane (2530-83-8)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.45 mg/l			
Marine water	0.045 mg/l			
Freshwater sediment	1.6 mg/kg dry weight			
Sewage treatment plant	8.2 mg/l			
Soil	0.063 mg/kg dry weight			
Marine sediment	0.16 mg/kg dry weight			

### 8.2. Exposure controls

 Engineering controls
 Ensure adequate ventilation, especially in confined areas. Please refer also to Safety Data Sheet of Part B.

 Personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Hand protection	Wear protective gloves: Nitrile rubber, Butyl rubber. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on
	breakthrough time for specific gloves. Gloves must conform to standard EN 374. Gloves must conform to standard EN 374
Skin and body protection Respiratory protection	Wear suitable protective clothing. Ensure adequate ventilation, especially in confined areas.
Respiratory protection	

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties				
Physical state	Liquid			
Appearance	Liquid			
Colour	Light yellow			
Odour	Slight.			
Odour threshold	No information available			
Property_	Values	Remarks • Method		
Melting point / freezing point	No data available	None known		
Initial boiling point and boiling	> 200 °C			
range				
Flammability	Not applicable for liquids .			
Flammability Limit in Air		None known		
Upper flammability or explosive	No data available			
limits				
Lower flammability or explosive	No data available			
limits				
Flash point	150 °C			

EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020 Revision date 20-Mar-2023 Revision Number 2

Autoignition temperature Decomposition temperature pH pH (as aqueous solution) Kinematic viscosity Dynamic viscosity Water solubility Solubility(ies) Partition coefficient Vapour pressure Relative density Bulk Density Liquid Density Relative vapour density Particle characteristics Particle Size	No data available 4 - 6 No data available No data available 8 - 12 Pa.s No data available. No data available No data available No data available No data available No data available 1.15 g/cm <sup>3</sup> No data available No information available	None known Not applicable. None known Wone known @ 25 °C None known None known None known None known None known
Particle Size Distribution	No information available	
9.2. Other information       No information available         9.2. Other information       No information available         VOC content       9.2.1. Information with regards to physical hazard classes         Not applicable       No information available		No data available

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity				
10.1. Reactivity				
Reactivity	No information available.			
10.2. Chemical stability				
Stability	Stable under normal conditions.			
Explosion data				
Sensitivity to mechanical	None.			
impact Sensitivity to static discharge	None.			
10.3. Possibility of hazardous reactions				
Possibility of hazardous reactions	None under normal processing.			
10.4. Conditions to avoid				
Conditions to avoid	None known based on information supplied.			
10.5. Incompatible materials				
Incompatible materials	Strong acids. Strong bases. Strong oxidising agents.			
10.6. Hazardous decomposition products				
Hazardous decomposition products	None under normal use conditions.			

Supercedes Date: 30-Dec-2020

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

### **Product Information**

Inhalation	May cause irritation of respiratory tract.	
Eye contact	Causes serious eye irritation.	
Skin contact	May cause sensitisation by skin contact. Causes skin irritation.	
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.	
Symptoms related to the physical, chemical and toxicological characteristics		

Symptoms

Acute toxicity

## Numerical measures of toxicity

### The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	29,000.00 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	20 mg/l

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
bis-[4-(2,3-epoxipropoxi)phenyl	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
]propane			
reaction products with	LD50 > 5 g/kg (Rattus) (OECD 401)	LD50 > 2000 mg/kg (Rattus)(OECD 402)	-
1-chloro-2,3-epoxypropane and			
phenol			
Glycidoxypropyltrimethoxysilan	=8025 mg/kg (Rattus)	= 4250 mg/kg (Oryctolagus	>5.3 mg/L (Rattus) 4 h
е		cuniculus)	

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Irritating to skin.

May cause redness and tearing of the eyes. May cause allergic skin reaction.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

#### Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Eye Damage
Acute Eye					
Irritation/Corrosion					

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

## EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed
Germ cell mutagenicity	Based on available of	lata, the classification criteria ar	e not met.
Carcinogenicity	Based on available c	lata, the classification criteria ar	e not met.
Reproductive toxicity	Based on available c	lata, the classification criteria an	e not met.
STOT - single exposure	Based on available c	lata, the classification criteria ar	e not met.
STOT - repeated exposure	Based on available c	lata, the classification criteria ar	e not met.
Aspiration hazard	Based on available of	lata, the classification criteria ar	e not met.
11.2. Information on other haze	ards		
11.2.1. Endocrine disrupting p	roperties		
Endocrine disrupting properties	5		
11.2.2. Other information			
Other adverse effects	No information availa	able.	
Note:		ponent adhesives and sealants of the kit This product is part of a	Please also refer to the SDS for t a kit

SECTION 12: Ecological information				

## 12.1. Toxicity

## Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
bis-[4-(2,3-epoxipropoxi )phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-0 09	(Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) =2.7 mg/L (Daphnia magna) (OECD 202)		
Glycidoxypropyltrimeth oxysilane 2530-83-8	350 mg/l	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203		EC50 (48h) =473 mg/L Daphnia magna		

## 12.2. Persistence and degradability

## **EVO-STIK EPOXY EXPRESS - RESIN**

Supercedes Date: 30-Dec-2020

#### Persistence and degradability No information available.

12.3. Bioaccumulative potential

## Bioaccumulation

#### **Component Information**

Chemical name	Partition coefficient
bis-[4-(2,3-epoxipropoxi)phenyl]propane	3.78

### 12.4. Mobility in soil

Mobility in soil No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
bis-[4-(2,3-epoxipropoxi)phenyl]propane	The substance is not PBT / vPvB
Formaldehyde, oligomeric reaction products with	The substance is not PBT / vPvB
1-chloro-2,3-epoxypropane and phenol	
Glycidoxypropyltrimethoxysilane	The substance is not PBT / vPvB

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/ container to an approved landfill.
Contaminated packaging	Do not reuse empty containers.
Waste codes / waste designations according to EWC	15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

## Note:

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020 Revision date 20-Mar-2023 Revision Number 2

<ul> <li>Land transport (ADR/RID)</li> <li>14.1 UN number or ID number</li> <li>14.2 Proper Shipping Name</li> <li>14.3 Transport hazard class(es) Labels</li> <li>14.4 Packing group Description</li> <li>14.5 Environmental hazards</li> <li>14.6 Special precautions for user Special Provisions Classification code Tunnel restriction code Limited quantity (LQ) ADR Hazard Id (Kemmler Number)</li> </ul>	UN3082 Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol) 9 9 III UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-) Yes 274, 335, 601, 375 M6 (-) 5 L 90
IMDG 14.1 UN number or ID number 14.2 Proper Shipping Name	UN3082 Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
<ul><li>14.3 Transport hazard class(es)</li><li>14.4 Packing group</li><li>Description</li></ul>	9 III UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, Marine Pollutant
<ul> <li>14.5 Marine pollutant</li> <li>14.6 Special precautions for user Special Provisions Limited Quantity (LQ) EmS-No</li> <li>14.7 Maritime transport in bulk according to IMO instruments Transport in bulk according to</li> </ul>	P 274, 335, 969 5 L F-A, S-F Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR	
14.1 UN number or ID number 14.2 Proper Shipping Name	UN3082 Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
<ul><li>14.3 Transport hazard class(es)</li><li>14.4 Packing group</li><li>Description</li></ul>	9 III UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III
<ul> <li>14.5 Environmental hazards</li> <li>14.6 Special precautions for user Special Provisions</li> <li>Limited quantity (LQ)</li> <li>ERG Code</li> </ul>	Yes A97, A158, A197 30 kg G 9L

## Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020

### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

- EUH205 Contains epoxy constituents. May produce an allergic reaction
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H319 Causes serious eye irritation
- H411 Toxic to aquatic life with long lasting effects
- H412 Harmful to aquatic life with long lasting effects

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)

### EVO-STIK EPOXY EXPRESS - RESIN Supercedes Date: 30-Dec-2020

Revision date 20-Mar-2023 Revision Number 2

Ceiling	Ceiling Limit Value Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sour No information available	rces for data
Prepared By	Product Safety & Regulatory Affairs
Revision date	20-Mar-2023
Indication of changes	
Revision note	SDS sections updated: 3.
Training Advice	When working with hazardous materials, regular training of operators is required by law
Further information	No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

### **End of Safety Data Sheet**