



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK EPOXY POWER - RESIN

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Resin

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1A - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

2.2. Label elements

Contains Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol , bis-[4-(2,3-epoxypropoxy)phenyl]propane



SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Signal word

Warning

Hazard statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

EU Specific Hazard Statements

EUH205 - Contains epoxy constituents. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
P337 + P313 - If eye irritation persists: Get medical advice/attention
P391 - Collect spillage
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product is part of a kit. Please also refer to the SDS for the other component(s) of the kit.

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(603-073-00-2) 216-823-5	1675-54-3	80 - 100	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411) (EUH205)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	500-006-8	9003-36-5	5 - <10	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Aquatic Chronic 2 (H411)	-	01-2119454392-40-XXXX

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Glycidoxypropyltrimethoxysilane	219-784-2	2530-83-8	1 - <2.5	Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)	-	01-2119513212-58-XXXX
---------------------------------	-----------	-----------	----------	---	---	-----------------------

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. May cause allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Silicon dioxide.

5.3. Advice for firefighters

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. See section 8 for more information.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Please also refer to the SDS for the other component(s) of the kit. This product is part of a kit.

General hygiene considerations Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.

Recommended storage temperature Keep at temperatures between 5 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Resin.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
 Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
 Revision Number 1.03

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12.25 mg/m ³	
worker Short term Systemic health effects	Inhalation	12.25 mg/m ³	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	

Glycidoxypropyltrimethoxysilane (2530-83-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	70.5 mg/m ³	
worker Long term Systemic health effects	Dermal	10 mg/kg bw/d	

Derived No Effect Level (DNEL)			
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d	

Glycidoxypropyltrimethoxysilane (2530-83-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer	Dermal	5 mg/kg bw/d	

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
 Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
 Revision Number 1.03

Long term Systemic health effects			
Consumer Long term Systemic health effects	Oral	5 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.001 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	0.996 mg/kg dry weight
Marine sediment	0.1 mg/kg dry weight
Soil	0.196 mg/kg dry weight

Glycidoxypropyltrimethoxysilane (2530-83-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.45 mg/l
Marine water	0.045 mg/l
Freshwater sediment	1.6 mg/kg dry weight
Sewage treatment plant	8.2 mg/l
Soil	0.063 mg/kg dry weight
Marine sediment	0.16 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Please refer also to Safety Data Sheet of Part B.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).
Hand protection Wear protective gloves: Wear protective nitrile rubber gloves, Butyl rubber. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374. Gloves must conform to standard EN 374
Skin and body protection Wear suitable protective clothing.
Respiratory protection Ensure adequate ventilation, especially in confined areas.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Colour Light yellow
Odour Slight.
Odour threshold No information available

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	> 200 °C	
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

limits		
Lower flammability or explosive limits	No data available	
Flash point	150 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	4 - 6	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	8 - 12 Pa.s	@ 25 °C
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.15 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supercedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract.
Eye contact Causes serious eye irritation.
Skin contact May cause sensitisation by skin contact. Causes skin irritation.
Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. May cause allergic skin reaction.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (dermal) 29,000.00 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
bis-[4-(2,3-epoxipropoxy)phenyl]propane	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	LD50 > 5 g/kg (Rattus) (OECD 401)	LD50 > 2000 mg/kg (Rattus)(OECD 402)	-
Glycidoxypropyltrimethoxysilane	=8025 mg/kg (Rattus)	= 4250 mg/kg (Oryctolagus cuniculus)	>5.3 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Eye Damage

Respiratory or skin sensitisation May cause sensitisation by skin contact.

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Glycidoxypropyltrimethoxysilane (2530-83-8)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

Note: PC-ADH-8 Multi-component adhesives and sealants Please also refer to the SDS for the other component(s) of the kit This product is part of a kit

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
bis-[4-(2,3-epoxypropoxy)phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) =2.7 mg/L (Daphnia magna) (OECD 202)		
Glycidoxypropyltrimethoxysilane 2530-83-8	EC50 (96hr): 350 mg/l Pseudokirchneriella subcapitata	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203	-	EC50 (48h) =473 mg/L Daphnia magna		

12.2. Persistence and degradability

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supercedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
bis-[4-(2,3-epoxipropoxy)phenyl]propane	3.78

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
bis-[4-(2,3-epoxipropoxy)phenyl]propane	The substance is not PBT / vPvB
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	The substance is not PBT / vPvB
Glycidoxypropyltrimethoxysilane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/ container to an approved landfill.

Contaminated packaging Do not reuse empty containers.

Waste codes / waste designations according to EWC 15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Land transport (ADR/RID)

14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	9
Labels	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)
14.5 Environmental hazards	Yes
14.6 Special Provisions	274, 335, 601, 375
Classification code	M6
Tunnel restriction code	(-)
Limited quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	90

IMDG

14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, Marine Pollutant
14.5 Marine pollutant	P
14.6 Special Provisions	274, 335, 969
Limited Quantity (LQ)	5 L
EmS-No	F-A, S-F
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN3082
14.2 Proper Shipping Name	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
14.3 Transport hazard class(es)	9
14.4 Packing group	III
Description	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III
14.5 Environmental hazards	Yes
14.6 Special Provisions	A97, A158, A197
Limited quantity (LQ)	30 kg G
ERG Code	9L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH205 - Contains epoxy constituents. May produce an allergic reaction

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

*

Skin designation

SVHC

Substance(s) of Very High Concern

PBT

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB

Very Persistent and very Bioaccumulative (vPvB) Chemicals

SAFETY DATA SHEET

EVO-STIK EPOXY POWER - RESIN
Supersedes Date: 30-Dec-2020

Revision date 02-Feb-2023
Revision Number 1.03

STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 02-Feb-2023

Indication of changes

Revision note SDS sections updated: 2, 3.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet