

Revision date 19-Apr-2023

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023 Revision Number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended useAdhesives and/or sealants

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine & N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine & Dioctyltinbis(acetylacetonate). May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

United Kingdom - BE Page 1 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

P102 - Keep out of reach of children

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Carbonic acid, calcium salt (1:1)	207-439-9	471-34-1	40 - <80	[C]	-	01-2119486795- 18-XXXX
Trimethoxyvinylsilane	(014-049-00- 0) 220-449-8	2768-02-7	1 - <2.5	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215- 52-XXXX
N-(3-(trimethoxysilyl)pro pyl)ethylenediamine	217-164-6	1760-24-3	0.1- <1	Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	01-2119970215- 39-XXXX
Dioctyltinbis(acetylaceto nate)		54068-28-9	0.1 - <0.5	(H371) Skin Sens. 1 (H317)	Skin Sens. 1 :: C>=5%	67-XXXX
N-[3-(Dimethoxymethylsi lyl)propyl]-ethylenediami ne		3069-29-2	0.1 - <0.5	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317)	-	01-2119963926- 21-xxxx

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

Full text of H- and EUH-phrases: see section 16

United Kingdom - BE Page 2/15

[[]C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[[]I] - Restricted substance per REACH Annex XVII

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

SECTION 4: First aid measures

4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. If medical advice is needed. General advice

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Consult an ophthalmologist. Rinse immediately with plenty of water, also under the

eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Small amounts of toxic methanol are released by

hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by

hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

United Kingdom - BE Page 3/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products

Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Silicon dioxide.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Do not get Personal precautions

in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions**

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Do not scatter spilled material with high pressure water streams. **Methods for containment**

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure adequate ventilation. Advice on safe handling

Do not eat, drink or smoke when using this product. Wash hands before breaks and after General hygiene considerations

work.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

United Kingdom - BE Page 4 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023 Revision Number 4

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product

Revision date 19-Apr-2023

Chemical name	European Union	United Kingdom
Diisononyl phthalate	-	TWA: 5 mg/m ³
28553-12-0		STEL: 15 mg/m ³
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³	TWA: 266 mg/m ³
	*	STEL: 250 ppm
		STEL: 333 mg/m ³
		Sk*
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Dioctyltinbis(acetylacetonate)	-	TWA: 0.1 mg/m ³
54068-28-9		STEL: 0.2 mg/m ³
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768-0	2-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Systemic health effects Long term	Inhalation	27,6 mg/m³			
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	35.5 mg/m³		
worker Systemic health effects Long term	Dermal	5 mg/kg bw/d		

Dioctyltinbis(acetylacetonate) (54068-28-9)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)			
Long term	Dermal	0.07 mg/kg bw/d			
Systemic health effects					

United Kingdom - BE Page 5 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

worker			
Long term Systemic health effects worker	Inhalation	84 mg/m³	
Short term Systemic health effects worker	Inhalation	84 mg/m³	
Long term Short term Local health effects worker	Inhalation	0.091 mg/m³	

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	12 mg/m³		
worker Long term Systemic health effects	Dermal	1.7 mg/kg bw/d		

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³			
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d			
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Systemic health effects Long term	Oral	2.5 mg/kg bw/d		
Consumer Systemic health effects Long term	Inhalation	8.7 mg/m³		
Consumer Systemic health effects Long term	Dermal	2.5 mg/kg bw/d		

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	2.9 mg/m³		
Consumer Long term Systemic health effects	Dermal	0.83 mg/kg bw/d		
Consumer	Oral	0.83 mg/kg bw/d		

United Kingdom - BE Page 6/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

Long term Systemic health effects		

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
Trimethoxyvinylsilane (2768-02-7)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.34 mg/l			
Marine water	0.034 mg/l			
Microorganisms in sewage treatment	110 mg/l			

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.062 mg/l			
Marine water	0.0062 mg/l			
Sewage treatment plant	25 mg/l			

Dioctyltinbis(acetylacetonate) (54068-28-9)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	26 μg/l		
Marine water	2.6 μg/l		
Freshwater - intermittent	260 μg/l		
Sewage treatment plant	1 mg/l		
Freshwater sediment	0.155 mg/kg dry weight		
Marine sediment	0.0155 mg/kg dry weight		
Soil	0.0158 mg/kg dry weight		

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.006 mg/l
Sewage treatment plant	25 mg/l
Freshwater sediment	0.24 mg/kg dry weight
Marine sediment	0.024 mg/kg dry weight
Soil	0.01 mg/kg dry weight

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. **Engineering controls**

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber. Hand protection

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

United Kingdom - BE Page 7/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023 Revision Number 4

@ 40°C

Revision date 19-Apr-2023

Physical stateSolidAppearancePasteColourWhite

Odour Characteristic.

Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point No data available Initial boiling point and boiling No data available

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

Flash point > 60 °C CC (closed cup)

Autoignition temperature No data available

Decomposition temperature No ne kn

Decomposition temperatureNone knownpHNot applicable. Reacts with water.

pH (as aqueous solution)
No data available
Kinematic viscosity
> 21 mm²/s

Dvnamic viscosity No data available

Water solubility Reacts with water. Product cures

Solubility(ies) No data available
Partition coefficient No data available
Vapour pressure No data available

Relative density 1.58

Bulk DensityNo data availableLiquid Density1.58 g/cm³Relative vapour densityNo data available

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Minimum Ignition Temperature 420

(°C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

United Kingdom - BE Page 8/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

sources of ignition.

10.5. Incompatible materials

None known based on information supplied. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are

formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

No information available. **Symptoms**

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

743.10 mg/l ATEmix (inhalation-vapour)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Carbonic acid, calcium salt	LD50 > 2000 mg/kg (Rattus)	> 2000 mg/kg (Rattus) LD50 >2000 mg/kg (Rattus)	
(1:1)	OECD 420	OECD 402	-
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
N-(3-(trimethoxysilyl)propyl)eth	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44
ylenediamine			mg/L air
Dioctyltinbis(acetylacetonate)	LD50 =2500 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	= 5.1 mg/L (Rat) 4 h

United Kingdom - BE Page 9 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023 Revision Number 4

N-[3-(Dimethoxymethylsilyl)pro	=200 - 2000 mg/Kg (Rattus)	>5000 mg/Kg (Oryctolagus cuniculus)	> 5.2 mg/L (Rattus) 4 h
pyl]-ethylenediamine	(OECD 401)		(OECD 403)
		(OECD 402)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Revision date 19-Apr-2023

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

	7/1 173 7				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit				Eye Damage
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation

May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising
Sensitisation, Buehler test			_

Dioctyltinbis(acetylacetonate) (54068-28-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin		Dermal	> 5 % sensitising
Sensitisation: Local Lymph Node			-
Assay			

N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine (3069-29-2)

Te (Billionick) mentylenylypropylj chrytenediamine (6666 26 2)						
Method	Species	Exposure route	Results			
OECD Test No. 406: Skin Sensitisation	Guinea pig		Sensitizing			

United Kingdom - BE Page 10 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023

Revision date 19-Apr-2023 Revision Number 4

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Carbonic acid, calcium	IC50 72H Algae	CL50 96H	-	EC50 48H		
salt (1:1)	>1000 mg/l	>1000 mg/l		Daphnia >1000		

United Kingdom - BE Page 11 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023 Revision Number 4

Revision date 19-Apr-2023

471-34-1				mg/l	
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)	
2768-02-7	957 mg/l	191 mg/l		168.7mg/l	
	(Desmodesmus	(Oncorhynchus		(Daphnia	
	subspicatus)	mykiss)		magna)	
	EU Method C.3				
N-(3-(trimethoxysilyl)pr	-	LC50 (96H)	-	EC50 (48h)	
opyl)ethylenediamine		=597 mg/L		=81mg/L	
1760-24-3		(Danio		Daphnia magna	
		rerio)Semi-static		Static	
Dioctyltinbis(acetylacet	-	LC50 (96h) =86	-	EC50 (48h)	
onate)		mg/L (Static)		=58.6 mg/L	
54068-28-9				(Daphnia	
				magna)	

12.2. Persistence and degradability

Persistence and degradability

No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

	Component information						
	Chemical name	Partition coefficient					
Trimethoxyvinylsilane		1.1					
	N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3					

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessmentThe product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Carbonic acid, calcium salt (1:1)	The substance is not PBT / vPvB PBT assessment does
	not apply
Trimethoxyvinylsilane	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Dioctyltinbis(acetylacetonate)	The substance is not PBT / vPvB
N-[3-(Dimethoxymethylsilyl)propyl]-ethylenediamine	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

United Kingdom - BE Page 12 / 15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Handle contaminated packages in the same way as the product itself. Contaminated packaging

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated Not regulated 14.3 Transport hazard class(es) 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

Not regulated 14.1 UN number or ID number 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group

14.5 Marine pollutant 14.6 Special precautions for user **Special Provisions** None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user **Special Provisions** None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

United Kingdom - BE Page 13/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Supercedes Date: 19-Apr-2023

Revision date 19-Apr-2023 Revision Number 4

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diisononyl phthalate	28553-12-0	52[a].
Dioctyltinbis(acetylacetonate)	54068-28-9	20.

52. Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex
	Number
Dioctyltinbis(acetylacetonate)	1.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H335 - May cause respiratory irritation

H371 - May cause damage to organs

Notes relating to the identification, classification and labelling of substances

United Kingdom - BE Page 14/15

EVO-STIK STRONG STUFF SEALANT AND ADHESIVE

Revision date 19-Apr-2023 Supercedes Date: 19-Apr-2023 **Revision Number** 4

Note V: If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

Legend

TWA TWA (time-weighted average) STEL (Short Term Exposure Limit) **STEL**

Ceiling Limit Value Ceiling Skin designation

SVHC Substance(s) of Very High Concern

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

Specific target organ toxicity - Repeated exposure STOT RE STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

European Agreement concerning the International Carriage of Dangerous Goods by **ADR**

Road

IMDG International Maritime Dangerous Goods (IMDG) IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 19-Apr-2023

Indication of changes

Revision note Not applicable.

No information available **Training Advice** Further information No information available

This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 15/15