

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022

Revision date 04-Jun-2024 Revision Number 1.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK INTUCRYLIC SEALANT WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

United Kingdom - BE Page 1 / 13

Revision date 04-Jun-2024

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022 Revision Number 1.01

2.3. Other hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Ethylene glycol	203-473-3 (603-027-00- 1)	107-21-1	0.1- <1	Acute Tox. 4 (H302) STOT RE 2 (H373)	-	01-2119456816- 28-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	220-120-9 (613-088-00- 6)	2634-33-5	0.01 < 0.036	Acute Tox. 2 (H330) Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Skin Sens. 1A :: C>=0.036%	01-2120761540- 60-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]		55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	-

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No.

United Kingdom - BE Page 2 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Revision date 04-Jun-2024 Supercedes Date: 13-Oct-2022 **Revision Number** 1.01

1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	В

SECTION 4: First aid measures

4.1. Description of first aid measures

Show this safety data sheet to the doctor in attendance. If medical advice is needed, **General advice**

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses Eye contact

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

No information available. **Effects of Exposure**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Carbon monoxide. Carbon dioxide (CO2). **Hazardous combustion products**

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

United Kingdom - BE Page 3 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022 Revision Number 1.01

Revision date 04-Jun-2024

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsDo not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

Other information Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food,

drink and animal feedingstuffs. Protect from moisture.

Recommended storage

temperature

Keep at temperatures between 5 and 25 °C. Keep at temperatures between 10 and 35

°C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Aluminum hydroxide (Al(OH)3)	-	TWA: 10 mg/m ³
21645-51-2		TWA: 4 mg/m ³

United Kingdom - BE Page 4/13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022

Revision date 04-Jun-2024 Revision Number 1.01

m TMA: 10 mg/m3
m TWA: 10 mg/m³ /m³ TWA: 20 ppm m TWA: 52 mg/m³ g/m³ STEL: 40 ppm STEL: 104 mg/m³ STEL: 30 mg/m³
ŗ

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Ethylene glycol (107-21-1)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d			
worker Long term Systemic health effects	Inhalation	35 mg/m³			

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)					
Туре	Exposure route	Derived No Effect Level Safety factor (DNEL)			
		7			
worker	Inhalation	6.81 mg/m³			
Long term					
Systemic health effects					
worker	Dermal	0.966 mg/kg bw/d			
Long term					
Systemic health effects					

Derived No Effect Level (DNEL)						
Ethylene glycol (107-21-1)	Ethylene glycol (107-21-1)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d				
Consumer Long term Local health effects	Inhalation	7 mg/m³				

1,2-benzisothiazol-3(2H)-one	[BIT] (2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m³	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)

United Kingdom - BE Page 5 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022 Revision Number 1.01

Ethylene glycol (107-21-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Microorganisms in sewage treatment	199.5 mg/l
Freshwater - intermittent	10 mg/l

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	4.03 μg/l			
Marine water	0.403 μg/l			
Sewage treatment plant	1.03 mg/l			
Freshwater sediment	49.9 μg/l			
Marine sediment	4.99 μg/l			
Soil	3 mg/kg dry weight			

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be

Revision date 04-Jun-2024

replaced regularly and if there is any sign of damage to the glove material. None under normal use conditions.

Skin and body protection Non

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White
Odour Characteristic.

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

Melting point / freezing point 0 °C None known

Initial boiling point and boiling 100 °C

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

mits

Lower flammability or explosive No data available

limits

Flash pointNo data availableNone knownAutoignition temperature420 °CNone knownDecomposition temperatureNone known

pH 7 - 9 Not applicable. Insoluble in water.

pH (as aqueous solution)

No data available

None known

kinematic viscosity

> 21 mm²/s

@ 40°C

United Kingdom - BE Page 6 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Revision date 04-Jun-2024 Supercedes Date: 13-Oct-2022 **Revision Number** 1.01

No data available Dynamic viscosity

Water solubility No data available. Miscible in water.

Solubility(ies) No data available None known **Partition coefficient** No data available None known No data available None known Vapour pressure Relative density No data available None known

Bulk Density No data available

Liquid Density 1.6 g/cm³

Relative vapour density No data available None known

Particle characteristics

No information available Particle Size **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

None. Sensitivity to mechanical

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from frost. Protect from moisture. Exposure to air or moisture over prolonged

periods. Do not freeze. Keep away from open flames, hot surfaces and sources of

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

None under normal use conditions. Stable under recommended storage conditions. Hazardous decomposition

products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

United Kingdom - BE Page 7 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022 Revision Number 1.01

Revision date 04-Jun-2024

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >2000 mg/kg

 ATEmix (dermal)
 >2000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

Chemical name Oral LD50		Dermal LD50	Inhalation LC50	
Ethylene glycol	ATE 500 mg/kg	= 10600 mg/kg (Rattus) = 9530 µL/kg (Oryctolagus cuniculus)	> 2.5 mg/L (Rat)6 h	
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-	
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation May produce an allergic reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

United Kingdom - BE Page 8 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022

Revision date 04-Jun-2024 Revision Number 1.01

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Ethylene glycol 107-21-1	EC50: 6500 - 13000mg/L (96h, Pseudokirchneri ella subcapitata)	9	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	EC50: =46300mg/L (48h, Daphnia magna)		
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner		-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			

12.3. Bioaccumulative potential

United Kingdom - BE Page 9 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022 Revision Number 1.01

Revision date 04-Jun-2024

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Ethylene glycol	-1.36	
1,2-benzisothiazol-3(2H)-one [BIT]	0.7	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	0.7	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment UN.

Chemical name	PBT and vPvB assessment	
Ethylene glycol	The substance is not PBT / vPvB	
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated

14.2 UN proper shipping name

14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

United Kingdom - BE Page 10 / 13

BOSTIK INTUCRYLIC SEALANT WHITE

Revision date 04-Jun-2024 Supercedes Date: 13-Oct-2022 Revision Number 1.01

IMDG

14.1 UN number or ID number Not regulated Not regulated 14.2 UN proper shipping name 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group

14.5 Marine pollutant 14.6 Special precautions for user **Special Provisions** None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

Not regulated 14.1 UN number or ID number 14.2 UN proper shipping name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

United Kingdom - BE Page 11/13

BOSTIK INTUCRYLIC SEALANT WHITE

Revision date 04-Jun-2024 Supercedes Date: 13-Oct-2022 Revision Number 1.01

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eve damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations.

In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Legend

TWA TWA (time-weighted average) **STEL** STEL (Short Term Exposure Limit)

Ceiling Limit Value Ceiling Skin designation Sk*

SVHC Substance(s) of Very High Concern

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

European Waste Catalogue **FWC**

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG) IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 04-Jun-2024

Indication of changes

Not applicable. **Revision note**

No information available **Training Advice Further information** No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

United Kingdom - BE Page 12/13

BOSTIK INTUCRYLIC SEALANT WHITE

Supercedes Date: 13-Oct-2022

Revision date 04-Jun-2024 Revision Number 1.01

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13