



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT GRAPHITE
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT GRAPHITE
Substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin irritation	Category 2 - (H315)
Serious eye damage	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

Contains Portland Cement; 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]

SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE**
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4



Signal word

Danger

Hazard statements

H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H335 - May cause respiratory irritation.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor
P362 + P364 - Take off contaminated clothing and wash it before reuse
P405 - Store locked up
P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can diminish prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
---------------	----------	---------------------------	--------------------	---	------------------------------------	----------	----------------------	-------

SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE**
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Quartz 14808-60-7	40 - <80	[5]	238-878-4	[B]	-	-	-	-
Portland Cement 65997-15-1	40 - <80	[5]	266-043-4	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	-
Cement, alumina, chemicals 65997-16-2	1 - <2.5	No data available	266-045-5	Eye Irrit. 2 (H319)	-	-	-	-
4,5-dichloro-2-octyl- 2H-isothiazol-3-one [DCOIT] 64359-81-5	0.01 < 0.036	No data available	264-843-8 (613-335-00-8)	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Corr. 1 (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Irrit. 2 :: 0.025%<=C< 5% Eye Irrit. 2 :: 0.025%<=C< 3% Skin Sens. 1A :: C>=0.0015%	100	100	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Quartz	238-878-4	14808-60-7	-	-	-	-	-
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-
Cement, alumina, chemicals	266-045-5	65997-16-2	-	-	-	-	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	264-843-8 (613-335-00-8)	64359-81-5	567 ⁺	-	0.16 ⁺	0.16 ⁺	0.16 ⁺

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.
Eye contact	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Burning sensation. May cause blindness. May cause redness and tearing of the eyes. Itching. Rashes. Hives. Erythema (skin redness). Dust irritates eyes and air passages. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
-----------------	--

Effects of Exposure	No information available.
----------------------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
-------------------------------------	---

Unsuitable extinguishing media	Full water jet.
---------------------------------------	-----------------

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.
---	---

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.
---	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.
-----------------------------	---

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supersedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Process mortar residues to let them harden, before returning the residues to recycling or disposing them according to applicable requirements. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.

Prevention of secondary hazards Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protective equipment. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. For cements treated with a Cr (VI) reducing agent the effectiveness of the reducing agent diminishes with time and if not stored in an appropriate manner. After absorption of moisture or exceeding the shelf life the reducing agent for chromate will lose its efficiency and sensitisation by skin contact may occur. Protect from moisture.

Recommended storage temperature Keep at temperatures between 2 and 10 °C.

7.3. Specific end use(s)

Specific use(s)
Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supersedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Exposure Limits

Chemical name	European Union	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable fraction STEL: 0.3 mg/m ³ ; respirable
Portland Cement 65997-15-1	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Dust RR-12364-8	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber.

Skin and body protection Suitable protective clothing. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection Avoid generation of dust. Possible nuisance dust. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Recommended filter type: Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Colour Dark Grey
Odour No information available.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	Not applicable
Initial boiling point and boiling range	No data available	Not applicable
Flammability	No data available	None known
Flammability Limit in Air		None known

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supersedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	Not applicable
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	Not applicable
Dynamic viscosity	No data available	Not applicable
Water solubility	No data available. Cement based products react and solidify in contact with water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	1.3	
Density	1.8 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	50-700 µm	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	100	
Softening point	Not applicable	
VOC content		0 %

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available . Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage.
Skin contact	Specific test data for the substance or mixture is not available. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/L
ATEmix (inhalation-vapour)	>20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	>2000 mg/kg (Rattus)	-	-
Portland Cement	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Cement, alumina, chemicals	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rattus	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supersedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Species	Exposure route	Results
OECD 406	Guinea pig	Dermal	Sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Onchorhyncus mykiss) >100 mg/L (OECD 203)	-	EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)		

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT GRAPHITE
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	EC50 (72h) =0.025 mg/L Algae (Scenedesmus subspicatus)(OECD 201)	LC50 (96h) 0.0078 mg/L (Oncorhynchus mykiss)(OECD 203)	-	EC50 (48h) 0.0097 mg/L Daphnia magna (OECD 202)	100	100
--	---	--	---	---	-----	-----

12.2. Persistence and degradability

Persistence and degradability No information available.

Quartz (14808-60-7)			
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)			
Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and Anaerobic Transformation in Aquatic Sediment Systems		Half-life	1.1-1.3 days

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Cement, alumina, chemicals	Not PBT/vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	Not PBT/vPvB

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

01, 17 09 02 and 17 09 03
10 13 06 particulates and dust (except 10 13 12 and 10 13 13)
Cured product can be treated as construction waste. In the management of larger quantities consult with local authorities and local waste disposal company
10 13 14 waste concrete and concrete sludge

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE**
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains DCOIT. May produce an allergic reaction.

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract
H302 - Harmful if swallowed

SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT
GRAPHITE**
Supercedes date 03-Jan-2025

Revision date 14-May-2026

Revision Number 4

H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H335 - May cause respiratory irritation
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 14-May-2026

Indication of changes

Revision Note Not applicable.
Training Advice No information available
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet