



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE**  
Supersedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT JASMINE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Building and construction work.  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650  
**Ireland** Bostik: +353 (1) 8624900 (Monday- Friday 9am-5pm)  
**Europe** 112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 1 - (H318)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Specific target organ toxicity — single exposure</b>	Category 3 - (H335)

### 2.2. Label elements

Contains Portland Cement, 2-octyl-2H-isothiazol-3-one [OIT]



#### Signal word

Danger

#### Hazard statements

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.

# SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE**  
Supersedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

H318 - Causes serious eye damage.  
H335 - May cause respiratory irritation.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P260 - Do not breathe dust  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P362 + P364 - Take off contaminated clothing and wash it before reuse  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Quartz	238-878-4	14808-60-7	40 - <80	^	-	[4]
Portland Cement	266-043-4	65997-15-1	40 - <80	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	[5]
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7	26530-20-1	0.01 - <0.1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331)	^	-

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

				Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute =10 M Factor Chronic = 1		
--	--	--	--	---	--	--

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH  
NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Brush off loose particles from skin. Remove material from skin immediately. Take off contaminated clothing and wash it before reuse. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Burning sensation. Itching. Rashes. Hives. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
-----------------	--

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

**Hazardous combustion products** Silicon dioxide.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

**Methods for cleaning up** Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled material and place in suitable container. Avoid generating dust.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Avoid generation of dust. Avoid contact with skin, eyes or clothing. Use personal protection equipment. Take off contaminated clothing and wash it before reuse.

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Protect from moisture.

## 7.3. Specific end use(s)

**Specific use(s)**  
Building and construction work.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
Portland Cement 65997-15-1	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Dust RR-12364-8	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

**Predicted No Effect Concentration (PNEC)** No information available.

### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

#### Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Use eye protection according to EN 166, designed to protect against powders and dusts.

**Hand protection** Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

**Skin and body protection** Suitable protective clothing. Gloves made of plastic or rubber. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.

**Respiratory protection** No protective equipment is needed under normal use conditions. If exposure limits are

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supersedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## Recommended filter type:

exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid generation of dust. Possible nuisance dust.  
black. with filter for particulates. Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Colour	Off-white
Odour	No information available
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
pH (as aqueous solution)	> 11	
Melting point / freezing point	Not applicable . °C	
Initial boiling point and boiling range	Not applicable . °C	
Flash point	Not applicable . °C	
Evaporation rate	Not applicable .	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	Cement based products react and solidify in contact with water	Insoluble
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	Not applicable .	
Dynamic viscosity	Not applicable .	
Explosive properties	No data available	
Oxidising properties	No data available	

### 9.2. Other information

Solid content (%)	100
Softening Point	Not relevant
VOC Content (%)	
Liquid Density	1.8 g/ml
Bulk density	1.3 50-700 µm

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## 10.2. Chemical stability

**Stability** Keep away from Incompatible materials. Stable under recommended storage conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture.

## 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.

**Skin contact** Specific test data for the substance or mixture is not available. May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

#### Numerical measures of toxicity

#### **Acute toxicity**

#### **Component Information**

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Portland Cement 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Irritating to skin.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Risk of serious damage to eyes.

**Respiratory or skin sensitisation** May cause sensitisation by skin contact.

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** May cause respiratory irritation.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards



# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

## 11.2.2. Other information

Other adverse effects No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	10	1

### 12.2. Persistence and degradability

Persistence and degradability No information available.

#### Component Information

##### 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

### 12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

#### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz 14808-60-7	-	0
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	2.92	-

### 12.4. Mobility in soil

Mobility in soil No information available.

### 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	The substance is not PBT / vPvB

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## 12.6. Other adverse effects

Other adverse effects No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03  
10 13 06 particulates and dust (except 10 13 12 and 10 13 13)  
Cured product can be treated as construction waste. In the management of larger quantities consult with local authorities and local waste disposal company  
10 13 14 waste concrete and concrete sludge

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special Provisions None  
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# SAFETY DATA SHEET

BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

## European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

**47** where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H301 - Toxic if swallowed

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

# SAFETY DATA SHEET

**BOSTIK J115 FLEXIBLE SMOOTH FINISH GROUT  
JASMINE**  
Supercedes Date: 20-Jul-2021

Revision date 28-Feb-2022

Revision Number 4.01

H318 - Causes serious eye damage  
H331 - Toxic if inhaled  
H335 - May cause respiratory irritation  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 28-Feb-2022

## Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**