

**BOSTIK J200 SGS FAST SETTING GROUT GREY**  
Supersedes Date: 07-Aug-2019Revision date 07-Aug-2019  
Revision Number 1.01**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product Identifier****Product Name** BOSTIK J200 SGS FAST SETTING GROUT GREY  
**Pure substance/mixture** Mixture**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended use** Cement. Building and construction work.  
**Uses advised against** None known**1.3. Details of the supplier of the safety data sheet****Company Name**Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36**E-mail address** SDS.box-EU@bostik.com**1.4. Emergency telephone number****United Kingdom** +44 (1785) 272650  
**Ireland** +353 (1) 8624900 (Monday- Friday 9am-5pm)**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Regulation (EC) No 1272/2008

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 1 - (H318)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Specific target organ toxicity (single exposure)</b>	Category 3 - (H335)

**2.2. Label Elements**

Contains: Cement, portland, chemicals

**Signal word**  
DANGER**Hazard statements**  
H315 - Causes skin irritation

# SAFETY DATA SHEET

**BOSTIK J200 SGS FAST SETTING GROUT GREY**  
**Supersedes Date:** 07-Aug-2019

**Revision date** 07-Aug-2019  
**Revision Number** 1.01

H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation

## Precautionary statements

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P260 - Do not breathe dust  
P271 - Use only outdoors or in a well-ventilated area  
P280 - Wear protective gloves and eye/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor  
P362 + P364 - Take off contaminated clothing and wash it before reuse  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other Hazards

Product dust may be irritating to eyes, skin and respiratory system  
When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers  
Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease

## PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	40 - <80	^		Exempt
Cement, portland, chemicals	266-043-4	65997-15-1	>25 - <40	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		No data available

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# SAFETY DATA SHEET

BOSTIK J200 SGS FAST SETTING GROUT GREY  
Supercedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Consult an ophthalmologist. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water for at least 15 minutes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Causes serious eye damage. Inhalation of dust in high concentration may cause irritation of respiratory system. Irritating to skin.
-----------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Product is or contains a sensitiser. May cause sensitisation by skin contact.
<b>Hazardous combustion products</b>	Carbon oxides.

### 5.3. Advice for firefighters

<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Avoid generation of dust.
-----------------------------	---

# SAFETY DATA SHEET

BOSTIK J200 SGS FAST SETTING GROUT GREY  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Prevent dust cloud.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Avoid generation of dust. Use personal protective equipment as required.

**General hygiene considerations** Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Building and construction work. Cement.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/Personal protection**

### 8.1. Control parameters

#### Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Quartz 14808-60-7	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
Cement, portland, chemicals 65997-15-1	-	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Calcium sulfate 7778-18-9	-	TWA: 10 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup>	-
Dust RR-12364-8	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup>

# SAFETY DATA SHEET

**BOSTIK J200 SGS FAST SETTING GROUT GREY**  
 Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
 Revision Number 1.01

			STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
--	--	--	--

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>
<b>Quartz (14808-60-7)</b>

**Predicted No Effect Concentration (PNEC)** No information available.

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### **Personal Protective Equipment**

- Eye/face protection** Tight sealing safety goggles. Face protection shield. Wear safety glasses with side shields (or goggles).
- Hand protection** Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Gloves must conform to standard EN 374. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.
- Skin and body protection** Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact.
- Respiratory protection** Avoid generation of dust. Ensure adequate ventilation, especially in confined areas. In case of insufficient ventilation, wear suitable respiratory equipment. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
- Recommended filter type:** with filter for particulates.

**Environmental exposure controls** Do not allow into any sewer, on the ground or into any body of water.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Powder
<b>Colour</b>	Grey
<b>Odour</b>	Cement
<b>Odour threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable	11 - 14
Melting point / freezing point	Not applicable	.
Boiling point / boiling range	.	.
Flash point	.	.
Evaporation rate	Not applicable	.
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	No data available	
Water solubility	Insoluble in water	Cement based products react and solidify in contact

# SAFETY DATA SHEET

BOSTIK J200 SGS FAST SETTING GROUT GREY  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

	with water
<b>Solubility(ies)</b>	No data available
<b>Partition coefficient</b>	No data available
<b>Autoignition temperature</b>	No data available
<b>Decomposition temperature</b>	No data available
<b>Kinematic viscosity</b>	Not applicable .
<b>Dynamic viscosity</b>	Not applicable .
<b>Explosive properties</b>	No data available
<b>Oxidising properties</b>	No data available

## 9.2. Other information

<b>Solid content (%)</b>	100
<b>Softening Point</b>	Not relevant
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	1.1 g/cm <sup>3</sup>

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** No information available.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion Data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture.

### 10.5. Incompatible materials

**Incompatible materials** Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** May cause irritation of respiratory tract. Specific test data for the substance or mixture is not available.

# SAFETY DATA SHEET

**BOSTIK J200 SGS FAST SETTING GROUT GREY**  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

- Eye contact** Causes serious eye damage.
- Skin contact** May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
- Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

## Numerical measures of toxicity

### Acute Toxicity

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg ( Rat )		
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rat)	LD50 >2000 mg/Kg	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Skin corrosion/irritation** Classification based on data available for ingredients. Causes skin irritation.
- Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Causes serious eye damage.
- Respiratory or skin sensitisation** May cause sensitisation by skin contact.
- Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- Carcinogenicity** Based on available data, the classification criteria are not met.
- Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT - single exposure** May cause respiratory irritation.
- STOT - repeated exposure** Based on available data, the classification criteria are not met.
- Aspiration hazard** Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

# SAFETY DATA SHEET

BOSTIK J200 SGS FAST SETTING GROUT GREY  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

Ecotoxicity

## 12.2. Persistence and degradability

Persistence and degradability No information available.

## 12.3. Bioaccumulative potential

Bioaccumulation No information available.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz 14808-60-7	-	0

## 12.4. Mobility in soil

Mobility in soil Not expected to adsorb on soil.

## 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

## 12.6. Other adverse effects

Other adverse effects No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1 UN Number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing Group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

### IMDG

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated



# SAFETY DATA SHEET

BOSTIK J200 SGS FAST SETTING GROUT GREY  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine Pollutant Np  
14.6 Special Provisions None  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number Not regulated  
14.2 Proper Shipping Name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Cement, portland, chemicals	65997-15-1	

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

#### National Regulations

### 15.2. Chemical safety assessment

# SAFETY DATA SHEET

**BOSTIK J200 SGS FAST SETTING GROUT GREY**  
Supersedes Date: 07-Aug-2019

Revision date 07-Aug-2019  
Revision Number 1.01

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No  
Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H335 - May cause respiratory irritation

#### **Legend**

SVHC: Substances of Very High Concern for Authorisation:

#### **Legend** SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals		
STOT RE	Specific target organ toxicity - Repeated exposure		
STOT SE	Specific target organ toxicity - Single exposure		
EWC:	European Waste Catalogue		

#### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 07-Aug-2019

#### Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**