

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK SL C780 FLEX

Supercedes Date: 18-Nov-2020

Revision date 18-Nov-2020 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK SL C780 FLEX

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Hydraulic Cement, Mortar, Grout and Concrete.

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE

Tel: +33 (0)1 49 00 90 00

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650

treland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)

2.2. Label Elements

Contains: Portland Cement, Flue dust, Cement Portland



Signal word Danger

Hazard statements

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

Precautionary statements

Supercedes Date: 18-Nov-2020 Revision Number 1

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

BOSTIK SL C780 FLEX

P264 - Wash skin thoroughly after handling.

P280 - Wear protective gloves and eve/face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P501 - Dispose of contents/ container to an approved waste disposal plant.

2.3. Other Hazards

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Quartz	238-878-4	14808-60-7	40 - <80	^		[4]
Portland Cement	266-043-4	65997-15-1	5 - <10	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		[5]
Quartz (fine fraction)	238-878-4	14808-60-7	0.1 - <1	STOT RE 1 (H372)		[4]
Flue dust, Cement Portland	270-659-9	68475-76-3	0.1 - <1	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		01-2119486767- 17-XXXX

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

Revision date 18-Nov-2020

Supercedes Date: 18-Nov-2020 Revision Number 1

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

BOSTIK SL C780 FLEX

4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Get immediate medical advice/attention. Rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

Revision date 18-Nov-2020

Skin contactWash off immediately with soap and plenty of water for at least 15 minutes. May cause

an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Prolonged contact may cause redness and

irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

chemical

Hazardous combustion products Carbon dioxide (CO2). Sulphur oxides. Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Supercedes Date: 18-Nov-2020 Revision Number 1

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required. Evacuate personnel to safe areas. Keep people away

Revision date 18-Nov-2020

from and upwind of spill/leak.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

BOSTIK SL C780 FLEX

Environmental precautions Prevent further leakage or spillage if safe to do so.

6.3. Methods and material for containment and cleaning up

and place into a container for later disposal.

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.

Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children.

7.3. Specific end use(s)

Specific Use(s)

Hydraulic Cement, Mortar, Grout and Concrete.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Quartz	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7	_	STEL: 0.3 mg/m ³	_
Limestone	-	TWA: 10 mg/m ³	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³	TWA: 4 mg/m ³

BOSTIK SL C780 FLEX Revision date 18-Nov-2020

Supercedes Date: 18-Nov-2020 Revision Number 1

		STEL: 30 mg/m ³ STEL: 12 mg/m ³	STEL: 30 mg/m ³ STEL: 12 mg/m ³
Portland Cement 65997-15-1	-	TWA: 1 mg/m³ STEL: 3 mg/m³	TWA: 10 mg/m³ TWA: 4 mg/m³ STEL: 30 mg/m³ STEL: 12 mg/m³
Calcium sulfate 7778-18-9	-	TWA: 10 mg/m³ STEL: 30 mg/m³	-
Dust RR-12364-8	-	TWA: 10 mg/m³ TWA: 4 mg/m³	TWA: 10 mg/m³ TWA: 4 mg/m³ STEL: 30 mg/m³ STEL: 12 mg/m³
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m³ STEL: 0.3 mg/m³	TWA: 0.1 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield. Wear safety glasses with side

shields (or goggles).

Hand protection For operations where prolonged or repeated skin contact may occur, impervious gloves

should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly

and if there is any sign of damage to the glove material.

Skin and body protection Suitable protective clothing. Wear impervious protective clothing, including boots, gloves,

lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear chemical resistant clothing such as gloves, apron, boots or whole bodysuits made from neoprene, as appropriate. Rubber boots. Gloves made of plastic or rubber. Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing to prevent skin contact. No protective equipment is needed under normal use conditions. If exposure limits are

Respiratory protectionNo protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid

generation of dust.

Recommended filter type: with filter for particulates.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolidAppearancePowderColourGrey BrownOdourOdourless

Odour threshold No information available

Property Values Remarks • Method

pH Not applicable . 11.5

Melting point / freezing Not applicable . °C

point

Boiling point / boiling °C

range

Flash point approx . °C Evaporation rate Not applicable .

Not applicable

Not applicable

BOSTIK SL C780 FLEX
Supercedes Date: 18-Nov-2020
Revision Number 1

Flammability (solid,

No data available

gas)

Flammability Limit in

Air

Upper flammability or No data available

explosive limits

Lower flammability or No data available

explosive limits

Vapour pressure No data available Relative vapour densityNo data available

Relative density 1.4

Water solubility Cement based products

react and solidify in contact with water

Solubility(ies)
Partition coefficient
Autoignition

No data available No data available No data available

temperature

Decomposition

No data available

temperature

Kinematic viscosity

Not applicable . mm²/s

Dynamic viscosity Not applicable .

Explosive propertiesNo data available **Oxidising properties**No data available

9.2. Other information

Solid content (%) 100 Softening Point Not relevant

VOC Content (%) No information available

Density 1.5 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition Thermal decomposition can lead to release of irritating and toxic gases and vapours.

Supercedes Date: 18-Nov-2020 Revision Number 1

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

BOSTIK SL C780 FLEX

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact May cause irritation. May cause sensitisation by skin contact. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). Specific test data for the substance or mixture is not available. Causes

mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. Prolonged contact may

cause redness and irritation.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>2000 mg/kg (Rattus)		
Portland Cement 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	
Quartz (fine fraction) 14808-60-7	>2000 mg/kg (Rattus)		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious

eye damage.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Revision date 18-Nov-2020

BOSTIK SL C780 FLEX
Supercedes Date: 18-Nov-2020
Revision Number 1

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicityBased on available data, the classification criteria are not met.

STOT - single exposureBased on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Quartz	-	0
14808-60-7		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment. The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Flue dust, Cement Portland	PBT assessment does not apply	
68475-76-3		

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

United Kingdom, Ireland - BE

BOSTIK SL C780 FLEX Revision date 18-Nov-2020 Supercedes Date: 18-Nov-2020 **Revision Number 1**

Do not reuse empty containers. Handle contaminated packages in the same way as the Contaminated packaging

product itself.

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 **European Waste Catalogue**

01, 17 09 02 and 17 09 03

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated Not regulated 14.4 Packing group 14.5 Environmental hazards Not applicable 14.6 Special Provisions None

IMDG

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated

14.5 Marine pollutant NP 14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated 14.2 Proper Shipping Name Not regulated Not regulated 14.3 Transport hazard class(es) 14.4 Packing group Not regulated 14.5 Environmental hazards Not applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

Supercedes Date: 18-Nov-2020 Revision Number 1

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

⁴⁷ where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

BOSTIK SL C780 FLEX

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H335 - May cause respiratory irritation

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 18-Nov-2020

Revision date 18-Nov-2020

BOSTIK SL C780 FLEX
Supercedes Date: 18-Nov-2020
Revision Number 1

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet