



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK WOOD H944 XTREM

Form This substance/ mixture contains nanoforms

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against Not to be used in articles intended for direct or prolonged skin contact Not to be used in production of toys or childcare articles Fabrics, textiles and apparel: bedding and clothing Gloves Footwear (shoes, boots) Paper products: tissue, towels, disposable dinnerware, nappies, feminine hygiene products, adult incontinence products, writing paper

Reason why uses advised against Restricted substance per REACH Annex XVII

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik GmbH
Industriestrasse 3 – 11
33829 Borgholzhausen, Germany
Tel: +49 (0) 5425 / 801 0
Fax: +49 (0) 5425 / 801 140

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland

NPIC - National Poison Information Centre

Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom

Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe

112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Hazard statements

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine. May produce an allergic reaction

EUH210 - Safety data sheet available on request

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No.)	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Trimethoxyvinylsilane 0.1- <1 %	220-449-8 (014-049-00-0)	2768-02-7	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	-	-	01-2119513215-52-XXXX
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 0.1- <1 %	309-629-8	100545-48-0	Skin Sens. 1B (H317)	Skin Sens. 1 :: C>=25%	-	-	01-2119979085-27-XXXX
Diocetyltin oxide 0.1 - <0.5 %	212-791-1	870-08-6	STOT SE 2 (H371)	-	-	-	01-2119971268-27-xxxx
Ethyl silicate 0.1 - <0.3 %	201-083-8 (014-005-00-0)	78-10-4	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	-	-	01-2119496195-28-xxxx

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

		(H225)				
--	--	--------	--	--	--	--

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	309-629-8	100545-48-0	-	-	-	-	-
Diocetyl tin oxide	212-791-1	870-08-6	-	-	-	-	-
Ethyl silicate	201-083-8 (014-005-00-0)	78-10-4	-	-	4.9	11	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
-----------------	-------------

Effects of Exposure	No information available.
----------------------------	---------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.
------------------------	-------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs.

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ * STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 260 mg/m ³ STEL: 600 ppm STEL: 780 mg/m ³ Sk*	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*
Diocetyltin oxide 870-08-6	-	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³	TWA: 0.1 mg/m ³ STEL: 0.2 mg/m ³ Sk*
Calcium distearate 1592-23-0	-	TWA: 10 mg/m ³ STEL: 30 mg/m ³	
Ethyl silicate 78-10-4	TWA: 44 mg/m ³ TWA: 5 ppm	TWA: 5 ppm TWA: 44 mg/m ³ STEL: 15 ppm STEL: 132 mg/m ³	TWA: 5 ppm TWA: 44 mg/m ³ STEL: 15 ppm STEL: 132 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	3,35 mg/m ³	

Diocetyltin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

worker Long term Systemic health effects	Inhalation	0.004 mg/m ³	
------------------------------------------------	------------	-------------------------	--

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m ³	
worker Short term Local health effects	Inhalation	85 mg/m ³	
worker Long term Systemic health effects	Inhalation	85 mg/m ³	
worker Long term Local health effects	Inhalation	85 mg/m ³	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Inhalation	0.83 mg/m ³	

Diocetyl tin oxide (870-08-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m ³	

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Ethyl silicate (78-10-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	25 mg/m ³	
Consumer Short term Local health effects	Inhalation	25 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	25 mg/m ³	
Consumer Long term Local health effects	Inhalation	25 mg/m ³	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Diocetyl oxide (870-08-6)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

Ethyl silicate (78-10-4)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Ensure that enough fresh air is supplied to dilute and remove dusts, fumes or vapours. Between 5 and 15 air changes per hour are recommended, with a through draught.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection

Wear suitable protective clothing.

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Paste, Thixotropic	
Colour	Beige	
Odour	Slight. Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data available	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	None known
Lower flammability or explosive limits	No data available	
Flash point	> 61 °C	CC (closed cup)
Autoignition temperature	No data available	
Decomposition temperature		
pH		
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	approx 3500 - 5500 Pa.s	Spindle 3 @ 1 rpm @ 23 °C
Water solubility	Reacts with water. Product cures with moisture	Not applicable. Reacts with water.
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	< 1100	
Relative density	1.4 - 1.6	
Bulk Density	No data available	
Density	ca. 1.5 g/cm³	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	LD50 >2000 mg/kg (Rattus)	-	LC50 > 5.05 mg/kg (Rattus)
Diocetyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Ethyl silicate	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L (Rat male) 4 h > 16.8 mg/L (Rat female) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 431: In Vitro Skin Corrosion: Human Skin Model Test	EPISKIN™	in vitro	0.02 g	4 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye	0.1 mL	72 hours	Non-irritant

Respiratory or skin sensitisation May produce an allergic reaction.

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Sensitizing > 25 %

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine (100545-48-0)

Method	Species	Results
OECD Test No. 421:	Rat	Not Classifiable

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Reproduction/Developmental Toxicity Screening Test	
----------------------------------------------------	--

STOT - single exposure Based on available data, the classification criteria are not met.

Diocyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocyltin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 - 0.5 mg/kg bw/d

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine 100545-48-0	EL50 (72h) >100 mg/L Algae (Pseudokirchneriella subcapitata)	LL50 (96h) >10mg/L (Onchohynchus mykiss)	-	EL50 (48h) >10mg/L Daphnia (Daphnia magna)		
Diocyltin oxide	EC50 (3hr)	LC50 (96hr)	-	EC50 (48Hr)		

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

870-08-6	>1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	>0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)		>0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Ethyl silicate 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) > 245 mg/L (Danio rerio) EU Method C.1	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyltin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	5.86
Diocetyltin oxide	6
Ethyl silicate	3.18

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Octadecanoic acid, 12-hydroxy-, reaction products with ethylenediamine	The substance is not PBT / vPvB
Diocetyltin oxide	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20.

20 (6) DOT.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 649/2012 - Annex Number
Diocetyl tin oxide	I.1

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

H335 - May cause respiratory irritation

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications

Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 09-Feb-2024

Revision note SDS sections updated

Training Advice No information available

SAFETY DATA SHEET

BOSTIK WOOD H944 XTREM
Supercedes Date: 23-Jan-2023

Revision date 09-Feb-2024
Revision Number 1.05

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet