

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK WOOD H180 CLASSIC-P

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & 1-o-Tolylbiguanide. May produce an allergic reaction

EUH210 - Safety data sheet available on request

2.3. Other hazards

United Kingdom - BE Page 1 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Trimethoxyvinylsilane	(014-049-00- 0) 220-449-8	2768-02-7	0.1- <1	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215- 52-XXXX
1-o-Tolylbiguanide	202-268-6	93-69-6	0.1 - <0.5	Skin Sens. 1 (H317) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)	-	01-2119976311- 39

Full text of H- and EUH-phrases: see section 16

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

United Kingdom - BE Page 2 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023

Revision date 21-Mar-2023 Revision Number 2.08

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Remove to fresh air. If symptoms persist, call a doctor. Inhalation

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

ophthalmologist.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by Ingestion

mouth to an unconscious person. Call a doctor or poison control centre immediately.

Small amounts of toxic methanol are released by hydrolysis.

Self-protection of the first aider Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by

hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Thermal decomposition can lead to release of irritating gases and vapours.

Carbon monoxide. Carbon dioxide (CO2). Hazardous combustion products

5.3. Advice for firefighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

precautions for fire-fighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get

in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

United Kingdom - BE Page 3 / 13

BOSTIK WOOD H180 CLASSIC-P
Supercedes Date: 06-Jan-2023
Revision Number 2.08

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin,

eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated

place. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 $^{\circ}\text{C}.$

7.3. Specific end use(s)

Specific use(s)

Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³	TWA: 266 mg/m ³
	*	STEL: 250 ppm
		STEL: 333 mg/m ³
		Sk*

Chemical name	European Union	Ireland	United Kingdom
---------------	----------------	---------	----------------

United Kingdom - BE Page 4 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023

Systemic health effects

Consumer

Revision date 21-Mar-2023 Revision Number 2.08

Methyl alcohol	_	15 mg/L (urine - Methanol end of	
67-56-1		shift)	
Perived No Effect Level (DNEL)	No information availa	able	
Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02 Type	Exposure route	Derived No Effect Level	Safety factor
ур с	Exposure route	(DNEL)	Carety factor
vorker Systemic health effects Long term	Inhalation	27,6 mg/m³	
vorker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	
-o-Tolylbiguanide (93-69-6)			
Гуре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	5.88 mg/m³	
worker Short term Systemic health effects	Inhalation	35.26 mg/m³	
vorker Long term Local health effects	Inhalation	5.88 mg/m³	
worker Short term Systemic health effects	Inhalation	35.26 mg/m³	
worker Short term Systemic health effects	Dermal	55.6 mg/kg bw/d	
worker Short term Local health effects	Dermal	55.6 mg/kg bw/d	
		1	
Derived No Effect Level (DNEL)			
Frimethoxyvinylsilane (2768-02 Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects ong term	Oral	0,3 mg/kg bw/d	
I-o-Tolylbiguanide (93-69-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.47 mg/m ³	

United Kingdom - BE Page 5 / 13

8.82 mg/m³

Inhalation

BOSTIK WOOD H180 CLASSIC-P
Supercedes Date: 06-Jan-2023
Revision Number 2.08

Short term			
Systemic health effects			
Consumer	Inhalation	1.47 mg/m³	
Long term			
Local health effects			
Consumer	Inhalation	8.82 mg/m³	
Short term			
Systemic health effects			
Consumer	Dermal	27.8 mg/kg bw/d	
Short term			
Systemic health effects			
Consumer	Oral	1.67 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Oral	10 mg/kg bw/d	
Short term			
Systemic health effects			
Consumer	Dermal	27.8 mg/kg bw/d	
Short term			
Local health effects			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

1-o-Tolylbiguanide (93-69-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.15 mg/l
Marine water	0.15 mg/l
Sewage treatment plant	50 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than

480 min. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

Wear suitable protective clothing.

In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid

United Kingdom - BE Page 6 / 13

None known

hPa @ 50 °C

Insoluble in water. Reacts with water.

Spindle Z3U @ 1 rpm @ 23 °C

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023

Revision date 21-Mar-2023 **Revision Number** 2.08

Paste **Appearance** Colour Grev

Odour Slight, Characteristic. **Odour threshold** No information available

Property Values Remarks • Method

Not applicable . Melting point / freezing point Initial boiling point and boiling Not applicable .

range

Flammability Not applicable for liquids .

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available limits

Flash point

No information available No data available

Autoignition temperature

Decomposition temperature

pH (as aqueous solution) No data available Kinematic viscosity No data available

Dynamic viscosity 500 - 900 Pa.s Reacts with water. Water solubility Solubility(ies) No data available

No data available **Partition coefficient** Vapour pressure < 1100

Relative density 1.7 - 1.9 **Bulk Density** No data available **Liquid Density** 1.7 - 1.9 g/cm³ Relative vapour density No data available

Particle characteristics

Particle Size No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity

10.2. Chemical stability

Stable under normal conditions. Stability

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

United Kingdom - BE Page 7/13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are

formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
• •	(Rattus) OECD 401	cuniculus)	OECD TG 403
1-o-Tolylbiguanide	LD50> 2000 mg/kg (Rattus)	LD50> 2000 mg/kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

United Kingdom - BE Page 8 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation May produce an allergic reaction.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitising
Sensitisation, Buehler test			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		_

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Thin out oxy this joint in the case of the					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation				-	
Toxicity: 90-day Study					

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

United Kingdom - BE Page 9 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023

Revision date 21-Mar-2023 **Revision Number** 2.08

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		
	EU Method C.3					
1-o-Tolylbiguanide	EC50 (72h) = 30	LC50 (96h) =	-	EC50 (48h) = 15		
93-69-6	-46 mg/l	150 mg/l		mg/l (Daphnia		
	((Desmodesmus	(Oncorhynchus		magna)		
	subspicatus)	mykiss)		OECD 202		
	OECD 201					

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Timite and Africa (2) of the first transfer				
Method	Exposure time	Value	Results	
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily	
Biodegradability: Manometric			biodegradable	
Respirometry Test (TG 301 F)				

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name		Partition coefficient
Trimethoxyvinylsila	ne	1.1
1-o-Tolylbiguanide)	0.71

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
1-o-Tolylbiguanide	The substance is not PBT / vPvB

United Kingdom - BE Page 10/13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1UN number or ID numberNot regulated14.2Proper Shipping NameNot regulated14.3Transport hazard class(es)Not regulated14.4Packing groupNot regulated

14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 Proper Shipping Name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not applicable

14.6 Special precautions for user Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

United Kingdom - BE Page 11 / 13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

United Kingdom - BE Page 12/13

BOSTIK WOOD H180 CLASSIC-P Supercedes Date: 06-Jan-2023 Revision date 21-Mar-2023 Revision Number 2.08

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 21-Mar-2023

Indication of changes

Revision note SDS sections updated, 1, 11.

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13