



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK WOOD H180 CLASSIC-P

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request

EUH208 - Contains Trimethoxyvinylsilane & 1-o-Tolylbiguanide. May produce an allergic reaction

2.3. Other hazards

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Trimethoxyvinylsilane 2768-02-7	0.1- <1	01-2119513215-52-XXXX	220-449-8 (014-049-00-0)	Acute Tox. 4 (H332) Skin Sens. 1B (H317) Flam. Liq. 3 (H226)	-	-	-	-
Quartz (fine fraction) 14808-60-7	0.1- <1	[5]	238-878-4	STOT RE 1 (H372)	-	-	-	-
1-o-Tolylbiguanide 93-69-6	0.1 - <0.5	01-2119976311-39	202-268-6	Skin Sens. 1 (H317) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)	-	-	-	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
1-o-Tolylbiguanide	202-268-6	93-69-6	-	3171	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.
-----------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂).

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
---------------------------	--

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Methyl alcohol 67-56-1	TWA: 200 ppm; TWA: 260 mg/m ³ ; pSk	TWA: 200 ppm; TWA: 266 mg/m ³ ; STEL: 250 ppm; STEL: 333 mg/m ³ ; pSk
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m ³ ;	TWA: 0.1 mg/m ³ ; respirable fraction STEL: 0.3 mg/m ³ ; respirable

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

67-56-1		shift)	
---------	--	--------	--

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m ³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

1-o-Tolylbiguanide (93-69-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	5.88 mg/m ³	
worker Short term Systemic health effects	Inhalation	35.26 mg/m ³	
worker Long term Local health effects	Inhalation	5.88 mg/m ³	
worker Short term Systemic health effects	Inhalation	35.26 mg/m ³	
worker Short term Systemic health effects	Dermal	55.6 mg/kg bw/d	
worker Short term Local health effects	Dermal	55.6 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m ³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Quartz (fine fraction) (14808-60-7)			
1-o-Tolylbiguanide (93-69-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.47 mg/m ³	
Consumer	Inhalation	8.82 mg/m ³	

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Short term Systemic health effects			
Consumer Long term Local health effects	Inhalation	1.47 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	8.82 mg/m ³	
Consumer Short term Systemic health effects	Dermal	27.8 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	1.67 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	10 mg/kg bw/d	
Consumer Short term Local health effects	Dermal	27.8 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Quartz (fine fraction) (14808-60-7)	
1-o-Tolylbiguanide (93-69-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.15 mg/l
Marine water	0.15 mg/l
Sewage treatment plant	50 mg/l

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection

Wear suitable gloves. Recommended Use: Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Physical state Liquid
Appearance Paste
Colour Grey
Odour Slight. Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	Not applicable	
Initial boiling point and boiling range	No data available	Not applicable
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	No data available	No information available
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	Insoluble in water. Reacts with water.
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	500 - 900 Pa.s	Spindle Z3U @ 1 rpm @ 23 °C
Water solubility	Reacts with water.	Reacts with water
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	< 1100	hPa @ 50 °C
Relative density	1.7 - 1.9	
Bulk density	No data available	
Liquid Density	1.7 - 1.9 g/cm ³	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Based on available data, the classification criteria are not met.
Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
1-o-Tolylbiguanide	LD50> 2000 mg/kg (Rattus)	LD50> 2000 mg/kg (Rattus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Quartz (fine fraction) (14808-60-7)

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Respiratory or skin sensitisation May produce an allergic reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
1-o-Tolylbiguanide 93-69-6	EC50 (72h) = 30 -46 mg/l (Desmodesmus subspicatus) OECD 201	LC50 (96h) = 150 mg/l (Oncorhynchus mykiss)	-	EC50 (48h) = 15 mg/l (Daphnia magna) OECD 202		

12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
1-o-Tolylbiguanide	0.71

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	Not PBT/vPvB
1-o-Tolylbiguanide	Not PBT/vPvB

12.6. Endocrine disrupting properties

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None
14.7 Maritime transport in bulk according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

SECTION 15: Regulatory information

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

SAFETY DATA SHEET

BOSTIK WOOD H180 CLASSIC-P
Supersedes date 21-Mar-2023

Revision date 29-Apr-2025
Revision Number 2.09

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	29-Apr-2025
<u>Indication of changes</u>	

Revision Note	SDS sections updated, 3.
Training Advice	No information available
Further information	No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet