

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended useCeramic Tile Adhesive

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin irritation	Category 2 - (H315)
Serious eye damage	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Target organ effects: Respiratory irritation.	

2.2. Label elements

Contains Portland Cement



United Kingdom - BE Page 1 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing dust

P264 - Wash face, hands and any exposed skin thoroughly after handling

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P362 + P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking. Material becomes extremely slippery when wet.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-	REACH	EC No (EU	Classification	•		M-Factor	Notes
	%	registration	Index No)	9	concentration		(long-ter	
		number		Regulation (EC) No.	limit (SCL)		m)	
				1272/2008 [CLP]				
Portland Cement	40 - <80	[5]	266-043-4	STOT SE 3 (H335)	-	-	-	-
65997-15-1				Skin Irrit. 2 (H315)				
				Eye Dam. 1 (H318)				
				Skin Sens. 1				
				(H317)				
				, ,				

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

Full text of H- and EUH-phrases: see section 16

United Kingdom - BE Page 2 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Acute Toxicity Estimate
No information available

Chemical name	EC No (EU	CAS No.	Oral LD50	Dermal LD50	Inhalation	Inhalation	Inhalation
	Index No)		mg/kg	mg/kg	LC50 - 4 hour -	LC50 - 4 hour -	LC50 - 4 hour -
	ŕ				dust/mist -	vapour - mg/L	gas - ppm
					mg/L		•
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the

Safety Data Sheet when going for medical treatment.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or

concerned: Get medical advice/attention.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash it before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Dust irritates eyes and air passages. Causes

serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

when kneeling in wet cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

United Kingdom - BE Page 3 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 **Revision Number** 1.03

surrounding environment.

No information available. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal **Personal precautions**

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry.

Prevent dust cloud.

Methods for cleaning up Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protection

equipment. Take off contaminated clothing and wash it before reuse.

Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. General hygiene considerations

Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. **Storage Conditions**

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity. Protect from moisture.

7.3. Specific end use(s)

United Kingdom - BE Page 4 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Specific use(s)

Ceramic Tile Adhesive.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Portland Cement	-	TWA: 10 mg/m ³ ; inhalable dust
65997-15-1		TWA: 4 mg/m ³ ; respirable dust
		STEL: 30 mg/m ³ ; inhalable dust
		STEL: 12 mg/m ³ ; respirable dust
Dust	-	TWA: 10 mg/m ³ ; inhalable dust
RR-12364-8		TWA: 4 mg/m³; respirable dust
		STEL: 30 mg/m ³ ; inhalable dust
		STEL: 12 mg/m ³ ; respirable dust

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available. **(PNEC)**

8.2. Exposure controls

Engineering controls Ensure that enough fresh air is supplied to dilute and remove dusts, fumes or vapours.

Between 5 and 15 air changes per hour are recommended, with a through draught.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Use eye protection according to EN

166, designed to protect against powders and dusts.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves should be replaced regularly and if there is any sign of damage to the glove

material. Gloves made of plastic or rubber.

Skin and body protection Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing

to prevent skin contact.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid

generation of dust. Possible nuisance dust.

Recommended filter type: Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Colour Grey

United Kingdom - BE Page 5 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 **Revision Number** 1.03

No information available. Odour

Values Remarks • Method Property

Melting point / freezing point Not applicable . Not applicable Initial boiling point and boiling No data available Not applicable

range

Flammability Flammability Limit in Air

No data available None known None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Not applicable Flash point No data available **Autoignition temperature** No data available None known None known

Decomposition temperature

рΗ No data available

pH (as aqueous solution) > 11 solution (75 %) Not applicable . Kinematic viscosity Not applicable Not applicable Dynamic viscosity Not applicable

Water solubility No data available. Cement based

products react and solidify in contact

with water

Solubility(ies) No data available None known Partition coefficient No data available None known No data available Vapour pressure None known Relative density No data available None known

Bulk density 0.11

1.7 g/ml Density

Relative vapour density No data available None known

Particle characteristics

50-1200 **Particle Size**

Particle Size Distribution No information available

9.2. Other information

100 Solid content (%)

Softening point Not applicable

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity

10.2. Chemical stability

Keep away from Incompatible materials. Stable under recommended storage conditions. Stability

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

United Kingdom - BE Page 6 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitisation

by skin contact. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness

and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Portland Cement	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

United Kingdom - BE Page 7 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye

damage.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazardBased on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

United Kingdom - BE Page 8 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

12.6. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

12.7. Other adverse effects

Other adverse effects No information available.

PMT or vPvM propertiesBased on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

10 13 06 particulates and dust (except 10 13 12 and 10 13 13)

Cured product can be treated as construction waste. In the management of larger

quantities consult with local authorities and local waste disposal company

10 13 14 waste concrete and concrete sludge

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards

Not regulated

Not regulated
Not regulated
Not regulated
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

<u>IMDG</u>

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 Not regulated
 Not regulated
 Not regulated
 Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

United Kingdom - BE Page 9 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
14.6 Special precautions for user

Not regulated Not regulated Not applicable

14.6 Special precautions for user
Special Provisions
None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	47

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

United Kingdom - BE Page 10 / 11

BOSTIK MC280 MEDIUM SET ADHESIVE GREY

Supercedes date 16-Mar-2023

Revision date 12-May-2025 Revision Number 1.03

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H335 - May cause respiratory irritation

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 12-May-2025

Indication of changes

Revision Note Not applicable.

Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 11 / 11