

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SOVEREIGN TANKING SLURRY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Category 3 Respiratory irritation	

2.2. Label elements

Contains Portland Cement; Calcium hydroxide



United Kingdom - BE Page 1 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing dust

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P362 + P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/ container to an approved waste disposal plant

P405 - Store locked up

2.3. Other hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight- %	REACH registration number	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	concentration		M-Factor (long-ter m)	Notes
Portland Cement 65997-15-1	40 - <80	[5]	266-043-4	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317)		-	-	-
Calcium hydroxide 1305-62-0	10 - <20	01-2119475151 -45-XXXX	215-137-3	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) STOT SE 3 (H335)		-	-	-
Quartz 14808-60-7	0.1- <1	[4]	238-878-4	STOT RE 1 (H372)	-	-	-	-

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

United Kingdom - BE Page 2 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 Revision Number 1.03

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU	CAS No.	Oral LD50	Dermal LD50	Inhalation	Inhalation	Inhalation
	Index No)		mg/kg	mg/kg	LC50 - 4 hour -	LC50 - 4 hour -	LC50 - 4 hour -
					dust/mist -	vapour - mg/L	gas - ppm
					mg/L		
Portland Cement	266-043-4	65997-15-1	-	-	-	-	-
Calcium hydroxide	215-137-3	1305-62-0	-	-	-	-	-
Quartz	238-878-4	14808-60-7	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the

Safety Data Sheet when going for medical treatment.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. IF exposed or

concerned: Get medical advice/attention.

Eye contact Do not rub affected area. Immediately flush with plenty of water. After initial flushing,

remove any contact lenses and continue flushing for at least 15 minutes. Consult an

ophthalmologist.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Take off

contaminated clothing and wash it before reuse.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Itching. Rashes. Hives. Dust irritates eyes and air passages. Causes

serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g.

when kneeling in wet cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

United Kingdom - BE Page 3 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 Revision Number 1.03

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Cover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry. Methods for containment

Prevent dust cloud.

Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect Methods for cleaning up

dust. Use appropriate personal protective equipment (PPE). Carefully shovel or sweep

up spilled material and place in suitable container. Avoid generating dust.

Clean contaminated objects and areas thoroughly observing environmental regulations. Prevention of secondary hazards

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protection

equipment. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

United Kingdom - BE 4 / 12 Page

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up.

Keep out of the reach of children. Keep the packing dry and well sealed to prevent

contamination and absorption of humidity.

7.3. Specific end use(s)

Specific use(s)

Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Portland Cement	-	TWA: 10 mg/m ³
65997-15-1		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Calcium hydroxide	TWA: 1 mg/m³ respirable fraction	TWA: 1 mg/m ³
1305-62-0	STEL: 4 mg/m³ respirable fraction	TWA: 5 mg/m ³
		STEL: 4 mg/m ³
		STEL: 15 mg/m ³
Dust	-	TWA: 10 mg/m ³
RR-12364-8		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Quartz	TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³
14808-60-7		STEL: 0.3 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (D	NEL)						
Portland Cement (65997-15-1)							
Calcium hydroxide (1305-6	52-0)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
worker Short term Local health effects	Inhalation	4 mg/m³					
worker Long term Local health effects	Inhalation	1 mg/m³					

Derived No Effect Level (DNEL) Calcium hydroxide (1305-62-0)							
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
Consumer Short term Local health effects	Inhalation	4 mg/m³					
Consumer	Inhalation	1 mg/m³					

United Kingdom - BE Page 5 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 **Revision Number** 1.03

Long term Local health effects		

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)				
Calcium hydroxide (1305-62-0)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	0.49 mg/l			
Marine water	0.32 mg/l			
Sewage treatment plant	3 mg/l			
Soil	1080 mg/kg dry weight			

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be **Engineering controls**

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the

breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn. Gloves made of plastic or rubber. Gloves should be replaced regularly and if there is any sign of damage

to the glove material.

Skin and body protection Avoid contact with skin, eyes or clothing. Wear appropriate personal protective clothing

to prevent skin contact.

No protective equipment is needed under normal use conditions. If exposure limits are Respiratory protection

exceeded or irritation is experienced, ventilation and evacuation may be required. Avoid

generation of dust. Possible nuisance dust.

Recommended filter type: Wear a respirator conforming to EN 140 with Type P2/P3 filter or better.

No information available. Environmental exposure controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Powder **Appearance** Colour Grev Odour Odourless. **Odour threshold** Not applicable

Values Remarks • Method **Property**

Not applicable . Melting point / freezing point Initial boiling point and boiling Not applicable . None known

range

Flammability

No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Flash point Not applicable None known **Autoignition temperature** No data available None known None known

Decomposition temperature

No data available

pH (as aqueous solution) 11 - 13 None known

United Kingdom - BE Page 6 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 Revision Number 1.03

Kinematic viscosity

Dynamic viscosity

Not applicable .

Not applicable .

Water solubility Slightly soluble. Cement based

products react and solidify in contact

with water

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk densityNo data availableDensityNo data available

Relative vapour density

No data available

None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) 100 Softening point Not relevant

VOC content 0 g/L European directive n°2010/75/UE

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics No information available Not applicable .

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Keep away from Incompatible materials. Stable under recommended storage conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Acids. Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions. **products**

SECTION 11: Toxicological information

United Kingdom - BE Page 7 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. May cause sensitisation

by skin contact. Repeated or prolonged skin contact may cause allergic reactions with

susceptible persons. (based on components). Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. May cause redness

and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg
ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chen	nical name	Oral LD50	Dermal LD50	Inhalation LC50
Portla	nd Cement	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Calciur	n hydroxide	=7340 mg/kg (Rattus)	LD50 > 2500 mg/kg bw (OECD	> 6.04 mg/L (Rat)4 h
			402, Oryctolagus cuniculus)	
	Quartz	=6450 mg/kg (Rattus)	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Calcium hydroxide (1305-62-0)							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
OECD Test No. 404:	Rabbit	Dermal			irritant		
Acute Dermal							
Irritation/Corrosion							

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

Calcium hydroxide (1305-62-0)

United Kingdom - BE Page 8 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 Revision Number 1.03

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye			Eye Damage

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

	Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
		plants		microorganisms			(long-term)
ſ	Calcium hydroxide	EC50 = 184.57	LC50: =160mg/L	-	EC50 = 49.1		
	1305-62-0	g/ml (72Hr)	(96h, Gambusia		g/ml (48 hr)		
		,	affinis)				

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility in soil No information available.

United Kingdom - BE Page 9 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment	
Calcium hydroxide	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

10 13 06 particulates and dust (except 10 13 12 and 10 13 13)

Cured product can be treated as construction waste. In the management of larger

quantities consult with local authorities and local waste disposal company

10 13 14 waste concrete and concrete sludge

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

IMDG

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
Not regulated

14.5 Marine pollutant NP14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

United Kingdom - BE Page 10 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022 Revision date 30-Oct-2024 Revision Number 1.03

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
 14.2 UN proper shipping name
 14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Portland Cement	65997-15-1	Use restricted. See entry 47.

47 where product supplied with reducing agent the packaging must be marked with the storage conditions and storage period appropriate to maintaining the activity of the reducing agent to keep the content of soluble chromium VI below 2mg/Kg.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the

United Kingdom - BE Page 11 / 12

SOVEREIGN TANKING SLURRY Supercedes date 28-Sep-2022

Revision date 30-Oct-2024 Revision Number 1.03

marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction H318 - Causes serious eye damage H335 - May cause respiratory irritation

H372 - Causes damage to organs through prolonged or repeated exposure

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Sk* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Oct-2024

Indication of changes

Revision Note Not applicable.

Training Advice No information available Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 12 / 12