



SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

1. Identification

1.1. Product Identifier

Product Name SL-200

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use No information available
Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.
11320 W. Watertown Plank Road
Wauwatosa, Wisconsin 53226 USA
Phone: +1 (800) 843-0844 (Domestic Toll Free)
Phone: +1 (414) 774-2250 (International)
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone Telephone: 1-800-227-0332
(Outside U.S.) 1-703-527-3887

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label Elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes skin irritation
Causes serious eye damage
May cause an allergic skin reaction
May cause cancer
Causes damage to organs through prolonged or repeated exposure

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020



Appearance Powder **Physical state** Solid **Odor** No information available

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Wear protective gloves/protective clothing/eye protection/face protection
Contaminated work clothing must not be allowed out of the workplace
Do not breathe dust/fume/gas/mist/vapors/spray
Wash face, hands and any exposed skin thoroughly after handling
Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Immediately call a POISON CENTER or doctor
Take off contaminated clothing and wash it before reuse
IF ON SKIN: Wash with plenty of water and soap
If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

4 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No	Weight-%
Quartz	14808-60-7	15 - 40
Limestone	1317-65-3	10 - 30
Cement, alumina, chemicals	65997-16-2	5 - <10
Calcium Sulfoaluminate Cement	960375-09-1	5 - <10
Cement, portland, chemicals	65997-15-1	1 - <5
Calcium sulfate dihydrate	10101-41-4	1 - <5

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Carbonic acid, magnesium salt (1:1)	546-93-0	1 - <5
Calcium sulfate hemihydrate	10034-76-1	1 - <5
Wollastonite	13983-17-0	1 - <5

**The exact percentage (concentration) of composition has been withheld as a trade secret*

4. First-aid measures

4.1. Description of first aid measures

Inhalation	Remove to fresh air. If symptoms persist, call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Brush off loose particles from skin. Wash off immediately with soap and plenty of water for at least 15 minutes. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If swallowed, call a poison control center or physician immediately.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Causes serious eye damage. Inhalation of dust in high concentration may cause irritation of respiratory system. Irritating to skin.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. May cause sensitization by skin contact. Treat symptomatically.
---------------------------	---

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous combustion products	Carbon dioxide (CO ₂). Oxides of sulfur. Silicon oxides.
Explosion data	
Sensitivity to mechanical impact	None.

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment for fire-fighters As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.

Methods for cleaning up Use personal protective equipment as required. Sweep up and shovel into suitable containers for disposal. Avoid generation of dust. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Ensure adequate ventilation. Avoid contact with skin and eyes. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture. Keep the packing dry and well sealed to prevent contamination and absorption of humidity.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY
Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

8.1. Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Quartz 14808-60-7	TWA: 0.025 mg/m ³ respirable particulate matter	TWA: 50 µg/m ³ TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m ³ respirable dust : (250)/(%SiO ₂ + 5) mppcf TWA respirable fraction : (10)/(%SiO ₂ + 2) mg/m ³ TWA respirable fraction	IDLH: 50 mg/m ³ respirable dust TWA: 0.05 mg/m ³ respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Cement, alumina, chemicals 65997-16-2	10 mg/m ³ (total; 5 mg/m ³ (resp)	-	-
Cement, portland, chemicals 65997-15-1	TWA: 1 mg/m ³ particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 10 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m ³ TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Calcium sulfate dihydrate 10101-41-4	TWA: 10 mg/m ³ inhalable particulate matter	-	-
Carbonic acid, magnesium salt (1:1) 546-93-0	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Calcium sulfate hemihydrate 10034-76-1	TWA: 10 mg/m ³ inhalable particulate matter	-	-
Wollastonite 13983-17-0	TWA: 1 mg/m ³ inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	-	-

Chemical name	Argentina	Brazil	Chile	Colombia
---------------	-----------	--------	-------	----------

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	TWA: 0.08 mg/m ³	TWA: 0.025mg/m ³
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 7 mg/m ³	-
Cement, portland, chemicals 65997-15-1	TWA: 10 mg/m ³	TWA: 1 mg/m ³	TWA: 8.8 mg/m ³	TWA: 1mg/m ³
Calcium sulfate dihydrate 10101-41-4	-	TWA: 10 mg/m ³	-	TWA: 10mg/m ³
Calcium sulfate hemihydrate 10034-76-1	-	TWA: 10 mg/m ³	-	TWA: 10mg/m ³
Wollastonite 13983-17-0	-	TWA: 1 mg/m ³	-	TWA: 1mg/m ³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m ³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³
Cement, portland, chemicals 65997-15-1	TWA: 1mg/m ³	TWA: 10mg/m ³	1 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	TWA: 10 mg/m ³
Calcium sulfate dihydrate 10101-41-4	TWA: 10mg/m ³	-	10 mg/m ³ TWA (inhalable particulate matter, listed under Calcium sulfate)	-
Calcium sulfate hemihydrate 10034-76-1	TWA: 10mg/m ³	-	10 mg/m ³ TWA (inhalable particulate matter, listed under Calcium sulfate)	-
Wollastonite 13983-17-0	TWA: 1mg/m ³	-	1 mg/m ³ TWA (inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica)	-

8.2. Exposure controls

Appropriate engineering controls

Engineering controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Hand protection

Wear suitable gloves. Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protection

Wear suitable protective clothing. Long sleeved clothing.

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Powder
Color	Gray
Odor	No information available
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not applicable .	
Melting point / freezing point	Not applicable .	
Boiling point / boiling range	Not applicable .	
Flash point	Not applicable .	
Evaporation rate	Not applicable .	
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	No data available	None known
Water solubility	Cement based products react and solidify in contact with water	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	.	
Dynamic viscosity	.	

9.2. Other information

Explosive properties	No information available
Oxidizing properties	No information available
Solvent content (%)	No information available
Solid content (%)	100
Softening Point	Not relevant
Molecular weight	No information available
VOC Content (%)	0 g/L / 0 %
Density	0.640 g/cm ³
Bulk density	No information available

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

10. Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Dust formation. Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Causes serious eye damage. May cause irreversible damage to eyes.

Skin contact Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact. Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Burning. May cause blindness. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	>20000 mg/kg	-	-

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Cement, alumina, chemicals 65997-16-2	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rat	-
Calcium Sulfoaluminate Cement 960375-09-1	>2000 mg/Kg	-	-
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Carbonic acid, magnesium salt (1:1) 546-93-0	>2000 mg/Kg Rat	-	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Irritating to skin.
Serious eye damage/eye irritation	Causes burns. Risk of serious damage to eyes.
Respiratory or skin sensitization	May cause sensitization by skin contact.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X
Wollastonite 13983-17-0	-	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	Respiratory system, Eyes, Skin, Lungs.
Aspiration hazard	Based on available data, the classification criteria are not met.
Other adverse effects	No information available.
Interactive effects	No information available.

12. Ecological information

12.1. Toxicity

US - EN

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Oncorhynchus mykiss) >100 mg/L (OECD 203)	-	EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

SAFETY DATA SHEET

SL-200
Revision Number 2

Revision Date: 24-Sep-2020
Supersedes Date: 27-May-2020

International Inventories

TSCA	Listed
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision Date: 24-Sep-2020

Revision note SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 10. 11. 12. 15.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet