



# SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

## 1. Identification

### 1.1. Product identifier

Product Name SL-200

### Other means of identification

Other information Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use No information available

Restrictions on use No information available

### 1.3. Details of the supplier of the safety data sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1(800) 726-7845 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

### 1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)  
Chemtrec: 1-800-424-9300 (US) , 1-703-527-3887 (Outside U.S.)  
**Rocky Mountain Poison Center: 1-866-767-5089**

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

### Hazards not otherwise classified (HNOC)

Not applicable

### 2.2. Label elements

#### EMERGENCY OVERVIEW

#### Danger

#### Hazard statements

Causes serious eye damage  
May cause an allergic skin reaction  
May cause cancer  
Causes damage to organs through prolonged or repeated exposure

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020



**Appearance** Powder      **Physical state** Solid      **Odor** No information available

## Precautionary Statements - Prevention

Contaminated work clothing must not be allowed out of the workplace  
Do not breathe dust/fume/gas/mist/vapors/spray  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Wear protective gloves/eye protection/face protection

## Precautionary Statements - Response

Get medical advice/attention if you feel unwell  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Immediately call a POISON CENTER or doctor  
IF ON SKIN: Wash with plenty of water and soap  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse

## Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

## Unknown acute toxicity

9 % of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

Causes mild skin irritation. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. Product dust may be irritating to eyes, skin and respiratory system. Repeated exposure may cause skin dryness or cracking.

## 3. Composition/information on ingredients

### 3.1. Substances

Not applicable.

### Mixture

Chemical name	CAS No.	Weight-%
Quartz	14808-60-7	15 - 40
Limestone	1317-65-3	10 - 30
Cement, alumina, chemicals	65997-16-2	10 - 30
Cement, portland, chemicals	65997-15-1	3 - <7
Calcium sulfate dihydrate	10101-41-4	1 - <5
Carbonic acid, magnesium salt (1:1)	546-93-0	1 - <5

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

Calcium sulfate hemihydrate	10034-76-1	1 - <5
Wollastonite	13983-17-0	1 - <5

*\*The exact percentage (concentration) of composition has been withheld as a trade secret*

## 4. First-aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Take a copy of the Safety Data Sheet when going for medical treatment.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Do not rub affected area. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	Brush off loose particles from skin. Remove material from skin immediately. Wash off immediately with soap and plenty of water for at least 15 minutes. Take off contaminated clothing and wash before reuse. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. If swallowed, call a poison control center or physician immediately.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Burning sensation. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers.
<b>Effects of Exposure</b>	No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization by skin contact. May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	---

## 5. Fire-Fighting Measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Large Fire</b>	CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitizer. May cause sensitization by skin contact.

**Hazardous combustion products** Carbon oxides. Sulfur oxides. Silicon dioxide.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **6. Accidental Release Measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment as required. Avoid generation of dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Sweep up to prevent slipping hazard.

### 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Cover powder spill with plastic sheet or tarp to minimize spreading and keep powder dry. Prevent dust cloud.

**Methods for cleaning up** Use personal protective equipment as required. Do not dry sweep dust. Wet dust with water before sweeping or use a vacuum to collect dust. Sweep up and shovel into suitable containers for disposal. Avoid generation of dust. Clean contaminated surface thoroughly.

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **7. Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Avoid generation of dust. Ensure adequate ventilation. Avoid contact with skin and eyes. Take off contaminated clothing and wash before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

## Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children. Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Protect from moisture.

## 7.3 References to other sections

### Reference to other sections

Section 10: STABILITY AND REACTIVITY  
Section 13: DISPOSAL CONSIDERATIONS

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Cement, alumina, chemicals 65997-16-2	10 mg/m <sup>3</sup> (total; 5 mg/m <sup>3</sup> (resp)	-	-
Cement, portland, chemicals 65997-15-1	TWA: 1 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction TWA: 50 mppcf <1% Crystalline silica	IDLH: 5000 mg/m <sup>3</sup> TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Calcium sulfate dihydrate 10101-41-4	TWA: 10 mg/m <sup>3</sup> inhalable particulate matter	-	-
Carbonic acid, magnesium salt (1:1) 546-93-0	-	-	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Calcium sulfate hemihydrate 10034-76-1	TWA: 10 mg/m <sup>3</sup> inhalable particulate matter	-	-
Wollastonite 13983-17-0	TWA: 1 mg/m <sup>3</sup> inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica	-	-

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
---------------	-----------	--------	---------------	----------

# SAFETY DATA SHEET

**SL-200**  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

Quartz 14808-60-7	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	LPP: 0.08 mg/m <sup>3</sup>	TWA: 0.025mg/m <sup>3</sup>
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	LPP: 7 mg/m <sup>3</sup> LPP: 5 mg/m <sup>3</sup>	-
Cement, portland, chemicals 65997-15-1	TWA: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>	LPP: 8.8 mg/m <sup>3</sup>	TWA: 1mg/m <sup>3</sup>
Calcium sulfate dihydrate 10101-41-4	-	TWA: 10 mg/m <sup>3</sup>	-	TWA: 10mg/m <sup>3</sup>
Calcium sulfate hemihydrate 10034-76-1	-	TWA: 10 mg/m <sup>3</sup>	-	TWA: 10mg/m <sup>3</sup>
Wollastonite 13983-17-0	-	TWA: 1 mg/m <sup>3</sup>	-	TWA: 1mg/m <sup>3</sup>

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Quartz 14808-60-7	TWA: 0.025mg/m <sup>3</sup>	TWA: 0.05mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup> TWA (respirable particulate matter)	TWA: 0.025 mg/m <sup>3</sup>
Cement, portland, chemicals 65997-15-1	TWA: 1mg/m <sup>3</sup>	TWA: 10mg/m <sup>3</sup>	1 mg/m <sup>3</sup> TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	TWA: 10 mg/m <sup>3</sup>
Calcium sulfate dihydrate 10101-41-4	TWA: 10mg/m <sup>3</sup>	-	10 mg/m <sup>3</sup> TWA (inhalable particulate matter, listed under Calcium sulfate)	-
Calcium sulfate hemihydrate 10034-76-1	TWA: 10mg/m <sup>3</sup>	-	10 mg/m <sup>3</sup> TWA (inhalable particulate matter, listed under Calcium sulfate)	-
Wollastonite 13983-17-0	TWA: 1mg/m <sup>3</sup>	-	1 mg/m <sup>3</sup> TWA (inhalable particulate matter, particulate matter containing no asbestos and <1% crystalline silica)	-

## 8.2. Exposure controls

### Appropriate engineering controls

#### Engineering controls

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles. If splashes are likely to occur: Face protection shield. Avoid contact with eyes.

#### Hand protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

<b>Skin and body protection</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	Use appropriate respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>General hygiene considerations</b>	Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid contact with skin, eyes or clothing. Wash hands and face before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Powder
<b>Color</b>	Gray
<b>Odor</b>	No information available
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	.	
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Melting point / freezing point</b>	Not applicable .	
<b>Initial boiling point and boiling range</b>	Not applicable .	
<b>Flash point</b>	Not applicable .	
<b>Evaporation rate</b>	Not applicable .	
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Relative vapor density</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Water solubility</b>	No data available Cement based products react and solidify in contact with water	
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	Not applicable . mm <sup>2</sup> /s	
<b>Dynamic viscosity</b>	.	None known

### 9.2. Other information

<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	
<b>Solvent content (%)</b>	No information available	
<b>Solid content (%)</b>	100	
<b>Softening point</b>	Not relevant	
<b>Molecular weight</b>	No information available	
<b>VOC content</b>		No information available

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

Density 0.640 g/cm<sup>3</sup>  
Bulk density No information available

## 10. Stability and reactivity

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Chemical stability Keep away from Incompatible materials. Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

### 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Acids. Aluminum.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye damage. May cause irreversible damage to eyes.
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. May cause sensitization by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Itching. Rashes. Hives. Prolonged contact may cause redness and irritation.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document



# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

ATEmix (oral) >5000 mg/kg  
ATEmix (dermal) >5000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/l  
ATEmix (inhalation-vapor) >20 mg/l

Unknown acute toxicity

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz 14808-60-7	=6450 mg/kg (Rattus)	-	-
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Cement, alumina, chemicals 65997-16-2	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rattus	-
Cement, portland, chemicals 65997-15-1	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
Carbonic acid, magnesium salt (1:1) 546-93-0	>2000 mg/Kg Rat	-	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. Causes mild skin irritation.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes burns. Causes serious eye damage.

**Respiratory or skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz 14808-60-7	A2	Group 1	Known	X
Wollastonite 13983-17-0	-	Group 3	-	-

### Legend

**ACGIH (American Conference of Governmental Industrial Hygienists)**

A2 - Suspected Human Carcinogen

**IARC (International Agency for Research on Cancer)**

Group 1 - Carcinogenic to Humans

**NTP (National Toxicology Program)**

Known - Known Carcinogen

**Occupational Safety and Health Administration of the US Department of Labor**

X - Present

**Reproductive toxicity** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Target organ effects** Respiratory system, Eyes, Skin, Lungs.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Other adverse effects** No information available.

**Interactive effects** No information available.

## 12. Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L (Onchorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Cement, alumina, chemicals 65997-16-2	EC50 (72h)Algae (Pseudokirchneriella subcapitata) >5.6mg/L	LC50 (96h) (Onchorhynchus mykiss) >100 mg/L (OECD 203)	-	EC50 (48h) Daphnia magna =6.6mg/L (OECD 202)

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9

### 12.4. Mobility in soil

**Mobility** No information available.

#### Other adverse effects

**Other adverse effects** No information available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

US - EN

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

**Waste from residues/unused products** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

## 14. Transport information

**DOT** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

## 15. Regulatory information

### International Inventories

<b>TSCA</b>	Complies
<b>DSL</b>	Not Listed

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Complies** - The components of this product are either listed or exempt from listing on inventory. Active

**Not Listed** - One or more components of this product are not listed on inventory.

### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

#### **SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

## 16. Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### **Legend**

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate

LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

#### **Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

# SAFETY DATA SHEET

SL-200  
Revision Number 3

Revision date 25-Jul-2024  
Supersedes date 24-Sep-2020

TWA Ceiling	TWA (time-weighted average) Maximum limit value	STEL SK*	STEL (Short Term Exposure Limit) Skin designation
-------------	---	----------	---

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 25-Jul-2024

Revision Note SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 10. 11.

## Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided “as-is” and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. (“Company”) expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user’s application(s). **NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN.** The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at <https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-management/medical-device-policy/> which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

**End of Safety Data Sheet**