

In accordance with OSHA 29 CFR 1910.1200

XL BRANDS LP-1 Revision Number 3 Revision date 22-Sep-2020 Supersedes date Not applicable

1. Identification

1.1. Product identifier

Product Name XL BRANDS LP-1

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Cement

Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

Bostik Inc.

11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA

Phone: +1(800) 726-7845 (Domestic Toll Free) Phone: +1 (414) 774-2250 (International)

E-mail msds@bostik.com

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (Chemical Transportation Emergency Center)

Chemtrec: 1-800-424-9300 (US), 1-703-527-3887 (Outside U.S.)

Rocky Mountain Poison Center: 1-866-767-5089

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label elements

EMERGENCY OVERVIEW

Danger

Hazard statements

Causes serious eye irritation May cause an allergic skin reaction

May cause cancer

Causes damage to organs through prolonged or repeated exposure

US - EN Page 1 / 11

XL BRANDS LP-1 Revision Number 3 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024



Appearance Powder Physical state Solid Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Wash face, hands and any exposed skin thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Do not breathe dust/fume/gas/mist/vapors/spray

Do not eat, drink or smoke when using this product

Wear protective gloves/eye protection/face protection

Precautionary Statements - Response

Get medical advice/attention if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of water and soap

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

2.3. Other Information

Product dust may be irritating to eyes, skin and respiratory system. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

<u>Mixture</u>

Chemical name	CAS No.	Weight-%
Calcium sulfate hemihydrate	10034-76-1	30 - 60
Quartz	14808-60-7	15 - 40
Cement, portland, chemicals	65997-15-1	1 - <5
Cement, alumina, chemicals	65997-16-2	1 - <5

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

US - EN Page 2 / 11

XL BRANDS LP-1 Revision Number 3 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024

4. First-aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Take a copy of the

Safety Data Sheet when going for medical treatment.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes.

Do not rub affected area. Keep eye wide open while rinsing. Get medical attention

immediately if symptoms occur.

Skin contact Brush off loose particles from skin. Remove material from skin immediately. Wash off

immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and wash before reuse. May cause sensitization by skin contact. In the case of skin irritation or

allergic reactions see a physician.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. If swallowed, call a poison control center or physician immediately.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

Prolonged contact may cause redness and irritation. Causes serious eye damage. Irritating to skin. Inhalation of dust in high concentration may cause irritation of respiratory system. Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease. When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet

cement even when wearing trousers.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

5. Fire-Fighting Measures

5.1. Extinguishing media

surrounding environment.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Product is or contains a sensitizer. May cause sensitization by skin contact. Thermal

decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products Sulfur oxides. Silicon dioxide.

US - EN Page 3 / 11

XL BRANDS LP-1 Revision date 22-Sep-2020
Revision Number 3 Supersedes date 09-Aug-2024

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

6. Accidental Release Measures

6.1. Personal precautions, protective equipment and emergency procedures

ventilation. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Sweep up to prevent slipping hazard.

6.2. Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent dust cloud. Cover powder spill with plastic sheet or tarp to minimize spreading and

keep powder dry.

Methods for cleaning up

Use appropriate personal protective equipment (PPE). Carefully shovel or sweep up spilled

material and place in suitable container. Avoid generating dust. Clean contaminated surface

thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

safety practice. Do not eat, drink or smoke when using this product. Avoid generation of dust. Ensure adequate ventilation. Avoid contact with skin and eyes. Wash thoroughly after

handling. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep the packing dry

and well sealed to prevent contamination and absorption of humidity. Protect from moisture.

7.3 References to other sections

US - EN Page 4 / 11

XL BRANDS LP-1Revision date22-Sep-2020Revision Number3Supersedes date09-Aug-2024

Reference to other sections Section 10: STABILITY AND REACTIVITY

Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium sulfate hemihydrate	TWA: 10 mg/m³ inhalable	-	-
10034-76-1	particulate matter		
Quartz	TWA: 0.025 mg/m³ respirable	TWA: 50 μg/m³	IDLH: 50 mg/m³ respirable dust
14808-60-7	particulate matter	(vacated) TWA: 0.1 mg/m ³	TWA: 0.05 mg/m³ respirable
		respirable dust	dust
		: (250)/(%SiO2 + 5) mppcf	
		TWA respirable fraction	
		: (10)/(%SiO2 + 2) mg/m ³	
		TWA respirable fraction	
Cement, portland, chemicals	TWA: 1 mg/m³ particulate	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
65997-15-1	matter containing no asbestos	TWA: 5 mg/m³ respirable	TWA: 10 mg/m³ total dust
	and <1% crystalline silica,	fraction	TWA: 5 mg/m ³ respirable dust
	respirable particulate matter	(vacated) TWA: 10 mg/m³ total	
		dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
		TWA: 50 mppcf <1% Crystalline	
		silica	
Cement, alumina, chemicals 65997-16-2	10 mg/m³(total; 5 mg/m³(resp)	-	-

Chemical name	Argentina	Brazil	S.D. 594/1999	Colombia
Calcium sulfate hemihydrate 10034-76-1	-	TWA: 10 mg/m ³	-	TWA: 10mg/m ³
Quartz 14808-60-7	TWA: 0.05 mg/m ³	TWA: 0.025 mg/m ³	LPP: 0.08 mg/m ³	TWA: 0.025mg/m ³
Cement, portland, chemicals 65997-15-1	TWA: 10 mg/m ³	TWA: 1 mg/m ³	LPP: 8.8 mg/m ³	TWA: 1mg/m³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Calcium sulfate hemihydrate 10034-76-1	TWA: 10mg/m³	-	10 mg/m³ TWA (inhalable particulate matter, listed under Calcium sulfate)	-
Quartz 14808-60-7	TWA: 0.025mg/m ³	TWA: 0.05mg/m ³	0.025 mg/m³ TWA (respirable particulate matter)	TWA: 0.025 mg/m ³
Cement, portland, chemicals 65997-15-1	TWA: 1mg/m³	TWA: 10mg/m³	1 mg/m³ TWA (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)	TWA: 10 mg/m ³

US - EN Page 5 / 11

XL BRANDS LP-1 Revision date 22-Sep-2020
Revision Number 3 Supersedes date 09-Aug-2024

8.2. Exposure controls

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face protection shield. If splashes are

likely to occur:. Avoid contact with eyes.

Hand protection Wear suitable chemical resistant gloves. The selection of suitable gloves does not only

depend on the material, but also on further marks of quality and various manufacturers.

Skin and body protectionWear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Wear suitable gloves and eye/face protection. Handle in accordance with good industrial

hygiene and safety practice. Do not eat, drink or smoke when using this product. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse. Regular

cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Color Gray

OdorNo information availableOdor thresholdNo information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH .

pH (as aqueous solution) No data available None known

Melting point / freezing pointNot applicable.Initial boiling point and boiling rangeNot applicable.Flash point> 93.3 / >200Evaporation rateNot applicable.

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableNone knownRelative vapor densityNo data availableNone knownRelative densityNo data availableNone known

US - EN Page 6 / 11

XL BRANDS LP-1 Revision date 22-Sep-2020
Revision Number 3 Supersedes date 09-Aug-2024

Water solubility No data available None known No data available Solubility(ies) None known No data available Partition coefficient None known No data available **Autoignition temperature** None known No data available None known **Decomposition temperature** Kinematic viscosity Not applicable .

Dynamic viscosity None known

9.2. Other information

Explosive properties

Oxidizing properties

No information available
No information available
No information available

Solid content (%) 100 Softening point Not relevant

Molecular weight No information available

VOC content

Liquid Density 0.87 g/cm³

Bulk density No information available

10. Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Chemical stability Keep away from Incompatible materials. Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials Strong oxidizing agents. Acids. Aluminum.

10.6. Hazardous decomposition products

Hazardous decomposition products None known based on information supplied

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation May cause irritation of respiratory tract.

Eye contact Causes serious eye irritation. May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons. May cause irritation. Prolonged contact may

No information available

US - EN Page 7 / 11

XL BRANDS LP-1 Revision Number 3 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024

cause redness and irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Prolonged contact may

cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >5000 mg/kg
ATEmix (dermal) >5000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapor) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Quartz	=6450 mg/kg (Rattus)	-	-
14808-60-7			
Cement, portland, chemicals	LD50 >2000 mg/Kg (Rattus)	LD50 >2000 mg/Kg	-
65997-15-1			
Cement, alumina, chemicals	LD50 >2000 mg/Kg Rat	LD50 >2000 mg/Kg Rattus	-
65997-16-2	-		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationClassification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Quartz	A2	Group 1	Known	X
14808-60-7		,		

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

US - EN Page 8 / 11

XL BRANDS LP-1 Revision Number 3 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Target organ effects Respiratory system, Eyes, Skin, Lungs.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Cement, alumina,	EC50 (72h)Algae	LC50 (96h)	-	EC50 (48h) Daphnia
chemicals	(Pseudokirchneriella	(Onchorhyncus mykiss)		magna =6.6mg/L (OECD
65997-16-2	subcapitata) >5.6mg/L	>100 mg/L (OECD 203)		202)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

US - EN Page 9 / 11

XL BRANDS LP-1 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024

Waste from residues/unused

products

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and

disposal methods in compliance with applicable regulations.

Contaminated packaging Dispose of in accordance with federal, state and local regulations.

14. Transport information

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

International Inventories

TSCA	Complies
DSL	Not Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Complies - The components of this product are either listed or exempt from listing on inventory. Active

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

US - EN Page 10 / 11

XL BRANDS LP-1 Revision date 22-Sep-2020 Supersedes date 09-Aug-2024

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value Sk* Skin designation

Prepared By Product Stewardship and Regulatory Affairs.

Revision date 22-Sep-2020

Revision Note SDS sections updated. 1. 2. 3. 4. 5. 6. 7. 8. 11.

Disclaimer

All information contained herein is believed to be accurate as of the date of publication, is provided "as-is" and is subject to change without notice. This is not a warranty, an agreement, or substitute for expert or professional advice. Bostik Inc. ("Company") expressly disclaims and assumes no liability for the use of the products or reliance on this information. It is the sole responsibility of the user to determine the suitability of any products for user's application(s). NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED (INCLUDING SUITABILITY FOR USE IN ANY MEDICAL DEVICE OR MEDICAL APPLICATION), IS MADE CONCERNING THE PRODUCTS OR THE INFORMATION PROVIDED HEREIN. The information provided relates only to the specific products designated herein and may not be valid where such products are used in combination with other materials or in any process. The performance of the product, its shelf life, and application characteristics depends on many variables, and changes in these variables can impact product performance. You are responsible to test the suitability of any product in advance for any intended use or application and before commercialization. Nothing herein shall be construed as a license for the use of any product in a manner that might infringe any patent and it should not be construed as an inducement to infringe any patent. Please carefully review the Safety Data Sheet for the product.

The Company adheres to a strict policy that applies to the use of any of its products in medical device applications. This policy can be found at

https://www.arkema.com/global/en/social-responsibility/innovation-and-sustainable-solutions/responsible-product-mana gement/medical-device-policy/ which is incorporated herein by reference and made a part hereof. Except as expressly authorized, the Company (i) has designated specific medical grade compositions for products used in medical device applications and Company products not so designated are not authorized for use in medical device applications and (ii) strictly prohibits the use of any of its products in medical device applications that are implanted in the body or in contact with bodily fluids or tissues for greater than 30 days. The Company does not design, manufacture and/or directly sell any medical devices. The Company does not co-design, or offer assistance to any purchaser of its products, in their design, manufacture and/or sale of products for medical devices. It is the sole responsibility of the manufacturer of medical devices to determine the suitability of all raw material, products and components, including any medical grade products, in order to ensure that the medical device is safe for end-use and complies with all applicable legal and regulatory requirements and to conduct all necessary tests and inspections.

End of Safety Data Sheet

US - EN Page 11 / 11