

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK WOOD H910 SILENTSTIK

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives

Uses advised against None known

## 1.3. Details of the supplier of the safety data sheet

### **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

NHS: 111

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### Signal word

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **EU Specific Hazard Statements**

EUH210 - Safety data sheet available on request

EUH208 - Contains Trimethoxyvinylsilane & 1-o-Tolylbiguanide. May produce an allergic reaction

### 2.3. Other hazards

United Kingdom - BE Page 1 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Trimethoxyvinylsilane 0.1- <1 %	220-449-8 (014-049-00- 0)	2768-02-7	Acute Tox. 4 (H332) Skin Sens. 1B (H317) Flam. Liq. 3 (H226)	-	-	-	01-2119513215- 52-XXXX
Quartz (fine fraction) 0.1- <1 %	238-878-4	14808-60-7	STOT RE 1 (H372)	-	-	-	[5]
1-o-Tolylbiguanide 0.1 - <0.5 %	202-268-6	93-69-6	Skin Sens. 1 (H317) Eye Dam. 1 (H318) Aquatic Chronic 3 (H412)	-	-	-	01-2119976311- 39

### Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307- 44-XXXX

Full text of H- and EUH-phrases: see section 16

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

### **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU	CAS No.	Oral LD50	Dermal LD50	Inhalation	Inhalation	Inhalation
	Index No)		mg/kg	mg/kg	LC50 - 4 hour -	LC50 - 4 hour -	LC50 - 4 hour -
					dust/mist -	vapour - mg/L	gas - ppm
					mg/L		

United Kingdom - BE Page 2 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
1-o-Tolylbiguanide	202-268-6	93-69-6	-	3171	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

**Inhalation** Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

ophthalmologist.

**Skin contact**Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

**Ingestion** Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Call a doctor or poison control centre immediately.

Small amounts of toxic methanol are released by hydrolysis.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

Effects of Exposure No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing. Treat symptomatically.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

# 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the** Thermal decomposition can lead to release of irritating gases and vapours.

chemical

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

United Kingdom - BE Page 3 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

#### 5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get

in eyes, on skin, or on clothing.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment

Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin,

eyes or clothing.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a dry, cool and well-ventilated

place. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s) Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

### SECTION 8: Exposure controls/personal protection

United Kingdom - BE Page 4 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

## 8.1. Control parameters

**Exposure Limits** 

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m <sup>3</sup>
1317-65-3		TWA: 4 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>
		STEL: 12 mg/m <sup>3</sup>
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m <sup>3</sup>	TWA: 266 mg/m <sup>3</sup>
	*	STEL: 250 ppm
		STEL: 333 mg/m <sup>3</sup>
		Sk*
Quartz (fine fraction)	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
14808-60-7		STEL: 0.3 mg/m <sup>3</sup>

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DN	EL)			
Trimethoxyvinylsilane (2768-02-7)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Systemic health effects Long term	Inhalation	27,6 mg/m³		
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d		

1-o-Tolylbiguanide (93-69-6)	1-o-Tolylbiguanide (93-69-6)				
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	5.88 mg/m³			
worker Short term Systemic health effects	Inhalation	35.26 mg/m³			
worker Long term Local health effects	Inhalation	5.88 mg/m³			
worker Short term Systemic health effects	Inhalation	35.26 mg/m <sup>3</sup>			
worker Short term Systemic health effects	Dermal	55.6 mg/kg bw/d			
worker Short term Local health effects	Dermal	55.6 mg/kg bw/d			

Derived No Effect Level (DNEL)				
Trimethoxyvinylsilane (2768-02-7)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	

United Kingdom - BE Page 5 / 13

### BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022

Revision date 12-Jan-2023 Revision Number 1.04

Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Quartz (fine fraction) (14808	Quartz (fine fraction) (14808-60-7)				
1-o-Tolylbiguanide (93-69-6)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	1.47 mg/m³			
Consumer Short term Systemic health effects	Inhalation	8.82 mg/m <sup>3</sup>			
Consumer Long term Local health effects	Inhalation	1.47 mg/m³			
Consumer Short term Systemic health effects	Inhalation	8.82 mg/m³			
Consumer Short term Systemic health effects	Dermal	27.8 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	1.67 mg/kg bw/d			
Consumer Short term Systemic health effects	Oral	10 mg/kg bw/d			
Consumer Short term Local health effects	Dermal	27.8 mg/kg bw/d			

# Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)			
Trimethoxyvinylsilane (2768-02-7)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.34 mg/l		
Marine water	0.034 mg/l		
Microorganisms in sewage treatment	110 mg/l		

Quartz (fine fraction) (14808-60-7)	
1-o-Tolylbiguanide (93-69-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.15 mg/l
Marine water	0.15 mg/l
Sewage treatment plant	50 mg/l

### 8.2. Exposure controls

**Engineering controls** 

Ensure adequate ventilation, especially in confined areas.

United Kingdom - BE Page 6 / 13

**BOSTIK WOOD H910 SILENTSTIK** 

Revision date 12-Jan-2023 Supercedes date 29-Mar-2022 Revision Number 1.04

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

> Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Wear suitable protective clothing.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

### SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid **Appearance** Paste Colour White Beige Odour Characteristic.

Property Values Remarks • Method

Melting point / freezing point No data available Initial boiling point and boiling No data available

range

Flammability No data available

Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

> 61 °C Flash point CC (closed cup)

**Autoignition temperature** No data available

**Decomposition temperature** 

No data available pН pH (as aqueous solution) No data available Kinematic viscosity No data available

Dynamic viscosity approx 600 - 900 Pa.s Spindle Z3U @ 1 rpm @ 23 °C

Water solubility Reacts with water. Solubility(ies) No data available **Partition coefficient** No data available Vapour pressure No data available Relative density 1.4 - 1.6 No data available **Bulk density** ca. 1.5 g/cm<sup>3</sup> **Liquid Density** Relative vapour density No data available

Particle characteristics

**Particle Size** No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) No information available

**VOC** content No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

United Kingdom - BE Page 7 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

# SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

**Stability** Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Product cures

with moisture.

10.5. Incompatible materials

**Incompatible materials**None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

formed by hydrolysis and released upon curing.

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are

products

# **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Information on likely routes of exposure

### **Product Information**

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact**Based on available data, the classification criteria are not met.

**Ingestion** Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Acute toxicity

## **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) >2000 mg/kg

United Kingdom - BE Page 8 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

ATEmix (dermal) >2000 mg/kg
ATEmix (inhalation-gas) >20000 ppm
ATEmix (inhalation-dust/mist) >5 mg/l
ATEmix (inhalation-vapour) >20 mg/l

### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
1-o-Tolylbiguanide	LD50> 2000 mg/kg (Rattus)	LD50> 2000 mg/kg (Rattus)	-

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (276	88-02-7)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

## Quartz (fine fraction) (14808-60-7)

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

	<del></del>				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant
Acute Eye					
Irritation/Corrosion					

**Respiratory or skin sensitisation** May produce an allergic reaction.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		_

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Thirteenexy viriyionano (2700 02 7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

United Kingdom - BE Page 9 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Aspiration hazard Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

11.2.2. Other information

Other adverse effects No information available.

# **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		
	EU Method C.3					
1-o-Tolylbiguanide	EC50 (72h) = 30	LC50 (96h) =	-	EC50 (48h) = 15		
93-69-6	-46 mg/l	150 mg/l		mg/l (Daphnia		
	((Desmodesmus	(Oncorhynchus		magna)		
	subspicatus)	mykiss)		OECD 202		
	OECD 201					

### 12.2. Persistence and degradability

Persistence and degradability No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric	_		biodegradable
Respirometry Test (TG 301 F)			

# 12.3. Bioaccumulative potential

### **Bioaccumulation**

**Component Information** 

Chemical name	Partition coefficient	

United Kingdom - BE Page 10 / 13

# BOSTIK WOOD H910 SILENTSTIK

Supercedes date 29-Mar-2022

Revision date 12-Jan-2023 Revision Number 1.04

Trimethoxyvinylsilane	1.1
1-o-Tolylbiguanide	0.71

### 12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
1-o-Tolylbiguanide	The substance is not PBT / vPvB

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

#### 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

# **SECTION 14: Transport information**

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated

14.2 UN proper shipping name

14.3 Transport hazard class(es)
 14.4 Packing group
 14.5 Environmental hazards
 Not regulated Not regulated Not applicable

14.6 Special precautions for user

Special Provisions None

<u>IMDG</u>

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
Not regulated

14.5 Marine pollutant NF

14.6 Special precautions for user

Special Provisions None

14.7 Maritime transport in bulk according to IMO instruments

United Kingdom - BE Page 11 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

### Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated
Not regulated
Not regulated
Not regulated
Not applicable

14.6 Special precautions for user

Special Provisions None

### Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**European Union** 

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.
Methyl alcohol	67-56-1
Toluene	108-88-3
Methyl alcohol	67-56-1

### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

# **Persistent Organic Pollutants**

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

#### **National regulations**

### 15.2. Chemical safety assessment

United Kingdom - BE Page 12 / 13

BOSTIK WOOD H910 SILENTSTIK Supercedes date 29-Mar-2022 Revision date 12-Jan-2023 Revision Number 1.04

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour H317 - May cause an allergic skin reaction H318 - Causes serious eye damage

H332 - Harmful if inhaled

H372 - Causes damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value Sk\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 12-Jan-2023

**Indication of changes** 

Revision Note SDS sections updated: 1, 3, 15.
Training Advice No information available
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

United Kingdom - BE Page 13 / 13