



# SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: Not applicable

## 1. Identification

### 1.1. Product identifier

Product Name LOCK P799 I/O RUBBER

### Other means of identification

Other information Not applicable

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesive  
Restrictions on use No information available

### 1.3. Details of the supplier of the safety data sheet

#### Responsible Party

Bostik Inc.  
11320 W. Watertown Plank Road  
Wauwatosa, Wisconsin 53226 USA  
Phone: +1 (800) 843-0844 (Domestic Toll Free)  
Phone: +1 (414) 774-2250 (International)  
Fax: +1 (414) 774-8075

E-mail msds@bostik.com

### 1.4. Emergency telephone number

Emergency Telephone Chemtrec (Transport/Environmental): 1-800-424-9300  
1-703-527-3887 (Outside U.S.)  
Rocky Mountain Poison Center: 1-866-767-5089

## 2. Hazard(s) identification

### 2.1. Classification of the substance or mixture

Respiratory sensitization	Category 1
Skin sensitization	Category 1
Reproductive toxicity	Category 1B

### Hazards not otherwise classified (HNOC)

Not applicable

### 2.2. Label elements

#### EMERGENCY OVERVIEW

#### Danger

#### Hazard statements

May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May damage fertility or the unborn child

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021



**Appearance** Paste

**Physical state** Liquid

**Odor** No information available

## Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Avoid breathing dust/fume/gas/mist/vapors/spray  
In case of inadequate ventilation wear respiratory protection  
Contaminated work clothing should not be allowed out of the workplace

## Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing  
If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

## Precautionary Statements - Storage

Store locked up

## Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

35 % of the mixture consists of ingredient(s) of unknown toxicity

## 2.3. Other Information

No information available.

## 3. Composition/information on ingredients

### 3.1. Substances

Not applicable.

### Mixture

Chemical name	CAS No.	Weight-%
Limestone	1317-65-3	40 - 70
Methylenediphenyl diisocyanate	26447-40-5	0.1 - <1
Dibutyltin dilaurate	77-58-7	0.1 - <1
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	0.1 - <1
Quartz	14808-60-7	0.1 - <1
N-(trichloromethylthio)phthalimide	133-07-3	<0.1

*\*The exact percentage (concentration) of composition has been withheld as a trade secret*

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

## 4. First-aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, (trained personnel should) give oxygen. If symptoms persist, call a physician. If breathing is irregular or stopped, administer artificial respiration. Get immediate medical advice/attention. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. May cause allergic respiratory reaction.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. May cause sensitization by skin contact. In the case of skin irritation or allergic reactions see a physician.
<b>Ingestion</b>	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician or poison control center immediately. May produce an allergic reaction.
<b>Self-protection of the first aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or wheezing. Itching. Rashes. Hives.
-----------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	May cause sensitization in susceptible persons. May cause sensitization by inhalation and skin contact. Treat symptomatically.
---------------------------	--

## 5. Fire-fighting measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b> <b>Large Fire</b>	Dry chemical, CO <sub>2</sub> , alcohol-resistant foam or water spray. CAUTION: Use of water spray when fighting fire may be inefficient.
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Product is or contains a sensitizer. May cause sensitization by inhalation and skin contact.
<b>Hazardous combustion products</b>	Carbon dioxide (CO <sub>2</sub> ). Oxides of sulfur.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	None.

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

## 5.3. Advice for firefighters

**Special protective equipment for fire-fighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## **6. Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

**Other information** Refer to protective measures listed in Sections 7 and 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Keep from any possible contact with water. Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

**Methods for cleaning up** Use personal protective equipment as required. Soak up with inert absorbent material. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **7. Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Use personal protective equipment as required. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Ensure adequate ventilation. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep out of the reach of children. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from water or moist air.

### 7.3 References to other sections

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

Reference to other sections Section 10: STABILITY AND REACTIVITY  
Section 13: DISPOSAL CONSIDERATIONS

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Methylenediphenyl diisocyanate 26447-40-5	-	Ceiling: 0.02 ppm Ceiling: 0.2 mg/m <sup>3</sup>	-
Dibutyltin dilaurate 77-58-7	STEL: 0.2 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> Sn S*	TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) TWA: 0.1 mg/m <sup>3</sup> Sn (vacated) S*	IDLH: 25 mg/m <sup>3</sup> Sn TWA: 0.1 mg/m <sup>3</sup> except Cyhexatin Sn
Quartz 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust
N-(trichloromethylthio)phthalimide 133-07-3	dermal sensitizer TWA: 1 mg/m <sup>3</sup> inhalable particulate matter	-	-

Chemical name	Argentina	Brazil	Chile	Colombia
Limestone 1317-65-3	TWA: 10 mg/m <sup>3</sup>	-	TWA: 7 mg/m <sup>3</sup>	-
Methylenediphenyl diisocyanate 26447-40-5	TWA: 0.005 ppm	-	TWA: 0.004 ppm TWA: 0.045 mg/m <sup>3</sup>	-
Dibutyltin dilaurate 77-58-7	TWA: 0.1 mg/m <sup>3</sup> Skin STEL: 0.2 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>	TWA: 0.09 mg/m <sup>3</sup> Skin	STEL: 0.2mg/m <sup>3</sup> TWA: 0.1mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.025 mg/m <sup>3</sup>	TWA: 0.08 mg/m <sup>3</sup>	TWA: 0.025mg/m <sup>3</sup>
N-(trichloromethylthio)phthalimide 133-07-3	-	TWA: 1 mg/m <sup>3</sup>	-	TWA: 1mg/m <sup>3</sup>

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Dibutyltin dilaurate 77-58-7	TWA: 0.1mg/m <sup>3</sup> STEL: 0.2mg/m <sup>3</sup>	STEL: 0.2mg/m <sup>3</sup> TWA: 0.1mg/m <sup>3</sup>	0.2 mg/m <sup>3</sup> STEL (as Sn) 0.1 mg/m <sup>3</sup> TWA (as Sn)	Skin STEL: 0.2 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup>
Quartz 14808-60-7	TWA: 0.025mg/m <sup>3</sup>	TWA: 0.05mg/m <sup>3</sup>	0.025 mg/m <sup>3</sup> TWA (respirable particulate matter)	TWA: 0.025 mg/m <sup>3</sup>
N-(trichloromethylthio)phthalimide 133-07-3	-	-	1 mg/m <sup>3</sup> TWA (inhalable particulate matter)	-

## 8.2. Exposure controls

### OTHER INFORMATION

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

Chemical name	Argentina	Brazil	Chile	Colombia
Methyl alcohol 67-56-1	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 156 ppm TWA: 200 mg/m <sup>3</sup> Skin	TWA: 175 ppm TWA: 229 mg/m <sup>3</sup> Skin	STEL: 250ppm TWA: 200ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl alcohol 67-56-1	TWA: 200ppm STEL: 250ppm	STEL: 250ppm STEL: 328mg/m <sup>3</sup> TWA: 200ppm TWA: 262mg/m <sup>3</sup>	250 ppm STEL 200 ppm TWA	Skin STEL: 250 ppm TWA: 200 ppm

### Appropriate engineering controls

#### Engineering controls

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles).

#### Hand protection

Wear suitable chemical resistant gloves. The selection of suitable gloves does not only depend on the material, but also on further marks of quality and various manufacturers.

#### Skin and body protection

Wear suitable protective clothing.

#### Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

**General hygiene considerations** Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes or clothing. Wash hands and face before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Regular cleaning of equipment, work area and clothing is recommended.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid	
<b>Appearance</b>	Paste	
<b>Color</b>	Gray	
<b>Odor</b>	No information available	
<b>Odor threshold</b>	No information available	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>pH</b>	No data available	None known
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flash point</b>	> 93.3 °C / 199.9 °F	
<b>Evaporation rate</b>	No data available	None known
<b>Flammability</b>	Not applicable for liquids	
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Vapor pressure</b>	No data available	None known
<b>Relative vapor density</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Water solubility</b>	No data available	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>	No data available	None known
<b>Kinematic viscosity</b>	No data available	None known
<b>Dynamic viscosity</b>	No data available	None known

### 9.2. Other information

<b>Explosive properties</b>	No information available	
<b>Oxidizing properties</b>	No information available	
<b>Solvent content (%)</b>	No information available	
<b>Solid content (%)</b>	100.0	
<b>Softening Point</b>	No information available	
<b>Molecular weight</b>	No information available	
<b>VOC Content (%)</b>		No information available
<b>Density</b>	1.72 g/cm <sup>3</sup>	
<b>Bulk density</b>	No information available	

## 10. Stability and reactivity

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

## 10.1. Reactivity

Reactivity No information available.

## 10.2. Chemical stability

Chemical stability Reacts with water.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization Hazardous polymerization may occur.

## 10.4. Conditions to avoid

Conditions to avoid Extremes of temperature and direct sunlight. Exposure to air or moisture over prolonged periods. Exposure to water.

## 10.5. Incompatible materials

Incompatible materials Water. Strong bases. Strong oxidizing agents. Finely powdered metals.

## 10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide Carbon dioxide (CO<sub>2</sub>) Nitrogen oxides (NO<sub>x</sub>) Hydrogen cyanide Thermal decomposition can lead to release of irritating and toxic gases and vapors

## **11. Toxicological information**

### 11.1. Information on toxicological effects

#### Product Information

Inhalation	May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause sensitization in susceptible persons.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation".

### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives.

### Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document



# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone 1317-65-3	>5000 mg/kg (Rattus)	-	-
Methylenediphenyl diisocyanate 26447-40-5	>10000 mg/kg (Rattus)	> 10000 mg/kg (Oryctolagus cuniculus)	=490 mg/m <sup>3</sup> (Rattus) 4 h
Dibutyltin dilaurate 77-58-7	=2071 mg/kg (Rattus) OECD 401	> 2000 mg/kg (Rattus)	-
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg OECD 402	>640 ppm (Rattus) 1 h
Quartz 14808-60-7	>20000 mg/kg	-	-
N-(trichloromethylthio)phthalimide 133-07-3	=2636 mg/kg (Rattus)	> 22600 mg/kg (Oryctolagus cuniculus) > 5000 mg/kg (Rattus)	>0.48 g/m <sup>3</sup> (Rattus) 4 h > 5 g/m <sup>3</sup> (Rattus) 2 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitization** May cause sensitization by inhalation. May cause sensitization by skin contact.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** As Quartz (14808-60-7) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Methylenediphenyl diisocyanate 26447-40-5	-	Group 3	-	-
Quartz 14808-60-7	A2	Group 1	Known	X
N-(trichloromethylthio)phthalimide 133-07-3	A3	-	-	-

### Legend

#### ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

#### IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

#### NTP (National Toxicology Program)

Known - Known Carcinogen

#### OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Methylenediphenyl diisocyanate (26447-40-5)

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

Method	Species	Results
	in vivo	Limited evidence of a carcinogenic effect

Quartz (14808-60-7)

Method	Species	Results
IARC (International Agency for Research on Cancer)	Human evidence	Carcinogenic

**Reproductive toxicity** Contains a known or suspected reproductive toxin. Classification based on data available for ingredients. May cause harm to breast-fed children.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Target organ effects** Eyes, Skin, Reproductive system, Respiratory system.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Other adverse effects** No information available.

**Interactive effects** No information available.

## 12. Ecological information

### 12.1. Toxicity

**Ecotoxicity** Not considered to be harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae ( <i>Desmodesmus subspicatus</i> )	CL50 (96h) >10000mg/L ( <i>Oncorhynchus mykiss</i> )	-	CE50 (48h) >1000 mg/L Daphnia Magna
Methylenediphenyl diisocyanate 26447-40-5	EC50: =3230mg/L (96h, <i>Skeletonema costatum</i> )	-	-	EC50: >1000mg/L (24h, Daphnia magna)
Dibutyltin dilaurate 77-58-7	EC50 1 (72h) mg/L ( <i>desmodesmus subspicatus</i> )	LC50: =2mg/L (48h, <i>Oryzias latipes</i> )	-	0,463 (48h) mg/L (daphnia magma)

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### Component Information

Chemical name	Partition coefficient
---------------	-----------------------

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

Limestone 1317-65-3	0.9
Methylenediphenyl diisocyanate 26447-40-5	4.5
Dibutyltin dilaurate 77-58-7	4.44
Benzenesulfonyl isocyanate, 4-methyl- 4083-64-1	0.6

## 12.4. Mobility in soil

**Mobility** No information available.

### Other adverse effects

**Other adverse effects** No information available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.

**Contaminated packaging** Dispose of in accordance with federal, state and local regulations.

## 14. Transport information

**DOT** Not regulated

**IATA** Not regulated

**IMDG** Not regulated

## 15. Regulatory information

### International Inventories

TSCA	Listed
DSL	Listed

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

**Listed** - The components of this product are either listed or exempt from listing on inventory.

**Not Listed** - One or more components of this product are not listed on inventory.

### US Federal Regulations

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

# SAFETY DATA SHEET

LOCK P799 I/O RUBBER  
Revision Number 1

Revision date 30-Jul-2021  
Supersedes Date: 30-Jul-2021

Chemical name	CAS No.	SARA 313 - Threshold Values %
Methylenediphenyl diisocyanate	26447-40-5	1.0
N-(trichloromethylthio)phthalimide	133-07-3	1.0

## SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

## Europe

### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

### SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## 16. Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Prepared By Product Safety & Regulatory Affairs.

Revision date 30-Jul-2021

Revision note SDS sections updated. 4. 5. 8. 9. 10. 12.

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet