

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

Revision date 18-Jul-2024 Revision Number 1.05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Product Name	BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID	
Pure substance/mixture	Mixture	
1.2. Relevant identified uses o	the substance or mixture and uses advised against	
Recommended use	Cement Plasters and floor equalisers	
Uses advised against	None known	
1.3. Details of the supplier of t	ne safety data sheet	
<u>Company Name</u> Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36		
E-mail address	SDS.box-EU@bostik.com	
1.4. Emergency telephone nun	<u>iber</u>	
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111	
SECTION 2: Hazards ide	ntification	
2.1. Classification of the subst	ance or mixture	
GB CLP (SI 2020/1567 as amer	ded)	
Skin sensitisation	Category 1 - (H317)	
2.2. Label elements		

Contains 1,2-benzisothiazol-3(2H)-one [BIT]; 2-methyl-2H-isothiazol-3-one [MIT]; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]



Signal word Warning

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID

Supercedes date 05-Jul-2023

Revision date 18-Jul-2024 Revision Number 1.05

Hazard statements

H317 - May cause an allergic skin reaction.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P261 - Avoid breathing vapours

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]	, , , , , , , , , , , , , , , , , , ,		,	
1,2-benzisothiazol-3(2H) -one [BIT] 0.01 < 0.036 %	220-120-9 (613-088-00- 6)	2634-33-5	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400)	Skin Sens. 1A :: C>=0.036%	1	1	01-2120761540- 60-XXXX
			Aquatic Chronic 1 (H410)				
2-methyl-2H-isothiazol-3- one [MIT] 0.01 < 0.036 %	220-239-6 (613-326-00- 9)	2682-20-4	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%	10	1	01-2120764690- 50-xxxx
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) [C(M)IT/MIT] <0.0015 %	611-341-5	55965-84-9	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	100	100	-

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
1,2-benzisothiazol-3(2 H)-one [BIT]	220-120-9 (613-088-00-6)	2634-33-5	450	-	=0.21 mg/L (ATE dust/mist)	0.21+	0.21 +
2-methyl-2H-isothiazol- 3-one [MIT]	220-239-6 (613-326-00-9)	2682-20-4	285	243	0.11	-	-
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT]		55965-84-9	66	141	0.17	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.	
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.	
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.	
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.	
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.	
4.2. Most important symptoms and	d effects, both acute and delayed	
Symptoms	Itching. Rashes. Hives.	
Effects of Exposure	No information available.	
4.3. Indication of any immediate medical attention and special treatment needed		
Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.	

SECTION 5: Firefighting measures

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID

Supercedes date 05-Jul-2023

Revision date 18-Jul-2024 Revision Number 1.05

5.1. Extinguishing media		
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.	
Unsuitable extinguishing media	No information available.	
5.2. Special hazards arising from the	ne substance or mixture	
Specific hazards arising from the chemical	Product is or contains a sensitiser. May cause sensitisation by skin contact.	
5.3. Advice for firefighters		
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	
SECTION 6: Accidental relea	ise measures	
6.1. Personal precautions, protecti	ve equipment and emergency procedures	
Personal precautions	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.	
For emergency responders	Use personal protection recommended in Section 8.	
6.2. Environmental precautions		
Environmental precautions	See Section 12 for additional Ecological Information.	
6.3. Methods and material for conta	ainment and cleaning up	
Methods for containment	Prevent further leakage or spillage if safe to do so.	
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.	
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.	
6.4. Reference to other sections		
Reference to other sections	See section 8 for more information. See section 13 for more information.	
SECTION 7: Handling and st	orage	
7.1. Precautions for safe handling	_	
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.	
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.	
7.2. Conditions for safe storage, in	cluding any incompatibilities	
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.	
Recommended storage temperature	Keep at temperatures between 5 and 35 °C.	

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID

Supercedes date 05-Jul-2023

7.3. Specific end use(s)

Specific use(s) Plasters and floor equalisers. Cement.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL	1		
1,2-benzisothiazol-3(2H)-one [l	BIT] (2634-33-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m³	
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	4.03 µg/l
Marine water	0.403 µg/l
Sewage treatment plant	1.03 mg/l
Freshwater sediment	49.9 µg/l
Marine sediment	4.99 µg/l
Soil	3 mg/kg dry weight

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

Revision date 18-Jul-2024 Revision Number 1.05

Personal protective equipment	
Eye/face protection	Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Skin and body protection Respiratory protection	Wear protective gloves and protective clothing. Avoid contact with skin, eyes or clothing. During spraying wear suitable respiratory equipment.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	-
Appearance	Liquid	
Colour	White	
Odour	Characteristic.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	No data available	None known
range		
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.01	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	1	No data available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023 Revision date 18-Jul-2024 Revision Number 1.05

SECTION 10: Stability and re	activity				
10.1. Reactivity					
Reactivity	No information available.				
10.2. Chemical stability					
Stability	Stable under normal conditions.				
Explosion data					
Sensitivity to mechanical impact	None.				
Sensitivity to static discharge	None.				
10.3. Possibility of hazardous reac	tions				
Possibility of hazardous reactions	None under normal processing.				
10.4. Conditions to avoid					
Conditions to avoid	Do not freeze.				
10.5. Incompatible materials					
Incompatible materials	None known based on information supplied.				
10.6. Hazardous decomposition pr	10.6. Hazardous decomposition products				
Hazardous decomposition products	Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons.				
SECTION 11: Toxicological i	nformation				
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008				
Information on likely routes of exp	osure				
Product Information					
Inhalation	Based on available data, the classification criteria are not met.				
Eye contact	Based on available data, the classification criteria are not met.				
Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).				
Ingestion	Based on available data, the classification criteria are not met.				
Symptoms related to the physical,	chemical and toxicological characteristics				
Symptoms	Itching. Rashes. Hives.				
Acute toxicity					
Numerical measures of toxicity					
The following values are calculated ATEmix (oral)	d based on chapter 3.1 of the GHS document >2000 mg/kg				
United Kingdom - BE	Page 7 / 13				

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
1,2-benzisothiazol-3(2H)-one [BIT]	=450 mg/kg (ATE)	LD50 > 2000 mg/kg (Rattus)	-
2-methyl-2H-isothiazol-3-one [MIT]	LD50 =285 mg/Kg (Rattus)	LD50 >242 mg/Kg (Rattus)	=0.11 mg/L (Rattus) 4 h
reaction mass of 5-chloro-2-methyl-2H-isothiazo I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	66 mg/kg (Rat)	LD50 = 8141 mg/kg (Rat) OECD 402	= 0.33 mg/L (Rat) 4h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.		
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.		
Respiratory or skin sensitisation	May cause an allergic skin reaction.		
Germ cell mutagenicity	Based on available data, the classification criteria are not met.		
Carcinogenicity	Based on available data, the classification criteria are not met.		
Reproductive toxicity	Based on available data, the classification criteria are not met.		
STOT - single exposure	Based on available data, the classification criteria are not met.		
STOT - repeated exposure	Based on available data, the classification criteria are not met.		
Aspiration hazard	Based on available data, the classification criteria are not met.		
11.2. Information on other hazard	<u>S</u>		
11.2.1. Endocrine disrupting prop	erties		
Endocrine disrupting properties	No information available.		
11.2.2. Other information			
Other adverse effects	No information available.		

SECTION 12: Ecological information

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5		LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
2-methyl-2H-isothiazol- 3-one [MIT] 2682-20-4	EC50 (72hr) 0.157 mg/l (Pseudokirchner iella subcapitata) (OECD 201)	· ·	-	EC50 (48hr) 1.68 mg/l (Daphnia) (OECD 202)	10	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner		-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability

No information available.

2-methyl-2H-isothiazol-3-one [MIT] (2682-20-4)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.28-2.1 days
Anaerobic Transformation in Aquatic			
Sediment Systems			
OECD Test No. 309: Aerobic		biodegradation Half-life	Readily biodegradable 4.1
Mineralization in Surface Water -		-	days
Simulation Biodegradation Test			

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Test	-	-	
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
2-methyl-2H-isothiazol-3-one [MIT]	-0.32
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

threshold of declaration.

Chemical name	PBT and vPvB assessment
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one [MIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	The substance is not PBT / vPvB
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note:	Keep from freezing.
Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions	Not regulated - Not regulated Not regulated Not applicable None
IMDG 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Marine pollutant 14.6 Special precautions for user Special Provisions 14.7 Maritime transport in bulk according to IMO instruments Transport in bulk according to	Not regulated Not regulated Not regulated Not regulated NP None Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group	Not regulated Not regulated Not regulated Not regulated

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023

14.5 Environmental hazardsNot applicable14.6 Special precautions for user
Special ProvisionsNone

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID

Supercedes date 05-Jul-2023

Revision date 18-Jul-2024 Revision Number 1.05

Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H311 - Toxic in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'.

In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

		_	-		-1	
L	_	е	C	en	α	
	-	-	J		-	
Т	-	۱ ۸	1	^		

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by
	Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data No information available	
Prepared By	Product Safety & Regulatory Affairs
Revision date	18-Jul-2024
Indication of changes	
Revision note	Not applicable.
Training Advice	No information available

No information available No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

BOSTIK SCREEDMASTER SL C500 ULTIMATE LIQUID Supercedes date 05-Jul-2023 Revision date 18-Jul-2024 Revision Number 1.05

End of Safety Data Sheet