



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER - PART A**  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER - PART A  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Primers, Sealers, and Undercoaters  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

<b>Skin corrosion/irritation</b>	Category 2 - (H315)
<b>Serious eye damage/eye irritation</b>	Category 2 - (H319)
<b>Skin sensitisation</b>	Category 1 - (H317)
<b>Chronic aquatic toxicity</b>	Category 2 - (H411)

### 2.2. Label elements

Contains bis-[4-(2,3-epoxypropoxy)phenyl]propane, Oxirane, mono[(C12-14-alkyloxy)methyl] derivs., Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02



## Signal word

Warning

## Hazard statements

H315 - Causes skin irritation.  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation.  
H411 - Toxic to aquatic life with long lasting effects.

## Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P261 - Avoid breathing mist/vapours/spray  
P273 - Avoid release to the environment  
P280 - Wear protective gloves and eye/face protection  
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P391 - Collect spillage  
P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Toxic to aquatic life.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
bis-[4-(2,3-epoxipropoxy)phenyl]propane	(603-073-00-2) 216-823-5	1675-54-3	40 - <80	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411) (EUH205)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26-xxxx
Formaldehyde,	500-006-8	9003-36-5	>25 - <40	Skin Irrit. 2	-	01-2119454392-

# SAFETY DATA SHEET

**BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A**  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol				(H315) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)		40-XXXX
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	(603-103-00-4) 271-846-8	68609-97-2	10 - <20	Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	-	01-2119485289-22-XXXX
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379-17-XXXX

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

**Full text of H- and EUH-phrases: see section 16**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. Get medical attention immediately if symptoms occur.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
<b>Skin contact</b>	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Ingestion</b>	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
<b>Self-protection of the first aider</b>	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Note to doctors** May cause sensitisation in susceptible persons. Treat symptomatically.

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supercedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable Extinguishing Media** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** No information available.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Product is or contains a sensitiser. May cause sensitisation by skin contact.

**Hazardous combustion products** Carbon oxides. Hydrogen chloride.

### 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

**Other information** Refer to protective measures listed in Sections 7 and 8.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

**General hygiene considerations** Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

product. Avoid contact with skin, eyes or clothing.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

## 7.3. Specific end use(s)

**Specific use(s)**  
Primers, Sealers, and Undercoaters.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	12.25 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	12.25 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	8.33 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.33 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

Derived No Effect Level (DNEL)			
bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

# SAFETY DATA SHEET

**BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A**  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

Consumer Long term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	3.571 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.75 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	0.75 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>bis-[4-(2,3-epoxipropoxy)phenyl]propane (1675-54-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.006 mg/l
Marine water	0.001 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	0.996 mg/kg dry weight
Marine sediment	0.1 mg/kg dry weight
Soil	0.196 mg/kg dry weight

<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas. Ensure that enough fresh air is supplied to dilute and remove dusts, fumes or vapours. Between 5 and 15 air changes per hour are recommended, with a through draught.

### Personal protective equipment

#### Eye/face protection

Avoid contact with eyes. Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature.

#### Skin and body protection

Wear appropriate personal protective clothing to prevent skin contact.

**Environmental exposure controls** No information available.

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Clear
Odour	No information available.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	Not applicable for liquids	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 150 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	None known.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.0	
Bulk Density	No data available	
Density	No data available	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### 9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

### 10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supercedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

Sensitivity to mechanical impact None.  
Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

### 10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.

#### Acute toxicity

##### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

##### Component Information



# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A

Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
bis-[4-(2,3-epoxipropoxy)phenyl]propane	=11300 µL/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	>2 g/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) (OECD 402)	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	=17100 mg/kg (Rattus)	LD50 >4000 mg/Kg Rabbit	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Skin corrosion/irritation**

Classification based on data available for ingredients. Causes skin irritation.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		24 hours	Product score 5.75 irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

### **Serious eye damage/eye irritation**

Classification based on data available for ingredients. Causes serious eye irritation.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Product score 2 irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

### **Respiratory or skin sensitisation**

May cause an allergic skin reaction.

Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. (68609-97-2)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	sensitising

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

Sensitisation: Local Lymph Node Assay			
---------------------------------------	--	--	--

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

### 11.2.2. Other information

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

**Ecotoxicity** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
bis-[4-(2,3-epoxipropoxy)phenyl]propane 1675-54-3	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutus) EPA-660/3-75-009	1.5 mg/l 96Hr (Oncorhynchus mykiss) (OECD 203)	-	LD50 (48h) =2.7 mg/L (Daphnia magna) (OECD 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

### 12.3. Bioaccumulative potential

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

## Bioaccumulation

### Component Information

Chemical name	Partition coefficient
bis-[4-(2,3-epoxipropoxy)phenyl]propane	3.78
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	3.6
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	3.77

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
bis-[4-(2,3-epoxipropoxy)phenyl]propane	The substance is not PBT / vPvB
Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol	The substance is not PBT / vPvB
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply

### 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Do not reuse empty containers.

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

### Land transport (ADR/RID)

**14.1 UN number or ID number**

UN3082

**14.2 UN proper shipping name**

Environmentally hazardous substances, liquid, n.o.s  
(bis-[4-(2,3-epoxipropoxy)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

# SAFETY DATA SHEET

BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

<b>14.3 Transport hazard class(es)</b>	9
<b>Labels</b>	9
<b>14.4 Packing group</b>	III
<b>Description</b>	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, (-)
<b>14.5 Environmental hazards</b>	Yes
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	274, 335, 601, 375
<b>Classification code</b>	M6
<b>Tunnel restriction code</b>	(-)
<b>Limited quantity (LQ)</b>	5 L
<b>ADR Hazard Id (Kemmler Number)</b>	90

## IMDG

<b>14.1 UN number or ID number</b>	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
<b>14.3 Transport hazard class(es)</b>	9
<b>14.4 Packing group</b>	III
<b>Description</b>	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III, Marine Pollutant
<b>14.5 Marine pollutant</b>	P
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	274, 335, 969
<b>Limited Quantity (LQ)</b>	5 L
<b>EmS-No.</b>	F-A, S-F
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
<b>Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	Not applicable

## Air transport (ICAO-TI / IATA-DGR)

<b>14.1 UN number or ID number</b>	UN3082
<b>14.2 UN proper shipping name</b>	Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)
<b>14.3 Transport hazard class(es)</b>	9
<b>14.4 Packing group</b>	III
<b>Description</b>	UN3082, Environmentally hazardous substances, liquid, n.o.s (bis-[4-(2,3-epoxipropoxi)phenyl]propane, Formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), 9, III
<b>14.5 Environmental hazards</b>	Yes
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	A97, A158, A197
<b>Limited quantity (LQ)</b>	30 kg G
<b>ERG Code</b>	9L

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

# SAFETY DATA SHEET

**BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A**  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## **Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Dangerous substance category per Seveso Directive (2012/18/EU)**

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

EUH205 - Contains epoxy constituents. May produce an allergic reaction

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

**Note V:** If the substance is to be placed on the market as fibres (with diameter  $< 3 \mu\text{m}$ , length  $> 5 \mu\text{m}$  and aspect ratio  $\geq 3:1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

#### **Notes relating to the classification and labelling of mixtures**

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

# SAFETY DATA SHEET

**BOSTIK SCREEDMASTER GRIP E946 EPOXY PRIMER -  
PART A**  
Supersedes Date: 05-Jul-2023

Revision date 05-Jul-2023

Revision Number 1.02

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 05-Jul-2023

## Indication of changes

**Revision note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

**This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**