



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY

Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

**GB CLP (SI 2020/1567 as amended)**

<b>Hazardous to the aquatic environment - chronic</b>	Category 3 - (H412)
---	---------------------

### 2.2. Label elements

Signal word  
None

Hazard statements  
H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements  
EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)  
P273 - Avoid release to the environment  
P501 - Dispose of contents/ container to an approved waste disposal plant

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

## PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
2-Pentandione, O,O',O''-(methylsilylyldyne)trioxime 37859-55-5	1 - <2.5	01-2120004323-76-XXXX	484-460-1	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	-	-	-
Titanium dioxide 13463-67-7	0.1 - <0.5	01-2119489379-17-XXXX	236-675-5	[C]	-	-	-	-
3-aminopropyltriethoxysilane 919-30-2	0.1 - <0.5	01-2119480479-24-XXXX	213-048-4 (612-108-00-0)	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	-
Octamethylcyclotetrasiloxane [D4] 556-67-2	0.05 - <0.1	01-2119529238-36-XXXX	209-136-7 (014-018-00-1)	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	-
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	0.0025 - <0.01	No data available	247-761-7 (613-112-00-5)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%	100	100	-

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - PBT / vPvB substance

**Full text of H- and EUH-phrases: see section 16**

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## **Acute Toxicity Estimate**

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE<sub>mix</sub>) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
2-Pentandione, O,O',O''-(methylsilylidylidene)trioxime	484-460-1	37859-55-5	1234	-	-	-	-
Titanium dioxide	236-675-5	13463-67-7	-	-	-	-	-
3-aminopropyltriethoxy silane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125 <sup>+</sup>	311 <sup>+</sup>	0.27 <sup>+</sup>	0.27 <sup>+</sup>	0.27 <sup>+</sup>

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## **SECTION 4: First aid measures**

### **4.1. Description of first aid measures**

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

### **4.2. Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	None known.
<b>Effects of Exposure</b>	No information available.

### **4.3. Indication of any immediate medical attention and special treatment needed**

<b>Note to doctors</b>	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
------------------------	---

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

<b>Suitable Extinguishing Media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam.
-------------------------------------	---

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supercedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

Unsuitable extinguishing media Full water jet.

## 5.2. Special hazards arising from the substance or mixture

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Silicon oxides. Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

## 5.3. Advice for firefighters

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste. Collect water from cleaning tools and reuse it or dispose it in local sewage systems. Do not spill water or dispose cleaning water into the environment.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture. Keep from freezing.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C. Do not freeze.

### 7.3. Specific end use(s)

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes date** 08-Aug-2024

**Revision date** 11-Mar-2026  
**Revision Number** 1.02

**Specific use(s)**

Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Exposure Limits**

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> ; inhalable dust TWA: 4 mg/m <sup>3</sup> ; respirable dust STEL: 30 mg/m <sup>3</sup> ; inhalable dust STEL: 12 mg/m <sup>3</sup> ; respirable dust
Silica, amorphous, fumed, crystalline-free 112945-52-5	-	TWA: 6 mg/m <sup>3</sup> ; inhalable dust TWA: 2.4 mg/m <sup>3</sup> ; respirable dust STEL: 18 mg/m <sup>3</sup> ; inhalable dust STEL: 7.2 mg/m <sup>3</sup> ; respirable dust
Ethanol 64-17-5	-	TWA: 1000 ppm; TWA: 1920 mg/m <sup>3</sup> ; STEL: 3000 ppm; STEL: 5760 mg/m <sup>3</sup> ;
Methyl alcohol 67-56-1	TWA: 200 ppm; TWA: 260 mg/m <sup>3</sup> ; pSk	TWA: 200 ppm; TWA: 266 mg/m <sup>3</sup> ; STEL: 250 ppm; STEL: 333 mg/m <sup>3</sup> ; pSk
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m <sup>3</sup> ; inhalable dust TWA: 2.4 mg/m <sup>3</sup> ; respirable dust STEL: 18 mg/m <sup>3</sup> ; inhalable dust STEL: 7.2 mg/m <sup>3</sup> ; respirable dust
Magnesium carbonate 546-93-0	-	TWA: 10 mg/m <sup>3</sup> ; inhalable dust TWA: 4 mg/m <sup>3</sup> ; respirable dust STEL: 30 mg/m <sup>3</sup> ; inhalable dust STEL: 12 mg/m <sup>3</sup> ; respirable dust
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> ; total inhalable TWA: 4 mg/m <sup>3</sup> ; respirable STEL: 30 mg/m <sup>3</sup> ; total inhalable STEL: 12 mg/m <sup>3</sup> ; respirable

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

**Derived No Effect Level (DNEL)**

**Titanium dioxide (13463-67-7)**

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes date** 08-Aug-2024

**Revision date** 11-Mar-2026  
**Revision Number** 1.02

<b>3-aminopropyltriethoxysilane (919-30-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>3-aminopropyltriethoxysilane (919-30-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
<b>Hand protection</b>	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid
<b>Appearance</b>	Paste
<b>Colour</b>	See section 1 for more information
<b>Odour</b>	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

**Upper flammability or explosive limits** No data available  
**Lower flammability or explosive limits** No data available  
**Flash point** No data available  
**Autoignition temperature** No data available  
**Decomposition temperature**  
**pH** No data available  
**pH (as aqueous solution)** No data available  
**Kinematic viscosity** > 21 mm<sup>2</sup>/s  
**Dynamic viscosity** No data available

None known  
None known  
None known  
Not applicable. Insoluble in water.  
None known

**Water solubility** Insoluble in water.  
Product cures with moisture

**Solubility(ies)** No data available  
**Partition coefficient** No data available  
**Vapour pressure** No data available  
**Relative density** No data available  
**Bulk density** No data available  
**Density** 1.26 g/cm<sup>3</sup>  
**Relative vapour density** No data available  
**Particle characteristics**  
**Particle Size** No information available  
**Particle Size** No information available  
**Distribution**

None known  
None known  
None known  
None known

None known

## 9.2. Other information

**Solid content (%)** No information available  
**VOC content** No data available

### **9.2.1. Information with regards to physical hazard classes**

Not applicable

### **9.2.2. Other safety characteristics**

No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## 10.5. Incompatible materials

**Incompatible materials** Strong oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.  
**Eye contact** Based on available data, the classification criteria are not met.  
**Skin contact** May cause sensitisation in susceptible persons.  
**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

**ATEmix (oral)** 53,544.80 mg/kg  
**ATEmix (dermal)** 86,825.90 mg/kg  
**ATEmix (inhalation-gas)** >20000 ppm  
**ATEmix (inhalation-dust/mist)** >5 mg/L  
**ATEmix (inhalation-vapour)** >20 mg/L

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Pentandione, O,O',O''-(methylsilylidyne)trioxi me	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
Titanium dioxide	> 5000 mg/kg ( Rattus ) OECD 425	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m <sup>3</sup> (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Corneal			Eye Damage

**Respiratory or skin sensitisation** No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Species	Exposure route	Results
GPMT - Guinea pig maximisation test	Guinea pig	Dermal	Sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes date** 08-Aug-2024

**Revision date** 11-Mar-2026  
**Revision Number** 1.02

**Reproductive toxicity** Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio	-	EC50: =25.2mg/L (24h, Daphnia magna)		10

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
**Supersedes date** 08-Aug-2024

**Revision date** 11-Mar-2026  
**Revision Number** 1.02

		erio)				
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)			
Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	1.25
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	Not PBT/vPvB
Titanium dioxide	Not PBT/vPvB
3-aminopropyltriethoxysilane	Not PBT/vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	Not PBT/vPvB

## 12.6. Endocrine disrupting properties Endocrine disrupting properties

**Endocrine disruption for the environment** Based on available data, the classification criteria are not met.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

## 12.7. Other adverse effects Other adverse effects

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

**Other adverse effects** No information available.  
**PMT or vPvM properties** Based on available data, the classification criteria are not met.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

**Contaminated packaging** Handle contaminated packages in the same way as the product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous substances

**Other information** Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

### IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None  
14.7 Maritime transport in bulk according to IMO instruments  
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supercedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## **Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)**

### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

### **Biocidal Products Regulation (EU) No 528/2012 (BPR)**

This product contains a biocidal product for the preservation of the dry film. Contains OIT.

### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

### **Ozone-depleting substances (ODS) regulation (EC) 2024/590**

Not applicable

### **Persistent Organic Pollutants**

Not applicable

### **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

Not applicable

### **Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)**

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE GREY**  
Supersedes date 08-Aug-2024

Revision date 11-Mar-2026  
Revision Number 1.02

## Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract  
H226 - Flammable liquid and vapour  
H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H361f - Suspected of damaging fertility  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

### **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 11-Mar-2026

### **Indication of changes**

**Revision Note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**