



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant

**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

### 2.2. Label elements

#### Signal word

None

#### Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

#### EU Specific Hazard Statements

EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children  
P273 - Avoid release to the environment

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

## PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 1 - <2.5 %	484-460-1	37859-55-5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	-	-	01-2120004323-76-XXXX
Titanium dioxide 0.1 - <1 %	236-675-5 (022-006-00-2)	13463-67-7	[C]	-	-	-	01-2119489379-17-XXXX
3-aminopropyltriethoxysilane 0.1 - <0.5 %	213-048-4 (612-108-00-0)	919-30-2	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	01-2119480479-24-XXXX
Octamethylcyclotetrasiloxane [D4] 0.05 - <0.1 %	209-136-7 (014-018-00-1)	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	01-2119529238-36-XXXX
Toluene 0.01 < 0.036 %	203-625-9 (601-021-00-3)	108-88-3	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	-	-	01-2119471310-51-XXXX
Methyl alcohol 0.0025 - <0.01 %	200-659-6 (603-001-00-X)	67-56-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX
2-octyl-2H-isothiazol-3-one [OIT] 0.0025 - <0.01 %	247-761-7 (613-112-00-5)	26530-20-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%	100	100	-

**Air contaminants formed when using the substance or mixture as intended**

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentanone oxime 623-40-5	484-470-6	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	-	-	-	01-2119980079-27-XXXX
Ethanol 64-17-5	200-578-6 (603-002-00-5)	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610-43-XXXX
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

**Full text of H- and EUH-phrases: see section 16**

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - PBT / vPvB substance

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	484-460-1	37859-55-5	1234	-	-	-	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
3-aminopropyltriethoxy silane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
Toluene	203-625-9 (601-021-00-3)	108-88-3	5580	12000	30	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	-	3	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125 +	311 +	0.27 +	0.27 +	0.27 +

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	None known.
<b>Effects of Exposure</b>	No information available.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.
------------------------	---

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable Extinguishing Media</b>	Water spray, carbon dioxide (CO <sub>2</sub> ), dry chemical, alcohol-resistant foam.
<b>Unsuitable extinguishing media</b>	Full water jet.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of irritating gases and vapours.
<b>Hazardous combustion products</b>	Carbon oxides. Carbon dioxide (CO <sub>2</sub> ). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

### 5.3. Advice for firefighters

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### 6.2. Environmental precautions

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

### 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture. Keep from freezing.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C. Do not freeze.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains substances which in their raw state are powder form,

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup>
Ethanol 64-17-5	-	TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup> STEL: 3000 ppm STEL: 5760 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m <sup>3</sup> *	TWA: 50 ppm TWA: 191 mg/m <sup>3</sup> STEL: 100 ppm STEL: 384 mg/m <sup>3</sup> Sk*
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*

Chemical name	European Union	Ireland	United Kingdom
Toluene 108-88-3	-	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	-
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Long term	Dermal	8.3 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

Systemic health effects worker Short term	Dermal	8.3 mg/kg bw/d	
Systemic health effects			

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m <sup>3</sup>	

<b>Toluene (108-88-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	384 mg/kg bw/d	
Long term Systemic health effects Local health effects worker	Inhalation	192 mg/m <sup>3</sup>	
Short term Systemic health effects worker	Inhalation	384 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	192 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	384 mg/m <sup>3</sup>	

<b>Methyl alcohol (67-56-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m <sup>3</sup>	
Short term Local health effects worker	Inhalation	260 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m <sup>3</sup>	
Long term Local health effects worker	Inhalation	260 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Oral	700 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

Long term Systemic health effects			
--------------------------------------	--	--	--

<b>3-aminopropyltriethoxysilane (919-30-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

<b>Octamethylcyclotetrasiloxane [D4] (556-67-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

<b>Toluene (108-88-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	56.5 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	226 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	56 mg/m <sup>3</sup>	
Consumer Local health effects Short term	Inhalation	226 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	226 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	8.13 mg/kg bw/d	

<b>Methyl alcohol (67-56-1)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	



# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

Consumer Long term Local health effects	Inhalation	50 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	50 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	50 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

Toluene (108-88-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.68 mg/l
Marine water	0.68 mg/l
Sewage treatment plant	13.61 mg/l
Freshwater sediment	16.39 mg/kg dry weight
Marine sediment	16.39 mg/kg dry weight
Soil	2.89 mg/kg dry weight

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

**Skin and body protection** gloves. Gloves must conform to standard EN 374  
**Respiratory protection** None under normal use conditions.  
In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.  
**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid	
<b>Appearance</b>	Paste	
<b>Colour</b>	White	
<b>Odour</b>	Characteristic.	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	
<b>Initial boiling point and boiling range</b>	No data available	
<b>Flammability</b>	No data available	
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	No data available	
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>		None known
<b>pH</b>	.	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	
<b>Kinematic viscosity</b>	> 21 mm <sup>2</sup> /s	@ 40 °C
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	Insoluble in water. Product cures with moisture	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Vapour pressure</b>	No data available	
<b>Relative density</b>	No data available	
<b>Bulk density</b>	No data available	
<b>Density</b>	1.26	
<b>Relative vapour density</b>	No data available	
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

**Solid content (%)** ca 100  
**VOC content** No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE  
Supercedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

**Reactivity** Product cures with moisture.

## 10.2. Chemical stability

**Stability** Stable under normal conditions.

## **Explosion data**

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

**Incompatible materials** Strong oxidising agents.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### **Product Information**

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Acute toxicity

#### **Numerical measures of toxicity**

The following values are calculated based on chapter 3.1 of the GHS document

**ATEmix (oral)** 53,572.10 mg/kg

**ATEmix (dermal)** 86,870.20 mg/kg

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

**ATEmix (inhalation-gas)** >20000 ppm  
**ATEmix (inhalation-dust/mist)** >5 mg/l  
**ATEmix (inhalation-vapour)** >20 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxi me	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m <sup>3</sup> (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

### Respiratory or skin sensitisation

May produce an allergic reaction. No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information  
Toluene (108-88-3)

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hpvt and xprt genes	Mouse	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Titanium dioxide	Carc. 2

**Reproductive toxicity** Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2
Toluene	Repr. 2

Toluene (108-88-3)

Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapour			NOAEL: 1.131 mg/l

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	1.25
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
Toluene	2.73
Methyl alcohol	-0.77
2-octyl-2H-isothiazol-3-one [OIT]	2.92

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
Toluene	The substance is not PBT / vPvB
Methyl alcohol	The substance is not PBT / vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Waste from residues/unused products** Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE  
Supersedes date 16-Mar-2023

Revision date 29-Aug-2024  
Revision Number 2.02

Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

**Note:** Keep from freezing.

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**



# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

## **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

## **Named dangerous substances per Seveso Directive (2012/18/EU)**

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

## **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

## **Persistent Organic Pollutants**

Not applicable

## **REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors**

Not applicable

## **National regulations**

### **15.2. Chemical safety assessment**

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### **Key or legend to abbreviations and acronyms used in the safety data sheet**

#### **Full text of H-Statements referred to under section 3**

H225 - Highly flammable liquid and vapour  
H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H304 - May be fatal if swallowed and enters airways  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H331 - Toxic if inhaled  
H336 - May cause drowsiness or dizziness  
H361d - Suspected of damaging the unborn child  
H370 - Causes damage to organs  
H373 - May cause damage to organs through prolonged or repeated exposure  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects  
H412 - Harmful to aquatic life with long lasting effects

#### **Notes relating to the identification, classification and labelling of substances**

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S31 SANITARY SILICONE WHITE**  
**Supersedes date** 16-Mar-2023

**Revision date** 29-Aug-2024  
**Revision Number** 2.02

**Note V:** If the substance is to be placed on the market as fibres (with diameter  $< 3 \mu\text{m}$ , length  $> 5 \mu\text{m}$  and aspect ratio  $\geq 3:1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

## **Notes relating to the classification and labelling of mixtures**

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

## **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 29-Aug-2024

## **Indication of changes**

**Revision note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**