

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

#### BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

Revision date 29-Aug-2024 Revision Number 1.02

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR
Pure substance/mixture	Mixture
1.2. Relevant identified uses of the	e substance or mixture and uses advised against
Recommended use	Sealant
Uses advised against	None known
1.3. Details of the supplier of the s	afety data sheet
<u>Company Name</u> Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36	
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone number	·
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111
SECTION 2: Hazards identifi	cation
2.1. Classification of the substance	e or mixture
GB CLP (SI 2020/1567 as amended	)
Chronic aquatic toxicity	Category 3 - (H412)
2.2. Label elements	
Signal word None	
Hazard statements	

H412 - Harmful to aquatic life with long lasting effects.

### **EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

# Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P273 - Avoid release to the environment

# BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

P501 - Dispose of contents/ container to an approved waste disposal plant

### 2.3. Other hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

### PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	registration number
Triacetoxy(propyl)silane 1 - <3 %	241-816-9	17865-07-5	Skin Corr. 1B (H314) (EUH071)	-	-	-	01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate 1 - <2.5 %	224-221-9	4253-34-3	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	01-2119962266- 32-XXXX
Octamethylcyclotetrasilo xane [D4] 0.05 - <0.1 %	209-136-7 (014-018-00- 1)	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	01-2119529238- 36-XXXX
Acetic acid 0.036 - < 0.05 %	200-580-7 (607-002-00- 6)	64-19-7	Skin Corr. 1A (H314) Flam. Liq. 3 (H226)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 25%<=C<90% Skin Irrit. 2 :: 10%<=C<25%	-	-	01-2119475328- 30-XXXX
4,5-dichloro-2-octyl-2H-is othiazol-3-one [DCOIT] 0.01 < 0.036 %	264-843-8 (613-335-00- 8)	64359-81-5	Acute Tox. 4 (H302) Acute Tox. 2 (H330) Skin Corr. 1 (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	100	100	-

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Acetic acid 64-19-7	200-580-7 (607-002-00-6)	Skin Corr. 1A (H314) Flam. Liq. 3 (H226)	Eye Irrit. 2 :: 10%<=C<25% Skin Corr. 1A :: C>=90% Skin Corr. 1B :: 25%<=C<90% Skin Irrit. 2 :: 10%<=C<25%	-	-	01-2119475328- 30-XXXX

# BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

# Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes [G] - PBT / vPvB substance

### Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg		Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1600	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
Acetic acid	200-580-7 (607-002-00-6)	64-19-7	-	1060	-	-	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT]	264-843-8 (613-335-00-8)	64359-81-5	567 +	-	0.16+	0.16+	0.16+

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### Notes

See section 16 for more information

Chemical name	Notes
Acetic acid - 64-19-7	В

SECTION 4: First aid mea	isures
--------------------------	--------

## 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
1.2 Most important symptoms and	affects both acute and delayed

#### 4.2. Most important symptoms and effects, both acute and delayed

## Symptoms

None known.

BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

Effects of Exposure	No information available.				
4.3. Indication of any immediate me	edical attention and special treatment needed				
Note to doctors	Treat symptomatically.				
SECTION 5: Firefighting measures					
5.1. Extinguishing media					
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.				
Unsuitable extinguishing media	Full water jet.				
5.2. Special hazards arising from the second s	ne substance or mixture				
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.				
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.				
5.3. Advice for firefighters					
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.				
SECTION 6: Accidental release measures					
6.1. Personal precautions, protecti	ve equipment and emergency procedures				
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.				
For emergency responders	Use personal protection recommended in Section 8.				
6.2. Environmental precautions					
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.				
6.3. Methods and material for conta	ainment and cleaning up				
Methods for containment	Do not scatter spilled material with high pressure water streams.				
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.				
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.				
6.4. Reference to other sections					
Reference to other sections	See section 8 for more information. See section 13 for more information.				
SECTION 7: Handling and st	orage				
7.1. Precautions for safe handling	_				
Advice on safe handling	Ensure adequate ventilation.				
General hygiene considerations	Take off all contaminated clothing and wash it before reuse.				

### BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

Revision date 29-Aug-2024 Revision Number 1.02

# 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.
7.3. Specific end use(s)	
<b>Specific use(s)</b> Sealant.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Exposure Limits

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Silica, amorphous	-	TWA: 6 mg/m <sup>3</sup>
7631-86-9		TWA: 2.4 mg/m <sup>3</sup>
		STEL: 18 mg/m <sup>3</sup>
		STEL: 7.2 mg/m <sup>3</sup>
Acetic acid	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>
	STEL: 50 mg/m <sup>3</sup>	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m <sup>3</sup>

### Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term	Inhalation	73 mg/m³		
Systemic health effects				

Derived No Effect Level (DNEL)				
Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>		
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d		

# Predicted No Effect Concentration (PNEC)

# BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

Revision date 29-Aug-2024 Revision Number 1.02

Predicted No Effect Concentration (PNEC)	
Octamethylcyclotetrasiloxane [D4] (556-67-2	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

## 8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene <sup>™</sup> . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.
Environmental exposure controls	Do not allow uncontrolled discharge of product into the environment.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical	and chemical properties	
Physical state	Solid	
Appearance	Paste	
Colour	Clear, colourless	
Odour	Acetic acid.	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	
Initial boiling point and boiling	No data available	
range		
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	> 100 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	@ 40°C
Dynamic viscosity	No data available	
Water solubility	Insoluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	1.02	
Bulk density	No data available	
Density	1.02 g/cm <sup>3</sup>	

## BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

Relative vapour density	No data available		None known
Particle characteristics Particle Size Particle Size Distribution	No information available No information available		
9.2. Other information Solid content (%) VOC content	No information available	44.9 g/L	
9.2.1. Information with regards to Not applicable	physical hazard classes		
0.2.2. Other cafety characteristics			

9.2.2. Other safety characteristics No information available

# SECTION 10: Stability and reactivity

10.1. Reactivity	
Reactivity	Product cures with moisture.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical	None.
impact Sensitivity to static discharge	None.
10.3. Possibility of hazardous react	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.
10.5. Incompatible materials	
Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition pro	oducts
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
SECTION 11: Toxicological i	nformation
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008
Information on likely routes of exp	osure
Product Information	
Inhalation	Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

# **BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR**

Supercedes date 12-Jun-2023

Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical,	chemical and toxicological characteristics
Symptoms	No information available.
Acute toxicity	
Numerical measures of toxicity	
The following values are calculated ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-gas) ATEmix (inhalation-dust/mist)	

### **Component Information**

ATEmix (inhalation-vapour)

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus) OECD 401	-	-	
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h	
Acetic acid	=3310 mg/kg (Rattus)	= 1060 mg/kg (Oryctolagus cuniculus)	=11.4 mg/L (Rattus) 4 h	
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT]	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h	

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

>20 mg/l

Skin corrosion/irritation

The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

Serious eye damage/eye irritation By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye		6 days	Product score <=1
					Non-irritant

# Respiratory or skin sensitisation

May produce an allergic reaction. No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses

# BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

Sensitisation			were observed	
Octamethylcyclotetrasiloxane [D4] (5 4,5-dichloro-2-octyl-2H-isothiazol-3-o	one [DCOIT] (64359-81-5)			
Method	Species	Exposure route	Results	
OECD 406	Guinea pig	Dermal	Sensitising	
Germ cell mutagenicity	Based on available data, the	classification criteria are not m	net.	
Carcinogenicity	Based on available data, the	classification criteria are not m	net.	
Reproductive toxicity	Based on available data, the	classification criteria are not m	net.	
The table below indicates ingredients		onsidered as relevant which are	e listed as reproductive toxins.	
Chemical na		European Union		
Octamethylcyclotetras	siloxane [D4]	Repr.	2	
STOT - single exposure		classification criteria are not m		
STOT - repeated exposure	Based on available data, the classification criteria are not met.			
Aspiration hazard	Based on available data, the classification criteria are not met.			
11.2. Information on other hazard	<u>IS</u>			
11.2.1. Endocrine disrupting prop	perties			
Endocrine disrupting properties	No information available.			
11.2.2. Other information				
Other adverse effects	No information available.			

# **SECTION 12: Ecological information**

# 12.1. Toxicity

## Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Triacetoxy(propyl)silane	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
17865-07-5	approx. 24	108.89 mg/L		89.59 mg/L		
	mg/I(Pseudokirc					
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h) >500	-	EC50 (48h) >500		
triacetate	>500 mg/l	mg/l		mg/l (Daphnia		
4253-34-3	(Pseudokirchner	(Brachydanio		magna)		
	ella subcapitata)	rerio)				
Octamethylcyclotetrasil	-	LC50:	-	EC50:		10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		

### BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

Revision date 29-Aug-2024 Revision Number 1.02

556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				
		rerio)				
Acetic acid	_	/	EC50 = 8.8 mg/l	EC50 48 h >300		
64-19-7		>1000 mg/L	15 min	mg/L (Daphnia		
04 19 7			-			
		(Danio rerio)	EC50 = 8.8 mg/L	magna Static)		
			25 min			
			EC50 = 8.8 mg/L			
			5 min			
4,5-dichloro-2-octyl-2H-	EC50 (72h)	LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus			(OECD 202)		
	subspicatus)(OE			, , ,		
	CD 201)	-,				

### 12.2. Persistence and degradability

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Exposure time	Value	Results
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days
Anaerobic Transformation in Aquatic			
Sediment Systems			

### 12.3. Bioaccumulative potential

### Bioaccumulation

#### **Component Information**

Chemical name	Partition coefficient
Triacetoxy(propyl)silane	1.23
Silanetriol, methyl-, triacetate	-2.4
Octamethylcyclotetrasiloxane [D4]	6.49
Acetic acid	-0.17
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4

#### 12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Triacetoxy(propyl)silane	The substance is not PBT / vPvB
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
Acetic acid	The substance is not PBT / vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB

#### 12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

# BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

# 12.7. Other adverse effects

No information available.

# SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

# **SECTION 14: Transport information**

Land transport (ADR/RID) 14.1 UN number or ID number 14.2 UN proper shipping name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions	Not regulated - Not regulated Not applicable None	
IMDG		
14.1 UN number or ID number	Not regulated	
14.2 UN proper shipping name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special precautions for user		
Special Provisions	None	
14.7 Maritime transport in bulk		
according to IMO instruments		NI 6 11
I ransport in bulk according to	Annex II of MARPOL and the IBC Code	Not applicable
Air transport (ICAO-TI / IATA-DGR)		
14.1 UN number or ID number	Not regulated	
14.2 UN proper shipping name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Environmental hazards	Not applicable	

None

**Special Provisions** 

14.6 Special precautions for user

BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR Supercedes date 12-Jun-2023

# Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### **Export Notification requirements**

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

#### Dangerous substance category per Seveso Directive (2012/18/EU)

O1 - Substances or mixtures with hazard statement EUH014

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

# REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

#### National regulations

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

Key or legend to abbreviations and acronyms used in the safety data sheet

BOSTIK PRO SEALANT S30 SANITARY SILICONE CLEAR

Supercedes date 12-Jun-2023

Revision date 29-Aug-2024 Revision Number 1.02

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

### Notes relating to the identification, classification and labelling of substances

Note B - Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Legena	
TŴĂ	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by
	Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sour No information available Prepared By Revision date Indication of changes	ces for data Product Safety & Regulatory Affairs 29-Aug-2024
Revision note	SDS sections updated.
Training Advice	No information available
Further information	No information available

#### This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**