



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK PRO SEALANT PU91 CONSTRUCTION POLYURETHANE BLACK
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request

EUH208 - Contains isocyanates & Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

2.3. Other hazards

Causes mild skin irritation.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Urea, N,N''-(methylenedi-4, 1-phenylene)bis[N'-butyl-77703-56-1	1 - <5	01-0000016345-72-xxxx	416-600-4	Aquatic Chronic 4 (H413)	-	-	-	-
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics RR-100255-7	1 - <2.5	01-2119453414-43-xxxx	920-107-4	Asp. Tox. 1 (H304) (EUH066)	-	-	-	-
N,N-dibenzyliden polyoxypropylene diamine (polymer) 136855-71-5	1 - <2.5	[7]	-	Skin Irrit. 2 (H315)	-	-	-	-
Aromatic Polyisocyanate 53317-61-6	0.1 - <0.5	[7]	500-120-8	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)	-	-	-	-
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate --	0.1 - <0.3	01-2119511174-52-xxxx	945-730-9	Aquatic Acute 1 (H400) Aquatic Chronic 3 (H412)	-	-	-	-
Calcium oxide 1305-78-8	0.1 - <0.3	01-2119475325-36-XXXX	215-138-9	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	-	-	-
Triphenyl phosphate 115-86-6	0.1 - <0.3	01-2119457432-41-XXXX	204-112-2	Aquatic Acute 1 (H400) Aquatic Chronic 2	-	1	1	-

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

				(H411)				
Ethyl acetate 141-78-6	0.1 - <0.3	01-2119475103 -46-XXXX	205-500-4 (607-022-00-5)	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)	-	-	-	-
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	0.05 - <0.1	01-2119491304 -40-XXXX	915-687-0	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	-	1	1	-
Isophorone diisocyanate 4098-71-9	0.05 - <0.1	01-2119490408 -31-XXXX	223-861-6 (615-008-00-5)	Acute Tox. 1 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) STOT SE 3 (H335) Aquatic Chronic 2 (H411)	Resp. Sens. 1 :: C>=0.5% Skin Sens. 1 :: C>=0.5%	-	-	2

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Note 2 - The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Urea, N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-	416-600-4	77703-56-1	-	-	-	-	-
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	920-107-4	RR-100255-7	-	-	-	-	-
Aromatic Polyisocyanate	500-120-8	53317-61-6	-	-	-	-	-
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl	945-730-9	--	-	-	-	-	-

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
4-methylphenyl phenyl phosphate and triphenyl phosphate							
Calcium oxide	215-138-9	1305-78-8	-	-	-	-	-
Triphenyl phosphate	204-112-2	115-86-6	-	-	-	-	-
Ethyl acetate	205-500-4 (607-022-00-5)	141-78-6	-	-	-	14.4131	-
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	-	-	-	-	-
Isophorone diisocyanate	223-861-6 (615-008-00-5)	4098-71-9	-	-	0.031	-	-

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No.	SVHC candidates
Triphenyl phosphate	115-86-6	x

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Prolonged contact may cause redness and irritation.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	No information available.
------------------------	---------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Phenols. Hydrogen cyanide. Isocyanates. Hydrochloric Acid. Sulphur oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product. This product contains substances which in their raw state are powder form, however in this product they are in a non-respirable form. Inhalation of powder/dust particles is unlikely to occur from exposure to this product.

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Polyvinyl chloride 9002-86-2	-	TWA: 10 mg/m ³ ; inhalable dust TWA: 4 mg/m ³ ; respirable dust STEL: 30 mg/m ³ ; inhalable dust STEL: 12 mg/m ³ ; respirable dust
Carbon black 1333-86-4	-	TWA: 3.5 mg/m ³ ; STEL: 7 mg/m ³ ;
Calcium oxide 1305-78-8	TWA: 1 mg/m ³ ; respirable fraction STEL: 4 mg/m ³ ; respirable fraction	TWA: 1 mg/m ³ ; respirable fraction TWA: 2 mg/m ³ ; STEL: 4 mg/m ³ ; respirable fraction STEL: 6 mg/m ³ ;
Triphenyl phosphate 115-86-6	-	TWA: 3 mg/m ³ ; STEL: 6 mg/m ³ ;
Ethyl acetate 141-78-6	TWA: 734 mg/m ³ ; TWA: 200 ppm; STEL: 1468 mg/m ³ ; STEL: 400 ppm;	TWA: 734 mg/m ³ ; TWA: 200 ppm; STEL: 1468 mg/m ³ ; STEL: 400 ppm;
Isophorone diisocyanate 4098-71-9	TWA: 10 µg NCO / m ³ (2.9 ppb) STEL: 20 µg NCO / m ³ (5.8 ppb) Sk* +	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ ; poS

Chemical name	European Union	Ireland	United Kingdom
Isophorone diisocyanate 4098-71-9	-	1 µmol/mol Creatinine (urine - urinary Diamine post task)	1 mmol isocyanate-derived diamine/mol creatinine - urine () - end of the period of exposure

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Urea, N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl- (77703-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	49.37 mg/m ³	
Long term Systemic health effects	Dermal	140 mg/kg bw/d	

Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

worker Long term Systemic health effects	Inhalation	3.5 mg/m ³	
worker Short term Systemic health effects	Inhalation	28 mg/m ³	
worker Long term Systemic health effects	Dermal	0.5 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	4 mg/kg bw/d	

Ethyl acetate (141-78-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m ³	
worker Long term Local health effects	Inhalation	734 mg/m ³	
worker Short term Local health effects	Inhalation	1468 mg/m ³	
worker Long term Systemic health effects	Inhalation	734 mg/m ³	

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1.27 mg/m ³	
worker Systemic health effects Long term	Dermal	1.8 mg/kg	

Isophorone diisocyanate (4098-71-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Local health effects	Inhalation	0.0453 mg/m ³	
worker Long term Local health effects	Inhalation	0.0453 mg/m ³	

Derived No Effect Level (DNEL)			
Urea, N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl- (77703-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term	Inhalation	7.4 mg/m ³	

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Systemic health effects			
Long term	Dermal	50 mg/kg bw/d	
Systemic health effects			
Long term	Oral	5 mg/kg bw/d	
Systemic health effects			

Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.875 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	7 mg/m ³	
Consumer Long term Systemic health effects	Dermal	0.25 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	2 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.25 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	2 mg/kg bw/d	

Ethyl acetate (141-78-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m ³	
Consumer Long term Local health effects	Inhalation	367 mg/m ³	
Consumer Short term Local health effects	Inhalation	734 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	367 mg/m ³	

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.31 mg/m ³	

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Consumer Long term Systemic health effects	Dermal	0.9 mg/kg	
Consumer Long term Systemic health effects	Oral	0.18 mg/kg	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Urea, N,N'-(methylenedi-4,1-phenylene)bis[N'-butyl- (77703-56-1)]	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	76.36 mg/kg dry weight
Marine sediment	7.636 mg/kg dry weight
Soil	15.15 mg/kg dry weight

Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Freshwater - intermittent	0.005 mg/l
Marine water - intermittent	0.001 mg/l
Freshwater sediment	3.43 mg/kg dry weight
Marine sediment	0.343 mg/kg dry weight
Microorganisms in sewage treatment	No hazard identified
Soil	0.68 mg/kg dry weight

Calcium oxide (1305-78-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater - intermittent	0.37 mg/l
Marine water Marine water - intermittent	0.24 mg/l
Sewage treatment plant	2.27 mg/l
Soil	817.4 mg/kg dry weight

Ethyl acetate (141-78-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.24 mg/l
Marine water	0.024 mg/l
Freshwater sediment	1.15 mg/kg
Marine sediment	0.115 mg/kg
Soil	0.148 mg/kg
Microorganisms in sewage treatment	650 mg/l

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0022 mg/l
Marine water	0.00022 mg/l
Freshwater - intermittent	0.009 mg/l
Freshwater sediment	1.05 mg/kg
Marine sediment	0.11 mg/kg
Soil	0.21 mg/kg
Sewage treatment plant	1 mg/l

Isophorone diisocyanate (4098-71-9)

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	60 µg/l
Marine water	6 µg/l
Freshwater - intermittent	40 µg/l
Freshwater sediment	218.9 mg/kg dry weight
Marine sediment	21.89 mg/kg dry weight
Soil	44.01 mg/kg dry weight
Microorganisms in sewage treatment	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

Skin and body protection Suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour Black
Odour Characteristic.

Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	Not applicable
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 61 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	No data available	Not applicable.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	approx 465000 mm²/s	
Dynamic viscosity	approx 600000 mPa s	
Water solubility	Reacts with water.	Reacts with water
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.29	
Relative vapour density	No data available	None known
Particle characteristics		

SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Particle Size No information available
Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.
Eye contact Based on available data, the classification criteria are not met.
Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Ingestion

Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

Prolonged contact may cause redness and irritation.

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	9,166.40 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Urea, N,N'-(methylenedi-4,1-phenylene)bis[N'-butyl-	>2000 mg/Kg (Rattus) (OECD 401)	>2000 mg/Kg (Rattus) (OECD 402)	-
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	LD50 >5000 mg/Kg (Rattus) (OECD 401)	LD50 >5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	LC50 >5000 mg/m ³ (OECD 403)
Aromatic Polyisocyanate	LD50 >2000 mg/Kg (Rattus)	-	LC50 >3.820 mg/L (Rattus) 4h dust/mist
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	>5000 mg/Kg (Rattus)	>2000 mg/Kg (Rattus) (OECD 402)	-
Calcium oxide	>2000 mg/kg (Rattus)	LD50 > 2500 mg/kg (Oryctolagus cuniculus)	> 6.04604 mg/L (Rat) 4 h
Triphenyl phosphate	=3500 mg/kg (Rattus)	> 10000 mg/kg (Oryctolagus cuniculus)	>200000 mg/m ³ (Rattus) 1 h
Ethyl acetate	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-pi peridyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperi dyl sebacate	LD50 = 3230 mg/Kg (Rattus) (OECD 401)	LD50 >3170 mg/Kg (Rattus) (OECD 402)	-
Isophorone diisocyanate	=4814 mg/kg (Rattus)	LD50 > 2000 mg/kg	=0.135 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Ethyl acetate (141-78-6)		
Method	Species	Results
OECD Test No. 474: Mammalian Erythrocyte Micronucleus Test	in vivo Hamster	Negative
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro Salmonella typhimurium	Negative
OECD Test No. 473: In vitro Mammalian Chromosome Aberration Test	in vitro Hamster Ovary	Negative

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties This mixture contains a substance that has endocrine disrupting properties with respect to humans.

Chemical name	Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4)
Triphenyl phosphate	health effects

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Ecotoxicity

Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Urea, N,N''-(methylenedi-4,1-phenylene)bis[N'-butyl-77703-56-1	-	LC50 (96h) >120 mg/L Danio rerio (OECD 203)	-	EC50 (48h) >100 mg/L Daphnia magna (OECD 202)		
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics RR-100255-7	ErL50 (72h) > 10000 mg/l (Skeletonema costatum -ISO 10253)	LL50 (96h) > 1028 mg/l (Scophthalmus maximus -OECD 203)	-	LL50 (48h) > 3193 mg/l (Acartia tonsa - ISO 14669)		
Calcium oxide 1305-78-8	EC50 (Pseudokirchneriella subcapitata (green algae)): 106,02 mg/l End point: Growth rate Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes	LC50 96 h = 50.6 mg/L (Oncorhynchus mykiss)	EC50 (Bacteria): 229,2 mg/l Exposure time: 3 h Test Type: static test Method: OECD Test Guideline 209 GLP: yes	EC50 (48h) = 49.1 mg/l(Daphnia magna) OECD 202		
Triphenyl phosphate 115-86-6	EC50: 0.6 - 4mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 0.28 - 0.5mg/L (96h, Oncorhynchus mykiss) LC50: 0.47 - 1.04mg/L (96h, Lepomis macrochirus) LC50: 0.53 - 0.8mg/L (96h, Pimephales promelas) LC50: 0.81 - 0.94mg/L (96h, Pimephales promelas) LC50: =1.2mg/L (96h, Oryzias latipes)	-	EC50: 0.86 - 1.2mg/L (48h, Daphnia magna)	1	1
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl)	EC50 (72h): 1.68 mg/l (Desmodesmus	LC50 (96h): 0.9 mg/L (Brachydanio	EC20 (3h)>= 100 mg/l OECD 209	-	1	1

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

sebacate and Methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate 1065336-91-5	subspicatus) OECD 201	erio) OECD 203				
Isophorone diisocyanate 4098-71-9	EC50: =118.7mg/L (72h, Desmodemus subspicatus)	LC50: =1.8mg/L (48h, Leuciscus idus)	-	EC50: =83.7mg/L (24h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Urea, N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl- (77703-56-1)			
Method	Exposure time	Value	Results
OECD Guideline 310	28 days	0.4%	Not readily biodegradable
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	11%	Not readily biodegradable

Aromatic Polyisocyanate (53317-61-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)		biodegradation	34 % Not readily biodegradable

Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate (--)			
Method	Exposure time	Value	Results
OECD Test No. 301C: Ready Biodegradability: Modified MITI Test (I) (TG 301 C)	28 days	75%	Readily biodegradable

Isophorone diisocyanate (4098-71-9)			
Method	Exposure time	Value	Results
EU C.4-D	28 days	0%	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Urea, N,N"-(methylenedi-4,1-phenylene)bis[N'-butyl-	5.5
Reaction mass of 3-methylphenyl diphenyl phosphate, 4-methylphenyl diphenyl phosphate, bis(3-methylphenyl) phenyl phosphate, 3-methylphenyl 4-methylphenyl phenyl phosphate and triphenyl phosphate	4.5
Triphenyl phosphate	4.63
Ethyl acetate	0.73
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	2.77

12.4. Mobility in soil

Mobility in soil No information available.

SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not PBT/vPvB
Calcium oxide	Not PBT/vPvB
Triphenyl phosphate	Not PBT/vPvB
Ethyl acetate	Not PBT/vPvB
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	Not PBT/vPvB
Isophorone diisocyanate	Not PBT/vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties This mixture contains a substance that has endocrine disrupting properties with respect to non-target organisms.

Chemical name	Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4)
Triphenyl phosphate	Environmental effects

12.7. Other adverse effects

Other adverse effects No information available.
PMT or vPvM properties The product contains substance(s) classified as PMT or vPvM.

Chemical name	PMT and vPvM assessment
Isophorone diisocyanate	PMT & vPvM

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated

SAFETY DATA SHEET

BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions None
14.7 Maritime transport in bulk
according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 UN proper shipping name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special precautions for user
Special Provisions None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59) $\geq 0.1\%$

Chemical name	CAS No.
Triphenyl phosphate	115-86-6

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 2024/590

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) which are regulated pursuant to the EU regulations on drug precursors [(EC) No. 111/2005 and (EC) No. 273/2004] above levels that can be easily used or extracted by readily applicable or economically viable means.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH066 - Repeated exposure may cause skin dryness or cracking
H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H361f - Suspected of damaging fertility
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects
H413 - May cause long lasting harmful effects to aquatic life

Notes relating to the classification and labelling of mixtures

Note 2 - The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

SAFETY DATA SHEET

**BOSTIK PRO SEALANT PU91 CONSTRUCTION
POLYURETHANE BLACK**
Supersedes date 08-Jul-2024

Revision date 14-Jul-2025

Revision Number 3.03

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 14-Jul-2025

Indication of changes

Revision Note SDS sections updated, 2.
Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE For further information, please contact: <https://www.safeusediisocyanates.eu/>

Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet