



# SAFETY DATA SHEET

This safety data sheet complies with the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE**  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME SILICONE ANTHRACITE  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant  
**Uses advised against** None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

<b>Chronic aquatic toxicity</b>	Category 3 - (H412)
---------------------------------	---------------------

### 2.2. Label elements

#### Signal word

None

#### Hazard statements

H412 - Harmful to aquatic life with long lasting effects.

#### EU Specific Hazard Statements

EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

#### Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand  
P102 - Keep out of reach of children

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

## 2.3. Other hazards

Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

## PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Silica, amorphous	231-545-4	7631-86-9	5 - <10	[B]	-	01-2119379499-16-XXXX
2-Pentandione, O,O',O''-(methylsilylidyn e)trioxime	484-460-1	37859-55-5	1 - <2.5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	01-2120004323-76-XXXX
3-aminopropyltriethoxysilane	(612-108-00-0) 213-048-4	919-30-2	0.1 - <0.5	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	01-2119480479-24-XXXX
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	0.1 - <0.3	[C]	-	01-2119489379-17-XXXX
Octamethylcyclotetrasiloxane [D4]	(014-018-00-1) 209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	01-2119529238-36-XXXX
2-octyl-2H-isothiazol-3-one [OIT]	(613-112-00-5) 247-761-7	26530-20-1	0.0025 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1	Skin Sens. 1A :: C>=0.0015%	-

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

				(H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		
--	--	--	--	---	--	--

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

[G] - This substance meets the PBT criteria of REACH, annex XIII

This substance meets the vPvB criteria of REACH, annex XIII

**Full text of H- and EUH-phrases: see section 16**

**Air contaminants formed when using the substance or mixture as intended**

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentanone oxime 623-40-5	484-470-6	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) Aquatic Chronic 3 (H412)	-	-	-	01-2119980079-27-XXXX
Ethanol 64-17-5	(603-002-00-5) 200-578-6	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610-43-XXXX
Methyl alcohol 67-56-1	(603-001-00-X) 200-659-6	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supercedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

## **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

## **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Treat symptomatically.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO<sub>2</sub>). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

**For emergency responders** Use personal protection recommended in Section 8.

### **6.2. Environmental precautions**

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

### **6.3. Methods and material for containment and cleaning up**

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m <sup>3</sup>	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup> STEL: 0.3 mg/m <sup>3</sup>
Ethanol 64-17-5	-	TWA: 1000 ppm TWA: 1920 mg/m <sup>3</sup> STEL: 3000 ppm STEL: 5760 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

		STEL: 333 mg/m <sup>3</sup> Sk*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Short term Systemic health effects	Inhalation	59 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m <sup>3</sup>	

Derived No Effect Level (DNEL)			
3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m <sup>3</sup>	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term	Dermal	5 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

Systemic health effects			
-------------------------	--	--	--

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

<b>Skin and body protection</b>	None under normal use conditions.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Solid	
<b>Appearance</b>	Paste	
<b>Colour</b>	Dark Grey	
<b>Odour</b>	Characteristic.	
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>
<b>Melting point / freezing point</b>	No data available	None known
<b>Initial boiling point and boiling range</b>	No data available	None known
<b>Flammability</b>	No data available	None known
<b>Flammability Limit in Air</b>		None known
<b>Upper flammability or explosive limits</b>	No data available	
<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	No data available	None known
<b>Autoignition temperature</b>	No data available	None known
<b>Decomposition temperature</b>		None known
<b>pH</b>	No data available	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	None known
<b>Kinematic viscosity</b>	> 21 mm <sup>2</sup> /s	None known
<b>Dynamic viscosity</b>	No data available	
<b>Water solubility</b>	No data available. Product cures with moisture	None known
<b>Solubility(ies)</b>	No data available	None known
<b>Partition coefficient</b>	No data available	None known
<b>Vapour pressure</b>	No data available	None known
<b>Relative density</b>	No data available	None known
<b>Bulk Density</b>	No data available	
<b>Density</b>	1.26	
<b>Relative vapour density</b>	No data available	None known
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

### 9.2. Other information

<b>Solid content (%)</b>	No information available
<b>VOC content</b>	No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity



# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

Reactivity Product cures with moisture.

## 10.2. Chemical stability

Stability Stable under normal conditions.

## Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge None.

## 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

## 10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

## 10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

## **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

Inhalation Based on available data, the classification criteria are not met.  
Eye contact Based on available data, the classification criteria are not met.  
Skin contact May cause sensitisation in susceptible persons.  
Ingestion Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 53,854.30 mg/kg  
ATEmix (dermal) 87,327.70 mg/kg

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

**ATEmix (inhalation-gas)** >20000 ppm  
**ATEmix (inhalation-dust/mist)** >5 mg/l  
**ATEmix (inhalation-vapour)** >20 mg/l

## Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m <sup>3</sup> (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Corrosive

### Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

**Respiratory or skin sensitisation** No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME**  
**SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

Octamethylcyclotetrasiloxane [D4] (556-67-2)  
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h,	LC50: =5000mg/L (96h,	-	EC50: =7600mg/L (48h,		

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE**  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

	Pseudokirchneriella subcapitata)	Brachydanio rerio)		Ceriodaphnia dubia)		
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
3-aminopropyltriethoxysilane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

Octamethylcyclotetrasiloxane [D4] (556-67-2)  
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation**

### Component Information

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	1.25
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

2-octyl-2H-isothiazol-3-one [OIT]	2.92
-----------------------------------	------

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does not apply
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## IMDG

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Marine pollutant NP  
14.6 Special precautions for user  
Special Provisions None

14.7 Maritime transport in bulk  
according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

## Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated  
14.2 UN proper shipping name Not regulated  
14.3 Transport hazard class(es) Not regulated  
14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special precautions for user  
Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

##### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### Persistent Organic Pollutants

Not applicable

# SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE  
Supersedes Date: 13-Apr-2022

Revision date 24-Jul-2023

Revision Number 1.01

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour  
H301 - Toxic if swallowed  
H302 - Harmful if swallowed  
H311 - Toxic in contact with skin  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H330 - Fatal if inhaled  
H361f - Suspected of damaging fertility  
H400 - Very toxic to aquatic life  
H410 - Very toxic to aquatic life with long lasting effects

#### Notes relating to the identification, classification and labelling of substances

**Note V:** If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

#### Notes relating to the classification and labelling of mixtures

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

#### Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 24-Jul-2023

#### Indication of changes

**Revision note** Not applicable.  
**Training Advice** No information available

# SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME  
SILICONE ANTHRACITE**  
**Supersedes Date:** 13-Apr-2022

**Revision date** 24-Jul-2023

**Revision Number** 1.01

---

**Further information**

No information available

**This material safety data sheet complies with requirements of UK REACH Regulations (SI 2019/758 as amended)**

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**