



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME SILICONE CLEAR
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)
NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

Chronic aquatic toxicity	Category 3 - (H412)
---------------------------------	---------------------

2.2. Label elements

Signal word
None

Hazard statements
H412 - Harmful to aquatic life with long lasting effects.

EU Specific Hazard Statements
EUH208 - Contains 3-aminopropyltriethoxysilane & 2-octyl-2H-isothiazol-3-one [OIT]. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)
P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

P273 - Avoid release to the environment
P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Small amounts of 2-Pentanone oxime (CAS 623-40-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 1 - <5 %	484-460-1	37859-55-5	Acute Tox. 4 (H302) Eye Irrit. 2 (H319)	-	-	-	01-2120004323-76-XXXX
3-aminopropyltriethoxysilane 0.1 - <0.5 %	213-048-4 (612-108-00-0)	919-30-2	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317)	-	-	-	01-2119480479-24-XXXX
Octamethylcyclotetrasiloxane [D4] 0.05 - <0.1 %	209-136-7 (014-018-00-1)	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	01-2119529238-36-XXXX
Toluene 0.036 - < 0.05 %	203-625-9 (601-021-00-3)	108-88-3	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 3 (H412) Flam. Liq. 2 (H225)	-	-	-	01-2119471310-51-XXXX
Methyl alcohol 0.0025 - <0.01 %	200-659-6 (603-001-00-X)	67-56-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX
2-octyl-2H-isothiazol-3-one [OIT] 0.0025 - <0.01 %	247-761-7 (613-112-00-5)	26530-20-1	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Sens. 1A :: C>=0.0015%	100	100	-

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No (EU Index)	Classification	Specific	M-Factor	M-Factor	REACH
---------------	------------------	----------------	----------	----------	----------	-------

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

	No)	according to Regulation (EC) No. 1272/2008 [CLP]	concentration limit (SCL)		(long-term)	registration number
2-Pentanone oxime 623-40-5	484-470-6	Acute Tox. 4 (H302) Eye Irrit. 2 (H319) STOT RE 2 (H373) Aquatic Chronic 3 (H412)	-	-	-	01-2119980079-27-XXXX
Ethanol 64-17-5	200-578-6 (603-002-00-5)	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-2119457610-43-XXXX
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C _≥ 10% STOT SE 2 :: 3%≤C<10%	-	-	01-2119433307-44-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[G] - PBT / vPvB substance

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE_{mix}) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime	484-460-1	37859-55-5	1234	-	-	-	-
3-aminopropyltriethoxysilane	213-048-4 (612-108-00-0)	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasiloxane [D4]	209-136-7 (014-018-00-1)	556-67-2	-	-	-	-	-
Toluene	203-625-9 (601-021-00-3)	108-88-3	5580	12000	30	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	100	300	-	3	-
2-octyl-2H-isothiazol-3-one [OIT]	247-761-7 (613-112-00-5)	26530-20-1	125 ⁺	311 ⁺	0.27 ⁺	0.27 ⁺	0.27 ⁺

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	None known.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.
-----------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Water spray, carbon dioxide (CO ₂), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon oxides. Carbon dioxide (CO ₂). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
--	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
----------------------	--

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs. Protect from moisture.

Recommended storage temperature Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³
Ethanol 64-17-5	-	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ *	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ Sk*
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m ³ *	TWA: 200 ppm TWA: 266 mg/m ³ STEL: 250 ppm STEL: 333 mg/m ³ Sk*

Chemical name	European Union	Ireland	United Kingdom
Toluene 108-88-3	-	0.02 mg/L (blood - Toluene prior to last shift of workweek) 0.03 mg/L (urine - Toluene end of shift) 0.3 mg/g Creatinine (urine - o-Cresol end of shift)	-
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
3-aminopropyltriethoxysilane (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m ³	
worker Short term Systemic health effects	Inhalation	59 mg/m ³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m ³	

Toluene (108-88-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Dermal	384 mg/kg bw/d	
Long term Systemic health effects Local health effects worker	Inhalation	192 mg/m ³	
Short term Systemic health effects worker	Inhalation	384 mg/m ³	
worker	Inhalation	192 mg/m ³	

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Long term Local health effects			
worker Short term Local health effects	Inhalation	384 mg/m ³	

Methyl alcohol (67-56-1)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Short term Systemic health effects worker	Dermal	40 mg/kg bw/d	
Short term Systemic health effects worker	Inhalation	260 mg/m ³	
Short term Local health effects worker	Inhalation	260 mg/m ³	
Long term Systemic health effects worker	Dermal	40 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	260 mg/m ³	
Long term Local health effects worker	Inhalation	260 mg/m ³	

Derived No Effect Level (DNEL)

3-aminopropyltriethoxysilane (919-30-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m ³	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m ³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

Toluene (108-88-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
------	----------------	--------------------------------	---------------

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Consumer Long term Systemic health effects	Inhalation	56.5 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	226 mg/m ³	
Consumer Long term Local health effects	Inhalation	56 mg/m ³	
Consumer Local health effects Short term	Inhalation	226 mg/m ³	
Consumer Long term Systemic health effects	Dermal	226 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	8.13 mg/kg bw/d	

Methyl alcohol (67-56-1)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Local health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Oral	8 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	50 mg/m ³	
Consumer Long term Systemic health effects	Dermal	50 mg/kg bw/d	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0015 mg/l
Marine water	0.00015 mg/l
Freshwater sediment	3 mg/kg
Marine sediment	0.3 mg/kg
Soil	0.54 mg/kg
Sewage treatment plant	10 mg/l

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Toluene (108-88-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.68 mg/l
Marine water	0.68 mg/l
Sewage treatment plant	13.61 mg/l
Freshwater sediment	16.39 mg/kg dry weight
Marine sediment	16.39 mg/kg dry weight
Soil	2.89 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Colourless
Odour	Characteristic.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 100 °C	CC (closed cup)
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	
Kinematic viscosity	> 21 mm ² /s	@ 40 °C
Dynamic viscosity	No data available	
Water solubility	Insoluble in water. Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	No data available	
Relative density	No data available	
Bulk density	No data available	

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Density	ca. 1.02 g/cm ³
Relative vapour density	No data available
Particle characteristics	
Particle Size	No information available
Particle Size Distribution	No information available
9.2. Other information	
Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.
Ingestion	Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	38,727.60 mg/kg
ATEmix (dermal)	62,799.00 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxi me	LD50 =1234 mg/kg bw (Rattus)(OECD guideline 425)	LD50 > 2000 mg/kg (Rattus) EU Method B.3	-
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rattus, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rattus, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rattus (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m ³ (Rattus) 4 h
Toluene	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Toluene (108-88-3)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.4	Rabbit	Dermal			Irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation No classification is proposed, based on conclusive negative data. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. May cause sensitisation in

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Component Information
Toluene (108-88-3)

Method	Species	Results
Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)	Salmonella typhimurium	Not mutagenic
OECD Test No. 476: In Vitro Mammalian Cell Gene Mutation Tests using the Hprt and xprt genes	Mouse	Not mutagenic

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2
Toluene	Repr. 2

Toluene (108-88-3)

Method	Species	Results
OECD 407	in vivo	Reproductive toxicant

STOT - single exposure

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Toluene (108-88-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
Regulation (EC) No. 440/2008, Annex, B.26	Rat, male, female	Oral		91 days	NOAEL: 625 mg/kg
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat, male, female	Inhalation, vapour			NOAEL: 1.131 mg/l

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-Pentandione, O,O',O''-(methylsilylidyne)trioxime 37859-55-5	EC50 (72h) = 88 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) >113 mg/L (Oncorhynchus mykiss) Static (OECD Guideline 203)	-	EC50 (48h) >100 mg/L (Daphnia magna) static (OECD guideline 202)		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasiloxane [D4] 556-67-2	-	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h = 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		
Methyl alcohol 67-56-1	-	LC50 96 h > 100 mg/L (Pimephales promelas static)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability No information available.

Octamethylcyclotetrasiloxane [D4] (556-67-2)

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results
OECD Test No. 309: Aerobic Mineralization in Surface Water - Simulation Biodegradation Test		Half-life 0.6-1.4 d	Readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	1.25
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
Toluene	2.73
Methyl alcohol	-0.77
2-octyl-2H-isothiazol-3-one [OIT]	2.92

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
2-Pentandione, O,O',O''-(methylsilyldiyl)trioxime	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
Toluene	The substance is not PBT / vPvB
Methyl alcohol	The substance is not PBT / vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100(3) or Commission Regulation (EU) 2018/605(4).	Negative.	

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

SAFETY DATA SHEET

**BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR**
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No.

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H225 - Highly flammable liquid and vapour
H301 - Toxic if swallowed
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H311 - Toxic in contact with skin
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H331 - Toxic if inhaled
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H370 - Causes damage to organs

SAFETY DATA SHEET

BOSTIK PRO SEALANT S41 WINDOW AND DOOR FRAME
SILICONE CLEAR
Supersedes date 10-Oct-2022

Revision date 29-Aug-2024

Revision Number 1.03

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs
Revision date 29-Aug-2024

Indication of changes

Revision note SDS sections updated, 1, 3, 11, 15.
Training Advice No information available
Further information No information available

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet