

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Revision date 09-Jul-2024 Revision Number 2.02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier			
Product Name	BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE		
Pure substance/mixture	Mixture		
1.2. Relevant identified uses of th	e substance or mixture and uses advised against		
Recommended use	Sealant		
Uses advised against	None known		
1.3. Details of the supplier of the	safety data sheet		
<u>Company Name</u> Bostik Limited Common Rd ST16 3EH Stafford UK Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36			
E-mail address	SDS.box-EU@bostik.com		
1.4. Emergency telephone numbe	<u>er</u>		
United Kingdom	Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri) NHS: 111		
SECTION 2: Hazards identi	fication		
2.1. Classification of the substand	ce or mixture		
GB CLP (SI 2020/1567 as amende	d)		

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH210 - Safety data sheet available on request EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE

Supercedes date 09-May-2022

P102 - Keep out of reach of children

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to Regulation (EC) No.	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
			1272/2008 [CLP]	(002)		,	nambor
Titanium dioxide 5 - <10 %	236-675-5 (022-006-00- 2)	13463-67-7	[C]	-	-	-	01-2119489379- 17-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

SECTION 4: First aid measures

4.1. Description of first aid measures

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE

Supercedes date 09-May-2022

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Never give anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Do NOT induce vomiting.
4.2. Most important symptoms and	l effects, both acute and delayed
Symptoms	None known.
Effects of Exposure	No information available.
4.3. Indication of any immediate m	edical attention and special treatment needed
Note to doctors	Treat symptomatically.
SECTION 5: Firefighting me	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.
Unsuitable extinguishing media <u>5.2. Special hazards arising from t</u>	
5.2. Special hazards arising from t	
5.2. Special hazards arising from t Specific hazards arising from the	he substance or mixture
5.2. Special hazards arising from t Specific hazards arising from the chemical 5.3. Advice for firefighters	he substance or mixture
5.2. Special hazards arising from t Specific hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary.
 5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated 	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary.
 5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated 	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary.
 5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated 6.1. Personal precautions, protection 	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary. Ase measures ve equipment and emergency procedures Do not get in eyes, on skin, or on clothing. Use personal protective equipment as
 5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releated 6.1. Personal precautions, protection 	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary. Ase measures ve equipment and emergency procedures Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
 5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releat 6.1. Personal precautions, protection Personal precautions For emergency responders 	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary. Ase measures ve equipment and emergency procedures Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releat 6.1. Personal precautions, protection Personal precautions	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary. Ase measures ve equipment and emergency procedures Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation. Use personal protection recommended in Section 8. Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
5.2. Special hazards arising from the chemical 5.3. Advice for firefighters Special protective equipment and precautions for fire-fighters SECTION 6: Accidental releat 6.1. Personal precautions, protection Personal precautions For emergency responders 6.2. Environmental precautions Environmental precautions	he substance or mixture Thermal decomposition can lead to release of irritating gases and vapours. Wear self contained breathing apparatus for fire fighting if necessary. Ase measures ve equipment and emergency procedures Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation. Use personal protection recommended in Section 8. Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Revision date 09-Jul-2024 Revision Number 2.02

Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	_
Advice on safe handling	Ensure adequate ventilation.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
7.2. Conditions for safe storage, in	cluding any incompatibilities
Storage Conditions	Protect from moisture. Keep away from food, drink and animal feedingstuffs.
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.
7.3. Specific end use(s)	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (D	NEL)		
Titanium dioxide (13463-67	-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	10 mg/m³	
Long term Local health effects			

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Oral	700 mg/kg bw/d	

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE

Supercedes date 09-May-2022

Systemic health effects		

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concent	tration (PNEC)	
Titanium dioxide (13463-67-7	7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Marine water	0.0184 mg/l	
Freshwater sediment	1000 mg/kg	
Freshwater	0.184 mg/l	
Marine sediment	100 mg/kg	
Soil	100 mg/kg	
Microorganisms in sewage treatme	ent 100 mg/l	
Freshwater - intermittent	0.193 mg/l	
8.2. Exposure controls Engineering controls	Ensure adequate ventilation, especially in confined areas.	
Personal protective equip Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.	
Hand protection	Wear suitable gloves. Recommended Use: Neoprene™ Nitrile rubber. Butyl rubber	

Hand protection	Wear suitable gloves. Recommended Use:. Neoprene [™] . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical a Physical state Appearance Colour	Solid Paste White	
Odour	Characteristic.	
<u>Property</u> Melting point / freezing point Initial boiling point and boiling range Flammability Flammability Limit in Air Upper flammability or explosive limits	<u>Values</u> No data available No data available No data available No data available	Remarks • Method None known None known None known None known
Lower flammability or explosive	No data available	
limits Flash point Autoignition temperature Decomposition temperature pH pH (as aqueous solution) Kinematic viscosity	93.3 °C No data available No data available No data available > 21	None known None known Not applicable. Insoluble in water. None known @ 40 °C

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Revision date 09-Jul-2024 Revision Number 2.02

Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk density	No data available	
Density	1.4 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data	a available

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity 10.2. Chemical stability Stable under normal conditions. Stability **Explosion data** Sensitivity to mechanical None. impact Sensitivity to static discharge None. 10.3. Possibility of hazardous reactions Possibility of hazardous reactions None under normal processing. 10.4. Conditions to avoid **Conditions to avoid** Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition. 10.5. Incompatible materials Incompatible materials Strong oxidising agents. 10.6. Hazardous decomposition products Hazardous decomposition None under normal use conditions. Stable under recommended storage conditions. products

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Information on likely routes of exposure

Product Information	
Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical	, chemical and toxicological characteristics
Symptoms	No information available.
Acute toxicity	

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)						
Method	Species	Exposure route	Effective dose	Exposure time	Results	
OECD Test No. 405:	Rabbit	Eye			Non-irritant	
Acute Eye Irritation/Corrosion						
Respiratory or skin sens	sitisation	Based on available data, th	e classification crite	ria are not met.		
Germ cell mutagenicity		Based on available data, the classification criteria are not met.				
Carcinogenicity		Based on available data, th	e classification crite	ria are not met.		

Chemical name	European Union
Titanium dioxide	Carc. 2

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Reproductive toxicity	Based on available data, the classification criteria are not met.		
STOT - single exposure	Based on available data, the classification criteria are not met.		
STOT - repeated exposure	Based on available data, the classification criteria are not met.		
Aspiration hazard	Based on available data, the classification criteria are not met.		
11.2. Information on other hazards			
11.2.1. Endocrine disrupting properties			
Endocrine disrupting properties	No information available.		
11.2.2. Other information			
Other adverse effects	No information available.		

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

There is no data for this product.

12.4. Mobility in soil

Mobility in soilNo information available.12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Titanium dioxide	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE

Supercedes date 09-May-2022

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	-
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None
IMDG	
14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk	
according to IMO instruments	
Transport in bulk according to	Annex II of MARPOL and the IBC Code Not applicable
Air transport (ICAO-TI / IATA-DGR)	=
14.1 UN number or ID number	Not regulated
14.2 LIN proper shipping name	Not regulated

1.4.1		riotrogulatea
14.2	UN proper shipping name	Not regulated
14.3	Transport hazard class(es)	Not regulated
14.4	Packing group	Not regulated
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	
Special Provisions		None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE

Supercedes date 09-May-2022

Revision date 09-Jul-2024 Revision Number 2.02

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Notes relating to the identification, classification and labelling of substances

Note V: If the substance is to be placed on the market as fibres (with diameter < $3 \mu m$, length > $5 \mu m$ and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W: It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

Notes relating to the classification and labelling of mixtures

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 µm

Legend	
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

BOSTIK PRO SEALANT S80 GLAZING SILICONE WHITE Supercedes date 09-May-2022

Revision date 09-Jul-2024 Revision Number 2.02

vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by
	Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data No information available Prepared By Product Safety & Regulatory Affairs Revision date 09-Jul-2024		
	00 001 2024	
Indication of changes		
Revision note	Not applicable.	
Training Advice	No information available	
Further information	No information available	
Further information	NU INIUMATION AVAIIADIE	

This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet