



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant

**Uses advised against** Not to be used in articles intended for direct or prolonged skin contact Not to be used in production of toys or childcare articles Fabrics, textiles and apparel: bedding and clothing Gloves Footwear (shoes, boots) Paper products: tissue, towels, disposable dinnerware, nappies, feminine hygiene products, adult incontinence products, writing paper

**Reason why uses advised against** Restricted substance per REACH Annex XVII

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supercedes Date: 10-May-2024

Revision date 21-May-2024

Revision Number 1.03

## EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

## Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Limestone	215-279-6	1317-65-3	40 - <80	[C]	-	[5]
Bis(2-propylheptyl)phthalate	258-469-4	53306-54-0	10 - <20	-	-	01-2119446694-30-XXXX
Poly[oxy(methyl-1,2-ethanediyl)],.alpha.-[3-(dimethoxymethylsilyl)propyl]-.omega.-[3-(dimethoxymethylsilyl)propoxy-].alpha.,.alpha.',.alpha."-1,2,3-Propanetriyltris[.omega.-(3-dimethoxymethylsilyl)propoxy]poly[oxy(methyl-1,2-ethanediyl)]	-	75009-88-0	10 - <20	-	-	[7]
	-	151865-59-7	10 - <20	-	-	[7]
Silica, amorphous, fumed, crystalline-free	601-216-3	112945-52-5	1 - <2.5	-	-	01-2119379499-16-XXXX
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	0.1- <1	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	01-2119537297-32-XXXX
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	0.1- <1	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Titanium dioxide	236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379-

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

	(022-006-00-2)					17-XXXX
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	0.1 - <1	Eye Dam. 1 (H318) Skin Sens. 1B (H317) STOT SE 3 (H335)	-	01-2119970215-39-XXXX
Dioctyltin oxide	212-791-1	870-08-6	0.1 - <0.5	STOT SE 2 (H371)	-	01-2119971268-27-xxxx
Quartz (fine fraction)	238-878-4	14808-60-7	0.1 - <0.3	STOT RE 1 (H372)	-	[5]
Mixture of inorganic pigments (concrete grey) - WGK 1	-	UNKNOWN	0.1 - <0.3	-	-	-
Ethyl silicate	201-083-8 (014-005-00-0)	78-10-4	0.1 - <0.3	Acute Tox. 4 (H332) Eye Irrit. 2 (H319) STOT SE 3 (H335) Flam. Liq. 3 (H226)	-	01-2119496195-28-xxxx
Antioxidant	-	UNKNOWN	0.05 - <0.1	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)	-	CAS confidential Ref: 722 43/00/2015.0004
1,2-Ethanediamine, N,N'-bis[3-(trimethoxysilyl)propyl]-	272-453-4	68845-16-9	0.05 - <0.1	Eye Dam. 1 (H318)	-	-
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	253-039-2	36443-68-2	0.036 - < 0.05	-	-	01-2119956160-44-XXXX
Synthetic antioxidant	-	UNKNOWN	0.036 - < 0.05	-	-	-
Ethane-1,1-diamine, N,N-bis(3-(trimethylsiloxy)propyl)	-	74956-86-8	0.01 < 0.036	Eye Dam. 1 (H318)	-	-
1-Aza-2-silacyclopentane-1-ethanamine, 2,2-dimethoxy-	-	618914-51-5	0.01 < 0.036	Eye Dam. 1 (H318)	-	-
Synthetic Amorphous, Pyrogenic Silica	231-545-4	112945-52-5	0.01 < 0.036	[K]	-	01-2119379499-16-XXXX
Ethanol	200-578-6 (603-002-00-5)	64-17-5	0.01 < 0.036	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	01-2119457610-43-XXXX
Vinyltrimethoxysilane, homopolymer	-	29382-69-2	0.0025 - <0.01	-	-	-
Methyl alcohol	200-659-6 (603-001-00-X)	67-56-1	0.0025 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	01-2119433307-44-XXXX

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

				STOT SE 1 (H370) Flam. Liq. 2 (H225)		
Methyl silicate	211-656-4	681-84-5	<0.0015	Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Acute Tox. 1 (H330) Flam. Liq. 3 (H226)	-	01-2119957658-18-XXXX
Nanoparticle - identity unknown	-	UNKNOWN	<0.0015	[K]	-	-

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

**Full text of H- and EUH-phrases: see section 16**

**Air contaminants formed when using the substance or mixture as intended**

Chemical name	EC No (EU Index No)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Methyl alcohol 67-56-1	200-659-6 (603-001-00-X)	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-2119433307-44-XXXX

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

ophthalmologist.

**Skin contact**

Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.

**Ingestion**

Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.

**4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms**

None known.

**Effects of Exposure**

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors**

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable Extinguishing Media**

Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical**

Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products**

Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters**

Wear self contained breathing apparatus for fire fighting if necessary.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions**

Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

**For emergency responders**

Use personal protection recommended in Section 8.

**6.2. Environmental precautions**

**Environmental precautions**

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

**6.3. Methods and material for containment and cleaning up**

**Methods for containment**

Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

**Methods for cleaning up**

Take up mechanically, placing in appropriate containers for disposal.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes Date: 10-May-2024

Revision date 21-May-2024

Revision Number 1.03

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protection equipment. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m <sup>3</sup> TWA: 2.4 mg/m <sup>3</sup> STEL: 18 mg/m <sup>3</sup> STEL: 7.2 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Diocetyltn oxide 870-08-6	-	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Sk*

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Ethyl silicate 78-10-4	TWA: 44 mg/m <sup>3</sup> TWA: 5 ppm	TWA: 5 ppm TWA: 44 mg/m <sup>3</sup> STEL: 15 ppm STEL: 132 mg/m <sup>3</sup>
---------------------------	---	--

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
Bis(2-propylheptyl)phthalate (53306-54-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	125 mg/kg bw/d	
worker Long term Local health effects	Inhalation	5 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	35.3 mg/m <sup>3</sup>	

Silica, amorphous, fumed, crystalline-free (112945-52-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term	Inhalation	4 mg/m <sup>3</sup>	

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
--	--	--	--

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	35.5 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	5 mg/kg bw/d	
Short term Systemic health effects worker	Dermal	5 mg/kg bw/d	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m <sup>3</sup>	

<b>Ethyl silicate (78-10-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Systemic health effects	Dermal	12.1 mg/kg bw/d	
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	85 mg/m <sup>3</sup>	

<b>Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	3 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	86 mg/kg	

<b>Ethanol (64-17-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	950 mg/m <sup>3</sup>	



# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Long term Systemic health effects worker Long term Systemic health effects	Dermal	343 mg/kg bw/d	
--	--------	----------------	--

Derived No Effect Level (DNEL)			
Bis(2-propylheptyl)phthalate (53306-54-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	62.5 mg/kg	
Consumer Long term Local health effects	Inhalation	1.25 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	8.7 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Oral	5 mg/kg	

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

Trimethoxyvinylsilane (2768-02-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Oral	2.5 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Consumer			
Long term	Inhalation	8.7 mg/m <sup>3</sup>	
Systemic health effects			
Consumer			
Long term	Dermal	mg/kg bw/d	
Systemic health effects			
Consumer			

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Oral	0.0005 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Dermal	0.025 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	0.0009 mg/m <sup>3</sup>	
Long term			
Systemic health effects			

<b>Quartz (fine fraction) (14808-60-7)</b>			
<b>Ethyl silicate (78-10-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Dermal	8.4 mg/kg bw/d	
Short term			
Systemic health effects			
Consumer	Dermal	8.4 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Inhalation	25 mg/m <sup>3</sup>	
Short term			
Systemic health effects			
Consumer	Inhalation	25 mg/m <sup>3</sup>	
Short term			
Local health effects			
Consumer	Inhalation	25 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Inhalation	25 mg/m <sup>3</sup>	
Long term			
Local health effects			

<b>Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term	Dermal	43 mg/kg	
Systemic health effects			
Consumer			
Long term	Oral	4,3 mg/kg	
Systemic health effects			
Consumer			

<b>Ethanol (64-17-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	114 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Long term Systemic health effects			
Consumer Long term Systemic health effects	Dermal	206 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	87 mg/kg bw/d	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Bis(2-propylheptyl)phthalate (53306-54-0)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.939 g/kg
Marine sediment	0.0939 mg/kg
Soil	26.5 mg/kg

Silica, amorphous, fumed, crystalline-free (112945-52-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Secondary poisoning	NOEC Food chain 60000 mg/kg

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Freshwater - intermittent	0.62 mg/l
Freshwater sediment	0.05 mg/kg
Marine sediment	0.005 mg/kg
Soil	0.0075 mg/kg
Sewage treatment plant	25 mg/l

Diocetyl tin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

## Quartz (fine fraction) (14808-60-7)

### Ethyl silicate (78-10-4)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

## Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester (36443-68-2)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Sewage treatment plant	1 mg/l
Freshwater	0.00055 mg/l
Marine water	0.00055 mg/l
Freshwater sediment	0.195 mg/kg dry weight

## Ethanol (64-17-5)

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	154 mg/l
Marine water	15.4 mg/l
Sewage treatment plant	100 mg/l

## 8.2. Exposure controls

### Engineering controls

Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

#### Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

#### Skin and body protection

Wear suitable protective clothing.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better.

#### Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Paste
Colour	Grey
Odour	Characteristic.

#### Property

#### Values

#### Remarks • Method

Melting point / freezing point	No data available	Data technically impossible to obtain
Initial boiling point and boiling range	No data available	Data technically impossible to obtain
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

<b>Lower flammability or explosive limits</b>	No data available	
<b>Flash point</b>	> 61 °C	CC (closed cup)
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>		None known
<b>pH</b>	.	Not applicable. Insoluble in water.
<b>pH (as aqueous solution)</b>	No data available	
<b>Kinematic viscosity</b>	No data available	
<b>Dynamic viscosity</b>	27 - 35 Pa.s	Spindle Z3U @ 100 rpm @ 23 °C
<b>Water solubility</b>	Reacts with water.	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Vapour pressure</b>	No data available	
<b>Relative density</b>	1.5	
<b>Bulk Density</b>	No data available	
<b>Liquid Density</b>	ca. 1.5 g/cm <sup>3</sup>	
<b>Relative vapour density</b>	No data available	
<b>Particle characteristics</b>		
<b>Particle Size</b>	No information available	
<b>Particle Size Distribution</b>	No information available	

## 9.2. Other information

<b>Solid content (%)</b>	No information available
<b>VOC content</b>	No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

**Stability** Stable under normal conditions.

### **Explosion data**

<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	None.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

### 10.4. Conditions to avoid

**Conditions to avoid** Protect from moisture. Product cures with moisture.

### 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

### 10.6. Hazardous decomposition products

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes Date: 10-May-2024

Revision date 21-May-2024

Revision Number 1.03

## Hazardous decomposition products

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.
Skin contact	Based on available data, the classification criteria are not met.
Ingestion	Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>2000 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	>5000 mg/kg (Rattus)	-	-
Bis(2-propylheptyl)phthalate	LD50 > 5000 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Oryctolagus cuniculus) OECD 402	> 20.5 mg/L ( Rat ) 1 h
Silica, amorphous, fumed, crystalline-free	>5000 mg/kg (Rattus) OECD 401	LD50 >5000 mg/Kg (Oryctolagus cuniculus)	LC50 (4h) >0.139 mg/L (Rattus) / (maximum technically attainable analytical concentration)
Bis(2,2,6,6-tetramethyl-4-piperi dyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m <sup>3</sup> (Rattus) 4 h
Trimethoxysilylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
N-(3-(trimethoxysilyl)propyl)eth ylenediamine	LD50 = 2295 mg/kg (Rattus) EPA OPPTS 870.1100	LD50 > 2000 mg/kg (Oryctolagus cuniculus) EPA OPPTS 870.1200	1.49 - 2.44 mg/L ( Rat ) 4 h
Dioctyltin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Ethyl silicate	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L ( Rat male ) 4 h > 16.8 mg/L ( Rat female ) 4 h
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	LD50 >7000 mg/kg Rat	LD50 >2000 mg/Kg Rat	-
Synthetic Amorphous, Pyrogenic Silica	LD50 >5000 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (rabbit) OECD 402	-
Ethanol	6200 - 15000 mg/kg (Rattus) OECD 401	-	=124.7 mg/L (Rattus) 4 h
Methyl alcohol	=2500 mg/kg (Rattus)	200-1000 mg/kg (Oryctolagus cuniculus)	=22500 ppm (Rattus) 8 h = 64000 ppm (Rattus) 4 h
Methyl silicate	LD50 > 2500 mg/kg	= 17 g/kg (Oryctolagus cuniculus) = 17 mL/kg (Oryctolagus cuniculus)	LC 50 = 0.392 mg/l

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Quartz (fine fraction) (14808-60-7)					
<b>Serious eye damage/eye irritation</b> Based on available data, the classification criteria are not met.					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

### **Respiratory or skin sensitisation**

May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

conclusive negative data.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

## Germ cell mutagenicity

Based on available data, the classification criteria are not met.

## Component Information

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

## Carcinogenicity

Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2

## Reproductive toxicity

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	reproductive toxicant

## STOT - single exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

## STOT - repeated exposure

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d



# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmodesmus subspicatus)	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna		
Bis(2-propylheptyl)phthalate 53306-54-0	EC50 (72h) > 100 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) > 10000 mg/l (Danio rerio) OECD 203	-	EC50 (48h) > 100 mg/l (Daphnia magna) EU Method C.2		
Silica, amorphous, fumed, crystalline-free 112945-52-5	EL50 (72h) > 10000 mg/L (Desmodesmus subspicatus) OECD 201	LC50 (96h) >10000 mg/L (Danio rerio)	-	EC50 (24h) >10000 mg/L (Daphnia magna)		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)		
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge,	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna))		

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supercedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

	Respiration Inhibition Test)	Test)		(Daphnia sp. Acute Immobilisation Test)		
Ethyl silicate 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) > 245 mg/L (Danio rerio) EU Method C.1	-	-		
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester 36443-68-2	EC50 (72h) >100 mg/L Algae (Desmodesmus subspicatus) Static	LC50 (96h) 43 mg/L (Lepomis macrochirus) OECD 203	-	LD50 (48h) >100 mg/L Daphnia magna		
Synthetic Amorphous, Pyrogenic Silica 112945-52-5	-	LC50 (96h) >10000 mg/L (Brachydanio rerio) OECD 203	-	EC50 (24h) >10000 mg/L (Daphnia magna) OECD 202		
Ethanol 64-17-5	EC50 72hr 12.9 g/l (Selenastrum capricornutum) NOEC 3.24 g/l (Skeletonema costatum)	LC50: >100mg/L (96h, Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, Daphnia magna) EC50: =12.34 mg/L		
Methyl alcohol 67-56-1	-	LC50: >100mg/L (96h, Pimephales promelas) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: =28200mg/L (96h, Pimephales promelas) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test - Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

Biodegradability: Manometric Respirometry Test (TG 301 F)			biodegradable
---	--	--	---------------

Diocetyl tin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Limestone	0.9
Bis(2-propylheptyl)phthalate	>6
Poly[oxy(methyl-1,2-ethanediyl)],.alpha.-[3-(dimethoxymethylsilyl)propyl]-.omega.-[3-(dimethoxymethylsilyl)propoxy-]	1.8
Silica, amorphous, fumed, crystalline-free	0.53
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Diocetyl tin oxide	6
Ethyl silicate	3.18
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	8.2
Ethanol	-0.35
Methyl alcohol	-0.77

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Bis(2-propylheptyl)phthalate	The substance is not PBT / vPvB
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	The substance is not PBT / vPvB
Diocetyl tin oxide	The substance is not PBT / vPvB
Ethyl silicate	The substance is not PBT / vPvB
Benzenepropanoic acid, 3-(1,1-dimethylethyl)-4-hydroxy-5-methyl-, 1,2-ethanediylbis(oxy-2,1-ethanediyl) ester	The substance is not PBT / vPvB
Ethanol	The substance is not PBT / vPvB
Methyl alcohol	The substance is not PBT / vPvB
Methyl silicate	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes Date: 10-May-2024

Revision date 21-May-2024

Revision Number 1.03

## 12.7. Other adverse effects

No information available.

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 UN proper shipping name</b>	-
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	None

### IMDG

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 UN proper shipping name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Marine pollutant</b>	NP
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	None
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	
<b>Transport in bulk according to Annex II of MARPOL and the IBC Code</b>	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

<b>14.1 UN number or ID number</b>	Not regulated
<b>14.2 UN proper shipping name</b>	Not regulated
<b>14.3 Transport hazard class(es)</b>	Not regulated
<b>14.4 Packing group</b>	Not regulated
<b>14.5 Environmental hazards</b>	Not applicable
<b>14.6 Special precautions for user</b>	
<b>Special Provisions</b>	None

## **Section 15: REGULATORY INFORMATION**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

## SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20.

**20 (6)** DOT.

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 649/2012 - Annex Number
Diocetyl tin oxide	I.1

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Methyl alcohol - 67-56-1	500	5000

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at  $>10$  tpa. No Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**

**Supersedes Date:** 10-May-2024

**Revision date** 21-May-2024

**Revision Number** 1.03

H361f - Suspected of damaging fertility  
H400 - Very toxic to aquatic life  
H411 - Toxic to aquatic life with long lasting effects

## Notes relating to the identification, classification and labelling of substances

**Note V:** If the substance is to be placed on the market as fibres (with diameter  $< 3 \mu\text{m}$ , length  $> 5 \mu\text{m}$  and aspect ratio  $\geq 3:1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

## Notes relating to the classification and labelling of mixtures

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

## Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 21-May-2024  
**Indication of changes**

**Revision note** Not applicable.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**