



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: REACH Regulation (EC) No 1907/2006, as retained in UK law by (SI 2019/758 as amended)

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Product Name** BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING

**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant

**Uses advised against** Not to be used in articles intended for direct or prolonged skin contact Not to be used in production of toys or childcare articles Fabrics, textiles and apparel: bedding and clothing Gloves Footwear (shoes, boots) Paper products: tissue, towels, disposable dinnerware, nappies, feminine hygiene products, adult incontinence products, writing paper

**Reason why uses advised against** Restricted substance per REACH Annex XVII

### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Limited  
Common Rd  
ST16 3EH  
Stafford UK  
Tel: +44 (1785) 27 26 25  
Fax: +44 (1785) 25 72 36

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**United Kingdom** Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)  
NHS: 111

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

GB CLP (SI 2020/1567 as amended)

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### **Signal word**

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

## EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane & N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction

EUH210 - Safety data sheet available on request

## Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

## 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0.1- <1	01-2119537297-32-XXXX	258-207-9	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	1	-	-
Trimethoxyvinylsilane 2768-02-7	0.1- <1	01-2119513215-52-XXXX	220-449-8 (014-049-00-0)	Acute Tox. 4 (H332) Skin Sens. 1B (H317) Flam. Liq. 3 (H226)	-	-	-	-
Titanium dioxide 13463-67-7	0.1- <1	01-2119489379-17-XXXX	236-675-5 (022-006-00-2)	[C]	-	-	-	V,W,10
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	0.1- <1	01-2119970215-39-XXXX	217-164-6	Eye Dam. 1 (H318) Skin Sens. 1B (H317) STOT SE 3 (H335)	-	-	-	-
Diocetyl tin oxide 870-08-6	0.1 - <0.5	01-2119971268-27-xxxx	212-791-1	STOT SE 2 (H371)	-	-	-	-
Quartz (fine fraction) 14808-60-7	0.1 - <0.3	[5]	238-878-4	STOT RE 1 (H372)	-	-	-	-
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester 78-10-4	0.1 - <0.3	01-2119496195-28-xxxx	201-083-8 (014-005-00-0)	Flam. Liq. 3 (H226) Eye Irrit. 2 (H319) Acute Tox. 4 (H332) STOT SE 3 (H335)	-	-	-	-

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(b) and Annex V of REACH  
Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Note V - If the substance is to be placed on the market as fibres (with diameter < 3 µm, length > 5 µm and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ .

**Full text of H- and EUH-phrases: see section 16**

## Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATE<sub>mix</sub>) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	258-207-9	52829-07-9	-	-	-	-	-
Trimethoxyvinylsilane	220-449-8 (014-049-00-0)	2768-02-7	-	-	-	11	-
Titanium dioxide	236-675-5 (022-006-00-2)	13463-67-7	-	-	-	-	-
N-(3-(trimethoxysilyl)propyl)ethylenediamine	217-164-6	1760-24-3	-	-	1.5	-	-
Diocetyl tin oxide	212-791-1	870-08-6	-	-	-	-	-
Quartz (fine fraction)	238-878-4	14808-60-7	-	-	-	-	-
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester	201-083-8 (014-005-00-0)	78-10-4	-	-	4.9	11	-

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor or poison control centre immediately. Small amounts of toxic methanol are released by hydrolysis.

### 4.2. Most important symptoms and effects, both acute and delayed

# SAFETY DATA SHEET

BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING

Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

Symptoms None known.

Effects of Exposure No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

#### 5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Wear self contained breathing apparatus for fire fighting if necessary.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

For emergency responders Use personal protection recommended in Section 8.

#### 6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

#### 6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

**Advice on safe handling** Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

## 7.3. Specific end use(s)

**Specific use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product.

Chemical name	European Union	United Kingdom
Limestone 1317-65-3	-	TWA: 10 mg/m <sup>3</sup> ; inhalable dust TWA: 4 mg/m <sup>3</sup> ; respirable dust STEL: 30 mg/m <sup>3</sup> ; inhalable dust STEL: 12 mg/m <sup>3</sup> ; respirable dust
Methyl alcohol 67-56-1	TWA: 200 ppm; TWA: 260 mg/m <sup>3</sup> ; pSk	TWA: 200 ppm; TWA: 266 mg/m <sup>3</sup> ; STEL: 250 ppm; STEL: 333 mg/m <sup>3</sup> ; pSk
Silica, amorphous 7631-86-9	-	TWA: 6 mg/m <sup>3</sup> ; inhalable dust TWA: 2.4 mg/m <sup>3</sup> ; respirable dust STEL: 18 mg/m <sup>3</sup> ; inhalable dust STEL: 7.2 mg/m <sup>3</sup> ; respirable dust
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> ; total inhalable TWA: 4 mg/m <sup>3</sup> ; respirable STEL: 30 mg/m <sup>3</sup> ; total inhalable STEL: 12 mg/m <sup>3</sup> ; respirable
Diocetyl tin oxide 870-08-6	-	TWA: 0.1 mg/m <sup>3</sup> ; STEL: 0.2 mg/m <sup>3</sup> ; pSk
Quartz (fine fraction) 14808-60-7	TWA: 0.1 mg/m <sup>3</sup> ;	TWA: 0.1 mg/m <sup>3</sup> ; respirable fraction STEL: 0.3 mg/m <sup>3</sup> ; respirable
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester 78-10-4	TWA: 44 mg/m <sup>3</sup> ; TWA: 5 ppm;	TWA: 5 ppm; TWA: 44 mg/m <sup>3</sup> ; STEL: 15 ppm; STEL: 132 mg/m <sup>3</sup> ;

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

**Derived No Effect Level (DNEL)** No information available

<b>Derived No Effect Level (DNEL)</b>			
<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Short term Long term Systemic health effects	Inhalation	2.82 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	1.6 mg/kg	

<b>Trimethoxyvinylsilane (2768-02-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m <sup>3</sup>	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects worker	Inhalation	35.5 mg/m <sup>3</sup>	
Long term Systemic health effects worker	Dermal	5 mg/kg bw/d	
Short term Systemic health effects worker	Dermal	5 mg/kg bw/d	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m <sup>3</sup>	

<b>Silicic acid (H4SiO4), tetraethyl ester (78-10-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Dermal	12.1 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

Short term Systemic health effects			
worker Systemic health effects Long term	Dermal	12.1 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	85 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	85 mg/m <sup>3</sup>	

## Derived No Effect Level (DNEL)

### Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	0.8 mg/kg	
Consumer Long term Systemic health effects	Oral	0.4 mg/kg	

### Trimethoxyvinylsilane (2768-02-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

### Titanium dioxide (13463-67-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

### N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects Consumer	Oral	2.5 mg/kg bw/d	
Long term Systemic health effects Consumer	Inhalation	8.7 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supercedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

Long term Systemic health effects Consumer	Dermal	mg/kg bw/d	
--	--------	------------	--

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m <sup>3</sup>	

<b>Quartz (fine fraction) (14808-60-7)</b>			
<b>Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester (78-10-4)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	8.4 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	25 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	25 mg/m <sup>3</sup>	

## Predicted No Effect Concentration (PNEC)

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

<b>Trimethoxyvinylsilane (2768-02-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

<b>Titanium dioxide (13463-67-7)</b>	
--------------------------------------	--

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

<b>N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.062 mg/l
Marine water	0.0062 mg/l
Freshwater - intermittent	0.62 mg/l
Freshwater sediment	0.05 mg/kg
Marine sediment	0.005 mg/kg
Soil	0.0075 mg/kg
Sewage treatment plant	25 mg/l

<b>Diocetyl tin oxide (870-08-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

<b>Quartz (fine fraction) (14808-60-7)</b>	
<b>Silicic acid (H<sub>4</sub>SiO<sub>4</sub>), tetraethyl ester (78-10-4)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.192 mg/l
Marine water	0.0192 mg/l
Freshwater sediment	0.18 mg/kg dry weight
Marine sediment	0.018 mg/kg dry weight
Soil	0.05 mg/kg

## 8.2. Exposure controls

<b>Engineering controls</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal protective equipment</b>	
<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
<b>Hand protection</b>	Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
<b>Skin and body protection</b>	Wear suitable protective clothing.
<b>Respiratory protection</b>	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
<b>Recommended filter type:</b>	Organic gases and vapours filter conforming to EN 14387. White. Brown.

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	Paste
<b>Colour</b>	Grey
<b>Odour</b>	Characteristic.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	Data technically impossible to obtain
Initial boiling point and boiling range	No data available	Data technically impossible to obtain
Flammability	No data available	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 61 °C	CC (closed cup)
Autoignition temperature	No data available	
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	27 - 35 Pa.s	Spindle Z3U @ 100 rpm @ 23 °C
Water solubility	Reacts with water.	Reacts with water
Solubility(ies)	No data available	
Partition coefficient	No data available	
Vapour pressure	No data available	
Relative density	1.5	
Bulk density	No data available	
Density	ca. 1.5 g/cm <sup>3</sup>	
Relative vapour density	No data available	
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
<b>9.2. Other information</b>		
Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reactivity Product cures with moisture.

### 10.2. Chemical stability

Stability Stable under normal conditions.

### Explosion data

Sensitivity to mechanical impact None.  
Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

## 10.4. Conditions to avoid

**Conditions to avoid** Protect from moisture. Exposure to air or moisture over prolonged periods. Product cures with moisture.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

##### Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

#### Acute toxicity

#### Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) >2000 mg/kg  
ATEmix (dermal) >2000 mg/kg  
ATEmix (inhalation-gas) >20000 ppm  
ATEmix (inhalation-dust/mist) >5 mg/L  
ATEmix (inhalation-vapour) >20 mg/L

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	LD50 (Rattus) > 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m <sup>3</sup> (Rattus) 4 h
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
N-(3-(trimethoxysilyl)propyl)ethylenediamine	LD50 = 2295 mg/kg (Rattus) EPA OPPTS 870.1100	LD50 > 2000 mg/kg (Oryctolagus cuniculus) EPA OPPTS 870.1200	1.49 mg/L (Rat) 4 h
Diocetyl tin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

		OECD 402	
Quartz (fine fraction)	>2000 mg/kg (Rattus)	-	-
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester	LD50 > 2500 mg/kg (Rattus) OECD 423	= 5878 mg/kg (Oryctolagus cuniculus) = 6300 µL/kg (Oryctolagus cuniculus)	= 10 mg/L ( Rat male ) 4 h > 16.8 mg/L ( Rat female ) 4 h

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

### **Skin corrosion/irritation**

Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

Quartz (fine fraction) (14808-60-7)					
<b>Serious eye damage/eye irritation</b> Based on available data, the classification criteria are not met.					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye			Eye Damage

Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

### **Respiratory or skin sensitisation**

May produce an allergic reaction. OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

### **Germ cell mutagenicity**

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**  
**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

Component Information		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide	Carc. 2

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)		
Method	Species	Results
OECD Test No. 414: Pre-natal Development Toxicity Study	Rat, Rabbit	Reproductive toxicant

Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

**STOT - single exposure** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Diocetyl tin oxide (870-08-6)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)					
Trimethoxyvinylsilane (2768-02-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **11.2. Information on other hazards**

### **11.2.1. Endocrine disrupting properties**

**Endocrine disrupting properties** Based on available data, the classification criteria are not met.

### **11.2.2. Other information**

**Other adverse effects** No information available.

## **SECTION 12: Ecological information**

### **12.1. Toxicity**

**Ecotoxicity** Based on available data, the classification criteria are not met.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	EC50 72Hr 0.705 mg/l (Pseudokirchnerella subcapitata)	LC50 (96h) = 5.29 mg/l (Oryzias latipes)	-	LC50 48Hr 8.58 mg/l (Daphnia magna)	1	
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Daphnia magna)) (Daphnia sp. Acute Immobilisation Test)		
Silicic acid (H4SiO4), tetraethyl ester 78-10-4	EC 50 (72h) > 100 mg/L (Pseudokirchnerella subcapitata) OECD 201	LC50 (96h)> 245 mg/L (Danio rerio) EU Method C.1	-	-		

### **12.2. Persistence and degradability**

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF COATING**

Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

**Persistence and degradability** No information available.

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)			
Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test -- A: Aerobic Sewage Treatment -- A: Activated Sludge Units; B: Biofilms	28 days	Total organic carbon (TOC)	24 % Moderate

Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

## 12.3. Bioaccumulative potential

### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35
Trimethoxyvinylsilane	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine	-0.3
Diocetyl tin oxide	6
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester	3.18

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** Based on available data, the classification criteria are not met.

Chemical name	PBT and vPvB assessment
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	Not PBT/vPvB
Trimethoxyvinylsilane	Not PBT/vPvB
Titanium dioxide	Not PBT/vPvB
N-(3-(trimethoxysilyl)propyl)ethylenediamine	Not PBT/vPvB
Diocetyl tin oxide	Not PBT/vPvB
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetraethyl ester	Not PBT/vPvB

## 12.6. Endocrine disrupting properties Endocrine disrupting properties

**Endocrine disruption for the environment** Based on available data, the classification criteria are not met.

## 12.7. Other adverse effects Other adverse effects

**Other adverse effects** No information available.

**PMT or vPvM properties** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**  
Supersedes date 21-May-2024

Revision date 18-Aug-2025

Revision Number 1.04

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special precautions for user	
Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	
Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 UN proper shipping name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special precautions for user	
Special Provisions	None

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

## EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diocetyl tin oxide	870-08-6	20

**20 (6)** DOT.

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

## Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

## Persistent Organic Pollutants

Not applicable

## REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

## Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

### Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H226 - Flammable liquid and vapour  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H319 - Causes serious eye irritation  
H332 - Harmful if inhaled  
H335 - May cause respiratory irritation  
H361f - Suspected of damaging fertility  
H371 - May cause damage to organs  
H372 - Causes damage to organs through prolonged or repeated exposure

# SAFETY DATA SHEET

**BOSTIK WATERSTOP EMERGENCY WATERPROOF  
COATING**

**Supersedes date** 21-May-2024

**Revision date** 18-Aug-2025

**Revision Number** 1.04

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

## **Notes relating to the identification, classification and labelling of substances**

Note V - If the substance is to be placed on the market as fibres (with diameter  $< 3 \mu\text{m}$ , length  $> 5 \mu\text{m}$  and aspect ratio  $\geq 3:1$ ) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation

## **Notes relating to the classification and labelling of mixtures**

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq 10 \mu\text{m}$

## **Legend**

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
Sk*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

## **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs  
**Revision date** 18-Aug-2025  
**Indication of changes**

**Revision Note** SDS sections updated: 1, 16.  
**Training Advice** No information available  
**Further information** No information available

**This SDS complies with the requirements of UK REACH Regulations SI 2019/758 (as amended)**

## **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**